MILITARY SPECIFICATION

FEED ASSEMBLY, AMMO

FOR

ARMAMENT SUBSYSTEM, HELICOPTER, 20MM: M97E1

AND M97E2

This specification is approved for use by the U.S. Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of feed assembly designated as Feed Assembly, Ammo for Armament Subsystem, Helicopter, 20MM: M97E1 and M97E2.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-C-5541	-	Chemical Conversion Coatings on Aluminum and Aluminum Alloys
MIL-C-6021	-	Castings, Classification and Inspection of
MIL-I-6181	-	Interference Control Requirements, Aircraft Equipment
MIL-I-6868	-	Inspection Process, Magnetic Particle

FSC 1005

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2024-01-23T15:56Z
Check the source to verify that this is the current version before use.

MIL-W-63150 - Weapons and Support Materiel, Standard Quality Assurance Provisions For

MIL-S-81591 - Steel, Investment Castings, Carbon and Corrosion, Resisting

FEDERAL

QQ-P-416 - Plating Cadmium (Electro deposited)

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-410 - Nondestructive Testing Personnel Qualification and Certification

MIL-STD-810 - Environmental Test Methods

DRAWINGS (SEE 6.5)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

Product

11830872 - Foam, Structural, Polycarbonate, Material Spec for (3 sheets)

11830886 - Feed Assembly, Ammo (Packaging Data Sheet)

Packaging

11830886 - Feed Assembly, Ammo

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM-E 8 - Tension testing of metallic materials

ASTM-E 18 - Method of Test for Rockwell Hardness

ASTM-B 117 - Method of Salt Spray (Fog) Testing

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2024-01-22T15:56Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

3.2 Assembly. The assembly shall comply with all requirements specified on Drawing (Dwg.) 11830886, all associated drawings, and with all requirements specified in applicable specifications.

3.3 Contamination and distoration of Lexan parts. Extreme care should be taken throughout all phases of manufacture to avoid contacting "Lexan" material. Specific information on "Lexan" destructive solvents may be obtained from the General Electric Co., Chemical and Metalurgical Division, Pittsfield, Mass.

3.4 Interchangeability. All parts having the same part number shall be completely interchangeable with each other and with like parts of other manufacture with respect to installation and performance. Parts joined together by welding, brazing, or riveting shall be interchangeable as assemblies.

3.5 Spare parts. When procurement documents (see 6.2) stipulate that spare parts are to be furnished with assembled ammo feed assemblies, the spare parts shall be produced concurrently with and of the same material lots as like parts used in the assembled ammo feed assembly.

3.6 Performance characteristics.

3.6.1 Cycling. The ammo feed system shall be capable of cycling linked ammunition at the rate of 730 $\pm$ 50 rounds per minute, when tested as specified in 4.5.8.1.

3.6.2 Loading. The ammo feed system shall be capable of being loaded with 750 $\pm$ 0/10 rounds of M51A2 series, linked, 20MM ammunition in not more than 10 minutes when loaded by a team of two people, when tested as specified in 4.5.8.2.

3.6.3 Feed assembly handling. When fully loaded, the feed assembly shall be capable of supporting a load of not less than 510 pounds when tested as specified in 4.5.8.3.

3.7 First article testing. This specification makes provisions for first article testing. Submission of first article quantity by the contractor shall be as specified in the contract.

3.7.1 Disassembly and inspection (first article only). The motor shall show no evidence of excessive wear damage, burning, galling or moving parts, etc when inspected as specified in 4.5.4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2024-01-23T15:56Z
Check the source to verify that this is the current version before use.

3.8 Workmanship. All parts and assemblies shall be fabricated, and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust, and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous; however, a few light scratches not exposing base material may be permitted. All required marking and stamping shall be neat and sharply defined. (See MIL-W-63150).

3.9 Plastic workmanship. All plastic components shall be fabricated in a thorough, workmanlike manner and shall be free of porosity, twist, warpage, heat marks, sinks, checks, cracks, chipped edges, burrs, blisters, scratches, excess flash, and other defects which would affect their serviceability.

4. QUALITY ASSURANCE PROVISONS

4.1 Responsibility for inspection and quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-W-63150 shall apply and are made a part of this detail specification.

4.2 Classification of inspection. The following type of inspections shall be conducted on this item:

a. First article inspection.

b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Sprock Shaft	189F858	3
Motor, 28 VDC	105D3303	2
Angle	114C2085	3
Support, Round, Hinged	11830413	3
Stop, Hinge	11830430	3

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2024-01-23T15:56Z
Check the source to verify that this is the current version before use.

Tube	11830476	3
Latch, Tension	11830532	3
Block, Clamp	11830615	3
Guide, Bulkhead	11830702	3
Guide, Bulkhead	11830744	3
Adapter, Booster	11830812	3
Panel, Support	11830835	3
Roller, Square	11830840	3
Chute, Ammo, Flex	11830873	3
Panel, Ammo, Box, 20MM	11830888	3
Support, Round, Hinged	11830889	3
Clip, Round	11830892	7
Box, Ammo	11830894	3
Cable Assembly, W1 Booster Drive	11830940	3
Handle, Ammo box	11831044	3
Feed Assembly, Ammo	11830886	3

4.3.2 Inspection to be performed. See TABLE I herein.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of any assembly, component or test specimen in the sample that fails to comply with any of the stated requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2024-01-22T15:56Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION

MIL-F-63428(AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 4		DRAWING NUMBER
	Feed Assembly, Ammo and components				SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Sprocket Shaft (Dwg. 189F858)				
	Examination for defects	3		3.2	4.4.2.1
	Mechanical properties (Tensile strength, yield strength and elongation)	a		3.2	4.5.1
	Motor, 28 VDC (Dwg. 105D3303)				
	Examination for defects	2		3.2	4.4.2.2
	Environmental Tests	a		3.2	4.5.4.1.2
	Performance Tests	a		3.2	4.5.4.1.1
	Weight	a		3.2	Balance
	Service life	a		3.2	4.5.4.2
	Output shaft rotation	a		3.2	4.5.4.3
	Side load test of motor	a		3.2	4.5.4.4
	Electro magnetic interference	a		3.2	4.5.4.6
	Disassembly and inspection	a		3.2	4.5.4.5
	Angle (Dwg. 114C2085)				
	Examination for defects	3		3.2	4.4.2.3
	Salt Spray Test	a			4.5.3

NOTES:

a. This test shall be performed on the same samples subjected to examination for defects.

Source: https://assist.dla.mil | Downloaded: 2026-04-26T04:27Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 2 OF 4		DRAWING NUMBER
	CONTINUATION SHEET				SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Support, Round, Hinged, (Dwg. 11830413)				
	Examination for defects	3		3.2	4.4.2.4
	Salt Spray Test	a		3.2	4.5.3
	Stop, Hinge (Dwg. 11830430)				
	Examination for defects	3		3.2	4.4.2.5
	Salt Spray Test	a		3.2	4.5.3
	Tube (Dwg. 11830476)				
	Examination for defects	3		3.2	4.4.2.6
	Salt Spray Test	a		3.2	4.5.3
	Latch, Tension (Dwg. 11830532)				
	Examination for defects	3		3.2	4.4.2.7
	Salt Spray Test	a		3.2	4.5.3
	Working strength and tensile load tests	a		3.2	4.7
	Block, Clamp (Dwg. 11830615)				
	Examination for defects	3		3.2	4.4.2.8
	Salt Spray Test	a		3.2	4.5.3
	Guide, Bulkhead (Dwg. 11830702)				
	Examination for defects	3		3.2	4.4.2.9
	Salt Spray Test	a		3.2	4.5.3

NOTES:

a. This test shall be performed on the same samples subjected to examination for defects.

Source: https://assist.dla.mil/online/start/ Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 3 OF 4		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
	CONTINUATION SHEET				SEE BELOW
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Guide, Bulkhead (Dwg. 11830744)				
	Examination for defects	3		3.2	4.4.2.10
	Salt Spray Test	a		3.2	4.5.3
	Adapter, Booster (Dwg. 11830812)				
	Examination for defects	3		3.2	4.4.2.11
	Salt Spray Test	a		3.2	4.5.3
	Panel, Support (Dwg. 11830835)				
	Examination for defects	3		3.2	4.4.2.12
	Salt Spray Test	a		3.2	4.5.3
	Roller, Square (Dwg. 11830840)				
	Examination for defects	3		3.2	4.4.2.13
	Salt Spray Test	a		3.2	4.5.3
	Chute, Ammo, Flex (Dwg. 11830873)				
	Examination for defects	3		3.2	4.4.3.14
	Salt Spray Test	a		3.2	4.5.3
	Freedom of rounds	a		3.2	4.5.5.1
	Twisting	a		3.2	4.5.5.2
	Flexibility (3 positions)	a		3.2	4.5.5.3
	Panel, Ammo, Box, 20MM (Dwg. 11830888)				
	Examination for defects	3		3.2	4.4.2.15
	Salt Spray Test	a		3.2	4.5.3

NOTES:

a. This test shall be performed on the same samples subjected to examination for defects.

Source: https://assist.dla.mil/ Downloaded: 2026-04-26T04:27Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 4 OF 4		DRAWING NUMBER
	CONTINUATION SHEET				SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Support, Round, Hinged (Dwg. 11830889)				
	Examination for defects	3		3.2	4.4.2.16
	Salt Spray Test	a		3.2	4.5.3
	Clip, Round (Dwg. 11830892)				
	Examination for defects	7		3.2	4.4.2.17
	Salt Spray Test	a		3.2	4.5.3
	Hardness	a		3.2	4.5.2
	Magnetic particle inspection	a		3.2	4.5.6
	Box, Ammo (Dwg. 11830894)				
	Examination for defects	3		3.2	4.4.2.18
	Voids	a		3.2	4.6
	Cable Assembly, W1, Booster Drive (Dwg. 11830940)				
	Examination for defects	3		3.2	4.4.2.19
	Continuity and insulation resistance	a		3.2	4.5.7
	Handle, Ammo Box (Dwg. 11831044)				
	Examination for defects	3		3.2	4.4.2.20
	Salt Spray Test	a		3.2	4.5.3
	Feed Assembly, Ammo (Dwg. 11830886)				
	Examination for defects	3		3.2	4.4.2.21
	Performance characteristics	a		3.2	4.5.8

NOTES:

This test shall be performed on the same samples to examination for defects.

Source: https://assist.dla.mil/Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions and complies with the provisions for submission of product as specified in MIL-STD-105. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements. In addition, motors shall be from not more than one lot from one manufacturer.

4.4.1.1 Spare parts lot. A spare part lot shall consist of spare parts as produced concurrently by a manufacturing process common to the lot. Each lot of spare parts shall not include more than one lot of material where parts are subjected to heat treatment.

4.4.1.2 Replacement parts lot. A replacement parts lot shall consist of all spare parts of the same design presented for acceptance at one time, in which the unit of product is a part manufactured separate from the process of assembled feed assemblies.

NOTE: An inspection lot shall not exceed one (1) month's production.

4.4.2 Examination. The examinations listed in the item detail specification for Classification of Defects shall be performed on inspection lots as defined in 4.4.1 of this specification.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Sprocket Shaft		1189F858
			NEXT HIGHER ASSEMBLY 11830881

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Mechanical properties (Tensile strength, yield strength and elongation)	1		3.2	4.5.1
MINOR					
201.	Diameter (Zone 1-E) (.590)		1.50%	3.2	Gage
202.	Profile of surfaces A and B (2 places)		1.50%	3.2	Gage
203.	Protective finish defective or missing		1.50%	3.2	Visual
204.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567, Feb 74, Which is Obsolete

Source: https://assist.dla.mil/... Downloaded: 2026-04-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 105D3303
4.4.2.2	Motor, 28 VDC				NEXT HIGHER ASSEMBLY 11830881
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Performance Tests		100%	3.2	4.5.4.1.1
102.	Height (View A) (2 places) (.375)		0.65%	3.2	Gage
103.	Second largest diameter ("A" surface) (2.300)		0.65%	3.2	Gage
104.	True position of corner holes (4)		0.65%	3.2	Gage
105.	True position of middle hole (.002)		0.65%	3.2	Gage
106.	Diameter of corner holes (4) (.285)		0.65%	3.2	Gage
107.	Evidence of poor workmanship		0.65%	3.8	Visual
MINOR:	None defined				

NOTES:

Source: https://assist.dla.mil/ Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 114C2085
4.4.2.3	Angle				NEXT HIGHER ASSEMBLY 11830889
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray Test	1		3.2	4.5.3
102.	Diameter of holes		0.65%	3.2	Gage
MINOR					
201.	Angle of taper (45°)		1.50%	3.2	Gage
202.	Radius in corner, max.		1.50%	3.2	Gage
203.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Support, Round, Hinged		11830413
			NEXT HIGHER ASSEMBLY 11830887

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray Test	1		3.2	4.5.3
MINOR					
201.	True position of holes with respect to A		1.50%	3.2	Gage
202.	Diameter in section B-B (34 places)		1.50%	3.2	Gage
203.	Distance from end to first stop (.34)		1.50%	3.2	Gage
204.	Distance from end to second stop		1.50%	3.2	Gage
205.	Distance from end to third stop		1.50%	3.2	Gage
206.	Distance from end to fourth stop		1.50%	3.2	Gage
207.	Distance from end to fifth stop		1.50%	3.2	Gage
208.	Total length (33.04)		1.50%	3.2	Gage
209.	Evidence of poor workmanshp		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11830430
4.4.2.5	Stop, Hinge				NEXT HIGHER ASSEMBLY 11830889
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray test	1		3.2	4.5.3
MINOR					
201.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Tube		11830476
			NEXT HIGHER ASSEMBLY 11830887

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray test	1		3.2	4.5.3
MINOR					
201.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil Downloaded: 2026-04-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER 11830532
4.4.2.7	Latch, Tension				NEXT HIGHER ASSEMBLY 11830895
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray test	1		3.2	4.5.3
102.	Working strength and tensile load tests	2		3.2	4.7
103.	Distance between center of holes (.562)		0.65%	3.2	Gage
104.	Secondary lock does not function properly		0.65%	3.2	Manual
105.	Part missing or damaged		0.65%	3.2	Visual
MINOR					
201.	Radius of drawhook		1.50%	3.2	Gage
202.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil | Downloaded: 2026-04-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.8	Block, Clamp		11830615
			NEXT HIGHER ASSEMBLY
			11830883

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray test	1		3.2	4.5.3
102.	True position of holes		0.65%	3.2	Gage
MINOR					
201.	Radius (.05)		1.50%	3.2	Gage
202.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-F-63428(AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.9	Guide, Bulkhead		11830702
			NEXT HIGHER ASSEMBLY 11830893

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray test	1		3.2	4.5.3
102.	True position of holes with all surfaces		0.65%	3.2	Gage
MINOR					
201.	Diameter of holes		1.50%	3.2	Gage
202.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil | Downloaded: 2026-04-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Guide, Bulkhead		11830744
			NEXT HIGHER ASSEMBLY 11830893

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray test	1		3.2	4.5.3
102.	True position of holes with all surfaces		0.65%	3.2	Gage
MINOR					
201.	Diameter of holes		1.50%	3.2	Gage
202.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil/online/start/ Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER 11830812
4.4.2.11	Adapter, Booster				NEXT HIGHER ASSEMBLY 11830884
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray test	1		3.2	4.5.3
102.	Weld incomplete or inadequate		100%	3.2	Visual/Manual
103.	True position of holes		0.65%	3.2	Gage
104.	Part missing or improperly assembled		0.65%	3.2	Visual
105.	Part damaged		0.65%	3.2	Visual
106.	Protective coating missing or inadequate		0.65%	3.2	Visual
MINOR					
201.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	Panel, Support	1 OF 1	11830835
			NEXT HIGHER ASSEMBLY 11830887

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray test	1		3.2	4.5.3
MINOR					
201.	Total length (9.75)		1.50%	3.2	Gage
202.	Distance from side to hook portion (.92)		1.50%	3.2	Gage
203.	Height of hool portion (.36)		1.50%	3.2	Gage
204.	Distance from bottom to hole (.45)		1.50%	3.2	Gage
205.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER 11830840
4.4.2.13	Roller, Square				NEXT HIGHER ASSEMBLY 11830884
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray test	1		3.2	4.5.3
102.	True position of holes at min length (2 places)		0.65%	3.2	Gage
103.	Weld incomplete (2 places) or inadequate		0.65%	3.2	Visual
104.	Distance between pin end and plug (both ends)		0.65%	3.2	Gage
105.	True position of pins (both ends)		0.65%	3.2	Gage
106.	Either pin loose		0.65%	3.2	Manual
107.	Part missing or improperly assembled		0.65%	3.2	Visual
108.	Part damaged		0.65%	3.2	Visual
MINOR					
201.	Distance between plugs (25.27)		1.50%	3.2	Gage
202.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-02-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.14	Chute, Ammo, Flex	1 OF 1	11830873
			NEXT HIGHER ASSEMBLY: 11830886

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray test	1		3.2	4.5.3
102.	Freedom of rounds		0.65%	3.2	4.5.5.1
103.	Twisting		0.65%	3.2	4.5.5.2
104.	Flexibility (3 positions)		0.65%	3.2	4.5.5.3
105.	Part missing or improperly assembled		0.65%	3.2	Visual
106.	Part damaged		0.65%	3.2	Visual
MINOR					
201.	Weight of assembly, max.		1.50%	3.2	Balance
202.	Width (2.389)		1.50%	3.2	Gage
203.	Total length (in extended condition)		1.50%	3.2	Gage
204.	Evidence of poor workmanship		2.50%	3.2	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.15	Panel, Ammo Box, 20MM		11830888
			NEXT HIGHER ASSEMBLY 11830887

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray test	1		3.2	4.5.3
MINOR					
201.	Total length		1.50%	3.2	Gage
202.	Total width		1.50%	3.2	Gage
203.	Height of tapered corner (.72)		1.50%	3.2	Gage
204.	Length of tapered corner (1.72)		1.50%	3.2	Gage
205.	Height of bend (2 places) (.68)		1.50%	3.2	Gage
206.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 which is Obsolete

Source: https://assist.dla.mil/Downloaded: 2025-10-10T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.16	Support, Round, Hinged		11830889
			NEXT HIGHER ASSEMBLY 11830887

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray test	1		3.2	4.5.3
102.	Part missing or improperly assembled		0.65%	3.2	Visual
103.	Part damaged		0.65%	3.2	Visual
MINOR					
201.	True position of holes with respect to A		1.50%	3.2	Gage
202.	Diameter, max (section B-B) (34 places)		1.50%	3.2	Gage
203.	Distance from end to first stop (.34)		1.50%	3.2	Gage
204.	Distance from end to second stop (8.34)		1.50%	3.2	Gage
205.	Distance from end to third stop (16.34)		1.50%	3.2	Gage
206.	Distance from end to fourth stop (24.34)		1.50%	3.2	Gage
207.	Distance from end to fifth stop (31.55)		1.50%	3.2	Gage
208.	Total length (33.04)		1.50%	3.2	Gage
209.	Protective finish missing or unsatisfactory		1.50%	3.2	Visual
210.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil | Downloaded: 2026-04-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER 11830892
4.4.2.17	Clip, Round				NEXT HIGHER ASSEMBLY 11830889
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray test	1		3.2	4.5.3
102.	Hardness		100%	3.2	4.5.2
103.	Magnetic particle inspection		100%	3.2	4.5.6
MINOR					
201.	Largest radius (.40)		1.50%	3.2	Gage
202.	Distance from base to center of largest radius		1.50%	3.2	Gage
203.	Height from base to top radius (1.05)		1.50%	3.2	Gage
204.	Height from base to outside smallest radius (.30)		1.50%	3.2	Gage
205.	Magnetic particle inspection stamp missing		1.50%	3.2	Visual
206.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 11830894
4.4.2.18	Box, Ammo				NEXT HIGHER ASSEMBLY 11830895
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Voids		0.65%	3.2	4.6
102.	Plastic workmanship unsatisfactory		0.65%	3.9	Visual
MINOR					
201.	Width of bay, min (3 places) (8.775) (Sh 1)		1.50%	3.2	Gage
202.	Thickness of outer wall, min (.250) (Sh 2)		1.50%	3.2	Gage
203.	Thickness of bay wall, min (2 places)		1.50%	3.2	Gage
204.	Thickness of bay bottom, min (10 places) (.25) (Sh 2)		1.50%	3.2	Gage
205.	Total width (26.20) (Sh 3)		1.50%	3.2	Gage
206.	Total length (41.63) (Sh 2)		1.50%	3.2	Gage
207.	Height of projection (.610 each end) (Sh 1)		1.50%	3.2	Gage
208.	Distance from outer wall to center of hole in bay 1 (1.08) (Sh 1)		1.50%	3.2	Gage
209.	Distance between outer wall and middle of wall between bays 1 and 2 (17.425) (Sh 1)		1.50%	3.2	Gage
210.	Distance from outer wall to middle of wall between bays 2 and 3 (8.775)		1.50%	3.2	Gage
211.	Middle of crossover bay (2 places) (6.27) (Sh 2)		1.50%	3.2	Gage

NOTES:

Source: https://assist.dla.mil Downloaded: 2025-10-20T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.18	Box, Ammo				11830894
					NEXT HIGHER ASSEMBLY 11830895
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
212.	Distance between end projection (42.49) (Sh 1)		1.50%	3.2	Gage
213.	Width of 3 bays, min. (8.10) (Sh 3)		1.50%	3.2	Gage
214.	True position of countersink holes with specified surfaces (Zone 7-G, Sh 3) (2 places)		1.50%	3.2	Gage
215.	True position of countersink Holes with C (2 places) (Zone 3-F, Sh 3)		1.50%	3.2	Gage
216.	True position of countersink Holes with B (2 places) (Zone 3-D, Sh 3)		1.50%	3.2	Gage
217.	True position of 12 holes in all bays with respect to surface A (Sh 1)		1.50%	3.2	Gage
218.	Weight of box		1.50%	3.2	Balance
219.	Protective finish improper		1.50%	3.2	Visual

NOTES:

Source: https://assist.dla.mil/Downloads/Index/2015-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11830940
4.4.2.19	Cable Assembly, W1, Booster Drive				NEXT HIGHER ASSEMBLY 11830886
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Continuity and insulation resistance		100%	3.2	4.5.7
102.	Solder workmanship unsatisfactory		0.65%	3.2	Visual
103.	Wire color incorrect		0.65%	3.2	Visual
104.	Part missing or improperly assembled		0.65%	3.2	Visual
MINOR					
201.	Markings missing or inadequate		1.50%	3.2	Visual
202.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil/Downloaded: 2008-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11831044
4.4.2.20	Handle, Ammo Box				NEXT HIGHER ASSEMBLY 11830893
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray test	1		3.2	4.5.3
102.	Part missing or improperly assembled		0.65%	3.2	Visual
103.	Part damaged		0.65%	3.2	Visual
MINOR					
201.	Length of sleeve, min (3.50)		1.50%	3.2	Gage
202.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil/online/start/ Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11830886
4.4.2.21	Feed Assembly, Ammo				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Performance characteristics	2		4.5.8	
102.	Any part missing, damaged or improperly assembled		0.65%	3.2	Visual
MINOR					
201.	Marking misleading or unidentifiable (including instruction plate)		1.50%	3.2	Visual
202.	Identification plate or instruction plate missing		1.50%	3.2	Visual
203.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil/Downloaded: 2008-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.22	Guide, Bell Mouth				11830831
					NEXT HIGHER ASSEMBLY
					11830885
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Any parts missing or improperly assembled		0.65%	3.2	Visual
MINOR					
201.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil/online/start/ Downloaded: 2024-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11830884
4.4.2.23	Cover, Assembly, Ammo Box				NEXT HIGHER ASSEMBLY 11830885
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Any parts missing or improperly assembled		0.65%	3.2	Visual
102.	Part damaged		0.65%	3.2	Visual
MINOR					
201.	Marking misleading or unidentifiable		1.50%	3.2	Visual
202.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil/online/start/ Downloaded: 2024-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.24	Support, Roller				11830559
					NEXT HIGHER ASSEMBLY
					11830884
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Inside diameter (.8109)		0.65%	3.2	Gage
MINOR					
201.	Distance between center and datum surface C (.68)		1.50%	3.2	Gage
202.	Distance between center and datum surface B (.40)		1.50%	3.2	Gage
203	Protective coating missing or inadequate		1.50%	3.2	Visual
204.	Part damaged		1.50%	3.2	Visual
205.	Part missing		1.50%	3.2	Visual
206.	Evidence of poor workmanship		2.50%	3.2	Gage

NOTES:

Source: https://assist.dla.mil | Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11830869
4.4.2.25	Stop, Bolt				NEXT HIGHER ASSEMBLY 11830884
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR	None defined				
MINOR					
201.	Outside diameter		1.50%	3.2	Gage
202.	Width of head		1.50%	3.2	Gage
203.	Thread damaged		1.50%	3.2	Gage
204.	Stud or washer missing		1.50%	3.2	Visual
205.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.daps.dla.mil | Downloaded: 2008-10-20T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11830881
4.4.2.26	Booster, Assy				NEXT HIGHER ASSEMBLY 11830884
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Part missing or improperly assembled		0.65%	3.2	Visual
102.	Part damaged		0.65%	3.2	Visual
103.	Evidence of poor workmanship		0.65%	3.8	Visual
MINOR					
201.	Marking misleading or unidentifiable		1.50%	3.2	Visual

NOTES:

Source: https://assist.daps.dla.mil | Downloaded: 2025-06-20T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.27	Housing, Booster		11830858
			NEXT HIGHER ASSEMBLY 11830881

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	True position of holes		0.65%	3.2	Gage
102.	Distance between datum A and datum H (section P-P) (Zone B-8) (sh 3)		0.65%	3.2	Gage
103.	Larger diameter of flange (2.301) (sh 3)		0.65%	3.2	Gage
104.	Smaller diameter of flange (1.2597) (sh 3)		0.65%	3.2	Gage
105.	Distance between datum G and center line of A (3 places) (2.844) (sh 3)		0.65%	3.2	Gage
106.	Insert missing		0.65%	3.2	Visual
107.	Insert tange not removed		0.65%	3.2	Visual
108.	Minor diameter of threaded insert hole (.2591) (sh 3)		0.65%	3.2	Gage
109 .	Pitch diameter of threaded insert hole (4 places)		0.65%	3.2	Gage
110.	Minor diameter of threaded insert hole (.1981) (3 places) (sh 3)		0.65%	3.2	Gage
111.	Pitch diameter of threaded insert hole (3 places)		0.65%	3.2	Gage
112.	Minor diameter of threaded insert motor mount holes (.2591) (4 places) (sh 3)		0.65%	3.2	Gage
MINOR					
201.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2024-10-20T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.28	Bearing, Ball, Annular		11830451
			NEXT HIGHER ASSEMBLY 11830881

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Hardness		0.65%	3.2	4.5.2
102.	Grease missing		0.65%	3.2	Visual
MINOR					
201.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Source: https://assist.dla.mil -- Downloaded: 2024-01-22T15:56Z
Check the source to verify that this is the current version before use.
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.29	Spacer, Ring		11830802
			NEXT HIGHER ASSEMBLY 11830881

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Salt spray test	1		3.2	4.5.3
MINOR					
201.	Inside diameter		1.50%	3.2	Gage
202.	Protective finish missing or inadequate		1.50%	3.2	Visual
203.	Evidence of poor workmanshiup		2.50%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.30	Box, Latch Assy				11830895
					NEXT HIGHER ASSEMBLY 11830893
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Part missing, damaged or improperly assembled		0.65%	3.2	Gage
102.	Evidence of poor workmanship		0.65%	3.2	Gage
MINOR					
201.	Length to first latch (2 places) (2.58)		1.50%	3.2	Gage
202.	Length to second latch (2 places) (8.31)		1.50%	3.2	Gage
203.	Length to latch (opposite end) (5.95)		1.50%	3.2	Gage

NOTES:

Source: https://assist.dla.mil/Document Created: 2008-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11830870
4.4.2.31	Nut, Dome				NEXT HIGHER ASSEMBLY 11830884
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR	None defined				
MINOR					
201.	Locking insert missing		1.50%	3.2	Visual
202.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil/online/start/ Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11831027
4.4.2.32	Pin, Straight				NEXT HIGHER ASSEMBLY 11830889
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR	None defined				
MINOR					
201.	Length		1.50%	3.2	Gage
202.	Evidence of poor workmanshp		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11830887
4.4.2.33	Panel, Support, 20MM Round				NEXT HIGHER ASSEMBLY 11830885
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Part missing, damaged or improperly assembled		0.65%	3.2	Visual
102.	Evidence of poor workmanship		0.65%	3.8	Visual
MINOR					
201.	Height to first support (2.50)		1.50%	3.2	Gage
202.	Height to second support (4.90)		1.50%	3.2	Gage
203.	Height to third support (7.30)		1.50%	3.2	Gage
204.	Height to fourth support (9.70)		1.50%	3.2	Gage
205.	Height to fifth support (13.17)		1.50%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z current version before use.
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11830883
4.4.2.34	Cover, Subassy				NEXT HIGHER ASSEMBLY 11830884
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	True position of holes (4)		0.65%	3.2	Gage
102.	Part missing, damaged or improperly assembled		0.65%	3.2	Visual
103.	Evidence or poor workmanship		0.65%	3.8	Visual
MINOR					
201.	Marking misleading or unidentifiable		1.50%	3.2	Visual
202.	Protective coating, missing or inadequate		1.50%	3.2	Visual

NOTES:

Source: https://assist.dla.mil/online/quickdoc/0024/0124015.PDF Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11830893
4.4.2.35	Box, Subassy				NEXT HIGHER ASSEMBLY 11830885
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Any parts missing, damaged or improperly assembled		0.65%	3.2	Visual
102.	Parts damaged		0.65%	3.2	Visual
103.	Evidence or poor workmanship		0.65%	3.8	Visual
MINOR					
201.	Marking misleading illegible or missing		1.50%	3.2	Visual

NOTES:

Source: https://assist.daps.dla.mil Downloaded: 2025-10-20T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.36	Hook, Latch		11830827
			NEXT HIGHER ASSEMBLY 11830883

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Distance between center of holes (.500)		0.65%	3.2	Gage
MINOR					
201.	Smallest radius (.09)		1.50%	3.2	Gage
202.	Second smallest radius (2 places) (.14)		1.50%	3.2	Gage
203.	Largest radius (.24)		1.50%	3.2	Gage
204.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.daps.dla.mil/Downloaded: 2008-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.37	Spring, Retainer, Loop		11830890
			NEXT HIGHER ASSEMBLY 11830883

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR	None defined				
MINOR					
201.	Angle (2 places)		1.50%	3.2	Gage
202.	Angle (2 places)		1.50%	3.2	Gage
203.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2025-10-20T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.38	Hook, Latch		11830775
			NEXT HIGHER ASSEMBLY 11830883

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	True position of holes		0.65%	3.2	Gage
MINOR					
201.	Smaller radius (.10)		1.50%	3.2	Gage
202.	Larger radius (.24)		1.50%	3.2	Gage
203.	Evidence of poor workmanship		2.50%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 which is obsolete

Source: https://assist.dla.mil - Downloaded: 2025-10-16T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63428(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11830882
4.4.2.39	Cover, Box				NEXT HIGHER ASSEMBLY 11830883
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Part damaged		0.65%	3.2	Visual
102.	Plastic workmanship		0.65%	3.2	Visual
MINOR					
201.	Radius (35 places) (Section E-E)		1.50%	3.2	Gage
202.	Distance between datum H and first recess (4 places) (1.11)		1.50%	3.2	Gage
203.	Distance between datum H and second recess (4 places (7.11)		1.50%	3.2	Gage
204.	Distance between datum H and third recess (9 places) (9.61)		1.50%	3.2	Gage
205.	Distance between datum H and fourth recess (9 places) (18.11)		1.50%	3.2	Gage
206.	Distance between datum H and fifth recess (9 places) (26.61)		1.50%	3.2	Gage
207.	Weight		1.50%	3.2	Balance
208.	Evidence of poor workmanship		2.50%	3.8	Visual

NOTES:

Source: https://assist.dla.mil/Downloaded: 2025-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the first article and quality conformance inspection tables.

4.4.3.1 Spare parts. Spare parts furnished with an inspection lot will be accepted provided like parts of the lot are accepted after all inspections and tests. In case of a failure of any part in any acceptance inspection and tests, like spare parts from the same lot as the defective components shall be accepted only after screening by the contractor for the revealed defect and resubmitting for inspection by the Government.

4.4.3.2 Replacement parts. Each lot of replacement parts will ordinarily be accepted on the basis of the inspections and tests of this specification, however, the Government inspector may, if he deems it necessary, submit a representative sample of replacement parts for the inspections and tests of this specification.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method Column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval, all inspection equipment designs in accordance with the terms of the contract. See MIL-W-63150 and 6.3 herein.

4.5 Test methods and procedures.

4.5.1 Mechanical properties of sprocket shaft (tensile strength, yield and elongation). The Sprocket Shafts shall be subjected to these tests in accordance with the applicable drawing using test procedures specified in ASTM E 8. All procedures and equipment shall be satisfactory to the Government. If any Sprocket fails to comply with the requirements specified on the applicable drawing, the lot shall be rejected.

4.5.2 Hardness. Samples shall be selected from each heat treatment batch. (See Note) The test shall be performed as specified in ASTM E 18. Each heat treat batch shall remain segregated until completion of all required tests. If any sample fails to comply with the specified hardness requirement, the sample shall be classed defective.

NOTE: A heat-treatment batch shall be defined as parts that have been heat-treated at the same time in the same furnace and quench bath for each of all phases of the entire heat-treatment process.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2024-01-22T15:56Z
Check the source to verify that this is the current version before use.

4.5.3 Salt spray test. Samples shall be selected from each lot and subjected to the salt spray test in accordance with the procedures in ASTM B 117. Unless otherwise specified on the applicable drawing the minimum exposure time shall be one and one half (1 1/2) hours using a 5% sodium chloride solution. If any part shown evidence of corrosion (red rust, salt deposits, etc.), it shall be classed defective and the lot shall be rejected. This is a destructive test. Any part subjective to it shall not be returned to the lot unless otherwise specified by the contracting officer.

4.5.4 Special tests and examinations of motor, 28 VDC.

4.5.4.1 Environmental and performance tests of motor.

4.5.4.1.1 Performance tests. The motor selected shall be subjected to all the performance tests specified on the applicable drawing. These shall include output, torque, speed and load, current, deceleration, stall torque time, stall condition. Test equipment and procedures shall be in accordance with the applicable drawing and satisfactory to the contracting officer. If any motor fails to comply with any test requirement, it shall be classed defective and the lot shall be rejected.

4.5.4.1.2 Environmental tests. The motor selected shall be subjected to all the environmental tests specified on the applicable drawing. These shall include altitude performance, extreme temperature performance, vibration, shock, humidity, salt fog, sand and dust and fungus resistance tests. Test equipment and procedures shall be in accordance with the applicable drawing, and MIL-STD-810 and satisfactory to the contracting officer. If any motor fails to comply with any test requirement, it shall be classed defective and the lot rejected.

4.5.4.2 Service life. The motor selected shall be subjected to the service life test as specified on the applicable drawing. Provisions shall be made for determining output, torque, speed and load, current, deceleration, stall torque time, stall condition on the first duty and last duty cycle. Test equipment and procedures shall be in accordance with the applicable drawing and satisfactory to the contracting officer. If any motor fails to comply with the specified requirement it shall be classed defective and the lot shall be rejected.

4.5.4.3 Output shaft rotation of motor. The output shaft of the motor shall be turned in the direction of rotation and observation made for any movement of the internal gear train. The test shall be performed as specified in the applicable drawing using methods and equipment satisfactory to the contracting officer. If any motor fails to comply with the specified requirements it shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2024-01-23T15:56Z
Check the source to verify that this is the current version before use.

4.5.4.4. Side load test of motor. The motor selected shall be subjected to the side load test as specified in the applicable drawing. The methods and equipment shall be as specified on the applicable drawing using methods and equipment satisfactory to the contracting officer. If any motor fails to comply with the requirement specified on the applicable drawing, it shall be classed defective and the lot shall be rejected.

4.5.4.5 Disassembly and inspection (first article only). At the conclusion of all first article tests, the motor shall be disassembled and inspected for excessive wear and defects as follows:

	Part	Inspect for:
a.	Shaft spline	Wear or damage
b.	Armature shaft	Wear or damage
c.	Bearings	Galling or binding
d.	Commutator	Damage, excessive grooving, thrown solder, burned segments
e.	Brushes	Excessive wear, broken leads
f.	Brush holders	Cracks, breaks, burned areas
g.	Brush springs	Damage or cracks
h.	Armature	Broken wires, damaged wires, insulation defects
i.	Spacers, washers, seals	Damage or cuts
j.	Yoke assembly	Broken or bare wires, stripped or damaged screw threads, cracked or broken housing, lose or broken connector pins, damaged connector body, loose or damaged pole shoes, loose, damaged or burned field windings

This inspection shall be performed using procedures satisfactory to the contracting officer. If any motor fails to comply with the requirements of 3.7.1, it shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2024-01-23T15:56Z
Check the source to verify that this is the current version before use.

4.5.4.6 Electro magnetic interference (EMI). The motor selected shall be subjected to the test for EMI as specified in the applicable drawing. Test equipment shall be in accordance with MIL-I-6181 and satisfactory to the contracting officer. If any motor fails to comply with the EMI requirements specified in MIL-I-6181, it shall be classed defective and the lot shall be rejected.

4.5.5 Chute, ammo, flex.

4.5.5.1 Freedom of rounds. This test shall be performed as specified on the applicable drawing using an approved fixture. If any chute fails to comply with the requirement specified on the applicable drawing it shall be classed defective. This test is a non-destructive test. Chutes may be used in subsequent testing.

4.5.5.2 Twisting. This test shall be performed as specified on the applicable drawing using an approved fixture. If any chute fails to comply with the requirement specified on the applicable drawing it shall be classed defective.

4.5.5.3 Flexibility (3 positions). This test shall be performed as specified on the applicable drawing using an approved fixture. If any chute fails to comply with the requirement specified on the applicable drawing it shall be classed defective.

4.5.6 Magnetic particle test. The procedures and equipment for performing this inspection shall be in accordance with MIL-I-6868 and MIL-W-63150 and shall be satisfactory to the Contracting Officer. Personnel performing this inspection shall be qualified in accordance with MIL-STD-410.

4.5.7 Continuity and insulation resistance of cable assembly, W1 booster drive. These tests shall be performed using methods and equipment satisfactory to the contracting officer. If any cable assembly fails to comply with the requirements specified on the applicable drawing, it shall be classed defective and removed from the lot.

4.5.8 Performance characteristics of feed assembly, ammo.

4.5.8.1 Cycling. The feed assembly, when assembled to an approved test fixture, using linked dummy ammunition, shall be capable of cycling ammunition in accordance with the requirement of 3.6.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2024-01-22T15:56Z
Check the source to verify that this is the current version before use.

4.5.8.2 Loading. This test shall be conducted by an approved method. Observation shall be made for the requirement of 3.6.2.

4.5.8.3 Feed assembly handling. This test shall be conducted by an approved method. Observation shall be made for the requirements of 3.6.3.

4.6 Voids in ammo boxes. The boxes shall be checked for voids in the material as specified on Dwg. 11830894. X-ray, infrared scan, or any other method satisfactory to the contracting officer shall be employed. If any box fails to comply with the requirements specified on Dwg. 11830894, the lot shall be classed defective.

4.7 Working strength and ultimate tensile load (tension latch). These tests shall be performed using methods and equipment satisfactory to the contracting officer. If any latch fails to comply with the requirements specified on the applicable drawing, the latch shall be classed defective.

5. PACKAGING

5.1 Preservation, packaging, packing and marking. Ammo Feed Assemblies shall be preserved, packaged, packed and marked in accordance with the requirements of the preservation and Packaging Data Sheet 11830886.

5.1.1 Spare parts or replacement parts. Spare parts or replacement parts shall be cleaned, preserved, packaged and packed as specified in the contract or order.

6. NOTES

6.1 Intended use. The ammo feed assembly covered by this specification is intended for use with Gun, automatic, 20MM: M197 on Armament Subsystem, Helicopter, 20MM: M97E1 and M97E2.

6.2 Ordering data. Procurements documents shall specify the following:

6.2.1 Procurement requirements

a. Title, number and date of this specification.

b. Quantity required and delivery schedules.

c. Serialization requirements, if applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2024-01-22T15:56Z
Check the source to verify that this is the current version before use.

d. Quality Conformance Inspection, if other than specified in Section 4 of this specification.

e. First Article Sample requirements, if other than specified in Section 4 of this specification.

f. Packaging requirements, if other than specified in Section 5 of this specification.

g. Certificates of conformance for each lot or shipment of product and as specified in MIL-W-63150.

h. Spare parts required.

i. Replacement parts schedules.

g. Marking requirements for shipment.

6.3 Submission of inspection equipment design for approval. See MIL-W-63150. Equipment designs shall be submitted as required to: Commander, ARRADCOM, ATTN: DRDAR-QAA-I, Dover, NJ 07801. Request letter of submittal should state contractor, contract number, specification number, item nomenclature and classification of defects and tests paragraph.

6.4 Submission of results of contractor-conducted examinations and tests. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to Commander, ARRADCOM, Dover, NJ 07801, ATTN: DRDAR-QAA-S.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing activity:
Army-AR

Project 1005-A601

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2024-02-22T15:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-F-63428 Feed Assembly, Ammo for Armament Subsystem, Helicopter, 20MM: M97E1 And M97E2

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2024-07-22T15:56Z
Check the source to verify that this is the current version before use.