MILITARY SPECIFICATION

FIRING ATTACHMENT, BLANK AMMO, XM21

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the blank ammunition firing attachment for the M240/M240C 7.62MM machine guns.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specificaitons and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-W-63150	-	Standard Quality Assurance Provisions for Weapons and Support Materiel.
MIL-W-13855	-	Weapons, Small Arms, General Specification for.

FSC 1005

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109	-	Quality Assurance Terms and Definitions.

(Copies of specifications and standards required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents forms a part of this specification to the extent specified herein.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

11833460	-	Firing Attachment, Blank Ammo, XM21.
11833471	-	System Drawing - Firing Attachment, Blank Ammo For M240 MG (XM21 with Ancillary Equipment).

PACKAGING DATA SHEET

11833460	-	Firing Attachment, Blank Ammo, XM21

2.2 Other publications. The following documents form a part of this standard to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM E 18	-	Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials
ASTM B 117	-	Salt Spray (Fog) Testing

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings, specifications, and standards.

3.2 Parts. All parts shall comply with applicable drawings, specifications and standards.

3.3 Blank firing attachment. The Blank Firing Attachment shall comply with all requirements specified on Dwg. 11833460, all associated drawings, and with all requirements specified in the applicable specifications and standards.

3.4 Assembleability. The Blank Firing Attachment and its ancillary components, (see Dwg. 11833471) shall readily attach to and detach from the specified weapon or a fixture simulating the specified weapon. When attached, firing attachments shall be securely retained on a simulator fixture or specified weapon.

3.5 Functioning. When assembled to the applicable weapon, the blank firing attachments shall permit the weapon to function properly. There shall be no stoppages or malfunctions directly attributable to the blank ammunition firing attachment. Testing shall be as specified in 4.5.4.

3.6 Marking. Blank ammunition firing attachments shall be clearly marked in accordance with the applicable drawing and the marking provisions of MIL-W-13855.

3.7 First article. When specified, a sample shall be subjected to first article inspection (see 4. and 6.)

3.8 Workmanship. All parts and assemblies shall be fabricated and assembled in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, surface defects, dirt, oil, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. All required markings shall be neat and sharply defined. See MIL-W-13855.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Test equipment and inspection facilities. The manufacturer shall insure that test and inspection facilities of sufficient accuracy, quality and quantity are established and maintained to permit performance of required inspections.

4.2 Classification of inspections. The inspections specified herein are classified as follows:

a. First Article Inspection (See 4.4).

b. Quality Conformance Inspection (See 4.5).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the contracting officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Firing Attachment, Blank Ammo, XM21	11833460	25
Chamber	11833464	10
Discriminator, Cartridge	11833463	10
Wire Rope Assembly	11833467	10
Clamp	11833466	10
Extension Assembly	11833450	10
Extension and Clamp Assembly	11833454	10
Body, Clamp	11833451	10
Extension	11833449	10
Shaft	11833452	10
Button	11833453	10
Support Assembly	11833455	10
Support	11833456	10
Strap	11833457	10
Bolt	11833458	10
Chute	11833459	10

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.3.2 Inspections to be performed. See MIL-W-63150, MIL-W-13855 and Table I herein.

4.3.3 Rejection. See MIL-W-63150.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Firing Attachment, Blank Ammo and Components	1 OF 3	See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Firing Attachment, Blank Ammo, XM21 (Dwg. 11833460) Examination for defects	25		3.2	4.4.2.1
	Chamber (Dwg. 11833464) Examination for defects	10		3.2	4.4.2.2
	Discriminator, Cartridge (Dwg. 11833463) Examination for defects	10		3.2	4.4.2.3
	Wire Rope Assembly (Dwg. 11833467) Examination for defects	10		3.2	4.4.2.4
	Clamp (Dwg. 11833466) Examination for defects	10		3.2	4.4.2.5
	Extension Assembly (Dwg. 11833450) Examination for defects	10		3.2	4.4.2.6

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER
	Firing Attachment, Blank Ammo and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Extension and Clamp Assembly (Dwg. 11833454) Examination for defects	10		3.2	4.4.2.7
	Body, Clamp (Dwg. 11833451) Examination for defects	10		3.2	4.4.2.8
	Extension (Dwg. 11833449) Examination for defects	10		3.2	4.4.2.9
	Shaft (Dwg. 11833452) Examination for defects	10		3.2	4.4.2.10
	Button (Dwg. 11833453) Examination for defects	10		3.2	4.4.2.11
	Support Assembly (Dwg. 11833455) Examination for defects	10		3.2	4.4.2.12

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63447(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Firing Attachment, Blank Ammo and Components	3 OF 3	See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Support (Dwg. 11833456) Examination for defects	10		3.2	4.4.2.13
	Strap (Dwg. 11833457) Examination for defects	10		3.2	4.4.2.14
	Bolt (Dwg. 11833458) Examination for defects	10		3.2	4.4.2.15
	Chute (Dwg. 11833459) Examination for defects	10		3.2	4.4.2.16

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. An inspection lot shall be as defined in MIL-STD-105.

4.4.2 Examination. See MIL-W-63150.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11833460
4.4.2.1	Firing Attachment, Blank Ammo, XM21				NEXT HIGHER ASSEMBLY 11833471
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101	Functioning		.65	3.5	4.5.4
102	Assembleability		.65	3.4	4.5.5
103	Part missing or improperly assembled		.65	3.2	Visual
104	Any part cracked		.65	3.2	Visual
MINOR:					
201	Marking of discriminator, cartridge		1.50	3.2	Visual
202	Evidence of poor workmanship		2.50	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 3	DRAWING NUMBER 11833464
4.4.2.2	Chamber		NEXT HIGHER ASSEMBLY 11833460

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101	Salt Spray Test	5		3.2	4.5.2
102	Hardness	5		3.2	4.5.3
103	Pitch diameter, .7812-24 UNS-3B, min, incorrect		.65	3.2	SMTE
104	Pitch diameter, .7812-24 UNS-3B, max, incorrect		.65	3.2	SMTE
105	Outside diameter of front end incorrect (1.123 - .003)		.65	3.2	SMTE
106	Perpendicularity of front barrel seat incorrect		.65	3.2	SMTE
107	Inside diameter of rear cavity incorrect (.900 + .003)		.65	3.2	SMTE
108	Outside diameter of countersink incorrect (.31 + .01)		.65	3.2	SMTE
109	True position of O.D. of countersink hole incorrect		.65	3.2	SMTE
110	Overall length incorrect (4.30 - .04)		.65	3.2	SMTE
111	Depth of rear cavity incorrect (.75 + .02)		.65	3.2	SMTE
112	Front internal spherical radius incorrect (.23 + .01)		.65	3.2	SMTE

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER 11833464
4.4.2.2	Chamber				NEXT HIGHER ASSEMBLY 11833460
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
113	Front inside diameter incorrect (.83 + .02)		.65	3.2	SMTE
114	True position of front inside diameter incorrect		.65	3.2	SMTE
115	Diameter of orifice incorrect (.158 + .006)		.65	3.2	SMTE
116	True position of orifice incorrect		.65	3.2	SMTE
117	Diameter of locking groove incorrect (1.000 - .002)		.65	3.2	SMTE
118	True position of locking groove incorrect		.65	3.2	SMTE
119	Locking groove radius incorrect (.094 + .002R)		.65	3.2	SMTE
120	True position of locking groove radius incorrect		.65	3.2	SMTE
121	Distance from front surface to shoulder incorrect (.65 + .01)		.65	3.2	SMTE

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63447(AR)

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER 11833464
4.4.2.2	Chamber				NEXT HIGHER ASSEMBLY 11833460
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
MINOR:					
201	Width of clamping surface incorrect		1.50	3.2	SMTE
202	Width of wrench flats incorrect (.905 - .005)		1.50	3.2	SMTE
203	True position of wrench flats		1.50	3.2	SMTE
204	Diameter of clamping surface incorrect (1.02 - .02Ø)		1.50	3.2	SMTE
205	Improper finish		1.50	3.2	Visual
206	Evidence of poor workmanship		2.50	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 4	DRAWING NUMBER
4.4.2.3	Discriminator, Cartridge		11833463 (3 shts)
			NEXT HIGHER ASSEMBLY
			11833472

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101	Salt Spray Test	5		3.2	4.5.2
102	Hardness	5		3.2	4.5.3
103	Width of arm incorrect (1.06 - .01) (2 places) (Sht 2)		.65	3.2	SMTE
104	Width of feed arch to flat incorrect (.250 + .005) (2 places) (Sht 2)		.65	3.2	SMTE
105	Height from base of arm to start of flat incorrect (.625 ± .005) (2 places) (Sht 2)		.65	3.2	SMTE
106	Height of flat incorrect (.150 + .005) (2 places) (Sht 2)		.65	3.2	SMTE
107	Width of inner arm incorrect (.565 - .005) (2 places) (Sht 2)		.65	3.2	SMTE
108	Feed arch radius incorrect (.250 + .005) (2 places) (Sht 2)		.65	3.2	SMTE
109	Flatness of surface "L" incorrect (2 places (Sht 2)		.65	3.2	SMTE
110	Width of slot between right feed arm and support incorrect (.16 + .01) (Sht 2)		.65	3.2	SMTE

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 4		DRAWING NUMBER 11833463 (3 shts)
4.4.2.3	Discriminator, Cartridge				NEXT HIGHER ASSEMBLY 11833472
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
111	Width of slot between left feed arm and support incorrect (.225 + .005) (Sht 2)		.65	3.2	SMTE
112	Thickness of inner arms incorrect (.180 - .005) (2 places) (Sht 2)		.65	3.2	SMTE
113	Radius of feed tray lip slot incorrect (.310 + .005R) (2 places (Sht 2)		.65	3.2	SMTE
114	Distance from radius of feed tray lip slot to outer surface of arm incorrect (.54 + .01) (2 places) (Sht 2)		.65	3.2	SMTE
115	Distance from center location of feed tray lip radius to outer surface of arm incorrect (.425 ± .005) (2 places) (Sht 2)		.65	3.2	SMTE
116	Width from outer surface to inner surface at base incorrect (.220 - .003) (2 places) (Sht 2)		.65	3.2	SMTE
117	Distance from arm base to tray lip slot incorrect (2.83 - .02) (2 places) (Sht 1)		.65	3.2	SMTE
118	Distance from feed arch base to feed tray support incorrect (.68 - .02) (2 places) (Sht 1)		.65	3.2	SMTE

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63447(AR)

PARAGRAPH	TITLE	SHEET 3 OF 4	DRAWING NUMBER 11833463 (3 shts)
4.4.2.3	Discriminator, Cartridge		NEXT HIGHER ASSEMBLY 11833472

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
119	Perpendicularity requirement not met (2 places) (Sht 1)		.65	3.2	SMTE
120	Diameter of wire rope insert incorrect (.20 + .02) (Sht 1)		.65	3.2	SMTE
121	Height from arm base to edge of cut out incorrect (2.35 + .02) (2 places) (Sht 1)		.65	3.2	SMTE
122	Diameter pin spring hole incorrect (1.25 + .004) (Sht 1)		.65	3.2	SMTE
123	Height from arm base to base of feed tray support incorrect (1.75 + .02) (2 places) (Sht 1)		.65	3.2	SMTE
MINOR					
201	Maximum overall width incorrect (1.32 - .02) (2 places) (Sht 1)		1.50	3.2	SMTE
202	Overall height incorrect (3.95 - .02) (2 places) (Sht 1)		1.50	3.2	SMTE
203	Height from arm base to edge of feed tray clearance at hinge incorrect (.46 ± .03) (2 places) (Sht 1)		1.50	3.2	SMTE
204	Width of angled surface to arm base incorrect (.150 + .005) (2 places) (Sht 1)		1.50	3.2	SMTE

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Discriminator, Cartridge	4 OF 4	11833463 (3 shts)
			NEXT HIGHER ASSEMBLY 11833472

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
205	Height of cut out for feed tray clearance incorrect (.25 + .03) (2 places) (Sht 1)		1.50	3.2	SMTE
206	Blend angle at feed arch incorrect ($55^{\circ} \pm 3^{\circ}$) (2 places) (Sht 1)		1.50	3.2	SMTE
207	Marking missing or incorrect		1.50	3.2	SMTE
208	Improper surface finish as specified		1.50	3.2	Visual
209	Improper protective finish as specified		1.50	3.2	Visual
210	Pitch diameter, 8-36 UNF-2B, Max		1.50	3.2	SMTE
211	Pitch diameter, 8-36 UNF-2B, Min		1.50	3.2	SMTE
212	Evidence of poor workmanship		2.50	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63447(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11833467
4.4.2.4	Wire Rope Assembly				NEXT HIGHER ASSEMBLY 11833472
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101	Pull-off test		.65	3.2	SMTE
102	Incorrect assembly or missing parts		.65	3.2	Visual
MINOR:					
201	Overall length incorrect		1.5	3.2	SMTE
202	Evidence of poor workmanship		2.5	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63447(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11833466
4.4.2.5	Clamp				NEXT HIGHER ASSEMBLY 11833467
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101	Inside diameter (free state), incorrect		.65	3.2	SMTE
102	Width of clamp incorrect		.65	3.2	SMTE
103	Spring force expanded state incorrect		.65	3.2	SMTE
MINOR:					
201	Protective finish improper		1.50	3.2	Visual
202	Thickness of clamp incorrect		1.50	3.2	SMTE
203	Evidence of poor workmanship		2.50	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11833450
4.4.2.6	Extension Assembly				NEXT HIGHER ASSEMBLY 11833448
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101	Peening missing or improper		.65	3.2	Visual
102	Missing parts or improper assembly		.65	3.2	Visual/Manual
MINOR:					
201	Evidence of poor workmanship		2.50	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63447(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Extension & Clamp Assembly	1 OF 1	11833454
			NEXT HIGHER ASSEMBLY 11833450

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101	Crimp improper		.65	3.2	Visual
102	Load test		.65	3.2	SMTE
103	Deflection requirements not met		.65	3.2	SMTE
MINOR:					
201	Finish improper		1.50	3.2	Visual
202	Evidence of poor workmanship		2.50	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 11833451
4.4.2.8	Body, Clamp				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101	Salt Spray Test	5		3.2	4.5.2
102	Diameter of lever side counterbore incorrect (.310 + .010)		.65	3.2	SMTE
103	True position of lever side counterbore incorrect		.65	3.2	SMTE
104	Diameter of thru hole incorrect (.187 + .003)		.65	3.2	SMTE
105	True position of thru hole incorrect		.65	3.2	SMTE
106	Depth of lever side counterbore incorrect (.22 + .01)		.65	3.2	SMTE
107	Location of lever side counterbore surface to centerline incorrect (.62 - .01)		.65	3.2	SMTE
108	Depth of largest counterbore incorrect (.24 + .02)		.65	3.2	SMTE
109	Overall depth of counterbore to thru hole incorrect (.48 + .02)		.65	3.2	SMTE
110	Distance from surface of largest counterbore to centerline incorrect (.88 - .01)		.65	3.2	SMTE
111	Rear inside diameter incorrect (1.125 + .01)		.65	3.2	SMTE

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 11833451
4.4.2.8	Body, Clamp				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
112	Diameter of largest counterbore incorrect (.50 + .01)		.65	3.2	SMTE
113	True position of largest counterbore incorrect		.65	3.2	SMTE
114	Smallest diameter counterbore on button side incorrect (.310 + .010)		.65	3.2	SMTE
115	True position of smallest diameter counterbore on button side incorrect		.65	3.2	SMTE
116	Front inside diameter incorrect (1.375 + .005)		.65	3.2	SMTE
117	True position of front inside diameter incorrect		.65	3.2	SMTE
118	Width of lever slot incorrect (.15 + .01)		.65	3.2	SMTE
119	True position of lever slot incorrect		.65	3.2	SMTE
120	Distance from edge to centerline (.350 + .005)		.65	3.2	SMTE
MINOR:					
201	Improper finish		1.50	3.2	Visual
202	Overall length		1.50	3.2	SMTE
203	Distance from lever edge to centerline incorrect (.69 - .01)		1.50	3.2	SMTE
204	Evidence of poor workmanship		2.50	3.8	SMTE

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER 11833449
4.4.2.9	Extension		NEXT HIGHER ASSEMBLY 11833448

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101	Hardness	5		3.2	4.5.3
102	Salt Spray Test	5		3.2	4.5.2
103	Outside diameter at largest shperical end incorrect (1.374 - .004)		.65	3.2	SMTE
104	Depth of taper at spherical end incorrect (.30 + .01)		.65	3.2	SMTE
105	Second largest outside diameter at front end incorrect (1.46 - .01)		.65	3.2	SMTE
106	True position of outside diameter at largest spherical end		.65	3.2	SMTE
107	Inside diameter at taper at spherical end incorrect (.85 + .01Ø)		.65	3.2	SMTE
108	Depth of left taper end and hole incorrect (.89 - .01)		.65	3.2	SMTE
109	True position of second largest front outside diameter		.65	3.2	SMTE
110	Largest front outside diameter incorrect (1.51 - .01Ø)		.65	3.2	SMTE
111	True position of largest front outside diameter incorrect		.65	3.2	SMTE

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER 11833449
4.4.2.9	Extension		NEXT HIGHER ASSEMBLY 11833448

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
112	Inside diameter at front end incorrect (1.25 + .01Ø)		.65	3.2	SMTE
113	True position of inside diameter at front end incorrect		.65	3.2	SMTE
MINOR					
201	Protective finish improper		1.50	3.2	Visual
202	Surface finish improper		1.50	3.2	Visual
203	Evidence of poor workmanship		2.50	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER 11833452
4.4.2.10	Shaft		NEXT HIGHER ASSEMBLY 11833450

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101	Hardness	5		3.2	4.5.3
102	Salt Spray Test	5		3.2	4.5.2
103	Thickness of lever		.65	3.2	SMTE
104	True position of lever		.65	3.2	SMTE
105	Distance from shaft end to base of lever incorrect (1.64 + .01)		.65	3.2	SMTE
106	Diameter of shaft base incorrect (.300 - .005)		.65	3.2	SMTE
107	True position of shaft base incorrect		.65	3.2	SMTE
108	Release radius incorrect (.625 + .010)		.65	3.2	SMTE
109	True position of release radius incorrect		.65	3.2	SMTE
110	Overall length of shaft incorrect (1.42 + .01)		.65	3.2	SMTE
111	Depth of release radius cut incorrect (.060 + .005)		.65	3.2	SMTE
112	Length of small shaft end incorrect (.30 + .01)		.65	3.2	SMTE

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 11833452
4.4.2.10	Shaft				NEXT HIGHER ASSEMBLY 11833450
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
113	Diameter of largest shaft section incorrect (.186 - .002)		.65	3.2	SMTE
114	Diameter of smallest shaft incorrect (.155 - .002)		.65	3.2	SMTE
115	True position of smallest shaft incorrect		.65	3.2	SMTE
MINOR:					
201	Improper finish		1.50	3.2	SMTE
202	Diameter of shaft end cut out incorrect (.10 + .01)		1.50	3.2	SMTE
203	Evidence of poor workmanship		2.50	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11833453
4.4.2.11	Button				NEXT HIGHER ASSEMBLY 11833450
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101	Salt Spray Test	5		3.2	4.5.2
102	Hardness	5		3.2	4.5.3
103	Inside diameter incorrect		.65	3.2	SMTE
104	Outside diameter incorrect		.65	3.2	SMTE
105	True position of inside diameter incorrect		.65	3.2	SMTE
MINOR:					
201.	Outside diameter of counterbore incorrect		1.50	3.2	SMTE
202.	Improper finish		1.50	3.2	SMTE
203.	Evidence of poor workmanship		2.50	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11833455
4.4.2.12	Support Assembly				NEXT HIGHER ASSEMBLY 11833448
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101	Staking of bolt end missing or improper		.65	3.2	Visual
102	Missing parts or improper assembly		.65	3.2	Visual
MINOR:					
201	Evidence of poor workmanship		2.50	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.13	Support		11833456
			NEXT HIGHER ASSEMBLY 11833455

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101	Salt Spray Test	5		3.2	4.5.2
102	Width of hinge opening incorrect (.50 + .02)		.65	3.2	SMTE
103	Thickness of backhinge support incorrect (.38 - .01)		.65	3.2	SMTE
104	Width of bolt end opening incorrect (.40 + .02)		.65	3.2	SMTE
105	Thickness of back bolt support incorrect (.42 - .01)		.65	3.2	SMTE
106	Thickness between cut outs incorrect (.35 - .02) (Three places)		.65	3.2	SMTE
107	Overall width of support incorrect (1.51 - .02)		.65	3.2	SMTE
108	Distance from back surface to inner cut out surface incorrect (1.00 + .02)		.65	3.2	SMTE
109	Smallest outside diameter at back support incorrect (2.12 - .02)		.65	3.2	SMTE
110	True position of smallest outside diameter at back support incorrect		.65	3.2	SMTE

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 11833456
4.4.2.13	Support				NEXT HIGHER ASSEMBLY 11833455
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
111	Largest inside diameter at back support incorrect (3.62 + .02)		.65	3.2	SMTE
112	Distance from centerline to inside flats incorrect (1.75 + .01) (2 places)		.65	3.2	SMTE
113	Diameter of holes incorrect (.185 + .007) (2 holes) (2 places)		.65	3.2	SMTE
114	True position of holes incorrect		.65	3.2	SMTE
115	Diameter of O-ring groove incorrect (1.88 + .01)		.65	3.2	SMTE
116	True position of O-ring groove incorrect ~~(1.88 + .01)~~		.65	3.2	SMTE
117	Outside diameter of O-ring groove incorrect (1.62 + .01)		.65	3.2	SMTE
118	True position of outside diameter of O-ring groove incorrect		.65	3.2	SMTE
119	Width of O-ring groove incorrect (2.10 + .005)		.65	3.2	SMTE
120	Distance from back surface to O-ring groove incorrect (.15 - .01)		.65	3.2	SMTE
MINOR:					
201	Improper surface finish		1.50	3.2	Visual
202	Evidence of poor workmanship		2.50	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63447(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.14	Strap		11833457
			NEXT HIGHER ASSEMBLY 11833455

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101	Salt Spray Test	5		3.2	4.5.2
102	True position of slotted hole incorrect		.65	3.2	SMTE
103	Width of strap incorrect (1.00 - 0.2)		.65	3.2	SMTE
104	Overall length of strap incorrect (5.29 - .02)		.65	3.2	SMTE
105	Width of hinge end incorrect (.49 - .01)		.65	3.2	SMTE
106	Distance from front strap surface to front hinge surface incorrect (.10 + .01)		.65	3.2	SMTE
107	Diameter of hinge hole incorrect (.218 + .007)		.65	3.2	SMTE
108	True position of hinge hole incorrect		.65	3.2	SMTE
109	Location of strap end to cradle radius incorrect (2.63 ± .01)		.65	3.2	SMTE
110	Inner cradle radius incorrect (2.00 + .02R)		.65	3.2	SMTE
111	Outer cradle radius incorrect (2.28 - .02R)		.65	3.2	SMTE

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 11833457
4.4.2.14	Strap				NEXT HIGHER ASSEMBLY 11833455
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
112	Radius of hinge end cut out incorrect (.50 + .02R) (Both sides)		.65	3.2	SMTE
113	Hinge radius incorrect (.41 - .01R)		.65	3.2	SMTE
MINOR					
201	Distance from strap edge to slotted hole incorrect (.16 - .02)		1.5	3.2	SMTE
202	Width of slotted hole incorrect		1.5	3.2	SMTE
203	Length of slotted hole incorrect		1.5	3.2	SMTE
204	Thickness of strap end incorrect		1.5	3.2	SMTE
205	Evidence of poor workmanship		2.5	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 11833458
4.4.2.15	Bolt				NEXT HIGHER ASSEMBLY 11833455
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101	Salt Spray Test	5		3.2	4.5.3
102	Diameter of hole incorrect		.65	3.2	SMTE
103	True position of hole incorrect		.65	3.2	SMTE
104	Diameter of bolt head incorrectr		.65	3.2	SMTE
105	Pitch diameter, .375-24UNF-2A, THD, max, incorrect		.65	3.2	SMTE
106	Pitch diameter, .375-24UNF-2A, THD, min, incorrect		.65	3.2	SMTE
MINOR					
201	Protective finish improper		1.5	3.2	Visual
202	Evidence of poor workmanship		2.5	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

MIL-F-63447(AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 11833459
4.4.2.16	Chute				NEXT HIGHER ASSEMBLY 11833471
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101	Salt Spray Test	5		3.2	4.5.2
102	Distance from front wall to edges of left and right walls incorrect (5.13 - .04)		.65	3.2	SMTE
103	Angularity of front wall incorrect (21°)		.65	3.2	SMTE
104	Length of top left wall incorrect (4.20 - .04)		.65	3.2	SMTE
105	Height of left wall to flange incorrect (1.39 - .02)		.65	3.2	SMTE
106	Angularity of left wall incorrect (15° + 1°)		.65	3.2	SMTE
107	Height of right wall to flange incorrect (.81 - .02)		.65	3.2	SMTE
108	Flatness of bottom flange incorrect (.01)		.65	3.2	SMTE
109	Distance between bottom walls incorrect (2.12 - .02)		.65	3.2	SMTE

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 11833459
4.4.2.16	Chute				NEXT HIGHER ASSEMBLY 11833471
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
MINOR:					
201	Protective finish improper		1.50	3.2	Visual
202	Evidence of poor workmanship		2.50	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the applicable paragraphs. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6.3.

4.5 Test methods and procedures.

4.5.1 Dimensional control of cast parts. In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least five (5) parts (as cast) from each cavity shall be dimensionally inspected to qualify a new or reworked cavity for use in production or as a control of the cavity during production. Inspection for control of each cavity during production shall be performed on the above quantities from each cavity after production of 500 parts. Individual cavity identification shall be provided.

If any defective parts are found during qualification of the cavity, the cavity producting the defective part will not be used in production. If any defective parts are found when inspection is performed for control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for corrective action.

All cavities formerly removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test as above. The contractor may request a change of inspection frequency providing he presents objective evidence of substantiate the request to the Contracting Officer.

4.5.2 Salt spray test. Five (5) of each specified part shall be selected from each lot and subjected to the salt spray test in accordance with the procedures specified in ASTM B 117. The minimum exposure time shall be one and one half (1 1/2) hours using a 5% sodium chloride solution. If any part shows evidence of corrosion, it shall be classed defective and the lot shall be rejected.

4.5.3 Hardness. Five (5) of each of the specified parts shall be selected from each heat treatment batch (see NOTE) and subjected to this test. If any part fails to comply with the requirement specified on the applicable drawing, the batch represented by the failing part shall be rejected. The hardness test shall be performed in accordance with the procedure specified in ASTM E 18.

NOTE: A heat-treament batch shall be defined as parts that have been heat treated at the same time in the same furnace and quench bath for each of all phases of the entire heat treatment process.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.5.4 Functioning. Samples of blank ammunition firing attachments shall be tested for functioning as follows:

4.5.4.1 Firing Attachment, Blank, XM21. Government standard 7.62MM Blank M82 Cartridges and the 7.62MM M240/M240C machine gun series shall be used for testing XM21 blank ammunition firing attachments. The blank firing attachment shall be assembled in a belt of 100 rounds fired in bursts of 20 rounds.

4.5.5 Assembleability. The Blank Firing Attachment and its ancillary components, (see Dwg. 11833471) shall readily attach to and detach from the specified weapon or a fixture simulating the specified weapon. When attached, firing attachments shall be securely retained on a simulator fixture or specified weapon.

5. PACKAGING

5.1 Levels A and B. The blank firing attachments shall be packaged in accordance with the Packaging Data Sheet and as specified in the contract.

5.2 Marking. Marking shall be in accordance with applicable Packaging Data Sheet and as specified in the contract.

5.3 Shipping. When components from more than one lot are shipped at one time, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. The assembly covered by this specification is intended for use with Machine Gun, 7.62MM, M240/M240C Machine Gun.

6.2 Ordering data. See MIL-W-63150.

6.3 Submission of inspection equipment designs for approval. See MIL-W-63150. Submit equipment desings as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAF-I, ARRADCOM, Dover, NJ 07801. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects or test paragraph number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading "U.S. Amry Armament Research and Development Command" (ARRADCOM) may also include drawings prepared by and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities are not under the cognizance of ARRADCOM.

Custodians:
Army-AR

Preparing activity:
Army-AR

(Project 1005-A607)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.