INCH-POUND

MIL-F-64042A (AR)
AMENDMENT 2
25 September 1991
SUPERSEDING
AMENDMENT 1
8 April 1988

MILITARY SPECIFICATION

FUZE, MT, SQ, M577A1
LOADING, ASSEMBLING, PACKING AND METAL PARTS
FUZE, MT, SQ, M582A1 METAL PARTS

This amendment forms a part of Military Specification MIL-F-64042A (AR), dated 6 June 1986, and is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.3: After the second sentence, add the following sentence:

"There shall not be any sealant internally beyond the body and ogive thread."

PAGE 4

3.11.3.1: Change to read as follows:

"3.11.3.1 Target impact non-function distance. The fuze, when set PD (see 6.5), shall not cause the projectile to function upon impact of the PD element when fired in the 105MM, M103 or M102 Tube, Charge 7 at a six (6) inch thick plywood target located 150 - 5 feet from the muzzle of the weapon."

PAGE 5

* 3.13 Delete in its entirety.

* Delete 3.15 and substitute the following:

"3.15 Marking. The SSD Assembly (see dwg. 9362838) and the Three Module Assembly (see dwg. 9352384 or 12554515), after undergoing critical classified tests, shall be marked as specified in 5.2 using mechanized equipment (preferably automated) in accordance with 4.4.4."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 6

* 3.19 Add Drawing "/12554516" after "see dwg. 9352376".

* Add the following paragraphs:

"3.22 Housing, barrel (see drawing 12554542). The Housing, Barrel shall not fracture when a load, as specified on the applicable drawing, is applied.

3.23 Barrel, mainspring, timer (see drawing 12554550). The Barrel, Mainspring, Timer shall not fracture, when a load as specified on the applicable drawing, is applied.

3.24 Housing, timer (see drawing 12554555). The Housing, Timer shall not fracture when a load, as specified on the applicable drawing, is applied.

3.25 Plate no. 1 timer (see drawing 12554579). The Plate No. 1, Timer teeth shall not fracture when a load, as specified on the applicable drawing, is applied.

3.26 Lubrication of timer assembly (see drawing 12598432). The contractor shall prepare a Process Control Document (PCD) in accordance with MIL-A-48078 for controlling lubrication of the timer."

PAGE 9

* Delete 4.3.1 and substitute the following:

"4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the items listed below in the sample quantities as indicated. In addition, when items are fabricated from die cast components, ten (10) components from each mold cavity shall be included in the first article sample. The components shall bear a mark which identifies the component with its individual cavity. The mark shall be located on a nonfunctional surface where subsequent machining operations will not obliterate the mark The three module assembly (dwg. 9352384 or dwg. 12554515), used only for first article examinations and tests, shall be loaded with inert detonators. These items shall be clearly and indelibly marked by the word "inert" on two visible surfaces located 180 apart. They will not be used for any testing that requires the functioning of the detonators."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 10

* Add the following drawings to the drawing column as shown:

Part Description	Drawing	Quantity
Plate No. 2, Timer	9236659/12554524	30
Lever Assembly, Timer	9236661/12554526	80
Plate No. 4 & Bearing, Assembly Timer	9236668/12554533	80
Escape Wheel & Pinion Assembly, Timer	9236672/12554530	80
Pinion, Escape, Timer	9236673/12554532	30
Wheel, Escape, Timer	9236674/12554531	30
Gear No. 1 & Pinion Assembly, Timer	9236675/12554535	30
Pinion, No. 1, Timer	9236677/12554537	30
Gear No. 2 & Pinion Assembly, Timer	9236678/12554538	80
Mainspring & Barrel Assembly, Timer	9236697/12554548	80
Pin, Setback, Timer	9236703/12554569	30

PAGE 11

* Add the following drawings to the drawing column as shown:

Part Description	Drawing	Quantity
Body Assembly	9352371/12554567	80
Body	9352372/12554568	30
Ogive	9352373/12554507	30
Key Setting	9352374/12554514	30
Plate, Top, Trigger	9352378/12554571	30
Trigger Assembly	12624555/12554570	80
Ogive Assembly	9362837/12554506	80

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Add the following items to the listed items:

Setting Key Assembly	12554508	80
Clutch Assembly	12554512	80
Three Module Assembly	12554515	80
Sleeve	12554516	40
Timer Assembly	12554517	80
Plate #1 Assembly	12554518	80
Plate #1, Timer	12554519	40
Pin, Pallet, Timer	12554529	30
Plate #4, Timer	12554534	30
Pinion #2, Timer	12554540	30
Housing, Barrel	12554542	40
Timing Scroll and Shaft Assy.	12554545	80
Timing Scroll, Timer	12554546	30
Shaft, Drive Gear, Timer	12554547	30
Barrel, Mainspring	12554550	40
Drive Gear	12554551	30
Timer Housing Assembly	12554554	30
Timer Housing, Timer	12554555	40
Setting Gear Assembly	12554556	80
Gear, Setting	12554557	40
Shaft, Setting	12554561	40
Counter Assembly	12554562	80
Ring, Retaining Counter	12554566	30
Timer Assembly	12624555	80
Plate No. 1 Assembly, Timer	12624556	80

Page 12

* Change from "Sheet 1 of 18" to "Sheet 1 of 24"

Page 13

* Change from "Sheet 2 of 18" to "Sheet 2 of 24"

Page 14

* Change from "Sheet 3 of 18" to "Sheet 3 of 24"

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Page 15

* Change from "Sheet 4 of 18" to "Sheet 4 of 24"

* After Dwg. 9236657, Add: "/12554522"

* After Dwg. 9236659, Add: "/12554524"

Page 16

* Change from "Sheet 5 of 18" to "Sheet 5 of 24"

* After Dwg. 9236661, Add: "/12554526"

* After Dwg. 9236668, Add: "/12554533"

Page 17

* Change from "Sheet 6 of 18" to "Sheet 6 of 24"

* After Dwg. 9236672, Add: "/12554530"

* After Dwg. 9236673, Add: "/12554532"

* After Dwg. 9236674, Add: "/12554531"

* After Dwg. 9236675, Add: "/12554535"

* After Dwg. 9236677, Add: "/12554537"

* After Dwg. 9236678, Add: "/12554538"

PAGE 18

* Change from "Sheet 7 of 18" to "Sheet 7 of 24"

PAGE 19

* Change from "Sheet 8 of 18" to "Sheet 8 of 24"

* After Dwg. 9236697, Add: "/12554548"

* After Dwg. 9236703, Add: "/12554569"

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:28Z
Check the source to verify that this is the currentversion before use.

PAGE 20

* Change from "Sheet 9 of 18" to "Sheet 9 of 24"

PAGE 21

* Change from "Sheet 10 of 18" to "Sheet 10 of 24"

PAGE 22

* Change from "Sheet 11 of 18" to "Sheet 11 of 24"

* After Dwg. 9352371, Add: "/12554567"

* After Dwg. 9352372, Add: "/12554568"

* After Dwg. 9352373, Add: "/12554507"

* After Dwg. 9352374, Add: "/12554514"

PAGE 23

* Change from "Sheet 12 of 18" to "Sheet 12 of 24"

* After Dwg. 9352378, Add: "/12554571"

PAGE 24

* Change from "Sheet 13 of 18" to "Sheet 13 of 24"

PAGE 25

* Change from "Sheet 14 of 18" to "Sheet 14 of 24"

* After Dwg. 9352387, Add: "/12554570"

PAGE 26

* Change from "Sheet 15 of 18" to "Sheet 15 of 24"

* After Dwg. 9362837, Add: "/12554507

PAGE 27

* Change from "Sheet 16 of 18" to "Sheet 16 of 24"

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 28

* Change from "Sheet 17 of 18" to "Sheet 17 of 24"

PAGE 29

* Change from "Sheet 18 of 18" to "Sheet 18 of 24"

* Add Pages 29a, 29b, 29c, 29d, 29e, and 29f. See included pages.

PAGE 34

* 4.4.2.4 Delete "9236546" and add "9362843" to the Next Higher Assembly block.

PAGE 35

* 4.4.2.5 Change Title:

From: "Detent Interlock, SSD"

To: "Detent, Spin, SSD"

PAGE 37

* 4.4.2.7 Add "12554562" to Next Higher Assembly block.

PAGE 38

* 4.4.2.8 Add "12554562" to Next Higher Assembly block.

PAGE 39

* 4.4.2.9 Change Title:

From: "Pinion, Setting"

To: "Gear, Setting"

PAGE 41

* 4.4.2.11 Add "12554515" to Next Higher Assembly block.

PAGE 42

* 4.4.2.12 Add "12554515" to Next Higher Assembly block.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Table I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 19 OF 24		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Timer Assembly (Dwg. 12624555)				
	Examination for Defects	30	-	3.2	4.4.2.98
	Timer Functioning Test	80	-	3.9.2	4.5.9
	Timer Non-Functioning Test	80	-	3.9.2	4.5.10
	SetBack Pin Arming Test	80	-	3.12	4.5.11
	Timer Beat Rate & Amplitude	80	-	3.2	4.5.13
	9 lb. Axial Load	40*	-	3.2	4.5.1.w
	Plate No. 1 Assembly Timer (Dwg. 12624556)				
	Examination for Defects	30	-	3.2	4.5.2.99
	50 lb. Torque Load on Ring Gear Assy	80	-	3.2	4.5.2.d
	5 lb. Axial unseating load on bushing	80	-	3.2	4.5.1.u
	5 lb. Axial unseating load on spin Detent Pivot Pin	80	-	3.2	4.5.1.t
	40 lb. Axial unseating load on Dowel Pins	80	-	3.2	4.5.1.v
	22 lb. Pull Off Load on Hairspring Support Bracket	40*	-	3.2	4.5.1.a.1

NOTES:

*Destructive Test

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Table I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 20 OF 24		DRAWING NUMBER
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Setting Key Assembly				
	(Dwg. 12554508)				
	Torque on Stop Washer	80		3.2	4.5.2.j
	Torque on Follower	40*		3.2	4.5.2.k
	Clutch Assembly				
	(Dwg. 12554512)				
	Grip Ring Torque	80		3.2	4.5.2.1
	Three Module Assembly				
	(Dwg. 12554515)				
	Examination for Defects	30		3.2	4.4.2.102
	4.5 Min. in.-lb. Setting Torque	80		3.2	4.5.2.p
	Sleeve				
	(Dwg. 12554516)				
	Examination for Defects	30		3.2	4.4.2.103
	Die Casting Defects	**		3.16	
	Load Test	*		3.19	4.5.22

NOTES:

*Destructive Test
**Ten pieces from each mold cavity

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Table I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 21 OF 24		DRAWING NUMBER NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Timer Assembly				
	(Dwg. 12554517)				
	Examination for Defects	30		3.2	4.4.2.104
	Timer Functioning Test	80		3.9.2	4.5.9
	Timer Non-Functioning Test	80		3.9.2	4.5.10
	Setback Pin Arming Test	80		3.12	4.5.11
	Timer Beat Rate & Amplitude	80		3.13	4.5.13
	9 lb. Axial Load	40*		3.2	4.5.1.w
	Plate No. 1 Assembly				
	(Dwg. 12554518)				
	Examination for Defects	30		3.2	4.4.2.105
	22 lb. Pull off Load on Hairspring Support Bracket	80		3.2	4.5.1.al
	Plate No. 1 Timer				
	(Dwg. 12554519)				
	Examination for Defects	30		3.2	4.4.2.106
	Torque Test	10*		3.2	4.5.2.m
	Die Casting Defects	**		3.2 & 3.16	
	Pin, Pallet, Timer				
	(Dwg. 12554529)				
	Examination for Defects	30		3.2	4.4.2.107
	Plate No. 4, Timer				
	(Dwg. 12554534)				
	Examination for Defects	30		3.2	4.4.2.108

NOTES:
*Destructive Test
**Ten pieces from each mold cavity

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Table I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 22 OF 24		DRAWING NUMBER
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Pinion No. 2, Timer				
	(Dwg. 12554540)				
	Examination for Defects	30		3.2	4.4.2.109
	Housing, Barrel				
	(Dwg. 12554542)				
	Examination for Defects	30		3.2	4.4.2.110
	Die Casting Defects	**		3.2 & 3.16	4.5.1.ao
	Static Load Test	10*		3.2	
	Timing Scroll and Shaft Assembly				
	(Dwg. 12554545)				
	20 lb Push Off Force	80		3.2	4.4.2.111, 4.5.1.am
	Scroll, Timing, Timer				
	(Dwg. 12554546)				
	Examination for Defects	30		3.2	4.4.2.112
	Die Casting Defects	**		3.2 & 3.16	
	Barrel, Mainspring				
	(Dwg. 12554550)				
	Die Casting Defects	**		3.2 & 3.16	
	Static Load	*10		3.2	4.5.1.ap

NOTES:
*Destructive Test
**10 pieces from each mold cavity

Source: https://assist.dla.mil (29d) Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Table I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 23 OF 24		DRAWING NUMBER
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Drive, Gear (Dwg. 12554551)				
	Examination for Defects	30		3.2	4.4.2.114
	Timer Housing Assembly (Dwg. 12554554)				
	Examination for Defects	80		3.2	4.4.2.115
	Housing, Timer (Dwg. 12554555)				
	Die Casting Defects	**		3.2 & 3.16	4.4.2.116
	Static Load	10*		3.2	4.5.1.aq
	Setting Gear Assembly (Dwg. 12554556)				
	20 lb. Push Off Load on Shaft	80		3.2	4.5.1.an
	Gear, Setting (Dwg. 12554557)				
	Examination for Defects	30		3.2	4.4.2.118
	Torque Test	10*			4.5.2.n
	Shaft, Setting (Dwg. 12554561)				
	Examination for Defects	30		3.2	4.4.2.119
	Torque Test	10*		3.2 & 3.16	4.5.2.o
	Die Casting Defects	**			

NOTES:
*Destructive Test
**10 pieces from each mold cavity

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Table I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF	DRAWING NUMBER
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	NEXT HIGHER ASSEMBLY / PARAGRAPH REFERENCE / INSPECTION METHOD
	Counter Assembly (Dwg. 12554562)				
	Counter Wheel Transfer	80		3.10	4.5.12
	Examination for Defects	30		3.2	4.4.2.120
	Ring, Retaining, Counter (Dwg. 12554566)				
	Die Casting Defects	**		3.2 & 3.16	
	Shaft, Drive Gear, Timer (Dwg. 12554547				
	Examination for Defects	30		3.2	4.4.2.123

NOTES:

** 10 pieces out of each mold cavity

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 43

* 4.4.2.13 Add "12554570" to Next Higher Assembly block.

PAGE 46

* 4.4.2.16 Add "12554570" to Next Higher Assembly block.

PAGE 50

* 4.4.2.20 Add "12554570" to Next Higher Assembly block.

PAGE 52

* 4.4.2.22 Add "12554570" to Next Higher Assembly block.

PAGE 53

4.4.2.23 Add "12624556" to Next Higher Assembly block.

PAGE 54

4.4.2.24 Add "12624556" to Next Higher Assembly block.

PAGE 56

* 4.4.2.26 Add "12554522" to Drawing Number block

Add "12554517" to Next Higher Assembly block.

PAGE 57

* 4.4.2.27 Add "12554517/12624555" to Next Higher Assembly block.

*

Add "12554524" to Drawing Number block

PAGE 58

* 4.4.2.28 Add "12554526" to Drawing Number block.

4.4.2.28 Add "12554517/12624555" to Next Higher Assembly block.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:28Z
Check the source to verify that this is the currentversion before use.

PAGE 61

* 4.4.2.31 Add "12554533" to Drawing Number block.

4.4.2.31 Add "12554517/12624555" to Next Higher Assembly block.

PAGE 63

* 4.4.2.33 Add "12554533" to Next Higher Assembly block.

PAGE 64

* 4.4.2.34 Add "12554530" to Drawing Number block.

4.4.2.34 Add "12554517/12624555" to Next Higher Assembly block.

PAGE 65

* 4.4.2.35 Add "12554532" to Drawing Number block.

Add "12554517" to Next Higher Assembly block.

PAGE 66

* 4.4.2.36 Add "12554531" to Drawing Number block.

Add "12554517" to Next Higher Assembly block.

PAGE 67

* 4.4.2.37 Add "12554535" to Drawing Number block.

4.4.2.37 Add "12554517/12624555" to Next Higher Assembly block.

PAGE 68

* 4.4.2.38 Add "12554537" to Drawing Number block.

Add "12554535" to Next Higher Assembly block.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 69

* 4.4.2.39 Add "12554538" to Drawing Number block.

4.4.2.39 Add "12554517/12624555" to Next Higher Assembly block.

PAGE 71

4.4.2.41 Add "12624555" to the Next Higher Assembly block.

PAGE 72

4.4.2.42 Add "12624555" to the Next Higher Assembly block.

PAGE 73

4.4.2.43 Add "12624555" to the Next Higher Assembly block.

PAGE 74

4.4.2.44 Add "12624555" to the Next Higher Assembly block.

PAGE 79

* 4.4.2.49 Add "12554548" to Drawing Number block.

Add "12554544" to the Next Higher Assembly block.

PAGE 80

4.4.2.50 Add "12624555" to the Next Higher Assembly block.

PAGE 81

* 4.4.2.51 Add "12554569" to Drawing Number block.

Add "12554517" to the Next Higher Assembly block.

PAGE 82

4.4.2.52 Add "12624555" to the Next Higher Assembly block.

PAGE 84

* 4.4.2.54 Major 108, delete "3.13" and add "3.2".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 89

4.4.2.59 Add "12554518/12624556" to the Next Higher Assembly block.

PAGE 92

* 4.4.2.62 Add "12554567" to Drawing Number block.

PAGE 93

* 4.4.2.63 Add "12554568" to Drawing Number block.

Add "12554567" to the Next Higher Assembly block.

PAGE 94

* 4.4.2.64 Add "12554507" to Drawing Number block.

Add "12554506" to the Next Higher Assembly block.

PAGE 95

* 4.4.2.65 Add "12554514" to Drawing Number block.

Add "12554508" to the Next Higher Assembly block.

PAGE 99

* 4.4.2.69 Add "12554571" to Drawing Number block.

Add "12554570" to the Next Higher Assembly block.

PAGE 100

* 4.4.2.70 Add "12554570" to the Next Higher Assembly block.

PAGE 102

4.4.2.72 Major 105, change "adhesive" to "sealant".

* 4.4.2.72 Add Major 106 as follows: "106, Limiter stop test, 100%, 3.2, Gage."

* Add in the Notes block "Major Category 106 only applies for Part Number 9352381-2 and 9352382-2."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 104

4.4.2.73: Delete Info Category 300, and add the following Major Category:

"108 Evidence of sealant beyond the body and ogive threads, i, h, 3.2 and 3.3"

PAGE 105

Add note i as follows:

"i To be performed on fuzes that are disassembled after Jolt and Jumble, transportation vibration, twelve meter drop and waterproofness tests."

PAGE 109

4.4.2.76 Add "12554570" to Drawing Number block.

PAGE 110

4.4.2.77 Add "12554506" to Drawing Number block.

PAGE 118

4.4.2.85 Add "12554570" to Next Higher Assembly block.

PAGE 119

4.4.2.86 Add "12554570" to Next Higher Assembly block.

PAGE 120

* 4.4.2.87 Add "12554570" to Next Higher Assembly block.

PAGE 130

* Add pages 130a, 130b, 130c, 130d, 130e, 130f, 130g, 130h, 130j, 130k, 130kk, 130m, 130n, 130p, 130q, 130r, 130s, 130t, 130u, 130v, 130w, 130x, 130y, 130z, 130aa, 130ab, See included pages.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.98	Timer Assembly	1 OF 1	12624555
			NEXT HIGHER ASSEMBLY 9236718

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Limits of angle between tumbler and scroll exit port		0.40%	3.2	Gage
102	Balance wheel not detented in proper position and setback detent not restraining spin detent		0.40%	3.2	Visual
103	Mainspring not wound as indicated		0.40%	3.2	Manual
104	Mainspring barrel stakes missing or insufficient		0.40%	3.2	Visual
105	Timer function test	a	100%	3.9.2	4.5.6
106	Timer non-function test	a	100%	3.9.2	4.5.10
107	Setback pin arming test	a	100%	3.12	4.5.11
108	Timer beat rate and amplitude	a	100%	3.2	4.5.13
109	Expansion plug above flush		0.40%	3.2	Visual
110	Protective cap missing		0.65%	3.2	Visual
111	9 lb. axial load	b	c	3.2	4.4.3.4
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

a. Non destructive
b. Destructive test, see par 4.4.3.4 for applicable sampling plan.
c. Reject timer assembly inspection lot if one (1) or more defective units are found.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.99	Plate No. 1 Assembly, Timer				12624556
					NEXT HIGHER ASSEMBLY 12624555
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of balance wheel, staff and hairspring assembly		0.40%	3.2	Gage
102	50 in. lb. torque load on ring gear assembly	a	0.40%	3.2	4.5.2.d
103	5 lb. axial unseating load on spin detent pin	a	0.40%	3.2	4.5.1.t
104	5 lb. axial unseating load on bushing	a	0.40%	3.2	4.5.1.u
105	40 lb. axial unseating load on dowel pins	a	0.40%	3.2	4.5.1.v
106	Balance wheel outside tolerance zone	a	0.40%	3.2	Gage
107	22 lb. pull off load on hairspring support bracket	b	0.40%	3.2	
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

a. Non destructive test
b. Destructive test

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Table I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.100	Setting Key Assembly				12554508
					NEXT HIGHER ASSEMBLY 12554506
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical.	None Defined				
Major					
101	Torque on Stop Washer	a	0.40%	3.2	4.5.2.j
102	Torque on Follower	b	0.40%	3.2	4.5.2.k
Minor					
201	Evidence of Poor Workmanship		1.0%	3.3	Visual

NOTES:

a. Non-destructive Test
b. Destructive Test

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Table I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12554512
4.4.2.101	Clutch Assembly				NEXT HIGHER ASSEMBLY 12554508
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical.	None Defined				
Major 101	Grip Ring Torque	a	0.40%	3.2	4.5.2.1
Minor 201	Evidence of Poor Workmanship		1.0%	3.3	Visual

NOTES:

a. Non-Destructive Test

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Table I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.102	Three Module Assembly				12554515
					NEXT HIGHER ASSEMBLY 9352381/9352382
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Setback detent dows not hold spin detent in position to lock the trigger in the unfired position		100%	3.2	Visual
2	SSD release lever missing or not restrained by firing armshaft in unfired position		100%	3.2	Visual
Major					
101	Timer housing stakes missing or insecure		0.40%	3.2	Visual/Manual
102	Setback retainer stakes missing or insecure		0.40%	3.2	Visual/Manual
103	Zero setting improper		0.40%	3.2	Visual
104	Trigger assembly not in unfired position		0.40%	3.2	Visual
105	Grease missing in setback pin cavity		0.40%	3.2	Visual
106	4.5 min. in.-lb. Setting Torque	a	0.40%	3.2	4.5.2.p

NOTES:

a. Non-Destructive Test

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.102	THREE MODULE ASSEMBLY				12554515
					NEXT HIGHER ASSEMBLY 9352381/9352382
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
107	Trigger Setback Function		0.40%	3.12	4.5.14
108	True Position of Hairline		0.40%	3.12	Gage
109	Gap Between Trigger and Sleeve		0.65%	3.2	Visual
Minor					
201	Evidence of Poor Workmanship		1.0%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Table I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12554516
4.4.2.103	Sleeve				NEXT HIGHER ASSEMBLY 12554515
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Barrel Dia., Max.		0.40%	3.2	Gage
102	Scroll Dia., Min.		0.40%	3.2	Gage
103	True Position of Scroll Dia.		0.40%	3.2	Gage
104	Dia. of Trigger Location Pin Holes, Max.		0.40%	3.2	Gage
105	True Position of Trigger Location Pin Hole		0.40%	3.2	Gage
106	Depth of Release Slot, Min.		0.40%	3.2	Gage
107	Height of Scroll Dia., Max.		0.40%	3.2	Gage
108	Die Casting Defects	10	a	3.2&3.16	Visual W/Aid c (See 6.12)
109	Load Test	10b	a	3.19	4.5.22
Minor					
201	Evidence of Poor Workmanship		1.0%	3.3	Visual

NOTES:
a. Reject the lot if one or more defective units are found
b. Destructive test

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Table I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.104	Timer Assembly				12554517
					NEXT HIGHER ASSEMBLY
					12554515
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical.	None defined				
Major					
101	Balance Wheel Not Detented in Proper Position and Setback Detent Not Restraining Spin Detent		0.40%	3.2	Visual
102	Mainspring Not wound as Indicated		0.40%	3.2	Manual
103	Mainspring Barrel Stakes Missing or Insufficient		0.40%	3.2	Visual
104	Timer Function Test	a	100%	3.9.2	4.5.9
105	Timer Non-function Test	a	100%	3.9.2	4.5.10
106	Setback Pin Arming Test	a	100%	3.12	4.5.11
107	Timer Beat Rate and Amplitude	a	100%	3.2	4.5.13
108	9 lb Axial Load	b	c	3.2	4.5.1.w
109	Grease Missing in Setback Pin Cavity		100%	3.2	Visual
Minor					
201	Evidence of Poor Workmanship		1.0%	3.3	Vsiual

NOTES:
a. Non-destructive Test
b. Destructive test see para. 4.4.3.4 for applicable sampling plan
c. Reject timer assembly inspection lot if one or more defective units are found

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 20260-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-F-64042A (AR)
AMENDMENT 2

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.105	PLATE NO. 1 ASSEMBLY				12554518
					NEXT HIGHER ASSEMBLY
					12554517
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	True Position of Balance Wheel, Staff and Hairspring Assembly		0.40%	3.2	Gage
102	Balance Wheel Outside Tolerance Zone		0.40%	3.2	Gage
103	22 lb. Min. Pullout Force on Hairspring Support Bracket		0.40%	3.2	4.5.1.a1
Minor					
201	Evidence of Poor Workmanship		1.0%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.106	PLATE NO. 1, TIMER		12554519
			NEXT HIGHER ASSEMBLY
			12554518

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Height from Bottom to Wheel Surface, Min.		0.40%	3.2	Gage
102	Screw Hold Dia. Max.		0.40%	3.2	Gage
103	Dia. of Bracket Hole Max.		0.40%	3.2	Gage
104	Torque Test	b	0.40%	3.25	4.5.2.m
105	Die Casting Defects	10	a	3.16	Visual W/Aid C See (6.12)
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:
a. Reject lot if one or more defective units are found
b. Destructive Test

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-F-64042A (AR)

AMEMDMENT 2

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12554529
4.4.2.107	Pin, Pallet, Timer				NEXT HIGHER ASSEMBLY 12554526
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major 101	Distance from lever seat to end of pin		0.40%	3.2	Gage
Minor 201	Evidence of poor workmanship		1.0%	3.3	Visual W/Aid C (See 6.12)

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.108	PLATE NO. 4, TIMER		12554534
			NEXT HIGHER ASSEMBLY 12554533

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	True Position of Gear and Pinion No. 2 Pivot Hole		0.40%	3.2	Gage
102	True Position of Gear and Pinion No. 1 Pivot Hole		0.40%	3.2	Gage
103	True Position of Lever Hole		0.40%	3.2	Gage
104	True Position of Location Pin Slot		0.40%	3.2	Gage
105	Dia. of Lever Hole		0.40%	3.2	Gage
106	Dia. of Gear and Pinion No. 2 Pivot Hole Max.		0.40%	3.2	Gage
107	Dia. of Gera and Pinion No. 1 Pivot Hole Max.		0.40%	3.2	Gage
108	Dia. of Location Pin Hole Max.		0.40%	3.2	Gage
109	Width of Location Pin Slot Max.		0.40%	3.2	Gage
Minor					
201	Evidence of Poor Workmanship		1.0%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.109	PINION NO. 2, TIMER				12554540
					NEXT HIGHER ASSEMBLY 12554538
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Dia. of Upper Pivot, Min.		0.40%	3.2	Gage
102	Dia. of Lower Pivot, Min.		0.40%	3.2	Gage
103	Total Composite Error		0.40%	3.2	Gage
104	Tooth to Tooth Composite Error		0.40%	3.2	Gage
Minor					
201	Evidence of Poor Workmanship		1.0%	3.3	Visual W/Aid B (See 6.12)

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12554542
4.4.2.110	HOUSING, BARREL				NEXT HIGHER ASSEMBLY 12554517
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Dia. of Location Pin Holes Max		0.40%	3.2	Gage
102	Dia. of Gear & Pinion No. 2 Hole Max.		0.40%	3.2	Gage
103	Dia. of Gear & Pinion No. 1 Hole Max.		0.40%	3.2	Gage
104	Dia. of Escapement Hole Max.		0.40%	3.2	Gage
105	Dia. of Scroll Shaft Pivot Hole Max.		0.40%	3.2	Gage
106	Depth of Barrel Dia. Min.		0.40%	3.2	Gage
107	Outside Dia. of Barrel Min.		0.40%	3.2	Gage
108	True Position of Location Pin Hole		0.40%	3.2	Gage
109	True Position of Gear & Pinion No. 2 Pivot Hole		0.40%	3.2	Gage
110	True Position of Gear & Pinion No. 1 Pivot Hole		0.40%	3.2	Gage
111	Lenght of Minor Outside Dia. Max.		0.40%	3.2	Gage
112	Die Casting Defects	10	a	3.16	Visual W/Aid C (See 6.12)
113	Static Load Test	10b	a	3.22	4.5.1.ao
Minor					
201	Evidence of Poor Workmanship		1.0%	3.3	Visual

NOTES:
a. Reject lot if one or more defective units found
b. Destructive Test

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.111	TIMING SCROLL AND SHAFT ASSEMBLY				12554545
					NEXT HIGHER ASSEMBLY 12554544
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical.	None Defined				
Major 101	20 lb. push-off force	a	0.40%	3.2	4.5.1.am
Minor 201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

a. Non-Destructive Test

Source: https://assist.dla.mil Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.112	SCROLL, TIMING, TIMER	1 OF 1	12554546
			NEXT HIGHER ASSEMBLY 12554545

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Discontinuity or crack in spiral wall		100%	3.2	Visual W/Aid A
Major					
101	Die casting defects	10	a	3.16	Visual W/Aid C
102	Depth of grooves, min.		0.40%	3.2	Gage
103	Height of lower contact surface, min.		0.40%	3.2	Gage
104	Width of groove at location 2		0.40%	3.2	Gage
105	True position of groove at location 2		0.40%	3.2	Gage
106	Width of groove at location 1		0.40%	3.2	Gage
107	Major dia, max.		0.40%	3.2	Gage
108	Width of groove at location 7		0.40%	3.2	Gage
109	True position of gorrve at location 1		0.40%	3.2	Gage
110	True position of groove at location 7		0.40%	3.2	Gage
111	True position of major dia.		0.65%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

a. Reject lot if one or more defective units are found.

Source: https://assist.dla.mil (130r)
Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-F-64042A (AR)
AMENDMENT 2

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12554550
4.4.2.113	BARREL, MAINSPRING, TIMER				NEXT HIGHER ASSEMBLY 12554548
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Die Casting defects	10	a	3.2&3.16	Visual W/Aid C (See 6.12)
102	Static Load	10b	a	3.23	4.5.1.ap
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:
a. Reject the lot if one or more defective units are found
b. Destructive Test

Source: https://assist.dla.mil downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12554551
4.4.2.114	DRIVE GEAR				NEXT HIGHER ASSEMBLY 12554544
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Tooth to tooth composite error		0.40%	3.2	Gage
Minor 201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12554554
4.4.2.115	TIMER HOUSING ASSEMBLY				NEXT HIGHER ASSEMBLY 12554515
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical 1	Setting gear assemblies missing or deformed		100%	3.2	Visual
Major 101	Stake of post above flush		0.40%	3.2	Visual
Minor 201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12554555
4.4.2.116	HOUSING, TIMER				NEXT HIGHER ASSEMBLY 12554554
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Die Casting Defects	10	a	3.2&3.16	Visual W/Aid C (See 6.12)
102	Static Load Test	10b	a	3.24	4.5.1.ag
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:
a. Reject the lot if one or more defective units are found
b. Destructive Test

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.117	SETTING GEAR ASSEMBLY				12554556
					NEXT HIGHER ASSEMBLY 12554554
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	20 lb. push-off load on shaft	a	0.40%	3.2	4.5.1.an
Minor 201	Evidence of poor workmanship		1.0%	3.3	Visual W/Aid A (See 6.12)

NOTES:

a. Non-destructive Test

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Table I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.118	Gear, Setting				12554557
					NEXT HIGHER ASSEMBLY 12554556
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical .	None defined				
Major					
101	Total composite error, gear		0.40%	3.2	Gage
102	Tooth to tooth composite error, gear		0.40%	3.2	Gage
103	Torque Test	a	0.40%	3.2	4.5.2.n
104	Total composite error, pinion		0.40%	3.2	Gage
105	Tooth to tooth composite error, pinion		0.40%	3.2	Gage
Minor . .					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES: a. Destructive Test

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Table I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.119	Shaft, Setting				12554561
					NEXT HIGHER ASSEMBLY 12554515
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total composite error, pinion		0.40%	3.2	Gage
102	Tooth to tooth composite error, pinion		0.40%	3.2	Gage
103	Torque Test	b	0.40%	3.2	4.5.2.o
104	Die Casting defects	10	a	3.2&3.16	Visual W/Aid C (See 6.12)
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:
a. Reject the lot if one or more defective units are found
b. Destructive Test

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil (13 Nov) Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12554562
4.4.2.120	COUNTER ASSEMBLY				NEXT HIGHER ASSEMBLY 12554515
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical 1	Counter Wheel transfer	a	100%	3.10	4.5.12
Major 101	Hairline not stationary with respect to body and in excess of allowable tolerances		0.40%	3.2	Visual
102	Index line missing or unreadable		0.40%	3.2	Visual
Minor 201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

a. Non-destructive Test

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12554566
4.4.2.121	RING, RETAINING, COUNTER				NEXT HIGHER ASSEMBLY 12554563
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Die Casting defects	10	a	3.2&3.16	Visual W/Aid C (See 6.12)
Minor 201	Evidence of poor workmanship		1.0%	3.3	Visual

COVER:

a. Reject the lot if one or more defects are found

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12554547
4.4.2.123	Shaft, Drive Gear, Timer				NEXT HIGHER ASSEMBLY 12554545
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major 102	Dia. of Pivots, Min.		0.40%	3.2	Gage
Minor 201	Evidence of Poor Workmanship		1.0%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 132

* Change 4.4.3.4 From: "Axial Load Test. The Timer Hairspring and . . . The samples shall contain the number of welds specified on drawing 9236711 and shall be welded . . . and the same equipment parameters."

To: "Axial Load Test. The Timer Hairspring and . . . The samples shall contain the number of welds specified and shall be welded . . . and the same equipment parameters."

PAGE 135

* 4.5.1 Test d. Add dwg. "12554567"

Test e. Add dwg. "12554506"

PAGE 137

4.5.1 Test t. Add dwg. "12624556"

* 4.5.1 Test o. Add dwg. "12554562"

PAGE 138

4.5.1 Test w. Add dwg. "12554518" and dwg. "12624556"

4.5.1 Test v. Add dwg. "12624556"

4.5.1 Test u. Add dwg. "12624556"

PAGE 139

* 4.5.1 Test ad. Add dwg. "12554533"

Test ae. Add dwg. "12554530

Test af. Add dwg. "12554535"

Test ag. Add dwg. "12554538"

PAGE 140

* Add Para. 4.5.1.akk as follows:

"Test	Load & Application
Hairspring Support Bracket. Plate No. 1 Assembly, Timer (Dwg. 12624556/12554518)	22 lb. min pullout as per dwg"

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:28Z
Check the source to verify that this is the current version before use.

Table II. Linear Load Test

Test	Orientation	Load & Application	Remarks
a.m. Timing Scroll Shaft Assembly (Dwg. 12554545)		10 lb. push off per Dwg.	
a.n. Setting Gear Assembly (Dwg. 12554556)		20 lb. push off per Dwg.	
a.o. Housing, Barrel (Dwg. 12554542)		Compressive load, apply load per drawing until measured load shows no further increase. Deflection rate shall not exceed .100 in. per second. Maximum load shall be greater than load specified by drawing.	
a.p. Barrel, Mainspring (Dwg. 12554550)		Compressive load, apply load per drawing until measured load shows no further increase. Deflection rate shall not exceed .100 in. per second. Maximum load shall be greater than load specified by drawing.	
a.q. Housing, Timer (Dwg. 12554555)		Compressive load, apply load per drawing until measured load shows no further increase. Deflection rate shall not exceed .100 in. per second. Maximum load shall be greater than load specified by drawing.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 140

* Add Page 140a, See included page.

PAGE 143

* 4.5.2 Add the following tests:

"	Test	Load & Application	Remarks
j.	Setting Key Assembly (dwg. 12554508)	7 in.-lb. of torque	Stake breaks
k.	Setting Key Assembly (dwg. 12554508)	20 in.-lb. of torque at both limits of travel	Limiter threads fail
l.	Clutch Assembly (dwg. 12554512) 15.0	11.0 + 4.0 in.-lb. of torque	Clutch must slip at in.-lb.
m.	Plate #1, Timer (Dwg. 12554519)	21 in-lbs of torque applied to teeth	Must not bend or crack
n.	Gear, Setting (Dwg. 12554557)	7 in-lbs of torque applied to teeth	Must not bend or crack
o.	Shaft, Setting (Dwg. 12554561)	21 in-lbs of torque	Must not applied to teeth bend or crack
p.	Three Module Assembly (Dwg. 12554515)	4.5 in-lbs min increasing time	Counter direction of Turns"

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 144

* Spring Load Test d: Add Dwg. "12554548"

PAGE 147

* Delete paragraph 4.5.13 in its entirety and substitute the following:

"4.5.13 Timer beat rate; timer assembly. The timer assembly shall be placed in a suitable test fixture. The spin detent and setback detent shall be manually subverted and the timer allowed to operate. The beat rate and amplitude shall be measured and recorded at equally spaced intervals throughout the required duration, a minimum of 19 times. If the beat rate or amplitude of any measurement, or the difference between the maximum and minimum measured amplitudes, fail to comply with the applicable requirements, that assembly shall be classed defective. Assemblies which pass the test shall be returned to the non-function position."

PAGE 151

Remove this page and insert new page 151 included.

PAGE 154

4.5.21.6 Delete in its entirety.

* Delete 4.5.22 and substitute the following:

"4.5.22 Load test of sleeve. The sleeve shall be assembled as shown on Drawing 9362801 or Drawing 12554516, then placed in a suitable test fixture and a load specified on Drawing 9252376 or 12554516 shall be applied at a deflection rate of less than 0.100 inches per second."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

TABLE V. Ballistic performance.

TEST	WEAPON	TUBE	PROJECTILE	CHARGE ZONE	SETTING	TEMPERATURE	SAMPLE(a) SIZE	SAMPLE(b) SIZE
Non-Function(e)	105MM	M103 or M102	M1	7	PD	70 F ± 10 F	15(c)	10(c)
Function(e)	155MM	M1	M107	1	PD	70 F ± 10 F	15	10
Mechanical Time(d)	155MM	M185	M107	f	50.0 Sec	70 F ± 10 F	10(c)	10(c)
	155MM	M185	M107	f	75.0 Sec	70 F ± 10 F	10	10
	105MM	M103 or M102	M1	7	50.0 Sec	70 F ± 10 F	10	20
	8 Inch	M2	M106	1	15.0 Sec	70 F ± 10 F	10	
Extreme Temperature(d)	105MM	M103 or M102	M1	7	50.0 Sec	+145 F -5 F	10	-
	8 Inch	M2	M106	1	25.0 Sec	-35 F +5 F	10	10

Notes:

a. For First Article and three consecutive acceptable lots (See 4.4.3.6.1).

b. For subsequent lots after "a" above (See 4.4.3.6.2).

c. Transportation Vibration samples.

d. The Quadrant Elevation (QE) and Height of Burst (HOB) shall be as specified in 6.10. All rounds fired shall use Spotting Charge, Model APG-2 (9297939).

e. The Spotting Charge above shall not be used.

f. M119 series charge.

Source: https://assist.dla.mil - Downloaded: 2026Jan-26T04:28Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisks or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project: 1390-A704)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.