INCH-POUND

MIL-F-64042A (AR)
AMENDMENT 3
10 June 1993
SUPERSEDING
AMENDMENT 2
25 September 1991

MILITARY SPECIFICATION

FUZE, MT, SQ, M577A1
LOADING, ASSEMBLING, PACKING AND METAL PARTS
FUZE, MT, SQ, M582A1 METAL PARTS

This amendment forms a part of Military Specification MIL-F-64042A (AR), dated 6 June 1986, and is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.3: After the second sentence, add the following sentence:

"There shall not be any sealant internally beyond the body and ogive thread."

PAGE 4

* 3.11.3.1: Change to read as follows:

"3.11.3.1 Target impact non-function distance. The fuze, when set in the point detonating (PD) mode (see 6.5), shall not cause the projectile to function upon impact of the PD element when fired in the 105MM, M103 or M137 Series Tube, Charge 7 at a six (6) inch thick plywood target located 150 - 5 feet from the muzzle of the weapon."

* 3.11.3.2 Change to read as follows:

"3.11.3.2 Target impact function distance. The fuze, when set in the point detonating (PD) mode (see 6.5) shall cause the projectile to function upon impact of the PD element when fired in the 155mm, M1 tube, Charge 1 at a six (6) inch thick plywood target located 820-5 feet from the muzzle of the weapon."

AMSC N/A

FSC 1390

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 5

3.13 Delete in its entirety.

Delete 3.15 and substitute the following:

"3.15 Marking. The SSD Assembly (see dwg. 9362838) and the Three Module Assembly (see dwg. 9352384 or 12554515), after undergoing critical classified tests, shall be marked as specified in 5.2 using mechanized equipment (preferably automated) in accordance with 4.4.4."

PAGE 6

3.19 Add Drawing "/12554516" after "see dwg. 9352376".

Add the following paragraphs:

"3.22 Housing, barrel (see drawing 12554542). The Housing, Barrel shall not fracture when a load, as specified on the applicable drawing, is applied.

3.23 Barrel, mainspring, timer (see drawing 12554550). The Barrel, Mainspring, Timer shall not fracture, when a load as specified on the applicable drawing, is applied.

3.24 Housing, timer (see drawing 12554555). The Housing, Timer shall not fracture when a load, as specified on theapplicable drawing, is applied.

3.25 Plate no. 1 timer (see drawing 12554579). The Plate No. 1, Timer teeth shall not fracture when a load, as specified on the applicable drawing, is applied.

3.26 Lubrication of timer assembly (see drawing 12598432). The contractor shall prepare a Process Control Document (PCD) in accordance with MIL-A-48078 for controlling lubrication of the timer."

PAGE 9

Delete 4.3.1 and substitute the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

"4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the items listed below in the sample quantities as indicated. In addition, when items are fabricated from die cast components, ten (10) components from each mold cavity shall be included in the first article sample. The components shall bear a mark which identifies the component with its individual cavity. The mark shall be located on a nonfunctional surface where subsequent machining operations will not obliterate the mark The three module assembly (dwg. 9352384 or dwg. 12554515), used only for first article examinations and tests, shall be loaded with inert detonators. These items shall be clearly and indelibly marked by the word "inert" on two visible surfaces located 180 apart. They will not be used for any testing that requires the functioning of the detonators."

PAGE 10

Add the following drawings to the drawing column as shown:

"Part Description	Drawing	Quantity
Plate No. 2, Timer	9236659/12554524	30
Lever Assembly, Timer	9236661/12554526	80
Plate No. 4 & Bearing, Assembly Timer	9236668/12554533	80
Escape Wheel & Pinion Assembly, Timer	9236672/12554530	80
Pinion, Escape, Timer	9236673/12554532	30
Wheel, Escape, Timer	9236674/12554531	30
Gear No. 1 & Pinion Assembly, Timer	9236675/12554535	30
Pinion, No. 1, Timer	9236677/12554537	30
Gear No. 2 & Pinion Assembly, Timer	9236678/12554538	80
Mainspring & Barrel Assembly, Timer	9236697/12554548	80
Pin, Setback, Timer	9236703/12554569	30"

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:28Z
Check the source to verify that this is the current version before use.

Add the following drawings to the drawing column as shown:

"Part Description	Drawing	Quantity
Body Assembly	9352371/12554567	80
Body	9352372/12554568	30
Ogive	9352373/12554507	30
Key Setting	9352374/12554514	30
Plate, Top, Trigger	9352378/12554571	30
Trigger Assembly	12624555/12554570	80
Ogive Assembly	9362837/12554506	80"

Add the following items to the listed items:

"Setting Key Assembly	12554508	80
Clutch Assembly	12554512	80
Three Module Assembly	12554515	80
Sleeve	12554516	40
Timer Assembly	12554517	80
Plate #1 Assembly	12554518	80
Plate #1, Timer	12554519	40
Pin, Pallet, Timer	12554529	30
Plate #4, Timer	12554534	30
Pinion #2, Timer	12554540	30
Housing, Barrel	12554542	40
Timing Scroll and Shaft Assy.	12554545	80
Timing Scroll, Timer	12554546	30
Shaft, Drive Gear, Timer	12554547	30
Barrel, Mainspring	12554550	40
Drive Gear	12554551	30
Timer Housing Assembly	12554554	30
Timer Housing, Timer	12554555	40
Setting Gear Assembly	12554556	80
Gear, Setting	12554557	40
Shaft, Setting	12554561	40
Counter Assembly	12554562	80
Ring, Retaining Counter	12554566	30
Timer Assembly	12624555	80
Plate No. 1 Assembly, Timer	12624556	80"

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Page 12

Change from "Sheet 1 of 18" to "Sheet 1 of 24"

Page 13

Change from "Sheet 2 of 18" to "Sheet 2 of 24"

Page 14

Change from "Sheet 3 of 18" to "Sheet 3 of 24"

Page 15

Change from "Sheet 4 of 18" to "Sheet 4 of 24"

After Dwg. 9236657, Add: "/12554522"

After Dwg. 9236659, Add: "/12554524"

Page 16

Change from "Sheet 5 of 18" to "Sheet 5 of 24"

After Dwg. 9236661, Add: "/12554526"

After Dwg. 9236668, Add: "/12554533"

Page 17

Change from "Sheet 6 of 18" to "Sheet 6 of 24"

After Dwg. 9236672, Add: "/12554530"

After Dwg. 9236673, Add: "/12554532"

After Dwg. 9236674, Add: "/12554531"

After Dwg. 9236675, Add: "/12554535"

After Dwg. 9236677, Add: "/12554537"

After Dwg. 9236678, Add: "/12554538"

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 18

Change from "Sheet 7 of 18" to "Sheet 7 of 24"

PAGE 19

Change from "Sheet 8 of 18" to "Sheet 8 of 24"

After Dwg. 9236697, Add: "/12554548"

After Dwg. 9236703, Add: "/12554569"

PAGE 20

Change from "Sheet 9 of 18" to "Sheet 9 of 24"

PAGE 21

Change from "Sheet 10 of 18" to "Sheet 10 of 24"

PAGE 22

Change from "Sheet 11 of 18" to "Sheet 11 of 24"

After Dwg. 9352371, Add: "/12554567"

After Dwg. 9352372, Add: "/12554568"

After Dwg. 9352373, Add: "/12554507"

After Dwg. 9352374, Add: "/12554514"

PAGE 23

Change from "Sheet 12 of 18" to "Sheet 12 of 24"

After Dwg. 9352378, Add: "/12554571"

PAGE 24

Change from "Sheet 13 of 18" to "Sheet 13 of 24"

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 25

Change from "Sheet 14 of 18" to "Sheet 14 of 24"

After Dwg. 9352387, Add: "/12554570"

PAGE 26

Change from "Sheet 15 of 18" to "Sheet 15 of 24"

After Dwg. 9362837, Add: "/12554507

PAGE 27

Change from "Sheet 16 of 18" to "Sheet 16 of 24"

PAGE 28

Change from "Sheet 17 of 18" to "Sheet 17 of 24"

PAGE 29

Change from "Sheet 18 of 18" to "Sheet 18 of 24"

Add Pages 29a, 29b, 29c, 29d, 29e, and 29f. See included pages.

PAGE 34

4.4.2.4 Delete "9236546" and add "9362843" to the Next Higher Assembly block.

PAGE 35

4.4.2.5 Change Title:

From: "Detent Interlock, SSD"

To: "Detent, Spin, SSD"

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 37

4.4.2.7 Add "12554562" to Next Higher Assembly block.

PAGE 38

4.4.2.8 Add "12554562" to Next Higher Assembly block.

PAGE 39

4.4.2.9 Change Title:

From: "Pinion, Setting"

To: "Gear, Setting"

PAGE 41

4.4.2.11 Add "12554515" to Next Higher Assembly block.

PAGE 42

4.4.2.12 Add "12554515" to Next Higher Assembly block.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 19 OF 24		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Timer Assembly (Dwg. 12624555)				
	Examination for defects	30	-	3.2	4.4.2.98
	Timer functioning test	80	-	3.9.2	4.4.5.9
	Timer non-functioning test	80	-	3.9.2	4.5.10
	Setback pin arming test	80	-	3.12	4.5.11
	Timer beat rate and amplitude	80	-	3.2	4.5.13
	9 lb. axial load	40*	-	3.2	4.5.1.w
	Plate No. 1 Assembly Timer (Dwg. 12624556)				
	Examination for defects	30	-	3.2	4.5.2.99
	50 lb. torque load on ring gear assy	80	-	3.2	4.5.2.d
	5 lb. axial unseating load on bushing	80	-	3.2	4.5.1.u
	5 lb. axial unseating load on spin detent pivot pin	80	-	3.2	4.5.1.t
	40 lb. axial unseating load on dowel pins	80	-	3.2	4.5.1.v
	22 lb pull off load on hairspring support bracket	40*	-	3.2	4.5.1.a.1

NOTES:
*Destructive Test

Source: https://assist.dla.mil (29a) Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 20 OF 24		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Setting Key Assembly				
	(Dwg. 12554508)				
	Torque on stop washer	80		3.2	4.5.2.j
	Torque on follower	40*		3.2	4.5.2.k
	Clutch Assembly				
	(Dwg. 12554512)				
	Grip ring torque	80		3.2	4.5.2.1
	Three Module Assembly				
	(Dwg. 12554515)				
	Examination for defects	30		3.2	4.4.2.102
	4.5 min. in.-lb. setting torque	80		3.2	4.5.2.p
	Sleeve				
	(Dwg. 12554516)				
	Examination for defects	30		3.2	4.4.2.103
	Die casting defects	**		3.16	
	Load test	*		3.19	4.5.22

NOTES: *Destructive test
**Ten pieces from each mold cavity

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 21 OF 24		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Timer Assembly (Dwg. 12554517)				
	Examination for defects	30		3.2	4.4.2.104
	Timer functioning test	80		3.9.2	4.5.9
	Timer non-functioning test	80		3.9.2	4.5.10
	Setback pin arming test	80		3.12	4.5.11
	Timer beat rate and amplitude	80		3.13	4.5.13
	9 lb. axial load	40*		3.2	4.5.1.w
	Plate No. 1 Assembly (Dwg. 12554518)				
	Examination for Defects	30		3.2	4.4.2.105
	22 lb. pull off load on hairspring support bracket	80		3.2	4.5.1.al
	Plate No. 1 Timer (Dwg. 12554519)				
	Examination for defects	30		3.2	4.4.2.106
	Torque test	10*		3.2	4.5.2.m
	Die casting defects	**		3.2 & 3.16	
	Pin, Pallet, Timer (Dwg. 12554529)				
	Examination for defects	30		3.2	4.4.2.107
	Plate No. 4, Timer (Dwg. 12554534)				
	Examination for defects	30		3.2	4.4.2.108

NOTES:
*Destructive test
**Ten pieces from each mold cavity

Source: https://assist.dla.mil (29) Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 22 OF 24		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Pinion No. 2, Timer (Dwg. 12554540)				
	Examination for defects	30		3.2	4.4.2.109
	Housing Barrel (Dwg. 12554542)				
	Examination for defects	30		3.2	4.4.2.110
	Die casting defects	**		3.2 & 3.16	4.5.1.ao
	Static load test	10*		3.2	
	Timing Scroll and Shaft Assembly (Dwg. 12554545)				
	20 lb push off force	80		3.2	4.4.2.111, 4.5.1.am
	Scroll, Timing, Timer (Dwg. 12554546)				
	Examination for defects	30		3.2	4.4.2.112
	Die casting defects	**		3.2 & 3.16	
	Barrel, Mainspring (Dwg. 12554550)				
	Die casting defects	**		3.2 & 3.16	
	Static load	*10		3.2	4.5.1.ap

NOTES:
*Destructive test
**10 pieces from each mold cavity

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:28Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 23 OF 24		DRAWING NUMBER
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Drive, Gear				
	(Dwg. 12554551)				
	Examination for defects	30		3.2	4.4.2.114
	Timer, Housing Assembly				
	(Dwg. 12554554)				
	Examination for defects	80		3.2	4.4.2.115
	Housing, Timer				
	(Dwg. 12554555)				
	Die casting defects	**		3.2 & 3.16	4.4.2.116
	Static load	10*		3.2	4.5.1.aq
	Setting Gear Assembly				
	(Dwg. 12554556)				
	20 lb. push off load on shaft	80		3.2	4.5.1.an
	Gear, Setting				
	(Dwg. 12554557)				
	Examination for defects	30		3.2	4.4.2.118
	Torque test	10*			4.5.2.n
	Shaft, Setting				
	(Dwg. 12554561)				
	Examination for defects	30		3.2	4.4.2.119
	Torque test	10*		3.2 & 3.16	4.5.2.0
	Die casting defects	**			

NOTES:
*Destructive test
**10 pieces from each mold cavity

Source: https://assist.dla.mil-1.3 (29e) Added: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Counter Assembly (Dwg. 12554562)				
	Counter wheel transfer	80		3.10	4.5.12
	Examination for defects	30		3.2	4.4.2.120
	Ring, Retaining, Counter (Dwg. 12554566)				
	Die casting defects	**		3.2 & 3.16	
	Shaft, Drive Gear, Timer (Dwg. 12554547)				
	Examination for Defects	30		3.2	4.4.2.123

NOTES:

*10 pieces out of each mold cavity

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 43

4.4.2.13 Add "12554570" to Next Higher Assembly block.

PAGE 46

4.4.2.16 Add "12554570" to Next Higher Assembly block.

PAGE 50

4.4.2.20 Add "12554570" to Next Higher Assembly block.

PAGE 52

4.4.2.22 Add "12554570" to Next Higher Assembly block.

PAGE 53

4.4.2.23 Add "12624556" to Next Higher Assembly block.

PAGE 54

4.4.2.24 Add "12624556" to Next Higher Assembly block.

PAGE 56

4.4.2.26 Add "12554522" to Drawing Number block

Add "12554517" to Next Higher Assembly block.

PAGE 57

4.4.2.27 Add "12554517/12624555" to Next Higher Assembly block.

Add "12554524" to Drawing Number block

PAGE 58

4.4.2.28 Add "12554526" to Drawing Number block.

4.4.2.28 Add "12554517/12624555" to Next Higher Assembly block.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 61

4.4.2.31 Add "12554533" to Drawing Number block.

4.4.2.31 Add "12554517/12624555" to Next Higher Assembly block.

PAGE 63

4.4.2.33 Add "12554533" to Next Higher Assembly block.

PAGE 64

4.4.2.34 Add "12554530" to Drawing Number block.

4.4.2.34 Add "12554517/12624555" to Next Higher Assembly block.

PAGE 65

4.4.2.35 Add "12554532" to Drawing Number block.

Add "12554517" to Next Higher Assembly block.

PAGE 66

4.4.2.36 Add "12554531" to Drawing Number block.

Add "12554517" to Next Higher Assembly block.

PAGE 67

4.4.2.37 Add "12554535" to Drawing Number block.

4.4.2.37 Add "12554517/12624555" to Next Higher Assembly block.

PAGE 68

4.4.2.38 Add "12554537" to Drawing Number block.

Add "12554535" to Next Higher Assembly block.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 69

4.4.2.39 Add "12554538" to Drawing Number block.

4.4.2.39 Add "12554517/12624555" to Next Higher Assembly block.

PAGE 71

4.4.2.41 Add "12624555" to the Next Higher Assembly block.

PAGE 72

4.4.2.42 Add "12624555" to the Next Higher Assembly block.

PAGE 73

4.4.2.43 Add "12624555" to the Next Higher Assembly block.

PAGE 74

4.4.2.44 Add "12624555" to the Next Higher Assembly block.

PAGE 79

4.4.2.49 Add "12554548" to Drawing Number block.

Add "12554544" to the Next Higher Assembly block.

PAGE 80

4.4.2.50 Add "12624555" to the Next Higher Assembly block.

PAGE 81

4.4.2.51 Add "12554569" to Drawing Number block.

Add "12554517" to the Next Higher Assembly block.

PAGE 82

4.4.2.52 Add "12624555" to the Next Higher Assembly block.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 84

4.4.2.54 Major 108, delete "3.13" and add "3.2".

PAGE 89

4.4.2.59 Add "12554518/12624556" to the Next Higher Assembly block.

PAGE 92

4.4.2.62 Add "12554567" to Drawing Number block.

PAGE 93

4.4.2.63 Add "12554568" to Drawing Number block.

Add "12554567" to the Next Higher Assembly block.

PAGE 94

4.4.2.64 Add "12554507" to Drawing Number block.

Add "12554506" to the Next Higher Assembly block.

PAGE 95

4.4.2.65 Add "12554514" to Drawing Number block.

Add "12554508" to the Next Higher Assembly block.

PAGE 99

4.4.2.69 Add "12554571" to Drawing Number block.

Add "12554570" to the Next Higher Assembly block.

PAGE 100

4.4.2.70 Add "12554570" to the Next Higher Assembly block.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 102

4.4.2.72 Major 105, change "adhesive" to "sealant".

4.4.2.72 Add Major 106 as follows: "106, Limiter stop test, 100%, 3.2, Gage."

Add in the Notes block "Major Category 106 only applies for Part Number 9352381-2 and 9352382-2."

PAGE 104

4.4.2.73: Delete Info Category 300, and add the following Major Category:

"108 Evidence of sealant beyond the body and ogive threads, i, h, 3.2 and 3.3"

PAGE 105

Add note i as follows:

"i To be performed on fuzes that are disassembled after Jolt and Jumble, transportation vibration, twelve meter drop and waterproofness tests."

PAGE 109

4.4.2.76 Add "12554570" to Drawing Number block.

PAGE 110

4.4.2.77 Add "12554506" to Drawing Number block.

PAGE 118

4.4.2.85 Add "12554570" to Next Higher Assembly block.

PAGE 119

4.4.2.86 Add "12554570" to Next Higher Assembly block.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:28Z
Check the source to verify that this is the currentversion before use.

PAGE 120

4.4.2.87 Add "12554570" to Next Higher Assembly block.

PAGE 130

Add pages 130a, 130b, 130c, 130d, 130e, 130f, 130g, 130h, 130j, 130k, 130kk, 130m, 130n, 130p, 130q, 130r, 130s, 130t, 130u, 130v, 130w, 130x, 130y, 130z, 130aa, 130ab, See included pages.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.98	Timer Assembly				12624555
					NEXT HIGHER ASSEMBLY 9236718
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Limits of angle between tumbler and scroll exit port		0.40%	3.2	Gage
102	Balance wheel not detented in proper position and setback detent not restraining spin detent		0.40%	3.2	Visual
103	Mainspring not wound as indicated		0.40%	3.2	Manual
104	Mainspring barrel stakes missing or insufficient		0.40%	3.2	Visual
105	Timer function test	a	100%	3.9.2	4.5.6
106	Timer non-function test	a	100%	3.9.2	4.5.10
107	Setback pin arming test	a	100%	3.12	4.5.11
108	Timer beat rate and amplitude	a	100%	3.2	4.5.13
109	Expansion plug above flush		0.40%	3.2	Visual
110	Protective cap missing		0.65%	3.2	Visual
111	9 lb. axial load	b	c	3.2	4.4.3.4
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:
a. Non-destructive
b. Destructive test, see par 4.4.3.4 for applicable sampling plan.
c. Reject timer assembly inspection lot if one (1) or more defective units are found.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.99	Plate No. 1 Assembly, Timer	1 OF 1	12624556
			NEXT HIGHER ASSEMBLY: 12624555

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of balance wheel, staff and hairspring assembly		0.40%	3.2	Gage
102	50 in. lb. torque load on ring gear assembly	a	0.40%	3.2	4.5.2.d
103	5 lb. axial unseating load on spin detent pin	a	0.40%	3.2	4.5.1.t
104	5 lb. axial unseating load on bushing	a	0.40%	3.2	4.5.1.u
105	40 lb. axial unseating load on dowel pins	a	0.40%	3.2	4.5.1.v
106	Balance wheel outside tolerance zone	a	0.40%	3.2	Gage
107	22 lb. pull off load on hairspring support bracket	b	0.40%	3.2	
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

a. Non-destructive test
b. Destructive test

Source: https://assist.dla.mil -- (U) 2026-10-22 -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

TABLE I. First atticle inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.100	Setting Key Assembly		12554508
			NEXT HIGHER ASSEMBLY 12554506

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Torque on stop washer	a	0.40%	3.2	4.5.2.j
102	Torque on follower	b	0.40%	3.2	4.5.2.k
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

a. Non-destructive test
b. Destructive test

Source: https://assist.dla.mil (130c) Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

TABLE I. First article insepction.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.101	Clutch Assembly		12554512
			NEXT HIGHER ASSEMBLY 11554508

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Grip ring torque	a	0.40%	3.2	4.5.2.1
Minor 201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

a. Non-destructive test

Source: https://assist.dla.mil (15 Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.102	Three Module Assembly	1	1	12554515
				NEXT HIGHER ASSEMBLY: 9352381/9352382

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Setback detent does not hold spin detent in position to lock the trigger in the unfired position		100%	3.2	Visual
2	SSD release laver missing or not restrained by firing armshaft in unfired position		100%	3.2	Visual
Major					
101	Timer housing stakes missing or insecure		0.40%	3.2	Visual/Manual
102	Setback retainer stakes missing or insecure		0.40%	3.2	Visual/Manual
103	Zero setting improper		0.40%	3.2	Visual
104	Trigger assembly not in unfired position		0.40%	3.2	Visual
105	Grease missing in setback pin cavity		0.40%	3.2	Visual
106	4.5 min. in.-lb. setting torque	a	0.40%	3.2	4.5.2.p

NOTES:
a. Non-destructive test

Source: https://assist.dla.mil (130e) Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-64042A (AR)
AMENDMENT 3

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.102	THREE MODULE ASSEMBLY	2	2	12554515
				NEXT HIGHER ASSEMBLY: 9352381/9352382

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
107	Trigger Setback Function		0.40%	3.12	4.5.14
108	True Position of Hairline		0.40%	3.12	Gage
109	Gap Between Trigger and Sleeve		0.65%	3.2	Visual
Minor					
201	Evidence of Poor Workmanship		1.0%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.103	Sleeve		12554516
			NEXT HIGHER ASSEMBLY 12554515

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Barrel dia., max.		0.40%	3.2	Gage
102	Scroll dia., min.		0.40%	3.2	Gage
103	True position of scroll dia.		0.40%	3.2	Gage
104	Dia. of trigger location pin holes, max.		0.40%	3.2	Gage
105	True position of trigger location pin hole		0.40%	3.2	Gage
106	Depth of release slot, min.		0.40%	3.2	Gage
107	Height of scroll dia., max.		0.40%	3.2	Gage
108	Die casting defects	10	a	3.2 & 3.16	Visual w/aid c (see 6.12)
109	Load test	10b	a	3.19	4.5.22
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:
a. Reject the lot if one or more defective units are found
b. Destructive test

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.104	Timer Assembly	1 OF 1	12554517
			NEXT HIGHER ASSEMBLY 12554515

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Balance wheel not detented in proper position and setback detent not restraining spin detent		0.40%	3.2	Visual
102	Mainspring not wound as indicated		0.40%	3.2	Manual
103	Mainspring barrel stakes missing or insufficient		0.40%	3.2	Visual
104	Timer function test	a	100%	3.9.2	4.5.9
105	Timer non-function test	a	100%	3.9.2	4.5.10
106	Setback pin arming test	a	100%	3.12	4.5.11
107	Timer beat rate and amplitude	a	100%	3.2	4.5.13
108	9 lb. axial load	b	c	3.2	4.5.1.w
109	Grease missing in setback pin cavity		100%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:
a. Non-destructive test
b. Destructive test see para 4.4.3.4 for applicable sampling plan
c. Reject timer assembly insepction lot if one or more defective units are found

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-64042A (AR)
AMENDMENT 3

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12554518
4.4.2.105	PLATE NO. 1 ASSEMBLY				NEXT HIGHER ASSEMBLY 12554517
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of balance wheel, staff and hairspring assembly		0.40%	3.2	Gage
102	Balance wheel outside tolerance zone		0.40%	3.2	Gage
103	22 lb. min. pullout force on hairspring support bracket		0.40%	3.2	4.5.1.a1
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-64042A (AR)
AMENDEMENT 3

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.106	PLATE NO. 1, TIMER		12554519
			NEXT HIGHER ASSEMBLY 12554518

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Height from Bottom to Wheel Surface, Min.		0.40%	3.2	Gage
102	Screw Hold Dia. Max.		0.40%	3.2	Gage
103	Dia. of Bracket Hole Max.		0.40%	3.2	Gage
104	Torque Test	b	0.40%	3.25	4.5.2.m
105	Die Casting Defects	10	a	3.16	Visual W/Aid C (See 6.12)
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:
a. Reject lot if one or more defective units are found
b. Destructive Test

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-64042A (AR)
AMENDMENT 3

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12554529
4.4.2.107	Pin, Pallet, Timer				NEXT HIGHER ASSEMBLY 12554526
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Distance from lever seat to end of pin		0.40%	3.2	Gage
Minor 201	Evidence of poor workmanship		1.0%	3.3	Visual W/Aid C (See 6.12)

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-F-64042A (AR)
AMENDMENT 3

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.108	PLATE NO. 4, TIMER		12554534
			NEXT HIGHER ASSEMBLY 12554533

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of gear and pinion no. 2 pivot hole		0.40%	3.2	Gage
102	True position of gear and pinion no. 1 pivot hole		0.40%	3.2	Gage
103	True position of lever hole		0.40%	3.2	Gage
104	True position of location pin slot		0.40%	3.2	Gage
105	Dia. of lever hole		0.40%	3.2	Gage
106	Dia. of gear and pinion no. 2 pivot hole max.		0.40%	3.2	Gage
107	Dia. of gear and pinion no. 1 pivot hole max.		0.40%	3.2	Gage
108	Dia. of location pin hole max.		0.40%	3.2	Gage
109	Width of loation pin slot max.		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

Source: https://assist.dla.mil - 12 (1950) Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.109	PINION NO. 2, TIMER		12554540
			NEXT HIGHER ASSEMBLY 12554538

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Dia. of upper pivot, min.		0.40%	3.2	Gage
102	Dia. of lower pivot, min.		0.40%	3.2	Gage
103	Total composite error		0.40%	3.2	Gage
104	Tooth to tooth composite error		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual w/aid b (see 6.12)

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-64042A (AR)
AMENDMENT 3

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.110	HOUSING, BARREL		12554542
			NEXT HIGHER ASSEMBLY 12554517

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Dia. of location pin holes max		0.40%	3.2	Gage
102	Dia. of gear 7 pinion no. 2 hole max.		0.40%	3.2	Gage
103	Dia. of gear & pinion no. 1 hole max.		0.40%	3.2	Gage
104	Dia. of escapement hole max.		0.40%	3.2	Gage
105	Dia. of scroll shaft pivot hole max.		0.40%	3.2	Gage
106	Depth of barrel dia. min.		0.40%	3.2	Gage
107	Outside dia. of barrel min.		0.40%	3.2	Gage
108	True position of location pin hole		0.40%	3.2	Gage
109	True position of gear & pinion no. 2 pivot hole		0.40%	3.2	Gage
110	True position of gear & pinion no. 1 pivot hole		0.40%	3.2	Gage
111	Length of minor outside dia. max.	10	a	3.16	Visual w/aid c (see 6.12)
112	Die casting defects	10b	a	3.22	4.5.1.ao
113	Static load test				
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:
a. Reject lot if one or more defective units found
b. Destructive test

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil (30 Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-64042A (AR)
AMENDMENT 3

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.111	TIMING SCROLL AND SHAFT ASSEMBLY				12554545
					NEXT HIGHER ASSEMBLY 12554544
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major 101	20 lb. push-off force	a	0.40%	3.2	4.5.1.am
Minor 201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

a. Non-Destructive Test

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-64042A (AR)
AMENDMENT 3

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.112	SCROLL, TIMING, TIMER		12554546
			NEXT HIGHER ASSEMBLY 12554545

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Discontinuity or crack in spiral wall		100%	3.2	Visual W/Aid A
Major					
101	Die casting defects	10	a	3.16	Visual W/Aid C
102	Depth of grooves, min.		0.40%	3.2	Gage
103	Height of lower contact surface, min.		0.40%	3.2	Gage
104	Width of groove at location 2		0.40%	3.2	Gage
105	True position of groove at location 2		0.40%	3.2	Gage
106	Width of groove at location 1		0.40%	3.2	Gage
107	Major dia, max.		0.40%	3.2	Gage
108	Width of groove at location 7		0.40%	3.2	Gage
109	True position of groove at location 1		0.40%	3.2	Gage
110	True position of groove at location 7		0.40%	3.2	Gage
111	True position of major dia.		0.65%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:
a. Reject lot if one or more defective units are found.

Source: https://assist.dla.mil 36 Downloaded: 2026-10-26T04:28Z (GMT)
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-64042A (AR)
AMENDMENT 3

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.113	BARREL, MAINSPRING, TIMER		12554550
			NEXT HIGHER ASSEMBLY 12554548

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Die Casting defects	10	a	3.2&3.16	Visual W/Aid C (See 6.12)
102	Static Load	10b	a	3.23	4.5.1.ap
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:
a. Reject the lot if one or more defective units are found
b. Destructive Test

Source: https://assist.dla.mil -- (1308) Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-64042A (AR)
AMENDMENT 3

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.114	DRIVE GEAR				12554551
					NEXT HIGHER ASSEMBLY 12554544
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Tooth to tooth composite error		0.40%	3.2	Gage
Minor 201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-64042A (AR)
AMENDMENT 3

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.115	TIMER HOUSING ASSEMBLY				12554554
					NEXT HIGHER ASSEMBLY 12554515
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical 1	Setting gear assemblies missing or deformed		100%	3.2	Visual
Major 101	Stake of post above flush		0.40%	3.2	Visual
Minor 201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil (130w) loaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12554555
4.4.2.116	HOUSING, TIMER				NEXT HIGHER ASSEMBLY 12554554
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Die Casting Defects	10	a	3.2&3.16	Visual W/Aid C (See 6.12)
102	Static Load Test	10b	a	3.24	4.5.1.ag
Minor 201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:
a. Reject the lot if one or more defective units are found
b. Destructive Test

Source: https://assist.dla.mil/ (1.30v.) Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.117	SETTING GEAR ASSEMBLY				12554556
					NEXT HIGHER ASSEMBLY 12554554
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	20 lb. push-off load on shaft	a	0.40%	3.2	4.5.1.an
Minor 201	Evidence of poor workmanship		1.0%	3.3	Visual W/Aid A (See 6.12)

NOTES:

a. Non-destructive Test

Source: https://assist.dla.mil - (D30W) Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.118	Gear, Setting		12554557
			NEXT HIGHER ASSEMBLY 12554556

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total composite error, gear	a	0.40%	3.2	Gage
102	Tooth to tooth composite error, gear		0.40%	3.2	Gage
103	Torque Test		0.40%	3.2	4.5.2.n
104	Total composite error, pinion		0.40%	3.2	Gage
105	Tooth to tooth composite error, pinion		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:
a. Destructive Test

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

Table I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.119	Shaft, Setting		12554561
			NEXT HIGHER ASSEMBLY 12554515

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total composite error, pinion		0.40%	3.2	Gage
102	Tooth to tooth composite error, pinion		0.40%	3.2	Gage
103	Torque Test	b	0.40%	3.2	4.5.2.o
104	Die Casting defects	10	a	3.2&3.16	Visual W/Aid C (See 6.12)
Minor	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:
a. Reject the lot if one or more defective units are found
b. Destructive Test

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-64042A (AR)
AMENDMENT 3

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12554562
4.4.2.120	COUNTER ASSEMBLY				NEXT HIGHER ASSEMBLY 12554515
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical 1	Counter Wheel transfer	a	100%	3.10	4.5.12
Major 101	Hairline not stationary with respect to body and in excess of allowable tolerances		0.40%	3.2	Visual
102	Index line missing or unreadable		0.40%	3.2	Visual
Minor 201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:
a. Non-destructive Test

Source: https://assist.dla.mil (1.30z) Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-64042A (AR)
AMENDMENT 3

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.121	RING, RETAINING, COUNTER		12554566
			NEXT HIGHER ASSEMBLY 12554563

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Die Casting defects	10	a	3.2&3.16	Visual W/Aid C (See 6.12)
Minor 201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

a. Reject the lot if one or more defects are found

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-64042A (AR)
AMENDMENT 3

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.123	Shaft, Drive Gear, Timer		12554547
			NEXT HIGHER ASSEMBLY 12554545

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major 102	Dia. of Pivots, Min.		0.40%	3.2	Gage
Minor 201	Evidence of Poor Workmanship		1.0%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

PAGE 132

Change 4.4.3.4 From: "Axial Load Test. The Timer Hairspring and . . . The samples shall contain the number of welds specified on drawing 9236711 and shall be welded . . . and the same equipment parameters."

To: "Axial Load Test. The Timer Hairspring and . . . The samples shall contain the number of welds specified and shall be welded . . . and the same equipment parameters."

PAGE 135

4.5.1 Test d. Add dwg. "12554567"

Test e. Add dwg. "12554506"

PAGE 137

4.5.1 Test t. Add dwg. "12624556"

4.5.1 Test o. Add dwg. "12554562"

PAGE 138

4.5.1 Test w. Add dwg. "12554518" and dwg. "12624556"

4.5.1 Test v. Add dwg. "12624556"

4.5.1 Test u. Add dwg. "12624556"

PAGE 139

4.5.1 Test ad. Add dwg. "12554533"

Test ae. Add dwg. "12554530

Test af. Add dwg. "12554535"

Test ag. Add dwg. "12554538"

PAGE 140

Add Para. 4.5.1.akk as follows:

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:28Z
Check the source to verify that this is the current version before use.

"Test	Load & Application
Hairspring Support Bracket. Plate No. 1 Assembly, Timer (Dwg. 12624556/12554518)	22 lb. min pullout as per dwg"

PAGE 140a

Table II. Linear Load Test

Test	Orientation	Load & Application	Remarks
a.m. Timing Scroll Shaft Assembly (Dwg. 12554545)		10 lb. push off per Dwg.	
a.n. Setting Gear Assembly (Dwg. 12554556)		20 lb. push off per Dwg.	
a.o. Housing, Barrel (Dwg. 12554542)		Compressive load, apply load per drawing until measured load shows no further increase. Deflection rate shall not exceed .100 in. per second. Maximum load shall be greater than load specified by drawing.	
a.p. Barrel, Mainspring (Dwg. 12554550)		Compressive load, apply load per drawing until measured load shows no further increase. Deflection rate shall not exceed .100 in. per second. Maximum load shall be greater than load specified by drawing.	
a.q. Housing, Timer (Dwg. 12554555)		Compressive load, apply load per drawing until measured load shows no further increase. Deflection rate shall not exceed .100 in. per second. Maximum load shall be greater than load specified by drawing.	

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 140

Add Page 140a, See included page.

PAGE 143

4.5.2 Add the following tests:

	"Test	Load & Application	Remarks
j.	Setting Key Assembly (dwg. 12554508)	7 in.-lb. of torque	Stake breaks
k.	Setting Key Assembly (dwg. 12554508)	20 in.-lb. of torque at both limits of travel	Limiter threads fail
l.	Clutch Assembly (dwg. 12554512)	11.0 + 4.0 in.-lb. of torque	Clutch must slip at 15.0 in.-lb.
m.	Plate #1, Timer (Dwg. 12554519)	21 in-lbs of torque applied to teeth	Must not bend or crack
n.	Gear, Setting (Dwg. 12554557)	7 in-lbs of torque applied to teeth	Must not bend or crack
o.	Shaft, Setting (Dwg. 12554561)	21 in-lbs of torque	Must not applied to teeth bend or crack
p.	Three Module Assembly (Dwg. 12554515)	4.5 in-lbs min increasing time	Counter direction of Turns"

PAGE 144

Spring Load Test d. Add dwg. "12554548"

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

PAGE 147

Delete paragraph 4.5.13 in its entirety and substitute the following:

"4.5.13 Timer beat rate; timer assembly. The timer assembly shall be placed in a suitable test fixture. The spin detent and setback detent shall be manually subverted and the timer allowed to operate. The beat rate and amplitude shall be measured and recorded at equally spaced intervals throughout the required duration, a minimum of 19 times. If the beat rate or amplitude of any measurement, or the difference between the maximum and minimum measured amplitudes, fail to comply with the applicable requirements, that assembly shall be classed defective. Assemblies which pass the test shall be returned to the non-function position."

PAGE 151

* Remove this page and insert new page 151 included.

PAGE 154

* 4.5.21.5 Change to read as follows:

"4.5.21.5 Dud recovery. For informational purposes, and when practical, efforts shall be made to recover all duds encountered during ballistic test, excluding those fuzes fired in the nonfunctioning test. Recovered fuzes are to be held for analysis by the design agency.

4.5.21.6 Delete in its entirety.

Delete 4.5.22 and substitute the following:

"4.5.22 Load test of sleeve. The sleeve shall be assembled as shown on Drawing 9362801 or Drawing 12554516, then placed in a suitable test fixture and a load specified on Drawing 9252376 or 12554516 shall be applied at a deflection rate of less than 0.100 inches per second."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

* 6.5 Change to read as follows:

"6.5 Point detonating dud. A fuze which does not function on impact when intended. A point detonating (Superquick) setting is indicated by a counter position of ◀98."

* 6.6 Change to read as follows:

"6.6 Time dud. When a fuze is set to function in flight (air burst) and fails to function as intended, it shall be classified a time dud. This is independent of whether or not the fuze functions on subsequent impact."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

TABLE V. Ballistic performance.

TEST	WEAPON	TUBE	PROJECTILE	CHARGE ZONE	SETTING	TEMPERATURE	SAMPLE(a) SIZE	SAMPLE(b) SIZE
Non-Function(e)	105MM	M103 or M137 Series	M1	7	PD	70 F ± 10 F	15(c)	10(c)
Function(e)	155MM	M1	M107	1	PD	70 F ± 10 F	15	10
Mechanical Time(d)	155MM	M185	M107	f	50.0 Sec	70 F ± 10 F	10(c)	10(c)
	155MM	M185	M107	f	75.0 Sec	70 F ± 10 F	10	10
	105MM	M103 or M137 Series	M1	7	50.0 Sec	70 F ± 10 F	10	20
	8 Inch	M2	M106	1	15.0 Sec	70 F ± 10 F	10	
Extreme Temperature(d)	105MM	M103 or M137 Series	M1	7	50.0 Sec	+145 F -5 F	10	-
	8 Inch	M2	M106	1	25.0 Sec	-35 F +5 F	10	10

Notes:

a. For First Article and three consecutive acceptable lots (See 4.4.3.6.1).

b. For subsequent lots after "a" above (See 4.4.3.6.2).

c. Transportation Vibration samples.

d. The Quadrant Elevation (QE) and Height of Burst (HOB) shall be as specified in 6.10. All rounds fired shall use Spotting Charge, Model APG-2 (9297939).

e. The Spotting Charge above shall not be used.

f. M119 series charge.

Source: https://assist.dla.mil-52 (11Sep)
Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assures no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautinoed to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1390-A786)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:28Z
Check the source to verify that this is the current version before use.