MIL-G-63444A (AR)
22 August 1983
SUPERSEDING
MIL-G-63444 (AR)
2 August 1982

MILITARY SPECIFICATION

GRENADE, GENERAL PURPOSE, M73

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the quality assurance provisions and special requirements not covered by the drawings for parts and assembly of the M73 General Purpose H.E. Grenade.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1. Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification for
MIL-F-63446	Fuzes, General Purpose Grenade: M230 and M231 (Practice)
* MIL-B-64043	Loaded Body Assembly, General Purpose Grenade: M73

* STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1167	Ammunition Data Card

FSC 1330

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn. DRSMC-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

* 2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

PRODUCT AND PACKAGE DRAWINGS

9334143	Grenade, General Purpose, High Explosive, M73

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

* 3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawing 9334143 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 M230 fuze. The fuze shall comply with specification MIL-F-63446.

3.4 Loaded Body assembly, M73. The loaded body assembly shall comply with specification MIL-B-64043.

3.5 Data requirements. The contractor shall generate data in accordance with the requirements of the data item descriptions cited in 4.5.2.

3.6 First article inspection. This specification makes provisions for first article inspection. Requirements for submission of first article samples by the contractor shall be as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

3.7 Workmanship. Unless otherwise specified on the drawing, all parts and assemblies shall be free from burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, porosity, warpage, burn marks, checks, blisters, excess flash, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. Surface coating shall be continuous except for a few slight scratches not exposing base material. The loading and assembly operations shall be performed in a thorough, workmanlike manner consistent with the best practices of the industry. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibilities for inspections. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the Contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the government. The government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are made a part of this specification.

4.2 Classification of inspections. Unless otherwise specified herein, or in the contract, the following types of inspection shall be conducted on this item.

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection.

* 4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated:

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:27Z
Check the source to verify that this is the current version before use.

Part Description	Drawing	Quantity
Fuze Pushout Assembly	See Note	15
Grenade, General Purpose, High Explosive: M73	9334143	25

Note: Empty M73 body assembly with cap removed and empty M230 fuze body.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-G-63444A (AR)

PARAGRAPH	TITLE: Grenade, General Purpose: M73		SHEET 1 OF 1		DRAWING NUMBER: Listed Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Fuze Pushout Assembly				
	Staked Fuze pushout test	15		3.2	4.5.1
	Grenade, General Purpose, High Explosive: M73 (Dwg. 9334143)				
	Examination for defects	25		3.2	4.4.2.1

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of M73 Grenades shall contain:

a. Body, loaded assemblies from no more than two lots bearing the same interfix number from one manufacturer.

b. M230 Fuzes from no more than two lots bearing the same interfix number from one manufacturer.

The quantity in each production lot shall not exceed 30,000 grenades.

4.4.2 Examination. See MIL-A-48078.

a. Sampling Plans. Unless otherwise specified in the Classification of Defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-63444A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Grenade, General Purpose High Explosive: M73	1 OF 1	9334143
			NEXT HIGHER ASSEMBLY N/A

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL					
1	Shear wire missing (before and after staking)		100%	3.2	Visual
MAJOR					
101	Staked fuze push out test		(a)	3.2	4.5.1
102	Staking improper		0.40%	3.2	Visual/Gage
103	Safety collar missing or loose or improperly positioned		0.40%	3.2	Visual
104	Top of fuze above top of body assembly		0.40%	3.2	Visual
MINOR					
201	Adhesive below threads on fuze arming shaft		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES: (a) One unit per shift or every two hundred units using empty M73 body and empty M230 fuze without RAD assembly.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein. The contractor shall submit all inspection equipment designs to the government for evaluation and approval prior to fabrication of such equipment.

4.5 Test methods and procedures.

PRECAUTION: This specification covers sampling and testing of chemical, toxic or explosive materials which are potentially hazardous to personnel. Accordingly, it is emphasized that all applicable safety rules, regulations and procedures must be followed in handling and processing these materials.

4.5.1 Staked fuze pushout test. One unit per shift or one of every two hundred units from each staking machine shall be subjected to the pushout force test. An empty M73 body assembly with the cap removed shall have an empty M230 Fuze Body staked in the normal manner. The staked assembly shall be tested in a Government approved Push Pull Test Fixture. Pushout of the Fuze Body at less than the minimum force specified on drawing 9334143 shall be cause for rejection of all units staked at the subject staking station since the previous pushout test.

4.5.2 Data requirements. The contractor shall submit a quality inspection test demonstration and evaluation report in accordance with Data Item Descriptions DI-R-1721 and DI-R-1724 giving the detailed test results.

5. PACKAGING

5.1 Packing and marking. Not applicable.

5.2 Ammunition data cards. Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 Intended use. The grenades covered by this specification are intended for loading the M261 Multipurpose Submunition Warhead.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approval. See 6.2 of MIL-A-48078. Submit designs as required to Commander, Armament Research and Development Center, U.S. Army Armament, Munitions and Chemical Command, ATTN: DRSMC-QAF-I(D), Dover, NJ 07801.

6.4 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DAR 7-104.9 (n) (2) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contrctor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs.

Paragraph No.	Data Requirement Title	Applicable DID No.
4.5.2	Quality Inspection Defect Report	DI-R-1721
4.5.2	Quality Inspection Test Demonstration and Evaluation Report	DI-R-1724

(Data item descriptions related to this specification, and identified in section 6 will be approved and listed as such in DoD 5000.19L, Vol II, AMSDL. Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.5 First article. When a first article is required for inspection and approval, see 3.6 and 4.3.

6.6 Source control and specification control drawings. Certificates of conformance from the supplier certifying that the item complies with the drawing requirements shall be provided to the government representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

6.7 Changes from previous issue. The margins of this specification are marked with asterisks or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and Contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1330-A186)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.