INCH-POUND

MIL-G-63445 (AR)
AMENDMENT 5
08 February 1999
SUPERSEDING
AMENDMENT 4
16 FEBRUARY 1990

MILITARY SPECIFICATION

GRENADE, GENERAL PURPOSE, PRACTICE, M75

This Amendment forms a part of Military Specification MIL-G-63445 (AR), dated 2 August 1982, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1, Under "SPECIFICATIONS" add:

"MIL-D-70430 Decelerator, Ram Air Parts and Container Assembly"

PAGE 2

2.1.2, Add:

"INSPECTION EQUIPMENT DRAWINGS

9362755 Detonator, Electric, PA526 (XM70)
9345168 Fuze, General Purpose Grenade, M231 (Practice)"

3.2, Delete in its entirety and substitute:

"3.2 Components and assemblies. The components and assemblies shall comply with all the requirements specified on drawings 9334151, 9386964 and associated drawings and with all requirements specified in applicable specifications and standards."

3.3, Add "and MIL-D-70430."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:27Z
Check the source to verify that this is the current version before use.

PAGE 3

* Add 3.9 as follows:

"3.9 Plastic integrity test. The lid, container P/N 9334146 and smoke, container P/N 9334145 shall be subjected to and pass the plastic integtity test as specified in 4.5.5."

PAGE 4

4.3.1, Add the following:

"Cone, Plastic	9386963	10
Submunition Body, Dummy (Powdered Metal)	9386964	15
Submunition Body Assembly, Dummy (No. 4 S/M)	9386965	10
Tolerance Pad Assembly	9390414	10
Submunition Body, Dummy (Powdered Metal No. 5-9 S/M)	12598684	15".

PAGE 5

TABLE I: Add the following:

"Cone, Plastic (Dwg. 9386963)			
Examination for defects	10	3.2	4.4.2.4
Submunition Body, Dummy (Powdered Metal) (Dwg. 9386964)			
Examination for defects	15	3.2	4.4.2.5
Submunition Body Assembly, Dummy (No. 4 S/M) (Dwg. 9386965)			
Examination for defects	10	3.2	4.4.2.6
Tolerance Pad Assembly (Dwg. 9390414)			
Examination for defects	10	3.2	4.4.2.8
Submunition Body, Dummy (Powdered Metal No. 5-9 S/M) (Dwg. 12598684)			
Examination for defects	15	3.2	4.4.2.9"

PAGE 7

* 4.4.2.1, Delete "None Defined" and add Major 101,

"101	Plastic integrity test	50	---	3.9 4.5.5".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

PAGE 9

4.4.2.3, Critical 1: Delete "Arming" and substitute "shear";

Add "(before and after staking)".

Major 102: Delete "0.65%" and substitute "0.40%"

Add Majors 103 and 104:

"103	Safety collar missing or loose or improperly positioned	0.40%	3.2	Visual
104	Fuze surface adjacent to staking area above top of body assembly	0.40%	3.2	Visual"

Add the following paragraphs:

4.4.2.4 included as (9a).
4.4.2.5 included as (9b).
4.4.2.6 included as (9c).
4.4.2.7 included as (9d).
4.4.2.8 included as (9e).
4.4.2.9 included as (9f).
* 4.4.2.10 included as (9g).

PAGE 10

Add 4.5.4 as follows:

"4.5.4 Density. The density shall be determined using the comparative weight method (weight in air - weight in distilled water). Compensating factors for air and water temperature shall be used in computing the density."

* Add 4.5.5 as follows:

"4.5.5 Plastic integrity. In preparation for testing the container lid, the container lid shall be bonded to the smoke container (vice versa applies when the smoke container is to be tested, namely the smoke container shall be bonded to the container lid) and inertly filled. The smoke container assembly shall be completely assembled into a M75 Grenade except a modified M231 fuze shall be used. A modified M231 is the same as an M231 except a hole is drilled into the fuze body to allow for external initiation of the M55 detonator in its fully safe position. Instead of staking, the modified M231 shall be secured to the M75 grenade in such a way that will provide the equivalent retaining force but allows for easy removal of the modified M231 without damaging the M75 grenade.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

The complete M75 grenade shall be conditioned to $-50^{o} \pm 5^{o}F$ for 4 hours prior to the test. Within 3 minutes after removal from the conditioning chamber, the modified M231 shall be initiated by dropping an external firing pin (P/N 9345321 for configuration of firing pin tip). Minimum energy required to fire the M55 detonator is 0.75 inch-ounce. After initiation of the detonator, the smoke container assembly shall be inspected for any evidence of cracks. The lot shall be rejected if any crack occurs as a result of the initiation of the detonator."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-63445 (AR)
AMENDMENT 5

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Cone, Plastic	1	9386963
			NEXT HIGHER ASSEMBLY 9386965

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major	None defined.				
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Height		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

5 (9a)

Source: https://assist.dla.mil -- Downloaded: Aug-1-2024 04:
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Submunition Body, Dummy (Powdered Metal)	1 of 1	9386964
			NEXT HIGHER ASSEMBLY: 9386965

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Largest outside diameter		0.40%	3.2	Gage
102	Staking height		0.40%	3.2	Gage
Minor					
201	Largest inside diameter		0.65%	3.2	Gage
202	Second largest inside diameter		0.65%	3.2	Gage
203	Smallest outside diameter		0.65%	3.2	Gage
204	Hardness		0.65%	3.2	Gage
205	Density		0.65%	3.2	4.5.4
206	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

(96)

Source: https://assist.dla.mil -- Downloaded: 2026[illegible]-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE			DRAWING NUMBER
4.4.2.6	Submunition Body Assembly, Dummy (No. 4 S/M)		1.0mm ♡	9386965
				NEXT HIGHER ASSEMBLY
				N/A
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR NOTE	REQUIREMENT PARAGRAPH	PARAGRAPH DESIGNATION /INSPECTION METHOD
Critical	None defined.				
Major					
101	Plastic cone missing or improperly installed		0.40%	3.2	Visual
Minor					
201	Black band missing		100%	N/A	Visual
202	Evidence of poor workmanship		0.65%	3.8	Visual
NOTES					

(SC) 7

Source: https://assist.dla.mil -- Downloaded: 2026-02-20 04:12 GMT
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Cover, Plastic	1 of 1	9386966
			NEXT HIGHER ASSEMBLY 9386967

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major	None defined.				
Minor					
201	Thickness		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

8 (96)

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-04-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Tolerence Pad Assembly	1 of 1	9390414
			NEXT HIGHER ASSEMBLY: N/A

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Plastic cover missing or improperly installed		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

(9e)

Source: https://assist.dla.mil -- Downloaded: 2022-08-27 22:27
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Submunition Body, Dummy (Powdered Metal No. 5-9 S/M)	1 of 1	12598684
			NEXT HIGHER ASSEMBLY: N/A

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR LOT%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Largest outside diameter		0.40%	3.2	Gage
102	Stacking height		0.40%	3.2	Gage
Minor					
201	Largest inside diameter		0.65%	3.2	Gage
202	Smallest outside diameter		0.65%	3.2	Gage
203	Hardness		0.65%	3.2	Gage
204	Density		0.65%	3.2	4.5.4
205	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-04-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-63445 (AR)
AMENDMENT 5

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Lid, Container.				9334416
					NEXT HIGHER ASSEMBLY 9334144
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Plastic integrity test	50		3.9	4.5.5
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

11 (99)

Source: https://assist.dla.mil -- Downloaded: 2026-02-20T04:27Z
Check the source to verify that this is the current version before use.

PAGE 11

6.3, Delete "US Army Armament Research and Development Command, ATTN: DRDAR-QAF-I" and substitute "Armament Research, Development and Engineering Center, US Army Armament, Munitions and Chemical Command, ATTN: AMSMC-QAF-I(D)".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1330-A361)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.