# MILITARY SPECIFICATION

# PRIMER, PERCUSSION, MODIFIED 209, LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery for Primer, Percussion, Modified 209. (See 6.1)

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

| | | |
|---|---|---|
| MIL-A-48078 | - | Ammunition, Standard Quality Assurance Provisions, General Specification For. |

STANDARDS

MILITARY

| | | |
|---|---|---|
| MIL-STD-105 | - | Sampling Procedures and Tables for Inspection by Attributes. |

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

DRAWINGS (See 6.4)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

| | | |
|---|---|---|
| 8864583 | - | Container, Ammunition, Plastic, for Percussion Primer, M39A1. |
| 8864584 | - | Box, Wire Bound, Packing, Ammunition, for Percussion Primer M39A1 Level "A" Packing. |
| 9207697 | - | Box, Fiberboard, Packing, Ammunition, for Percussion Primer, M39A1 Level "C" Packing. |
| 9357997 | - | Primer, Percussion, Modified 209, Assembly. |

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order to precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings, specifications and standards.

3.2 Parts. All parts shall comply with applicable drawings, specifications and standards.

3.3 Primers. The primers shall comply with all requirements specified on Drawing (Dwg.) 9357997 all associated drawings, and with all requirements specified in applicable specifications and standards.

3.4 Sensitivity. The primer assembly shall fire without evidence of failure when a maximum (max.) of twenty-nine and forty hundredths (29.40) inch ounces (see 6.6) of energy is applied and shall not fire when a minimum (min.) of two and ninety-one hundredths (2.91) inch-ounces of energy is applied. The test shall be performed as specified in 4.5.1.

3.5 Failure to fire (Duc). The primer assembly shall not fail to fire when tested as specified in 4.5.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

3.6 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship. All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, dents, punctures, cracks, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agent. All required markings ahll be neat and sharply defined. All packing components shall be dry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions, of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below and Table I.

| Part Description | Drawings | Quantity |
|---|---|---|
| Primer, Percussion, Modified 209 | 9357997 | 1015 |

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

**CLASSIFICATION OF DEFECTS & TESTS** MIL-P-70433(AR)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| | Primer, Percussion, Modified 209 Assembly | | | | 9357997 |
| | | | | | NEXT HIGHER ASSEMBLY |
| | | | | | -- |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| | Examination for Defects | 315 | | 3.3 | 4.4.2.1 |
| | Sensitivity | 315 | (Note A) | 3.4 | 4.5.1 |
| | Failure to fire | 700 | | 3.5 | 4.5.2 |

NOTES: A. This test may be performed on the same samples subjected to this examination for defects.

DRDAR-QA Form 160 Jul 77



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot shall contain parts of one lot interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Tests Tables sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.1 | Primer, Percussion, Modified 209, Assembly | 1 OF 2 | 9357997 |
| | | | NEXT HIGHER ASSEMBLY: -- |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | None defined. | | | | |
| Major | | NOTES | | | |
| 101 | Sensitivity test | A | - | 3.4 | 4.5.1 |
| 102 | Failure to fire test | B | - | 3.5 | 4.5.2 |
| 103 | Total length | | 0.40% | 3.3 | Gage |
| 104 | Diameter of body, max. | | 0.40% | 3.3 | Gage |
| 105 | Body cracked, punctured, dented or distorted | | 0.40% | 3.3 | Visual |
| 106 | Cup dented or punctured | | 0.40% | 3.3 | Visual |
| Minor | | | | | |
| 201 | Diameter of flange | | 0.65% | 3.3 | Gage |
| 202 | Crimp at bottom incomplete or missing | | 0.65% | 3.3 | Visual |
| 203 | Marking incorrect, illegible or missing | | 0.65% | 3.3 | Visual |
| 204 | Poor workmanship (excl. 105 and 106) | | 1.0% | 3.7 | Visual |

NOTES:

DRDAR-QA Form 160 Jul 77



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70433(AR)

| PARAGRAPH | TITLE | | SHEET 2 OF 2 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.1 | Primer, Percussion, Modified 209, Assembly | | | | 9357997 |
| | | | | | NEXT HIGHER ASSEMBLY -- |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| NOTES: | A. A sample of seven hundred (700) percussion primers shall be selected from each lot for this test. If the sum of the average critical height (H average) plus 5 times the standard deviation(s) multiplied by the weight of the ball exceeds the maximum requirement, or, if the sum of the average critical height (H average) minus 2 times the standard deviation(s) multiplied by the weight of the ball is less than the min. requirement, the lot shall be rejected.<br><br>B. A sample of three hundred and fifteen (315) percussion primers shall be selected from each lot for this test. If two (2) or more primers fail to comply with the requirement, the lot shall be rejected. | | | | |

NOTES:

DRDAR-QA Form 160 Jul 77



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70433(AR)

| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.2 | Container or set-up box (prior to sealing) | 1 OF 1 | 8864583 or 9207697 |
| | | | NEXT HIGHER ASSEMBLY: 8864584 |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | None defined. | | | | |
| Major | | | | | |
| 101 | Tray missing or damaged | | 0.40% | 3.3 | Visual |
| 102 | Primer missing | | 0.40% | 3.3 | Visual |
| Minor | | | | | |
| 201 | Packing component missing | | 0.65% | 3.3 | Visual |
| 202 | Poor workmanship | | 1.0% | 3.7 | Visual |

NOTES:

DRDAR-QA Form 160 Jul 77



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70433(AR)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.3 | Sealed Plastic Container, Set-up Box and Carton | | | | 8864583 or 9207697 |
| | | | | | NEXT HIGHER ASSEMBLY |
| | | | | | 8864564 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined. | | | | |
| Major | | | | | |
| 101 | Sealing tape incomplete, badly wrinkled or missing | | 0.40% | 3.3 | Visual |
| 102 | Container cut, punctured or torn | | 0.40% | 3.3 | Visual |
| Minor | | | | | |
| 201 | Marking incorrect, illegible or missing | | 0.65% | 3.3 | Visual |
| 202 | Poor workmanship | | 1.0% | 3.7 | Visual |

NOTES:

DRDAR-QA Form 160 Jul 77



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70433(AR)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.4 | Packing Box (Sealed) | | | | 8864584 |
| | | | | | NEXT HIGHER ASSEMBLY -- |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined. | | | | |
| Major | | | | | |
| 101 | Hardware or wire broken, loose or missing | | 0.40% | 3.3 | Visual/Manual |
| 102 | Board broken or split | | 0.40% | 3.3 | Visual |
| Minor | | | | | |
| 201 | Contents loose (when box is tilted) | | 0.65% | 3.3 | Manual |
| 202 | Hardware or wire improperly engaged or mislocated | | 0.65% | 3.3 | Visual |
| 203 | Metallic seal unsealed, mislocated or missing | | 0.65% | 3.3 | Visual |
| 204 | Marking incorrect, illegible or missing | | 0.65% | 3.3 | Visual |

NOTES:

DRDAR-QA Form 160 Jul 77



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1, and the test method paragraph (See 4.5). The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Sensitivity. The primer assemblies shall be conditioned at a temperature of seventy-five (75) plus or minus five (5) degrees Fahrenheit (F.) for twenty-four (24) hours min. prior to performing this test.

The sample of seven-hundred (700) primer assemblies shall be divided into groups of 50 primers each. A group shall be selected, and each primer in the group shall be assembled in the test fixture specified in 4.4.4, and tested by dropping a steel ball weighing 1.94 plus or minus .02 ounces on the firing pin from a height of three and one-half (3.5) inches. The drop height is measured as the distance from the bottom of the ball to the top of the firing pin. The number of primers that fire, or exhibit a firing failure shall be recorded. This procedure shall be repeated at successively increasing heights of one-half (0.5) inch using a new group of 50 primers at each height until a height is reached at which all primers fire in the group being tested. The test fixture shall then be set at a height of three (3) inches and the above procedure repeated at successively decreasing heights of one-half (0.5) inch, using a new group of 50 primers at each height, until a height is reached at which all primers in the group being tested do not fire. Acceptance or rejection of the lot shall be determined from calculations based on recorded data (see 6.7). All primers subjected to test shall be scrapped. Untested primers may be returned to the lot.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.5.2 Failure to fire (duds). The primer assemblies shall be conditioned at a temperature of seventy-five (75) plus or minus five (5) degrees Fahrenheit (F.) for twenty-four (24) hours min. prior to performing this test. Each primer shall be assembled in the test fixture specified in 4.4.4 and a steel ball weighing 1.94 plus or minus .02 ounces dropped on the firing pin from a height of 15 inches, max. The number of primers that exhibit a firing failure shall be recorded to determine compliance with the requirement.

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level A. The primer assemblies shall be preserved and packaged in accordance with Dwg. 8864583.

5.1.2 Level C. The primer assemblies shall be preserved and packaged in accordance with Dwg. 9207697.

5.2 Packing.

5.2.1 Level A. The containers shall be packed in accordance with Dwg. 8864584.

5.2.2 Level C. The packages shall be packed in accordance with Dwg. 9207697.

5.3 Marking. Unit and exterior containers shall be marked in accordance with instructions contained on Dwgs. 8864583, 8864584 and 9207697, as applicable.

5.4 Shipping. When components from more than one lot are shipped at one time, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. The assembly covered by this specification is intended for use with Igniter, Time, Blasting Fuse, Weatherproof: M60.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAT-I, Dover, New Jersey 07801. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects and tests paragraph number.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARRADCOM.

6.5 Firing failure. A firing failure is defined as follows:

a. Dud - A failure wherein initiation of the primer mixture does not occur.

b. Squib - A failure wherein the primer mixture burns with a hiss or fizz.

c. Hangfire - A failure wherein an audible delay occurs between the application of energy and the detonation report.

6.6 Inch-ounces. The product of drop height in inches and the weight of the ball in ounces.

6.7 Formula and method of determining H average and s.

6.7.1 Formula.

H average = A plus B plus C
s = I times the square root of L minus M

where: (see 6.7.2)
A = the sum of column 3
B = the first drop height at which all primers misfired
C = One-half the drop height increment (see 6.8)
L = the sum of column 5
M = the square of the sum of column 3
I = the drop height increment

6.7.2 Tabulation of data. Divide a sheet a paper into 5 columns and tabulate the data as follows:

a. Title Column 1 "Height of Drop" and list all drop heights in order starting with the lowest height. Do not list the heights at which all elements fired or misfired.

b. Title Column 2 "Number of Failures" and list the sum of the number of elements that misfired, squibbed or hangfire (see 6.5) at each intermediate height.

c. Title Column 3 "Decimal Fraction of Elements Failing to Fire at Each Intermediate Height" and record the decimal fraction that failed to fire at each intermediate height. This number is obtained by dividing the value obtained under "Number of Failures" by the number of elements tested at that height. Caculation should be carried out and recorded to the nearest one-hundredth (0.01).



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

d. Title Column 4 "Standard Deviation Factor" and list odd numerals in sequence starting with "1", for as many drop heights as are listed in Column 1.

e. Title Column 5 "Standard Deviation Factor Times Fraction of Failures" and, by multiplying each decimal fraction in Column 3 by the number on the same line in Column 4, enter the product on the corresponding line in Column 5.

6.7.3 Procedure for solving equations.

a. To obtain "A" - Add the values in Column 3 and substitute the sum for "A".

b. To obtain "B" - The first drop height at which all primers failed to fire.

c. To obtain "C" - Divide the drop height increment by 2 and substitute the dividend for "C".

d. To obtain "L" - Add the value in Column 5 and substitute the sum for "L".

e. To obtain "M" - Square the sum of Column 3 and substitute the sum for "M".

f. To obtain "H average" - Add the values substituted for A, B and C.

g. To obtain "s" - Subtract the value substituted for "M" from the value substituted for "L" and then obtain the square root of the difference and then multiply the square root by the height of increment.

h. Using the calculated values for "H average" plus 5s multiplied by the maximum weight of the ball is equal to or less than the maximum inch ounce energy value required, and "H average" minus 2s multiplied by the minimum weight of the ball is equal to or greater than the minimum energy value required, the lot should be considered acceptable for sensitivity.

6.8 Height of increment. The height of increment is defined as a constant interval in inches between successive drop heights which must be considered in calculating average height and the standard deviation in drop height, whenever it differs from one-half (0.5) inch.

6.9 Check test for possible deterioration of primers. The following test is designed to prevent primers that have deteriorated from being assembled into major ammunition items. The test shall be performed on primers from any lot which has been stored under normal conditions for more than two (2) years, or under adverse conditions for any period of time. If the specification for the ammunition item into which primers are assembled does not require that the check test be performed, the Contracting Officer should insert in the contract a provision for the performance of the check test. The Contracting Officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check tests for possible deterioration. The primers shall be selected from each lot and tested as specified in 6.9.1 and 6.9.2.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

6.9.1 Sensitivity. The test shall be performed as specified in 4.5.1 using test equipment specified in 4.4.4. A sample of 1050 primers shall be selected from each lot for this test. Seventy-five primers shall be tested at each height. If H average plus 4.66s exceeds the upper limit specified in 3.4, or if H average minus 1.86s is less than the lower limit specified in 3.4 the lot shall be rejected.

6.9.2 Failure to fire (duds). This test shall be performed as specified in 4.5.2. A sample of 315 primers shall be selected from each lot for this test. Failure to function of three (3) or more primers shall reject the lot.

6.10 Data cards. (See MIL-A-48078). Distribution of data cards shall include the following: Commander, U. S. Army Armament Research and Development Command, ATTN: DRDAR-QAT-M, Dover, New Jersey 07801.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A270)



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS:** In a continuing effort to make our standardization documents better, the DoD provides this form for submitting comments and suggestions for improvements. All users of military standardization documents are invited to p suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE* mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretatic too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate th problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, ar acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are bein considered.

*NOTE:* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification o specification requirements on current contracts. Comments submitted on this form do not constitute or imply authoriza to waive any portion of the referenced document*(s)* or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEPARTMENT OF THE ARMY

NO PO
NECES
IF MA
IN T
UNITED

**OFFICIAL BUSINESS**
PENALTY FOR PRIVATE USE $300

**BUSINESS REPLY MAIL**
FIRST CLASS PERMIT NO. 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
U.S ARMY ARMAMENT RESEARCH & DEVELOPMENT COMMAND
ATTN: DRSMC-QA
DOVER, NJ 07801

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| MIL-P-70433 | PRIMER, PERCUSSION, MODIFIED 209 LOADING, ASSEMBLING AND PACKING |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR<br>☐ USER<br>☐ MANUFACTURER<br>☐ OTHER *(Specify)*: _____ |
| b. ADDRESS *(Street, City, State, ZIP Code)* | |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.