INCH-POUND
MIL-P-70452C (AR)
20 JULY 1991
SUPERSEDING
MIL-P-70452B (AR)
10 JULY 1985

MILITARY SPECIFICATION

PRIMER, ELECTRIC, M125
METAL PARTS FOR

This specification is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1.0 SCOPE

1.1 Scope: This specification covers the requirements and quality assurance provisions for the metal parts for the Primer, Electric M125.

2.0 APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. - Unless otherwise specified, the following specifications, standards, and handbooks of the issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament Research and Development Center, Attn: AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC-1315

Distribution Statement A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-A-48078	Ammunition, Standard Quality Assurance Provision, General Specification for

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1169	Packaging, Packing and Marking for Shipment of Inert Ammunition Components
MIL-STD-1235	Single and Multiple Continuous Sampling Procedures and Tables for Inspection by Attributes

OTHER

ASTM E-3	Metals Handbook (Volume 7)

2.1.2 Other Government documents, drawings and publications. - The following Government documents, drawings and publications form a part of this specification to the extent specified herein.

DRAWINGS (See 6.4)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

8839509	Retainer
8839514	Closing Disc
9327341	Liner
9327342	Plug, Closing
12525016	Primer, Electric, M125
12525018	Body
12525019	Head, Primer
12525631	Tip, Primer

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

2.2 Order of precedence. - In the event of a conflict between the text of this specification and the reference specifications cited herein, the text of this specification shall take precedence.

3.0 REQUIREMENTS

3.1 Material. - Materials shall be in accordance with applicable drawings and specifications.

3.2 Metal parts components. - The metal parts components shall comply with all requirements specified on applicable drawings and specifications referenced herein.

3.3 Hydrostatic test. - The body tubing shall withstand the application of a minimum hydrostatic pressure without rupture or indication of flaws, as evidenced by leaks, and without permanent deformation beyond drawing requirements.

3.4 Workmanship. - All parts shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be legible.

3.5 First article inspection. - This specification makes provisions for first article inspection. Requirements for submission of first article samples by the contractor shall be as specified in the contract.

4.0 QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply.

4.2 Classification of inspection. - The inspection requirements specified herein are classified as follows:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. - The contractor shall submit a first article sample for evaluation in accordance with 4.3.2. The sample shall consist of parts which have been produced by the contractor or furnished by a supplier which have been manufactured using the same production processes, procedures, and equipment which will be used in fulfilling the contract. All parts and materials shall be obtained from the same source of supply as will be used in regular production. A first article sample, or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing processes, material used, drawing, specification or source of supply as to significantly affect product uniformity as determined by

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

the Government. The first article sample shall consist of ten each o. every component. Whenever castings, mold or die cast parts are involved, five parts minimum from each cavity are required when there are two or more cavities.

4.3.2 Inspections to be performed. - See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. - See MIL-A-48078.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. - Inspection lots shall comply with lot provisions of MIL-A-48078.

4.4.2 Examination. - Unless otherwise specified in the classification of defects and tests tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

TABLE I. - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH	TITLE: Retainer		SHEET 1 OF 1		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Retainer (dwg. 8839509) Examination for Defects	10		3.2	4.4.2.1
	Head Primer (dwg. 12525019) Examination for Defects	10		3.2	4.4.2.2
	Body (dwg. 12525018) Examination for Defects	10		3.2	4.4.2.3
	Tip, Primer (dwg. 12525631) Examination for Defects	10		3.2	4.4.2.4
	Disc, Closing (dwg. 8839514) Examination for Defects	10		3.2	4.4.2.5
	Liner (dwg. 9327341) Examination for Defects	10		3.2	4.4.2.6
	Plug, Closing (dwg. 9327342) Examination for Defects	10		3.2	4.4.2.7

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.1	TITLE Retainer		SHEET 1 OF 1		DRAWING NUMBER 8839509
					NEXT HIGHER ASSEMBLY 12525017
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter, minimum		0.40%	3.2	Gage
102	Major diameter, minimum		0.40%	3.2	Gage
103	Diameter of hole, minimum		0.40%	3.2	Gage
Minor					
201	Thickness, minimum		0.65%	3.2	Gage
202	Slot missing		0.65%	3.2	Visual
203	Surface finish incorrect		0.65%	3.2	Visual
204	Pitch diameter, maximum		0.65%	3.2	Gage
205	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.2	TITLE Head Primer		SHEET 1 OF 5		DRAWING NUMBER 12525019
					NEXT HIGHER ASSEMBLY 12525017
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Minor diameter of large internal threads, maximum		100%	3.2	Gage
2	Pitch diameter of large internal threads, maximum		100%	3.2	Gage
Major					
101	Pitch diameter of external threads, minimum		0.40%	3.2	Gage
102	True position of pitch diameter of large internal threads with pitch diameter of external threads		0.40%	3.2	Gage
103	Pitch diameter of small internal threads, maximum		0.40%	3.2	Gage
104	Minor diameter of small internal threads, maximum		0.40%	3.2	Gage
105	Major diameter of external threads, minimum		0.40%	3.2	Gage

NOTES:

,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.2	TITLE Head Primer		SHEET 2 OF 5		DRAWING NUMBER 12525019
					NEXT HIGHER ASSEMBLY 12525017
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
106	True position of pitch diameter of small internal threads with diameter of large unthreaded cavity		0.40%	3.2	Gage
107	Flange diameter		0.40%	3.2	Gage
108	True position of flange diameter with pitch diameter of external threads		0.40%	3.2	Gage
109	Flange thickness		0.40%	3.2	Gage
110	Diameter of large unthreaded cavity		0.40%	3.2	Gage
111	Diameter of small unthreaded cavity		0.40%	3.2	Gage
112	True position of diameter of small unthreaded cavity with diameter of large unthreaded cavity		0.40%	3.2	Gage
113	Protective coating missing		0.40%	3.2	Visual
114	Protective coating inadequate	See 4.5.2		3.2	4.5.2
115	Perpendicularity of forward face of flange to external thread pitch diameter		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.2	TITLE Head Primer		SHEET 3 OF 5		DRAWING NUMBER 12525019
					NEXT HIGHER ASSEMBLY 12525017
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Pitch diameter of external threads, maximum		0.65%	3.2	Gage
202	Pitch diameter of large internal threads, minimum		0.65%	3.2	Gage
203	Pitch diameter of small internal threads, minimum		0.65%	3.2	Gage
204	Length, total		0.65%	3.2	Gage
205	Length from flange to beginning of external threads		0.65%	3.2	Gage
206	Length from flange to end of external threads		0.65%	3.2	Gage
207	Depth of small unthreaded cavity		0.65%	3.2	Gage
208	Diameter, forward end of large threaded cavity		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.2	TITLE Head Primer		SHEET 4 OF 5		DRAWING NUMBER 12525019
					NEXT HIGHER ASSEMBLY 12525017
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
209	Outside diameter, forward		0.65%	3.2	Gage
210	Depth from aft end of large threaded cavity to front face		0.65%	3.2	Gage
211	Minimum effective length of large internal thread		0.65%	3.2	Gage
212	Depth from front face to rear of small threaded cavity		0.65%	3.2	Gage
213	Countersink angle at the rear of small threaded cavity		0.65%	3.2	Visual
214	True position of largest internal diameter to large internal threads		0.65%	3.2	Gage
215	Depth from front face to forward end of large internal threads		0.65%	3.2	Gage
216	Minimum effective length of small internal threads		0.65%	3.2	Gage
217	Depth of wrench holes		0.65%	3.2	Gage
NOTES:					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.2	TITLE Head Primer		SHEET 5 OF 5		DRAWING NUMBER 12525019
					NEXT HIGHER ASSEMBLY 12525017
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
218	Diameter of wrench holes		0.65%	3.2	Gage
219	True position of wrench holes		0.65%	3.2	Gage
220	Chamfers missing or incorrect		0.65%	3.2	Visual
221	Radii missing or incorrect		0.65%	3.2	Visual
222	Surface finish incorrect		0.65%	3.2	Visual
223	Evidence of poor workmanship		0.65%	3.2	Visual
224	True position of minor diameter of large internal thread with large unthreaded cavity		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.3	TITLE Body		SHEET 1 OF 3		DRAWING NUMBER 12525018
					NEXT HIGHER ASSEMBLY 12525016
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
*1	Flash hole(s) missing		100%	3.2	Gage
2	Hydrostatic (Prior to machining)		100%	3.3	4.5.1
3	Metal parts defects 1/		100%	3.2	Visual 2/
4	Major diameter of external thread, minimum		100%	3.2	Gage
5	Pitch diameter of external thread, minimum		100%	3.2	Gage
6	Martensite microstructure	3/		3.2	4.5.3
Major					
101	Plug gage fails to pass through body		0.40%	3.2	Gage
102	Location of first row of holes		0.40%	3.2	Gage
103	Location of second row of holes		0.40%	3.2	Gage
104	Wall thickness		0.40%	3.2	Gage
105	Diameter of flash holes		0.40%	3.2	Gage

NOTES:
1/ Cracks, splits, tears, metal discontinuities, etc.
2/ Use 4x magnification aid.
3/ Two (2) samples shall be pulled per inspection lot as defined in MIL-STD-105D

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.3	TITLE Body		SHEET 2 OF 3		DRAWING NUMBER 12525018
					NEXT HIGHER ASSEMBLY 12525016
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
106	Pitch diameter of internal thread, maximum	See 4.5.2	0.40%	3.2	Gage
107	Minor diameter of internal thread, maximum		0.40%	3.2	Gage
108	True position of flash holes		0.40%	3.2	Gage
109	Protective finish missing		0.40%	3.2	Visual
110	Protective finish inadequate			3.2	4.5.2
111	Outside diameter		0.40%	3.2	Gage
112	Flash hole variations, maximum 3/		0.40%	3.2	Gage
113	Total length minimum		100%	3.2	Gage
Minor					
201	Total length maximum		0.65%	3.2	Gage
202	Length of internal thread, minimum		0.65%	3.2	Gage
203	Length to end of external threads		0.65%	3.2	Gage

NOTES:
3/ Check two holes, minimum, in each row.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.3	TITLE Body		SHEET 3 OF 3		DRAWING NUMBER 12525018
					NEXT HIGHER ASSEMBLY 12525016
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
204	Length of thread pilot		0.65%	3.2	Gage
205	Diameter of thread pilot		0.65%	3.2	Gage
206	Pitch diameter of external threads, maximum		0.65%	3.2	Gage
207	Pitch diameter of internal threads, minimum		0.65%	3.2	Gage
208	Evidence of poor workmanship		0.65%	3.4	Visual
209	True position of external thread		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.4	TITLE Tip, Primer		SHEET 1 OF 2		DRAWING NUMBER 12525631
					NEXT HIGHER ASSEMBLY 12525016
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Major diameter of thread, minimum		0.40%	3.2	Gage
102	Pitch diameter of thread, minimum		0.40%	3.2	Gage
Minor					
201	Major diameter of thread, maximum		0.65%	3.2	Gage
202	Pitch diameter of thread, maximum		0.65%	3.2	Gage
203	Diameter of blade		0.65%	3.2	Gage
204	Width of blade		0.65%	3.2	Gage
205	Radius on blade		0.65%	3.2	Visual
206	Length of blade		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.4	TITLE Tip, Primer		SHEET 2 OF 2		DRAWING NUMBER 12525631
					NEXT HIGHER ASSEMBLY 12525016
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
207	Length from aft end of blade to aft end of threads		0.65%	3.2	Gage
208	Protective finish missing		0.65%	3.2	Visual
209	Protective finish inadequate	4.5.2		3.2	4.5.2
210	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Disc, Clo ng				8839514
					NEXT HIGHER ASSEMBLY 12525017
CATEGORY	EXAMINAT N OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter		0.40%	3.2	Gage
102	Thickness		0.40%	3.2	Gage
Minor					
201	Evidence of p r workmanship		0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.6	TITLE Liner		SHEET 1 OF 1		DRAWING NUMBER 9327341
					NEXT HIGHER ASSEMBLY 12525016
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Length		0.65%	3.2	Gage
202	Width		0.65%	3.2	Gage
203	Thickness		0.65%	3.2	Gage
204	Evidence of poor workmanship		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.7	TITLE Plug, Closing		SHEET 1 OF 2		DRAWING NUMBER 9327342
					NEXT HIGHER ASSEMBLY 9327346
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter, minimum		0.40%	3.2	Gage
102	Hole missing or obstructed		0.40%	3.2	Gage
103	Major diameter, minimum		0.40%	3.2	Gage
104	Thread length of engagement		0.40%	3.2	Gage
105	True position of large outside diameter		0.40%	3.2	Gage
Minor					
201	Pitch diameter, maximum		0.65%	3.2	Gage
202	Diameter of hole, minimum		0.65%	3.2	Gage
203	Diameter of counterbore		0.65%	3.2	Gage
204	Total length, maximum		0.65%	3.2	Gage
205	Length to shoulder, minimum		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.7	TITLE Plug, Closing		SHEET 2 OF 2		DRAWING NUMBER 9327342
					NEXT HIGHER ASSEMBLY 9327346
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
206	Length of thread relief		0.65%	3.2	Gage
207	Evidence of poor workmanship		0.65%	3.4	Visual
208	Depth of slot		0.65%	3.2	Gage
209	Width of slot		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:29Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. - Testing is described in the Quality Conformance Inspection tables.

4.4.4 Inspection equipment. - The inspection equipment required to perform the examination and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and Section 6.3 herein.

4.5 Test methods and procedures.

4.5.1 Hydrostatic test. - Prior to machining, the primer tubing shall be tested for not less than five seconds at the minimum hydrostatic pressure as calculated by the following formula:

$$P = \frac{1.8\ St}{D}$$

Where:

P = tests pressure in pounds per square inch (psi)
S = minimum specified annealed material yield strength, psi
t = specified minimum wall thickness in inches
D = specified maximum outside diameter in inches

Failure to meet the specified requirements shall be cause for rejection. Acceptable units shall be marked with an "H".

If the primer tubing procured for the bodies manufactured in accordance with this specification has been previously subjected to the hydrostatic test specified in this specification, a second hydrostatic test will not be required.

4.5.2 Protective coatings. - Procedures for testing, the cleaning of components and the application of protective coatings shall be in accordance with the criteria for testing as specified on the applicable component drawings and in the specification referenced thereon. One component per lot of components having protective finish applied shall be tested.

4.5.3 Heat treatment microstructure. - The heat microstructure shall be tempered martensite as determined by preparing the samples in accordance with Sections 27 and 29 of specification ASTM E-3. The structure shall be determined at magnifications of 500x or higher. Typical structures are depicted on pages 38 and 39 of the Volume 7 of the Eighth edition of Metals Handbook.

5.0 PACKAGING

5.1 Packaging, packing and marking. - The parts shall be packaged, packed and marked in accordance with MIL-STD-1169.

6.0 NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

6.1 Intended use. - The components covered by this specification are intended for use in the M125 electric primer. The M125 primer is utilized in the 120mm Kinetic Energy (KE) cartridges.

6.2 Ordering data. - See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. - (See MIL-A-48078). - Submit equipment designs as required, to Commander, ARDC, ATTN: DRSMC-QAT-I(D)D, Dover, New Jersey 07801.

6.4 Drawings. - Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research and Development Center (ARDC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal, or U.S. Army Research and Development Command drawings. Technical data originally prepared by these activities is now under the cognizance of ARDC.

Custodian:
ARMY-AR

Preparing Activity:
ARMY-AR

Project Number:
1315-AD46

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

RECOMMEND A CHANGE	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-P-70452C	910720

3. DOCUMENT TITLE

PRIMER, ELECTRIC, M125 METAL PARTS FOR

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION

c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME COMMANDER, U.S. ARMY ARMAMENT RESEARCH DEVELOPMENT AND ENGINEERING CENTER	b. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON
c. ADDRESS (Include Zip Code) ATTN: AMSMC-QAA(D) PICATINNY ARSENAL, NEW JERSEY 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 Previous editions are obsolete 198/290

Source: https://assist.dla.mil -- Downloaded: 20240-26T04:29Z
Check the source to verify that this is the current version before use.