INCH-POUND
MIL-S-70535 (AR)
13 September 1994

MILITARY SPECIFICATION

SIMULATOR, TARGET HIT, M25
PARTS FOR AND LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements, examination and tests for loading, assembling and packing for one type of simulator designated as Simulator, Target Hit, M25. (See 6.1)

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use to improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 1370

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-1234 - Pyrotechnics: Sampling, Inspection and Testing

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from DODSSP - Customer Service, Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (See 6.4)

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT DRAWINGS

12972801 - Simulator, Target Hit, M25
12972823 - Packing & Marking for Box, Fiberboard, for Simulator, Target Hit, M25
12972824 - Packing & Marking for Box, Packing, for Simulator, Target Hit, M25
12972825 - Combination of Adopted Items for Simulator, Target Hit, M25
12972829 - Palletized Pack, Simulator, Target Hit, M25

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

TEST PROCEDURES

ITOP 4-2-602 - International Test Operations Procedure

(Copies of other Government documents, drawings, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM B-117 - Method of Salt Spray (Fog) Testing

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained. (See contract provisions for additional precedence criteria).

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with the applicable drawings and specifications.

3.1.1 Nonmetals. Nonmetal materials such as sealants, adhesives and plastics shall not deteriorate with age or change properties to the extent that the simulators fail to conform to the functional requirements specified herein.

3.1.2 Metals. Metals shall be corrosion resistant or shall be suitably treated to resist corrosion. Metals shall meet the requirements of the Salt Spray test IAW ASTM B-117.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

3.1.3 Moisture content.

3.1.3.1 Composition. The moisture content of all compositions at time of loading shall be as specified in applicable drawings.

3.1.3.2 Paper and paper products. The moisture content of the paper and paper product components of the simulator assembly shall not exceed 6.0 percent at time of loading.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Dwg. 12972801, all associated drawings, and with all requirements specified in applicable specifications and standards.

3.2.1 Assembly. The simulator assembly shall correctly interface with the gunfire device manufactured by Hoffmann-Werke designated as Simulator, Tank, Gunfire Device 17-61.

3.3 Functioning. The Target Hit Simulator shall be capable of functioning when initiated by a 12 volt, 1.2 amps power source and comply with the following requirements after conditioning at specified temperatures.

3.3.1 Performance characteristics. The simulators when properly initiated shall provide a flash, and shower of sparks visible at 3000 meters.

3.4 Environmental conditions.

3.4.1 Temperature conditioning. The simulators shall meet the performance requirements after temperature conditioning as follows:

a. Cold, $-25^{\circ} \pm 5^{\circ}$ F.
b. Ambient, $70^{\circ} \pm 5^{\circ}$ F
c. Hot, $125^{\circ} \pm/5^{\circ}$ F
d. Hot, Storage $145^{\circ} \pm 5^{\circ}$ F
e. Cold, Storage $-60^{\circ} \pm 5^{\circ}$ F

3.5 Jumble. The simulators shall be safe to handle and shall meet the following requirements when tested as specified in 4.5.4.

a. The simulators shall not function during test.

b. There shall be not evidence of powder leakage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

3.6 Resistance. The simulator assembly resistance shall be as specified in Dwg. 12972801.

3.7 Water immersion. The simulators shall withstand the ingress of water when tested in accordance with 4.5.5 and shall meet the functioning requirements as specified in 3.3.

3.8 Five foot drop. The simulators shall be safe to handle and be operable after being subjected to a Five foot test in accordance with 4.5.6.

3.9 Seven foot drop. The packaged simulators shall be safe to handle and be operable after being subjected to a Seven foot drop test in accordance with 4.5.7.

3.10 Loose cargo. The packaged simulators shall be safe to handle and be operable after being subjected to Loose Cargo test in accordance with 4.5.8.

3.11 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provision herein (see 4.3).

3.12 Workmanship. The parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, crazes, porosity, warpage, burn marks, blisters, excess flash, scratches, dirt, grease and other defects and foreign matter which would affect appearance and serviceability. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined. All packing components shall be dry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 General provisions. Unless otherwise specified herein, the provisions of MIL-A-48078 apply and form a part of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)

b. Quality conformance inspection (see 4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the assemblies, components, and test specimens listed in Table I in the quantities indicated.

4.3.2 Inspections to be performed. As determined by the Government, the first article assemblies, components, and test specimens may be subjected to any or all of the examinations and test specified in this detail specification and be inspected for compliance with any or all requirements of the applicable drawings.

4.3.2.1 Components and assemblies. See Table I and MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.3.2.2 Target hit simulators. The 162 simulators (1 shipping case) shall be subjected to the sequential tests of Table I. The simulators shall be serialized to identify the units being temperature conditioned.

4.3.3 Rejection. If any assembly, component, or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon any failure of an assembly, component, or test specimen to comply with any of the requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET		DRAWING NUMBER
	Simulator, Target Hit, M25	1 OF 4		See below
				NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Cable, Electrical (Dwg. 12972821) Examination for Defects	30	3.2	4.4.2.1
	Plug Electrical Assembly (Dwg. 12972810) Examination for Defects	30	3.2	4.4.2.2
	Pin, Electrical (Dwg. 12972813) Examination for Defects	60	3.2	4.4.2.3
	Cap, Pin Protecting (Dwg. 12972807) Examination for Defects	30	3.2	4.4.2.4
	Cover, Polystyrene (Dwg. 12972812) Examination for Defects	30	3.2	4.4.2.5
	Cover, Flash Charge (Dwg. 12972811) Examination for Defects	30	3.2	4.4.2.6

NOTES:
(a) Box shall be refilled w/inert simulators before test to compensate for withdrawn units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE Simulator, Target Hit, M25	SHEET 2 OF 4		DRAWING NUMBER See below
				NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Quickmatch (Dwg. 9342150) Examination for Defects	30	3.2	4.4.2.7
	Tube, Outer (Dwg. 12972814) Examination for Defects	30	3.2	4.4.2.8
	Tube, Inner (Dwg. 12972815) Examination for Defects	30	3.2	4.4.2.9
	Base (Dwg. 12972817) Examination for Defects	30	3.2	4.4.2.10
	Body (Dwg. 9342143) Examination for Defects	30	3.2	4.4.2.11
	Cap, Protecting (Dwg. 12972808) Examination for Defects	30	3.2	4.4.2.12

NOTES:
(b) From the 7ft drop units. (c) Of these units, 5 each shall be previously temp conditioned at hot storage and cold storage temp.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE Simulator, Target Hit, M25	SHEET 3 OF 4		DRAWING NUMBER See below
				NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Igniter and Cable Assembly (Dwg. 12972809) Examination for Defects	30	3.2	4.4.2.13
	Case Cartridge Assembly (Dwg. 12972803) Examination for Defects	30	3.2	4.4.2.14
	Igniter, Electrical Assembly (Dwg. 12972802) Examination for Defects	30	3.2	4.4.2.15
	Black Powder Grain (Dwg. 12972826) Examination for Defects		3.2	4.4.2.16
	Charge, Expulsion (Dwg. 12972805) Examination for Defects		3.2	4.4.2.17
	Composition, Combustible (Dwg. 12972806) Examination for Defects		3.2	4.4.2.18

NOTES:
(d) From the water immersed units. (e) From the 5ft drop units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE Simulator, Target Hit, M25	SHEET 4 OF 4		DRAWING NUMBER See below
				NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Star Ignition (Dwg. 12972819) Examination for Defects		3.2	4.4.2.19
	Star Mix (Dwg. 12972818) Examination for Defects		3.2	4.4.2.20
	Simulator, Target Hit, M25 (Dwg. 12972801)			
	Examination for Defects	212	3.1.3, 3.2	4.4.2.23, 4.4.2.24
	Jumble	50	3.5	4.5.4
	Sequential tests:	1 box		
	Functioning-amb (w/resist measure)	10	3.6, 3.9	4.5.2, 4.5.3
	Seven foot drop	152 (a)	3.6, 3.9	4.5.7
	Functioning-amb (w/resist measure)	10 (b)	3.6, 3.4.1	4.5.2, 4.5.3
	Functioning-hot (w/resist measure)	10 (b)	3.6, 3.4.1	4.5.2, 4.5.3
	Loose Cargo	132(a)(c)	3.10	4.5.8
	Water Immersion	10	3.7	4.5.5
	Functioning-amb (w/resist measure)	10 (d)	3.6, 3.4.1	4.5.2, 4.5.3
	Five foot drop	10(c)(f)	3.8	4.5.6
	Functioning-amb (w/resist measure)	10 (e)	3.6, 3.4.1	4.5.2, 4.5.3
	Functioning-amb (w/resist measure)	112	3.6, 3.4.1	4.5.2, 4.5.3

NOTES:
(f) Drop Orientations (per temperature): 2 bottom down, 2 protecting cap down, 1 face down.

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of simulators shall contain:

a. Parts of one kind from one manufacturer.
b. Electric igniters from not more than one lot interfix number from one manufacturer.
c. Composition ingredients from not more than one lot or batch.

4.4.2 Examinations and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II, using the inspection levels stated in the Classification of Characteristics paragraphs.

TABLE II. Attributes sampling inspection.

	Inspection Levels	
Lot Size	I	II
2 to 8	*	3
9 to 15	*	3
16 to 25	*	3
26 to 50	*	3
51 to 90	*	5
91 to 150	125	5
151 to 280	125	8
281 to 500	125	8
501 to 1200	125	13
1201 to 3200	125	13
3201 to 10000	125	13
10001 to 35000	315	13
35001 to 150000	315	13
150001 to 500000	500	13
500001 and over	500	13

Numbers under inspection levels indicate sample size; asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

b. Alternative quality conformance provisions. Unless otherwise specified herein or provided for in the contract, alternative quality conformance procedures, methods, or equipment, such as statistical process control, tool control, variables sampling or other types of sampling plans, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.6). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality conformance provision(s) herein. In case of dispute as to whether the contractors proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Cable, Electrical	1 OF 1	12972821
			NEXT HIGHER ASSEMBLY 12972809

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material		3.1	Certification
102	Diameter with insulation	Level I	3.2	Gage
103	Length of longer stripped end	Level I	3.2	Gage
104	Length of shorter stripped end	Level I	3.2	Gage
Minor				
201	Overall length	Level II	3.2	Gage
202	Color	Level II	3.2	Visual
203	Poor workmanship	Level II	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Plug, Electrical Assembly	1 OF 1	12972810
			NEXT HIGHER ASSEMBLY 12972802

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material		3.1	Certification
102	Threaded insert missing	Level I	3.2	Visual
103	Presence of molding compound, dirt or foreign matter on or around insert threads	Level I	3.2	Visual
Minor				
201	Color	Level II	3.2	Visual
202	Poor workmanship	Level II	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Pin, Electrical	1 OF 1	12972813
			NEXT HIGHER ASSEMBLY 12972802

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material		3.1	Certification
102	Outer diameter of pin	Level I	3.2	Gage
103	Pitch diameter	Level I	3.2	Gage
104	Major diameter	Level I	3.2	Gage
Minor				
201	Presence of slot	Level II	3.2	Visual
202	Poor workmanship	Level II	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Cap, Pin Protecting	1 OF 1	12972807
			NEXT HIGHER ASSEMBLY 12972801

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material		3.1	Certification
102	Inner diameter of pin cavity	Level I	3.2	Gage
Minor				
201	Color	Level II	3.2	Visual
202	Poor workmanship	Level II	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-S-70535 (AR)

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Cover, Polystyrene			12972812
				NEXT HIGHER ASSEMBLY 12972802
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material		3.1	Certification
102	Larger cover diameter	Level I	3.2	Gage
103	Smaller cover diameter	Level I	3.2	Gage
Minor				
201	Poor workmanship	Level II	3.12	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Cover, Flash Charge	1 OF 1	12972811
			NEXT HIGHER ASSEMBLY 12972802

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material		3.1	Certification
102	Overall diameter	Level I	3.2	Gage
103	Small outer diameter	Level I	3.2	Gage
104	Overall height	Level I	3.2	Gage
105	Fin thickness	Level I	3.2	Gage
106	Sealing lip properly molded	Level I	3.2	Visual
Minor				
201	Poor workmanship	Level II	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Quickmatch	1 OF 1	9342150
			NEXT HIGHER ASSEMBLY 12972802

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material		3.1	Certification
Minor				
201	Length	Level II	3.2	Gage
202	Poor workmanship	Level II	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Tube, Outer	1 OF 1	12972814
			NEXT HIGHER ASSEMBLY 12972803

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material		3.1	Certification
102	Outer diameter	Level I	3.2	Gage
103	Inner diameter	Level I	3.2	Gage
104	Length	Level I	3.2	Gage
Minor				
201	Poor workmanship	Level II	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Tube, Inner	1 OF 1	12972815
			NEXT HIGHER ASSEMBLY 12972803

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material		3.1	Certification
102	Inner diameter	Level I	3.2	Gage
103	Outer diameter	Level I	3.2	Gage
104	Length	Level I	3.2	Gage
Minor				
201	Poor workmanship	Level II	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Base	1 OF 1	12972817
			NEXT HIGHER ASSEMBLY 12972803

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material		3.1	Certification
102	Large outer diameter, max.	Level I	3.2	Gage
103	Small outer diameter, max.	Level I	3.2	Gage
Minor				
201	Inner diameter, max.	Level II	3.2	Gage
202	Thickness of flange	Level II	3.2	Gage
203	Overall height	Level II	3.2	Gage
204	Poor workmanship	Level II	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Body	1 OF 1	9342143
			NEXT HIGHER ASSEMBLY 12972803

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material		3.1	Certification
102	Distance across corners	Level I	3.2	Gage
103	Body outer diameter	Level I	3.2	Gage
104	Inner diameter at open end	Level I	3.2	Gage
105	Mold properly shaped	Level I	3.2	Visual
Minor				
201	Color	Level II	3.2	Visual
202	Overall length	Level II	3.2	Gage
203	Poor workmanship	Level II	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	Cap, Protecting	1 OF 1	12972808
			NEXT HIGHER ASSEMBLY 12972801

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material		3.1	Certification
102	Proper shape	Level I	3.2	Visual
103	Large inner diameter, min.	Level I	3.2	Gage
104	Outer diameter	Level I	3.2	Gage
Minor				
201	Color	Level II	3.2	Visual
202	Length of large inner diameter	Level II	3.2	Gage
203	Overall height	Level II	3.2	Gage
204	Poor workmanship	Level II	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.13	Igniter and Cable Assembly	1 OF 1	12972809
			NEXT HIGHER ASSEMBLY 12972802

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Igniter insecure or improperly assembled	Level I	3.2	Visual/Manual
Minor 201	Poor workmanship	Level II	3.12	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.14	Case Cartridge Assembly	1 OF 1	12972803
			NEXT HIGHER ASSEMBLY 12972801

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Any component loose, to the extent that it may slide out from body	Level I	3.2	Visual/Manual
102	Any component missing, damaged or improperly assembled	Level I	3.2	Visual
Minor				
201	Poor workmanship	Level II	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.15	Igniter, Electrical Assembly	1 OF 1	12972802
			NEXT HIGHER ASSEMBLY 12972801

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Quickmatch insecure or improperly assembled	Level I	3.2	Visual/Manual
102	Any component missing or improperly assembled (backwards)	Level I	3.2	Visual
103	Resistance test	Level I	3.2	Ohmmeter
104	Total length, min.	Level I	3.2	Gage
Minor				
201	Total length, max.	Level II	3.2	Gage
202	Poor workmanship	Level II	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.16	Black Powder Grain	1 OF 1	12972826
			NEXT HIGHER ASSEMBLY: 12972819/12972806

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material		3.1	Certification
102	Composition analysis		3.1	Certification (a)
102	Moisture content	(b)	3.1.3	4.4.3.1, 4.5.1.1
Minor				
201	Poor workmanship	Level II	3.12	Visual

NOTES:
(a) Show batch weight and ingredients weight breakdown.
(b) See para. 4.4.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.17	Charge, Expulsion	1 OF 1	12972805
			NEXT HIGHER ASSEMBLY 12972801

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material - Potassium Nitrate		3.1	Certification
102	Composition analysis		3.1	Certification (a)
103	Material - Sulfur		3.1	Certification
104	Material - Charcoal		3.1	Certification
Minor				
201	Poor workmanship	Level II	3.12	Visual

NOTES:
(a) Show batch weight and ingredients weight breakdown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.18	Composition, Combustible	1 OF 1	12972806
			NEXT HIGHER ASSEMBLY 12972801

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material - Dextrin		3.1	Certification
102	Material - Acacia Gum		3.1	Certification
103	Composition analysis		3.1	Certification (a)
Minor				
201	Poor workmanship	Level II	3.12	Visual

NOTES:
(a) Show batch weight and ingredients weight breakdown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.19	Star Ignition	1 OF 1	12972819
			NEXT HIGHER ASSEMBLY 12972804

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material - Rubber		3.1	Certification
102	Material - Ethylacetate		3.1	Certification
103	Material - Charcoal, beech		3.1	Certification
104	Material - Titanium		3.1	Certification
105	Material - Aluminum powder		3.1	Certification
106	Composition analysis		3.1	Certification (a)
Minor				
201	Poor workmanship	Level II	3.12	Visual

NOTES:
(a) Show batch weight and ingredients weight breakdown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.20	Star Mix	1 OF 1	12972818
			NEXT HIGHER ASSEMBLY 12972804

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material - Barium Nitrate		3.1	Certification
102	Material - Strontium Nitrate		3.1	Certification
103	Material - Vestolit		3.1	Certification
104	Material - Magnesium Powder (.77 density)		3.1	Certification
105	Material - Magnesium Powder (.56 density)		3.1	Certification
106	Composition Analysis		3.1	Certification (a)
Minor				
201	Poor workmanship	Level II	3.12	Visual

NOTES:
(a) Show batch weight and ingredients weight breakdown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.21	Simulator, Target Hit, M25 (Prior to Assembly of the Igniter, Electrical Assembly	1 OF 1	12972801
			NEXT HIGHER ASSEMBLY ---

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Moisture content - Star Flash Charge	(a)	3.1.3	4.5.1
102	Moisture content - Composition Combustible	(a)	3.1.3	4.5.1
103	Moisture content - Charge Expulsion	(a)	3.1.3	4.5.1
Minor				
201	Poor workmanship	Level II	3.12	Visual

NOTES:
(a) See para. 4.4.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4.4.2.22	TITLE Simulator, Target Hit, M25	SHEET 1 OF 1		DRAWING NUMBER 12972801
				NEXT HIGHER ASSEMBLY ---
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Jumble	20, 0-1	3.5	4.5.4
Special				
1	Leakage of explosive from assembly, or explosive (powder) on exterior of assembly	100%	3.2	Visual
Major				
101	Resistance test of 12972802, Electrical Igniter at assembly prior to installation of 12972808, Cap, Protecting	100%	3.2	4.6.2
102	Marking missing, incorrect or unidentifiable	Level I	3.2	Visual
103	Sealing tape missing, peeling, or incorrectly applied	Level I	3.2	Visual
104	Assembly damaged, dented or deformed	Level I	3.2	Visual
105	Water immersion	50,0-1(a)	3.7	4.5.5
106	Functioning - Hot (w/resist measure)	50,2-3(b)	3.6, 3.4.1	4.5.2, 4.5.3
107	Functioning - Cold (w/resist measure)	50,3-4(b)	3.6, 3.4.1	4.5.2, 4.5.3
108	Functioning - Amb (w/resist measure)	50,2-3(b)	3.6,3.4.1	4.5.2, 4.5.3
Minor				
201	Poor workmanship	Level II	3.12	Visual

NOTES:
(a) Water immersion test samples to be used in ambient function test. (b) After three (3) consecutive lots have been accepted, sample size may be reduced IAW 4.4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.23	Packing and Marking for Box, Fiberboard for Simulator, Target Hit M25 (Prior to Sealing with Tape)	1 OF 1	12972823
			NEXT HIGHER ASSEMBLY 12972824

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Incorrect number of simulators	Level I	3.2	Visual
102	Fillers missing or inadequate	Level I	3.2	Visual
103	Packaging components obviously damp or wet	Level I	3.2	Visual/Manual
Minor				
201	Poor workmanship	Level II	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.24	Packing and Marking for Box, Fiberboard for Simulator, Target Hit, M25 (After Sealing with Tape)	1 OF 1	12972823
			NEXT HIGHER ASSEMBLY 12972824

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Box not properly sealed	Level I	3.2	Visual
102	Marking missing, incorrect or unidentifiable	Level I	3.2	Visual
Minor				
201	Poor workmanship	Level II	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.25	Packing and Marking for Box, Packing for Simulator, Target Hit, M25	1 OF 1	12972824
			NEXT HIGHER ASSEMBLY ---

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Marking missing, incorrect or unidentifiable	Level I	3.2	Visual
102	Strapping missing, broken or loose	Level I	3.2	Visual
103	Box broken or split	Level I	3.2	Visual
104	Contents loose	Level I	3.2	Manual
Minor				
201	Strapping improperly assembled	Level II	3.2	Visual
202	Poor workmanship	Level II	3.12	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Moisture content (see Table II) - Major defects.

TABLE II Moisture content.

Black Powder Grain	(See 12972826)
Expulsion Charge	(See 12972805)
Combustible Composition	(See 12922806)
Star, Flash Charge	(See 12922804)
Paper and Paper Products	(See 3.1.3.2)

The contractor shall provide adequate controls to insure that the materials comply with the requirements. For verification, the contractor shall select and subject to test, one sample of each material from each eight (8) hours production. If a composite sample exceeds the requirement, that quantity or sub-lot material represented by the sample shall not be used in loading and packing, the remaining unloaded and unpacked material shall not be used in production, and the loaded and packed simulators shall be rejected. Test shall be performed as specified in 4.5.1.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections specified herein is identified in the "Inspection Method Reference" column of the Classification of Characteristics listings starting with 4.4.2.1. Contractor inspection equipment designs shall be submitted for Government approval as specified in the contract. Designs which provide variable measurements instead of attributes data are preferred in order to facilitate the use of statistical process control. See MIL-A-48078 and 6.3 herein.

4.4.5 Functioning test. Beginning with the first lot produced and continuing until three (3) consecutive lots have complied with the acceptance criteria of 4.4.2.22, fifty simulator assemblies shall be selected from each lot for test. After three (3) consecutive lots have met the criteria of 4.4.2.22, thirty-two simulators shall be selected from each lot for this test. The lot shall be rejected if two (2) or more functioning defects occur after hot or ambient temperature conditioning or if three (3) or more functioning defects occur after cold temperature conditioning. Lot sampling shall then revert to 50 samples per lot IAW 4.4.2.22.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection.

4.5.1 Moisture content.

4.5.1.1 Compositions. The method of determining the percentage of moisture shall be in accordance with MIL-STD-1234, Method 102. Observations shall be made for compliance with the applicable requirements.

4.5.1.3 Paper and paper products. The moisture content shall be determined in accordance with MIL-STD-1234, Method 102, except that a ten (10) grams sample shall be used and drying time shall be for two (2) hours. Observations shall be made for compliance with the applicable requirement.

4.5.2 Function test. The simulators shall be conditioned for six (6) hours minimum at specified temperatures and functioned within five (5) min. after removal from the conditioning chamber. (The simulator shall be mounted horizontally in an approved fixture) and initiated by approved 12 volts, 1.2 amps power source. (Destructive Test)

4.5.2.1 Flash and sparks characteristics. Observations shall be taken in line with the direction of fire of the simulator. The simulator shall be positioned at three (3) ft. max. above the ground. At least five (5) non-contractor personnel shall be positioned a minimum of 3000 meters from the simulator. At least one (1) observer shall be a government representative. The test shall be conducted during standard clear day conditions in winds not exceeding eight (8) miles per hour and at humidity levels between 10 percent and 90 percent. The observers shall be notified prior to each firing in order to alert them to watch for the flash and sparks. The informers shall also be notified after each firing to confirm that the firing took place, allowing them to record their observations. Observations shall be recorded as visible or non-visible. Three (3) out of five (5) of the observers must record a visible observation for the firing to be deemed visible. Observations shall be made for compliance with the applicable requirements.

4.5.3 Resistance. Prior to functioning, the simulators shall be tested for required resistance with an approved ohmmeter in accordance with 4.4.4. Observation shall be made for compliance with the applicable requirements. (Non-destructive test)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.5.4 Jumble. The simulators shall be tested in accordance with ITOP 4-2-602 with approved test equipment. Observations shall be made for compliance with the applicable requirements. (Destructive test)

4.5.5 Water immersion. The simulators shall be submerged in 12 inches minimum of water at ambient temperature (75°F ± 5°F) for a minimum of one (1) hour. The simulators shall then be removed from the water, wiped off, and placed in the firing device and functioned in accordance with 4.5.2.

4.5.6 Five foot drop. The simulators shall be tested in accordance with ITOP 4-2-602, Appendix C. Observations shall be made for compliance with the applicable requirements.

4.5.7 Seven foot drop. The simulators shall be tested in accordance with ITOP 4-2-602, Appendix B. The orientation drops shall be as follows: bottom down and face down. Observations shall be made for compliance with the applicable requirements.

4.5.8 Loose cargo. The packaged simulators shall be tested in accordance with ITOP 4-2-602. Observations shall be made for compliance with the applicable requirements.

5. PACKAGING

5.1 Packaging requirements.

5.1.1 Packaging shall be in accordance with drawing 12972823.

5.2 Packing and marking.

5.2.1 Packing and marking shall be in accordance with drawing 12972824.

5.3 Palletizing.

5.3.1 Palletizing shall be in accordance with drawing 12972829.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The components covered by this specification are intended for use on the Simulator, Target Hit, M25.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and, if required, the specific issue of individual documents referenced (see 2.1.1).

c. Requirements for submission for first article sample.

d. Applicable stock number.

e. Packaging requirements, if other than specified in Section 5.

f. Serialization requirements, if applicable.

g. Certificate of conformance for each lot or shipment of product.

6.3 Submission of inspection equipment designs for approval. Submit designs as required to: Commander, U.S. Army ARDEC, ATTN: SMCAR-QAT-I, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament, Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as U.S. Army Armament, Research and Development Command (ARRADCOM), Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under cognizance of ARDEC.

6.5 Distribution of ammunition data cards. Distribution of data cards include the following: Commander, U.S. Army Armament, Research and Development Center, ATTN: SMCAR-QAT-M, Picatinny Arsenal, NJ 07806-5000.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

6.6 Submission of alternative quality conformance provisions. All contractor proposed alternative quality conformance provisions will be submitted to the Government for evaluation/approval as directed by the contracting activity.

6.7 Subject term (key word) listing.

Flash
Resistance
Sparks

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1370-0001)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-S-70535 (AR)	940927

3. DOCUMENT TITLE: SIMULATOR, TARGET HIT, M25 PARTS FOR AND LOADING, ASSEMBLING AND PACKING

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S. ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial 201-724-6675	(2) AUTOVON DSN-880-6675
c. ADDRESS (Include Zip Code) ATTN: AMSTA-AR-EDE-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 — *Previous editions are obsolete.* — 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.