MILITARY SPECIFICATION

TURRET SUBSYSTEM, UNIVERSAL (UTS) FOR ARMAMENT SUBSYSTEM, HELICOPTER, 20MM: M97E1 AND M97E2, GUN CONTROL ASSEMBLY FOR

This specification is approved for use by the US. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions for Control Assembly, Gun, for Armament Subsystem Helicopter, 20MM: M497E1 and M97E2. The Gun Control Assembly is a totally enclosed box that contains the required circuitry to translate signals from the aircraft into appropriate signals for turret subsystem control and safe weapon firing sequence.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the isue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-B-5087	-	Bonding, Electrical and Lightning Protection, for Aerospace Systems.
MIL-W-63150	-	Weapons and Support Materiel, Standard Quality Assurance Provisions for.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

STANDARDS:

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109	Quality Assurance Terms and Definitions.
MIL-STD-454	Standard General Requirement for Electronic Equipment.
MIL-STD-461	Electromagnetic Interference Characteristics Requirement for Equipment, Subsystem and system.
MIL-STD-704	Electric Power, Aircraft Characteristics and Utilization of.
MIL-STD-810	Environmental Test Methods.

2.1.2 Other Government documents, drawings, and publications. The following other Governmetn documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWIN6S :

US ARMY RESEARCH AND DEVELOPMENT COMMAND

11830418	-	Control Assembly, Gun.

PACKAGING DATA SHEETS

P11830418	-	Control Assembly, Gun.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM E 18	Method of Tests for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials.
ASTM B 117	Method of Salt Spray (Fog) Testing.

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herin, the text of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings, specifications and standards.

3.2 Parts and subassemblies. All parts and subassemblies shall comply with applicable drawings, specifications and standards.

3.3 Gun control assembly. The gun control assembly shall comply with all requirements specified on Drawing (Dwg.) F11830418, all associated drawings, and with all requirements specified in applicable specifications and standards.

3.4 Environmental requirements. The gun control assembly shall perform as specified in 3.8 after exposure to the environments specified herein.

3.4.1 Aircraft vibration. The gun control assembly shall perform all functions satisfactorily aftter being subjected to MIL-STD-810, test method 514.2, Procedure I, Part 1, Category C using curve C of Figure 514.2-2 and curve M of Figure 514.2-3.

3.4.2 Transpiration vibration. The control pamel shall perfrom all functions satisfactorily after being subjected to MIL-STD-810, test method 514.2, procedure X using curve AW of Figure 514.2.7.

3.4.3 Shock. The gun control assembly shall perform all functions satisfactory after being subjected to MIL-STD-8l0, test method 516.2, Procedure 1.

3.4.4 High temperature. The gun control assembly shall perform all functions at + 160°F according to MIL-STD-81O, test method 501.1.

3.4.5 Temperature altitude. Gun control assembly shall operate while exposes to conditions specified in Method 504.1 of MIL-STD-810 simulating an altitude of 20,000 feet (temperature of -25° F and barometric pressure 2.12 inches mercury).

3.4.6 Humidity. The gun control assembly shall perform all functions satisfactorily after being subjected to MIL-STD-810, test method 507.1, Procedure 1.

3.5 First article inspection. This specification contains technical provisions for irst article Inspections. Requirements for the submissionn of first article by the contractor shall be as specified in the contract and 4.3.

3.6 Interchangeability. Unless otherwise specified on the applicable drawings, all parts shall be interchangeable.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T04:27Z
Check the source to verify that this is the currentversion before use.

3.7 Electrical power supply. The control shall operate from power sources with characteristics conforming to MIL-STD-704, The power supplies for all acceptance tests shall be as specified in Table I.

Table I. Electrical Power

Pin	Function	Power Characteristics
J1-A	Arming	28 +0.5 -O Vdc at 10A
J1-B	Ground	-----
J1-C	Low Level Power	28+0.5 -O Vdc at 4A
J1-D	Low Level Power	28 +0.5 -0 Vdc at 4A
J1-G	400 Hz Power Input	115 +5% Vat, 400 Hz at 0.6A
J1-H	400 Hz Power Return	115 Vac Return

3.7.1 Ground. When the Gun Control Assembly is installed in the helicopter, the enclusures and mounting components shall be electrically bonded in accordance with MIL-B-5087.

3.8 Performance requirements. The gun control assemblies shall comply with the performance requirements specified herein, when tested as specified in 4.5.6.

3.8.1 Electronic characteristics. The gun control assembly shall comply with the electronic characteristics specified in Table II. The signal Parameter column of Table II presents-the inputs, outputs, and external loads, as applicable, that characterize the interface with the Gun Control Assembly,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

Table II. Electronic Characteristics

Connector Pin	Function	Signal Parameter
J1-A	Arming Power Input	28 +0.5 -0 Vdc at 10A
J1-B	Ground	----
J1-C	Low Level Power Input	28 +0.5 -0 Vdc at 4A
J1-D	Low Level Power Input	28 +0.5 -0 Vdc at 4A
J1-E	Rocket Lockout Input	0 Vdc or 26 +4 Vdc at a maximum of 20 mA
J1 - F	Turret Delay Input	26 +4 Vdc at a maximum of 1A
J1 - G	400 Hz Power Input	115 ± 5%Vac, 400 Hz at 0.6A
J1-H	400 Hz Power Return	115 Vac Return
J1-J	Turret Delay Output	Minimum of 100 ohms to Ground
J1-K	Gun Motor Relay Return	26 +4 Vdc through a minimum of 100 ohms
J1-L	Trigger Input Power	26 +4 VdC at a maximum of 250 mA
J1-M	Pilot Relay Input	26 ± 4 Vdc at 250 mA
J1 - N	Trigger Input	0 Vdc or 26 +4 Vdc at a maximum of 100 mA
J1-P	Burst Limit Supply Output	Minimum of 1500 ohms to Ground
J1-R	Rounds Counter Output	26 +4 Vdc thru a minimum of 30 ohms
J1-S	Burst Limit Input	0 Vdc or 26 ± Vdc at a maximum of 20 mA

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

Table II. Electronic Characteristics (cont)

Connector Pin	Function	Signal Parameter
J2-A	Fire Volts Output	See 3.9.7
J2-B	Fire Volts Return	See 3.9.7
J2-C	Feed Solenoid Power	3 ohms +10%, 300W Resistor between J2-C and J2-D
J2-D	Feed Solenoid Return	Same as J2-C
J2-E	Chassis Return	----
J2-F	Filtered 28 Vdc Output	8 ohms +10%, 100W Resistor to Ground
J2-G	Filtered Ground	----
J2 -H	Fire Volts Sensor Out	10,000 ohms ± lO% to Ground
J3-A	Regulated 28 Vdc Output	100 ohms +10% to J3-B
J3-B	Regulated 28 Vdc Return	----
J3-C	10 Vac 400 Hz Output	200,000 ohms ± lO% to J3-D
J3-D	10 Vac, 400 Hz Return	----
J3-E	Sight Trigger Input	In Parallel with J1-N
J3-F	26 Vac, 400 Hz Output	10,000 ohms +10% to J3-G
J3-G	26 Vac, 400 Hz Return	----
J3-H	Trigger Power Out	1000 ohms +10% to Ground
J3-J	28 Vdc Low Level Output	100 ohms ± lO% to Ground
J3-K	Ground	-----
J3-L	115 Vac Out	1000 ohms ± 10% to J3-a

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T04:27Z
Check the source to verify that this is the current version before use.

Table II. Electronic Characteristics (Cont)

Connector Pin	Function	Signal Parameter
J3-M	Pilot Relay Out	1000 ohms ± 10% to Ground
J3-N	Azimuth Error Input	0.5 +0.5 Vdc or 16 + 4 Vdc at-a maximum of l-MA
J3-P	Right Azimuth Limit input	0.5 +0.5 Vdc or 26 +4 Vdc at-a maximum of 20 mA
J3-R	Rounds Counter Input	Open Circuit or Short Circuit to Ground
J3-S	28 Vdc Output to Reticle	1000 ohms ± l0% to J3-T
J3-I	Reticle Return	----
J3-U	Down Elevation Limit Input	0.5 +0.5 Vdc or 26 +4 Vdc at-a maximum of 20 mA
J3-V	Up Elevation Limit Input	0.5 +0.5 Vdc or 26 +4 Vdc at-a maximum of 20 mA
J3-W	Left Azimuth Limit Input	0.5 +0.5 Vdc or 26 +4 Vdc at-a maximum of 20 mA
J3-X	Elevation Error Gate Input	0.5 +0.5 Vdc Or 16 +4 vdc at-a maximum of 1 mA
J3-Y	115 Vac Output	1000 ohms +10% to J3-Z
J3-Z	115 Vac Return	----
J3-a	115 Vac Return for J3-L	----
J3-b	Chassis Ground	----
J3-c	Interlocked Trigger	1000 ohms +10% to 28 Vdc

3.8.2 Test points. The J-4 test connector characteristics shall be as shown in Table III. The voltage characteristics specified in Table III were obtained with a 100,000 ohm (+10 percent) input impedance measuring device. The resistance values presented are measured between the specified pins.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T04:27Z
Check the source to verify that this is the current version before use.

Table III. Gun Control Unit Test Connector J4 Signals

Connector Pin	Function	Signal Parameter
A	Reticle Flasher Output	4700 ohms +5% to J3-T
B	Not Used	----
C	Burst Limit Time Delay	12 +1 Vdc at 6 mA normally: -12 +1 Vdc within 1.28 +0.32 seconds after JI-S equals 28 Vdc
D	Interlocked Trigger	Parallel with J3-c
E	Fire Volts Relay Coil	24 +4 Vdc at 2 mA when J2-A is O Vdc. 0.5 +0.5 Vdc when J2-A is 350 +50 Vdc .
F	Declutching Feeder Solenoid	10,000 ohms ± lO% to J2-D
G	Gun Motor Relay (Low End)	10,000 ohms ± l0% to JI-K
H	28 Vdc Regulated	10,000 ohms ± lO% to J3-A
J	28 Vdc Regulated Return	O Vdc (Reference)
K	26 Vac, 400 Hz	10,000 ohms ± lO% to J3-F
L	Not Uses	----
M	115 Vac, 400 Hz	10,000 ohms ± lO% to J1-G
N	115 Vac, 400 Hz Return	O Vac (Reference)
P	Fire Volts	10,000 OhmS to J2-A
R	Not Used	----
S	28 Vdc High Level Control	10,000 ohms ± lO% to J1-J
T	Sight Trigger Voltage	Parallel with J1-J

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:27Z
Check the source to verify that this is the current version before use.

Table III. Gun Control Unit Test Connector J4 Signals

(Cont)

Connector Pin	Function	Signal Parameter
U	Right Azimuth Proximity Limit	Parallel with J3-P
V	Left Azimuth Proximity Limit Switch	Parallel with J3-W
W	Up Elevation Proximity Limit Switch	Parallel with J3-V
X	Down Elevation Proximity Limit Switch	Parallel with J3-U
Y	Azimuth Error Gate	Parallel with J3-N
z	Elevation Error Gate	Parallel with J3-X
a	10 Vat, 400 Hz	Parallel with J3-C
b	Not Used	----
c	Not Used	----
d	Not Used	----
e	Not Used	----
f	Turret Control Power	10,000 ohms ± lO% to J1-C
g	28 Vdc Return	0 Vdc (Reference)

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T04:27Z
Check the source to verify that this is the currentversion before use.

Table III. Gun Control Unit Test Connector J4 Signals

(Cont)

Connector Pin	Function	Signal Parameter
h	Rocket Lockout Delay	0 + 0.5 Vdc normally with J1-E at 0 Vdc 26 +4 Vdc at 8 mA when J1-E is at 28.0 Vdc. 0 +0.5 Vdc reoccurs within 1.0 +0.5 seconds after pin J1-E is at 0 Vdc.
j	Rocket Lockout Signal	Parallel with J1-E

3.8.3 Feed-through wiring. The feed-through (continuity) characteristics of the Gun Control Assembly shall be as shown in Table IV. Logic operations are not performed between the specified pins.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

Table IV. Feed-Through Wiring

Pin		Pin
J1-c	connected ot	J3-J
J1-C		J3-S
J1-M		J3-M
J1-R		J3-R
J1-L		J3-H
J1-B		J3-K
J1-B		J3-G
J1-B		J3-D
J1-B		J3-B
J1-B		J2-G
J1-D		J2-F
J1-G		J3-L
J1-G		J3-Y
J1-H		J3-a
J1-H		J3-Z
J1-N		J1-P
J1-N		J3-E
J1-A		J2-C

3.8.4 Power outputs. With the power specified in Table I applied to Pins J1-G, J1-H, J1-C, J11A and J1-B, the Gun Control Assembly shall provide the following power outputs. The loads shall be as specified in Table II.

a. J3-F = 26.0 +4.0 -1.3 Vat, 400 Hz ± 5 percent

b. J4-K = 23.4 +4.0 -1.3 Vat, 400 Hz ± 5 percent

c. J3-C and J4-a = 10.0 ± 1.3 Vat, 400 Hz +5 percent with a phase lag of 2.5 ± 9.5 degrees when measured at the 400 Hz input frequency.

d. J3-A = 28.0 ± 1 Vdc (Note: See 3.2.l.6(a).)

e. J4-H = 25.2 ± 1 Vdc

3.8.5 Input/output relationships. The following input/output relationships shall be as specified in the following subparagraphs. The output response is measured between the specified output pin and ground.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:27Z
Check the source to verify that this is the currentversion before use.

3.8.5.1 Turret time delay. With 28.0 Vdc applied to Pin J1-F, zero +0.5 Vdc shall appear at Pin J1-J when the input power on Pins J1-C and J1-G is removed. Twenty-eight + 0.5 Vdc shall appear at Pin J1-J within 4.0 +0.0 -1.8 seconds after application of the specified input power at Pins J1-C and J1-G. A failure of the regulated 28 Vdc circuit also causes zero ± 0.5 Vdc to appear at Pin J1-J.

3.8.5.2 Ready-to-fire indication. The presence of a constant 0.7 +0.7 Vdc at Pin J3-T indicates that the firing circuits are enabled. A pulse train at Pin J3-T, having the following characteristics, indicates the Gun Control Assembly firing circuits are disabled.

a. 25 +5 Vdc for 200 ± 100 milliseconds (ms)

b. 0.7 ± 0.7 Vdc for 175 ± 100 ms

c. A total period between pulses of 375 ± 100 ms

A steady "low" voltage occurs on Pin J3-T when all normal input signal levels, as defined in Table V, have been applied. When one or more of the input signals is abnormal, a pulsating output voltage shall occur at Pin J3-T.

Table V. Logic Inputs

Signal	Connector Pin	Normal Vdc	Abnormal Vdc
Azimuth Error	J3-N	>10	< 5
Elevation Error	J3-X	>10	< 5
Up Limit	J3-V	>10	< 5
Down Limit	J3-U	>10	< 5
Right Limit	J3-P	>10	< 5
Left Limit	J3-W	>10	< 5
Rocket Lockout	J1-E	< 2	>10

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

3.8.5.3 Interlocked trigger. With the input power specified in Table I and the normal logic signals specified in Table V, the voltage at Pin J3-c shall be 28.0 +0.5 Vdc. When a 28 Vdc signal is applied to Pin J1-N, the voltage at Pin J3-c shall be 5.0 ± 1.0 Vdc. When any one or more of the logic signals specified in Table VI are-abnormal, the voltage at Pin J3-c shall be 28.0 ± 0.5 Vdc independent of the voltage input at Pin J1-N.

3.8.5.4 Trigger application. With input power as specified in Table I, normal logic inputs as specified in Table V and a 28 Vdc trigger signal is applied, the following output characteristics shall occur:

a. The voltage at Pin J2-D shall be 1.0 ± 1.0 Vdc within 2 ms after applying 28 Vdc at Pin J1-N.

b. The voltage at Pin J1-K shall be 1.0 + 1.0 Vdc within 35 ms after applying 28 Vdc at Pin J1-N.

c. With no dynamic load (see 3.8.7) on Pin J2-A, the voltage at Pin J2-A shall be 350 ± 50 Vdc within 40 ms after applying 28 Vdc at Pin J1-N.

d. The voltage at Pin J2-H shall be 1.0 ± 1.0.Vdc within 40 ms after1 applying 28 Vdc at Pin J1-N.

e. The voltage on J3-c shall be 5.0 ± 1.0 Vdc within 1.5 ms after applying 28 Vdc at Pin J1-N.

3.8.5.5 Trigger signal revoval. The following output characteristics shall occur when the input at Pin J1-N changes from 28 Vdc to 0 Vdc with input power specified in Table I and normal Logic Signals specified in Table V. (Note: Pin J1-N must be maintained at 28 Vdc for a minimum of 100 ms prior to a transition to O Vdc).

a. The voltage at Pin J2-D shall be 28.0 ± 5 Vdc within 11 ms after removing the 28 Vdc at Pin J1-N.

b. The voltage at Pin J1-K shall remain at 1.0 + 1.0 Vdc for 750+250 ms after removing the 28 Vdc at Pin J1-N. After the above delay, the voltage at Pin J1-K shall be 28 + 1 Vdc.

c. The voltage at Pin J2-A shall remain at 350 +50 Vdc for 1.5 +0.5 seconds after removing the 28 Vdc at Pin J1-N. After the-above delay, the voltage at Pin J-2A shall be O Vdc.

d. The voltage at Pin J2-H shall be 24 ± 2 Vdc within 2 ms after the voltage at Pin J2-A falls below 100 Vdc.

e. The voltage at Pin J3-c shall be 28.0 ± 5 Vdc within 1.5 ms after removinq the 28 Vdc at Pin J1-N.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T04:27Z
Check the source to verify that this is the currentversion before use.

3.8.5.6 Firing interruption. The output characteristics specified in 3.8.5.4 shall be terminated as follows:

a. Removing the normal signal at either Pin J3-N or Pin J3-X shall cause the voltage at Pin J2-A to go to 0 Vdc within 10 ms. The above requirement is independent of the voltage at Pin J1-N remaining at 28 Vdc.

b. Removing the normal signals at any of Pins J3-V, J3-P, J3-W or J3-U shall cause removal of the trigger signal as specified in 3.8.5.5. The above requirement is independent of the voltage at Pin J1-N remaining at 28 Vdc.

c. Applying 28 Vdc at Pin J1-E causes removal of the trigger signal as specified in 3.8.5.5 when 28 Vdc is maintained at Pin J1-N. After removing the 28 Vdc at Pin J1-E, the outputs specified in 3.8.5.4 shall occur within 1.0 + 0.5 seconds.

3.8.5.7 Burst limit operation. With the input conditions specified in 3.8.5.4 and a 28 Vdc signal is applied to J1-S, the output characteristics specified in 3.8.5.4 shall occur for 1.5 ± 0.1 seconds after which the trigger signal removal characteristics of 3.8.5.5 shall occur. Removing the 28 Vdc on Pin J1-S for a minimum of 25 ms is required to reset this function. (See 3.8.6(b)).

3.8.5.8 Fire volts sensing. When the output load characteristics occur at Pin J2-A (See 3.8.7), the following characteristics shall occur at Pin J2-H.

a. When the voltage at Pin J2-A is less than 50 Vdc, the voltage at Pin J2-H shall be 24 ± 2 Vdc within 1 ms of the voltage transition at Pin J2-A.

b. When the voltage at Pin J2-A is greater than 100 Vdc, the voltage at Pin J2-H shall be 0.7 ± 0.7 Vdc within 1 ms of the voltage transition at Pin J2-A.

3.8.6 Adjustments. The following output characteristics shall be capable of being modified as described below:

a. The output at Pin J3-A shall be 25 Vdc to 30 Vdc when the regulated 28 volt trim resistor (A4R7) is adjusted from the minimum (rein) to maximum (max) value.

b. The time delay specified in 3.8.5.7 shall have the minimum and maximun delay of 0.4 to 2.3 seconds respectively when the burst limit resistor (A2R14) is adjusted throughout its full range.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

3.8.7 Fire voltage output load. The system load characteristics for Pin J2-A shall be a short circuit (less than 2 ohms) for two milliseconds. An open circuit (greater than 100,000 ohms) shall be the load on Pin J2-A for 80 ms. This cycle shall be repetitive.

3.8.8 Power supply fail safe. Whenever the -12 Vdc internal supply is less than -5 Vdc, a low voltage protection circuit shall inhibit the output functions at Pins J2-A and J1-K.

3.8.9 Time totalizing meter. The gun control assembly shall include a meter(without reset capability) that provides a readout in hours of the time that 115 Vac has been applied.

3.8.10 Proof test (first article inspection only). Gun control assemblies shall operate when assembled to an accepted Universal Turret Subsystem (UTS)

3.9 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. The parts shall be clean and free of burrs, sharp edges, cracks, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous: however, a few light scratches not exposing base material may be permitted. All required markings and stamping shall be neat and sharply defined. Required packing shall be dry.

3.9.1 Solder and electronic workmanship. Solder and electronic workmanship shall be in accordance with MIL-STD-454. All parts and assemblies shall be clean and free of any fingerprints, dirt, oils, cleaning agents, corrosive material or other material which could affect serviceability. There shall be no evidence of burning, warpage, cracking, chipped edges or other defects which could made the part unsatisfactory for the purpose intended.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-W-63150 shall apply and are hereby made a part of this detail specification.

4.1.1 Certification provisions. The certification provisions of MIL-W-63150 shall apply (see 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The following types of inspection shall be conducted on this item:

a. First Article Inspection.

b. Quality Conformance Inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing	Quantity
Absorber Voltage	D105D3528	5
Filter, EMI, Gun Control	C116C3553	5
Heat Sink	011830465	5
Spacer, Swage Type	C11830494	5
Terminal Insulated	C11830496	5
Jackpost, Kit	B11830498	5
Holder, Printed Circuit Board	C125C3857	5
Spacer, Swage Type	B162B7983	5
Transformer, Power Stepdown	C167C1097	5
Transformer, Rectifier Assembly	C905D583	5
Gun Control Assembly	F11830418	5

4.3.2 Inspections to be performed. See Table VI specified herein.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, The first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of any assembly, component or test specimen in the sample to comply with any of the stated requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

TABLE VI. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-

PARAGRAPH	TITLE: Control Assy, Gun and Components		SHEET 1 OF 3		DRAWING NUM: See
					NEXT HIGHER: ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH R
	Absorber Overvoltage				
	(DWG D105D3528)				
	Examination for defects (including majors 101 to 105)	5		3.2	4.
	Filter, EMI, Gun Control				
	(DWG C116C3553)				
	Examination for defects (including majors 101 and 102)	5		3.2	4.
	Heat Sink				
	(DWG D11830465)				
	Examination for defects (including majors 101 and 103)	5		3.2	4.
	Salt Spray Test (note 4) *	3	a	3.2	4.

NOTES:
a. If any sample shows evidence of corrosion (rust or salt deposits), the first artic rejected.
* Notes refer to applicable drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:27Z
Check the source to verify that this is the current version before use.

TABLE VI. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH cont'd	TITLE Control Assy, Gun and Components		SHEET 2 OF 3		DRAWIN NEXT
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGR
	Spacer, Swage Type (DWG C11830494)				
	Examination for defects	5		3.2	
	Salt Spray Test (Note 2) *	3	a	3.2	
	Terminal Insulated (DWG C11830496)				
	Examination for defects	5		3.2	
	Salt Spray Test (Note 2) *	3	a	3.2	
	Dialectric withstanding voltage (Note 3) *	5		3.2	
	Jackpost, Kit (Dwg. B11830498)				
	Examination for defects	5		3.2	
	Salt Spray Test (Note 2) *	3	a	3.2	
	Holder, Printer Circuit Board (Dwg. C125C3857				
	Examination for defects	5		3.2	
	Salt Spray Test (Note 2) *	5	a	3.2	
	Spacer, Swage Type (DWG B162B7983)				
	Examination for defects	5		3.2	
	Salt Spray Test (Note 4) *	3	a	3.2	
	Hardness, max (Note 5) *	5		3.2	

NOTES:

a. If any sample shows evidence of corrosion (rust or salt deposits), the first rejected.

* Notes refer to applicable drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:27Z
Check the source to verify that this is the current version before use.

TABLE VI. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-T-63520 (Af?j

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER
cont'd	Control Assy, Gun and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Transformer, Power Stepdown (Dwg. C167C1097)				
	Examination for defects (Including Majors 101 and 102)	5		3.2	4.4.2.9
	Transformer Rectifier Assembly (Dwg. D905D583)				
	Examination for defects (including Majors 101 to 103)	5		3.2	4.4.2.10
	Gun Control Assembly (Dwg. F11830418)				
	Examination for defects (including Majors 107 and 108)	5		3.2	4.4.2.25
	Environmental	3		3.4	4.5.6.1
	Proof test	5		3.8.10	4.5.6.2
	Electromagnetic Interference (EMI)	5		3.2	4.7

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:27Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term “inspection lot” is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions, and complies with the provisions for submission of product as specified in MIL-STD- 105. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements. The lot shall contain:

a. Overvoltage absorbers of one lot interfix number from one manufacturer.

b. Transformer rectifier assemblies of one lot interfix number from one manufacturer.

c. EMI, gun control filters of one lot interfix number from one manufacturer.

d. Step-down power transformers of one interfix number from one manufacturer.

e. Jackscrew, assembly, kits of one lot interfix number from one manufacturer.

f. Jam nut electrical receptacle connectors of one lot interfix number from one manufacturer.

g. Electronic component, mounting pads of one lot interfix number from one manufacturer.

h. Electrical insulators of one lot interfix number from one manufacturer.

i. Kit jackposts of one lot interfix number from one manufacturer.

j. Semi-conductor device, mounting pads of one lot interfix number form one manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

k. Insulated terminals of one lot interfix number from one manufacturer.

l. Transipads of one lot interfix number from one manufacturer.

m. Right angle floating nut-anchors of one lot interfix number from one manufacturer.

n. Mounting transipads of one lot interfix number from one manufacturer.

o. Rectangular electrical connectors of one lot interfix number from one manufacturer.

p. Printed circuit board holders of one lot interfix number from one manufacturer.

4.4.2 Examination. The examinations listed in this specification for Classification of Defects shall be performed on inspection lots as defined in 4.4.1 of this specification. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, of sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63520(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Absorber Overvoltage		D10503528
			NEXT HIGHER ASSEMBLY F11830418

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Electrical characteristics (Note 1) *		100%	3.2	4.5.4
102	Environmental characteristics (Note 2)*		0.65%	3.2	4.5.5
103	Physical characteristics (Note 3) *		--	3.2	Certification
Minor					
201	Assembly damaged		1.50%	3.2	Visual
202	Marking incorrect, unidentifiable or missing		1.50%	3.2	Visual
203	Poor workmanship		2.50%	3.9	Visual

NOTES: * Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63520(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Filter, EMI, Gun Control		C11603553 (3 sheets)
			NEXT HIGHER ASSEMBLY F11830418

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Electrical requirements (Note 3.3) *				
	a. ambient	a	--	3.2	4.5.4
	b. cold temperature (Note 3.5) *	a	--	3.2	4.5.4
	c. hot temperature (Note 3.5) *	a	--	3.2	4.5.4
102	Environmental requirements (Note 3.4) *				
	a. vibration	a	--	3.2	4.5.5
	b. shock	a	--	3.2	4.5.5
	c. temperature - humidity altitude	a	--	3.2	4.5.5
	d. terminal strength	a	--	3.2	4.5.5
103	Soldering workmanship unsatisfactory (Note 3.6.1) *	-	--	3.9.1	Certification
104	Material (Note 3.2) *	-	--	3.2	Certification
Minor					
201	Marking incorrect, unidentifiable or missing		1.50%	3.2	Visual
202	Assembly damaged		1.50%	3.2	Visual
203	Part missing		1.50%	3.2	Visual
204	Poor workmanship		2.50%	3.9	Visual

NOTES:
a: 3 samples, accept on 0 reject on 1 failure
* Notes refer to drawing.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63520(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Heat Sink				D11830465
					NEXT HIGHER ASSEMBLY 11830497
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material and mechanical properties (Notes 1 & 5)*		--	3.2	Certification
102	Salt spray test (Note 4) *		--	3.2	Certification
103	Brazing workmanship unsatisfactory (Note 5) *		0.65%	3.2	Visual
104	Protruding and securing members above flush		0.65%	3.2	Visual
Minor					
201	Primer missing from inserts		1.50%	3.2	Visual
202	Notched tangs not removed (Note 8) *		1.00%	3.2	Visual
203	Part missing		1.50%	3.2	Visual
204	Assembly damaged		1.50%	3.2	Visual
205	Part improperly assembled		1.50%	3.2	Visual
206	Poor workmanship		2.50%	3.9	Visual

NOTES:

* Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECT JON

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63520(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER C11830494
4.4.2.4	Spacer, Swage Type				NEXT HIGHER ASSEMBLY F11830497
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Salt spray test (Note 2) *			3.2	Certification
Minor					
201	Insert missing		1.50%	3.2	Visual
202	Primer missing from inserts		1.50%	3.2	Visual
203	Notched tangs not removed (Note 5) *		1.50%	3.2	Visual
204	Assembly damaged		1.50%	3.2	Visual
205	Poor workmanship		2.50%	3.9	Visual

NOTES:

* Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63520(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Terminal, Insulated				C11830496
					NEXT HIGHER ASSEMBLY F11830497
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material (Note 1) *		--	3.2	Certification
102	Salt spray test (Note 2) *		--	3.2	Certification
103	Electric withstanding voltage (Note 3) *		--	3.2	Certification
Minor					
201	Part damaged		1.50%	3.2	Visual
202	Marking, incorrect, unidentifiable or missing		1.50%	3.2	Visual
203	Poor workmanship		2.50%	3.9	Visual

NOTES: * Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63520(ARI

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Jackpost, Kit		B11830498
			NEXT HIGHER ASSEMBLY
			F11830497

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Salt spray test (Note 2) *	--	--	3.2	Certification
Minor					
201	Thread damaged		1.50%	3.2	Visual
202	Marking incorrect, unidentifiable or missing		1.50%	3.2	Visual
203	Poor workmanship		2.50%	3.9	Visual

NOTES:

* Notes refer to drawing.

Source: https://assist.dla.mil Downloaded: 2026-02-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63520(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Holder, Printed Circuit Board				C125C3857
					NEXT HIGHER ASSEMBLY
					F11830419
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Salt spray test (Note 2) *	--	--	3.2	Certification
Minor					
201	Marking incorrect, unidentifiable or missing		1.50%	3.2	Visual
202	Poor workmanship		2.50%	3.9	Visual

NOTES:

* Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-T63520(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Spacer, Swage Type				B162B7983
					NEXT HIGHER ASSEMBLY
					F11830497
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Salt spray test (Note 4) *		--	3.2	Certification
102	Hardness, max (Note 5) *		--	3.2	Certification
Minor					
201	Assembly damaged		1.50%	3.2	Visual
202	Poor workmanship		2.50%	3.9	Visual

NOTES:

* Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Transformer, Power Step-down				C167C1097
					NEXT HIGHER ASSEMBLY F11830418
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Electrical requirements (Note 1) *		100%	3.2	4.5.4
102	Environmental requirements		--	3.2	Certification
103	Weight, max		.65%	3.2	Balance
Minor					
201	Transformer damaged		1.50%	3.2	Visual
202	Protective finish damaged		1.50%	3.2	Visual
203	Marking misleading, unidentifiable or missing (Note 6) *		1.50%	3.2	Visual
204	Poor workmanship		2.50%	3.9	Visual

NOTES:

* Notes refer to drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63520(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Transformer Rectifier Assembly				D905D583
					NEXT HIGHER ASSEMBLY F1183041B
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Electrical characteristics (Note 4) *				
	a. ambient temperature		100%	3.2	4.5.4
	b. hot temperature (Note 3) *	a	--	3.2	4.5.4
	c. low temperature (Note 3) *	a	--	3.2	4.5.4
102	Relay characteristics (Note 5) *	--	--	3.2	Certification
103	Vibration (Note 6) *	a	--	3.2	Certification
Minor					
201	Assembly damaged		1.50%	3.2	Visual
202	Part missing		1.50%	3.2	Visual
203	Marking incorrect, unidentifiable or missing		1.50%	3.2	Visual
204	Wire color incorrect (seven leads)		1.50%	3.2	Visual
205	Poor workmanship		2.50%	3.9	Visual

NOTES:

a: 3 samples, accept on 0 reject on 1 failure

* Notes refer to drawing

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete.

Source: https://assist.dla.mil -- Downloaded: 2026-01-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Cover, Gun Control	1 OF 1	C11403016
			NEXT HIGHER ASSEMBLY F11830418

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Assembly damaged		0.65%	3.2	Visual
102	Cushion peeling (poor bonding)		0.65%	3.2	Visual
103	Cushion missing		0.65%	3.2	Visual
104	Weld workmanship unsatisfactory		0.65%	3.2	Visual
105	Protective finish damaged		0.65%	3.2	Visual
106	Primer or final coating on inside surface missing		0.65%	3.2	Visual
107	Marking misleading, unidentifiable or missing (Note 7) *		0.65%	3.2	Visual
Minor					
201	Poor workmanship		2.50%	3.9	Visual

NOTES:
* Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION Of DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Case, Gun Control				F11830419 (2 sheets)
					NEXT HIGHER ASSEMBLY F11830418
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Drain holes missing (Note 4) *		0.65%	3.2	Visual
102	Welding workmanship unsatisfactory		0.65%	3.2	Visual
103	Brazing workmanship unsatisfactory (Note 5) *		0.65%	3.2	Visual
Minor					
201	Assembly damaged		1.50%	3.2	Visual
202	Part missing		1.50%	3.2	Visual
203	Specified areas not flushed after brazing (Note 6)*		1.50%	3.2	Visual
204	Protective finish damaged		1.50%	3.2	Visual
205	Primer or final coating present on prohibited areas (Note 4) *		1.50%	3.2	Visual
206	Notched tangs not removed (Note 10) *		1.50%	3.2	Visual
207	Primer missing from inserts (Note 11) *		1.50%	3.9	Visual

NOTES: * Notes refer to drawing.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:27Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Component Assy, Power Supply				F11830420
					NEXT HIGHER ASSEMBLY F11830418
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Moisture present on assembly		0.65%	3.2	Visual
102	Moisture protection missing		0.65%	3.2	Visual
103	Solder workmanship poor (Note 1) *		0.65%	3.2	Visual
Minor					
201	Part missing		1.50%	3.2	Visual
202	Assembly damaged		1.50%	3.2	Visual
203	Marking misleading, unidentifiable or missing (Notes 2 & 5) *		1.50%	3.2	Visual
204	Fillet missing		1.50%	3.2	Visual
205	Compound on prohibited areas		1.50%	3.2	Visual
206	Poor workmanship		2.50%	3.9	Visual

NOTES: * Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:27Z
Check the source to verify that this is the currentversion before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.14	Component Assembly Interconnection				F11830497 (2 sheets)
					NEXT HIGHER ASSEMBLY F11830418
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Moisture present on assembly		0.65%	3.2	Visual
102	Moisture protection compound missing		0.65%	3.2	Visual
103	Solder workmanship poor (Note 1) *		0.65%	3.2	Visual
Minor					
201	Part missing		1.50%	3.2	Visual
202	Part incorrectly assembled (including wiring)		1.50%	3.2	Visual
203	Assembly damaged		1.50%	3.2	Visual
204	Marking misleading, unidentifiable or missing (Note 2) *		1.50%	3.2	Visual
205	Compound on prohibited surfaces		1.50%	3.2	Visual
206	Poor workmanship		2.50%	3.9	Visual

NOTES:

* Notes refer to drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-T-63520(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.15	Jackscrew, Assembly, Kit				R11830578
					NEXT HIGHER ASSEMBLY
					F11830418
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Knurl incorrect or missing		0.65%	3.2	Visual
Minor					
201	Assembly damaged		1.50%	3.2	Visual
202	Part missing		1.50%	3.2	Visual
203	Marking incorrect, unidentifiable or missing		1.50%	3.2	Visual
204	Poor workmanship		2.50%	3.9	Visual

NOTES:

* Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.16	Connector, Receptacle Electrical Jam Nut	1 OF 1	C12502785
			NEXT HIGHER ASSEMBLY: F11830418

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Performance (Note 1) *	--	--	3.2	Certification
102	Improper resilient insert material (Note 3) *	--	--	3.2	Certification
Minor					
201	Marking misleading, unidentifiable or missing (Note 5) *		1.50%	3.2	Visual
202	Part missing		1.50%	3.2	Visual
203	Part improperly assembled		1.50%	3.2	Visual
204	Thread damaged		1.50%	3.2	Visual
205	Poor workmanship		2.50%	3.9	Visual

NOTES:

* Notes refer to drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63520(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Component Assy, Limit and Error Logic				F189F902
					NEXT HIGHER ASSEMBLY F1183041B
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Moisture present on assembly		0.65%	3.2	Visual
102	Moisture protection compound missing		0.65%	3.2	Visual
103	Solder workmanship poor (Note 1) *		0.65%	3.2	Visual
Minor					
201	Part missing		1.50%	3.2	Visual
202	Assembly damaged		1.50%	3.2	Visual
203	Marking misleading, unidentifiable or missing (Notes 2 & 5) *		1.50%	3.2	Visual
204	Fillet missing		1.50%	3.2	Visual
205	Compound on prohibited areas		1.50%	3.2	Visual
206	Poor workmanship		2.50%	3.9	Visual

NOTES: * Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION DEFECTS & TESTS MIL-T-63520(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.18	Component Assembly, Comparator				F189F903
					NEXT HIGHER ASSEMBLY
					F1183041B
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Moisture present on assembly		0.65%	3.2	Visual
102	Moisture protection compound missing		0.65%	3.2	Visual
103	Solder workmanship unsatisfactory (Note 1) *		0.65%	3.2	Visual
Minor					
201	Part missing		1.50%	3.2	Visual
202	Assembly damaged		1.50%	3.2	Visual
203	Marking misleading, unidentifiable or missing (Notes 2 & 5) *		1.50%	3.2	Visual
204	Fillet missing		1.50%	3.2	Visual
205	Compound on prohibited areas		1.50%	3.2	Visual
206	Poor workmanship		2.50%	3.9	Visual

NOTES:

* Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete
Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.19	Component Assy, Time Delays				F189F904
					NEXT HIGHER ASSEMBLY F11830418
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Moisture present on assembly		0.65%	3.2	Visual
102	Moisture protection compound missing		0.65%	3.2	Visual
103	Solder workmanship poor (Note 1) *		0.65%	3.2	Visual
Minor					
201	Part missing		1.50%	3.2	Visual
202	Assembly damaged		1.50%	3.2	Visual
203	Marking misleading, unidentifiable or missing (Notes 2 & 5) *		1.50%	3.2	Visual
204	Fillet missing		1.50%	3.2	Visual
205	Compound on prohibited areas		1.50%	3.2	Visual
206	Poor workmanship		2.50%	3.9	Visual

NOTES: * Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.20	Printed Wiring Board, Limit and Error Logic	1 OF 1	F189F964 (3 sheets)
			NEXT HIGHER ASSEMBLY: F189F902

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material (Note 1) *		--	3.2	Certification
102	Wiring incorrect (Note 2) *		--	3.2	Certification
103	Wiring unsatisfactory (Note 2) *		--	3.2	Certification
Minor					
201	Part missing		1.50%	3.2	Visual
202	Part incorrectly assembled		1.50%	3.2	Visual
203	Assembly damaged		1.50%	3.2	Visual
204	Marking misleading, unidentifiable or missing		1.50%	3.2	Visual
205	Poor workmanship		2.50%	3.9.1	Visual

NOTES:
* Notes refer to drawing.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-T-63520(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.21	Printed Wiring Board, Comparator				F189F965 (7 sheets)
					NEXT HIGHER ASSEMBLY F189F903
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material (Note 1) *		--	3.2	Certification
102	Wiring incorrect (Note 2) *		--	3.2	Certification
103	Wiring unsatisfactory (Note 2) *		--	3.2	Certification
Minor					
201	Part missing		1.50%	3.2	Visual
202	Part incorrectly assembled		1.50%	3.2	Visual
203	Assembly damaged		1.50%	3.2	Visual
204	Marking misleading, unidentifiable or missing		1.50%	3.2	Visual
205	Poor workmanship		2.50%	3.9.1	Visual

NOTES:

* Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.22	Printed Wiring Board, Time Delays				F189F966 (3 sheets)
					NEXT HIGHER ASSEMBLY F189F104
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material (Note 1) *		--	3.2	Certification
102	Wiring incorrect (Note 2) *		--	3.2	Certification
103	Wiring unsatisfactory (Note 2) *		--	3.2	Certification
Minor					
201	Part missing		1.50%	3.2	Visual
202	Part incorrectly assembled		1.50%	3.2	Visual
203	Assembly damaged		1.50%	3.2	Visual
204	Marking misleading unidentifiable or missing		1.50%	3.2	Visual
205	Poor workmanship		2.50%	3.9.1	Visual

NOTES:
* Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:27Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.23	Printed Wiring Board, Power Supply				F189F967 (3 sheets)
					NEXT HIGHER ASSEMBLY F11830420
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material (Note 1) *		--	3.2	Certification
102	Wiring incorrect (Note 2) *		--	3.2	Certification
103	Wiring unsatisfactory (Note 2) *		--	3.2	Certification
Minor					
201	Part missing		1.50%	3.2	Visual
202	Part incorrectly assembled		1.50%	3.2	Visual
203	Assembly damaged		1.50%	3.2	Visual
204	Marking misleading, unidentifiable or missing		1.50%	3.2	Visual
205	Poor workmanship		2.50%	3.9.1	Visual

NOTES:

* Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER E798E251 (3 sheets)
4.4.2.24	Printed Wiring Board, Interconnecting				NEXT HIGHER ASSEMBLY F11830497
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material (Note 1) *		--	3.2	Certification
102	Wiring incorrect		--	3.2	Certification
103	Wiring unsatisfactory		--	3.2	Certification
Minor					
201	Part missing		1.50%	3.2	Visual
202	Part incorrectly assembled		1.50%	3.2	Visual
203	Assembly damaged		1.50%	3.2	Visual
204	Marking misleading, unidentifiable or missing		1.50%	3.2	Visual
205	Poor workmanship		2.50%	3.9.1	Visual

NOTES:

* Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-6?520(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.25	Gun Control Assembly				F11830418
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Solder workmanship unsatisfactory (Note 1) *		100%	3.2	Visual
102	Wiring workmanship unsatisfactory		100%	3.2	Visual
103	Wire marking improper or missing (Note 7) *		100%	3.2	Visual
104	Part or assembly damaged		100%	3.2	Visual
105	Part or assembly missing		100%	3.2	Visual
106	Part or assembly incorrectly assembled		100%	3.2	Visual
107	Performance	a	--	3.8	4.5.6
108	Interchangeability	a	--	3.6	4.6
Minor					
201	Corrector hexagon loose		1.50%	3.2	Manual
202	Identification plate separating from surface		1.50%	3.2	Visual-Manual
203	Identification plate lettering misleading, unidentifiable or missing		1.50%	3.2	Visual
204	Exposed surfaces unprotected (Note 10)*		1.50%	3.2	Visual
205	Solder connections not insulated (Note 11) *		1.50%	3.2	Visual
206	Silicone compound missing from specified surface (Note 15) *		1.50%	3.2	Visual
207	Poor workmanship		2.50%	3.9	Visual

NOTES: a: 3 samples, accept on 0 reject on 1 failure

* Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.26	Control Assembly, Gun (Packaging Data Sheet)				PDS P11830418
					NEXT HIGHER ASSEMBLY ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Waterproofness of sealed barrier bag destroyed by separation of heat seal, tear or puncture		0.65%	3.2	Visual
103	Marking missing, misleading or unidentifiable		0.65%	3.2	Visual
Minor					
201	Poor workmanship		2.50%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:27Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perrorm the inspections and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection method" column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (See 4.5). The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See 6.3 herein.

4.5 Methods of inspection.

4.5.1 Salt spray test. Samples shall be seleted from each protective finished lot and subjected to the salt spray test in accordance with the procedures specified in ASTM B 117. Unless otherwise specified on the applicable drawing the minimum exposure time shall be one and one half (1 1/2) hours using a 5% sodium chloride solution. rejection shall be in accordance with the applicable protective finish specification.

4.5.2 Hardness. Samples shall be selected from each heat treatment batch (see Note) and subjected to this test. If any part fails to comply with the requirement specified on the applicable drawing, the part shall be classed defective. The hardness test shall be performed in accordance with the procedure specified in ASTM E 18. Each heat treat batch shall remain segregated wuntil completion of all hardness tests.

Note: A heat-treatment batch shall be defined as parts that have been heat-treated at the same time in the same furnace and quench batch for each of all phases of the entire heat-treatment process.

4.5.3 Dialectic withstanding voltage. The terminal insulated shall be tested for compliance with the dialectic withstanding voltage requirement as specified on drawing C11830496 Note 3. Test equipment and procedures shall be satisfactory to the contracting officer. (see 4.4.4)

4.5.4 Electrical requirements. The part of assembly shall be subjected to the electrical tests in order to determine conformance to the electrical characteristics specified on the applicable drawing. Test equipment and procedures shall be satisfactory to the contracting agency. If any part or assembly fails to comply with any specified electric requirement, it shall be classed defective and rejected. Items subjected to cold and hot temperature conditioning shall be conditioned for not less than 24 hours. Temperature tolerance shall be + 3°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.5.5 Environmental requirements. The part or assembly shall he subjected to the environmental tests in order to determine conformance to the environmental characteristics specified on the applicable drawing. Test equipment and procedures shall be satisfactory to the contracting agency. If any part or assembly fails to comply with any specified environmental requirement, it shall be classed defective and rejected.

4.5.6 Performance characteristics: The gun control assembly shall be tested for compliance with specified electronic, test points, feed-through winding, power outputs, input/output relationships, adjustments, fire voltage output load, and power supply fail safe. Any assembly which fails to comply with the specified performance characteristic requirements or evidences degradation of its operational performance shall be classed defective. Test equipment and procedures shall be satisfactory to the contracting officer. (See 4.4.4)

4.5.6.1 Environmental characteristics (first article inspection only): The gun control assemblies shall be subjected to the aircraft vibration, transpiration vibration, shock, high temperature, temperature-altitude, and humidity test specified in MIL-STD-810 to determine compliance with the applicable specification requirements. The gun control assemblies shall be function tested for compliance with the performance characteristics of 4.5.6 when the requirements specify that the system shall be operated. Any gun control assembly which fails to comply with the specified performance test shall be classed defective.

4.5.6.2 Proof test (first article inspection only). When specified in the contract (see 6.2) five (5) gun control assemblies shall be forwarded to the cite specified by the contracting agency and assembled to an accepted Universo Turret Subsystem (UTS). The gun control assemblies shall function in accordance to the intent of the design and with no evidence of malfunction. When approved by the contracting agency, this test may be performed at the aircraft system level.

4.6 Interchangeability testing.

4.6.1 Gun control assembly. A sample of 3 control assemblies randomly selected from each inspection lot shall be tested for interchangeability using the test method specified in 4.6.3. Control assemblies taken for interchangeability testing shall have been found satisfactory in all other examinations and tests. Test frequency may be reduced to not less than one test of 3 control assemblies each lot when a record of consistently satisfactory results has been established. The 3 control assemblies shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

comply with the applicable specification functioning requirements of 4.5.6 before and after the interchange of parts. It shall be the responsibility of the agency responsible for the test to inform the contracting officer by letter or other methods satisfactory to the contracting officer, when selective assembly has become necessary. Statement shall contain, as a minimum, contractor's name and FSCM, contract number, parts involved in the selective fit, conditions of parts and rationale for action taken. No hand refinement of parts shall be permissible without approval by the contracting officer. No malfunctions shall be allowed in the functioning tests. Failure of a control assembly in the interchangeability test shall cause retest or rejection of the represented lot.

At the discretion of the Government representative, an interchangeability retest may be allowed without reconditioning the lot. Failure during the retest shall cause rejection of the represented lot subject to reconditioning and further test as a reconditioned lot. A sample of 6 control assemblies from each retest or reconditioned lot shall be tested using the same procedures described above.

4.6.2 Repair parts. At least 2 parts from each inspection lot of concurrent repair parts shall be subjected to the interchangeability test specified in 4.6.3. Failure of any part to meet the interchangeability requirements shall be cause for rejection of the represented lot, subject to reconditioning and further test as a reconditioned lot. A sample consisting of double the number of parts used in the original test shall be tested from each reconditioned lot using the test methods specified above.

4.6.3 Test method for interchangeability. Control assemblies shall be tested by disassembling and the reassembling the parts specified below Parts shall be disassembled from the control and identical parts placed together and mixed. Any commercial part (screws, pins, etc) rendered unserviceable by disassembly shall be replaced without penalty to the interchangeability test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

List of Interchangeable Parts

Component	Drawing
Case, Gun Control	F11830419
Component Assembly, Limit and Error logic	F189F902
Component Assembly, Comparator	F189F903
Component Assembly, Time Delays	F189F904
Component Assembly Power Supply	F11830420
Component Assembly, Interconnection	F11830497

4.6.4 Repair parts. Concurrent repair parts shall be tested by disassembling 2 control assemblies previously tested in 4.6.3 and then reassembling them using the concurrent repair parts. No hand refinement of parts till be allowed and the assembled control assemlies shall operate and function as intended. This test may be performed independently of the control assembly interchangeability testing specified in 4.5.1 and at more frequent internals using accepted drive assemblies taken from current production.

4.7 Electromagnetic Interference (EMI) (first article inspection only). The Gun Control Assembly shall be installed in laboratory test fixtures in a manner that will simulate actual service usage and tested to MIL-STD-461, Methods CE03, CSO1, CS02, CS06, RE02, RS02 Part I, and RS03.

5. PACKAGING

5.1 Preservation, packaging, packing and marking. The gun control assemblies shall be prepared, packaged, packed, and marked In accordance with Packaging data Sheet (PDS) P11830418 for the level of protection specified in the contract. (See 6.2)

5.1.1 Spare parts or replacement parts. Spare parts or replacement parts shall be cleaned, preserved, packaged and packed as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The gun control assembly covered by this specification is intended for use with gun, automatic, 20MM: M197 on Armament Subsystem. Helicopter, 20MM M97E1 and M97E2.

6.2 Ordering data. Procurement documents shall specify the following:

6.2.1 Acquisition requirements.

a. Title, number and date of this specification.

b. Quantity required and delivery schedules.

c. Serialization requirements, if applicable.

d. Quality Conformance Inspection, if other than specified in Section 4 of this specification.

e. First Article sample requirements, if other than specified in Section 4 of this specification.

f. Packaging requirements. If other than specified in Section 5 of this specification.

g. Certified test reports and certificates of conformance for each lot or shipment of product.

6.2.2 Contract data requirements. Contract data requirements for inspection equipment design shall conform to Data Item Description DI-R-1714, Tailored.

6.3 Submission of inspection equipment design for approval. See MIL-W-63150 equipment designs shall be submitted as equired to: Commander, ARRADCOM, ATTN: DRDAR-QAH, Dover, NJ 07801. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects and test paragraphs.

6.4 Submission of results of contractor-conducted examinations and tests. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to: Commander, ARRADCOM, ATTN: DRDAR-QAF-S, Dover, NJ 07801.

Custodian:
Army-AR

Preparing activity:
Army-AR

Project 1005-A611

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-T-63520 TURRET SUBSYSTEM, UNIVERSAL (UTS) FOR ARMAMENR SUBSYSTEM, HELICOPTER 20MM: M97Eland 97E2, GUN CONTROL A-SEMBLY FOR

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.