MIL-B-40611C(GL)

1 November 1972
SUPERSEDING
MIL-B-40611B(GL)
31 March 1969

MILITARY SPECIFICATION

BAGGING MACHINE, FRUIT AND PRODUCE

1. SCOPE

1.1 Scope. This specification covers one type of fruit and produce bagging machine with single hopper and universal bagging head.

2. APPLICABLE DOCUMENTS

* 2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

UU-P-268	-	Paper, Kraft, Untreated, Wrapping.
MMM-A-260	-	Adhesive, Water-Resistant (For Sealing Waterproofed Paper).
PPP-B-601	-	Boxes, Wood, Cleated Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-B-1055	-	Barrier Material, Weatherproofed and Flexible.
PPP-C-650	-	Crates, Wood, Open and Covered.
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain For Sealing and Securing.
PPP-T-60	-	Tape; Pressure-Sensitive Adhesive, Waterproof, for Packaging and Sealing.

MILITARY

MIL-C-104	-	Crates, Wood: Lumber and Plywood Sheathed, Nailed and Bolted.
MIL-P-116	-	Preservation, Methods Of.
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-461 - Electromagnetic Interference Characteristics, Requirements for Equipment.
MIL-STD-462 - Electromagnetic Interference Characteristic, Measurements Of.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

Underwriters' Laboratories, Inc. (UL)

Electrical Construction Materials List.

(Application for copies should be obtained from Underwriters' Laboratories, Inc., 207 East Ohio Street, Chicago, Illinois, 60611; 1285 Walt Whitman Road, Melville, N.Y., 11746; or 1655 Scott Boulevard, Santa Clara, California 95050.)

National Electrical Manufacturers' Association (NEMA)

ICS-1970 - Industrial Controls and Systems

(Application for copies should be obtained from National Electrical Manufacturers' Association, 155 East 44th Street, New York, N.Y., 10017.)

National Fire Protection Association (NFPA)

Standard No. 70 - National Electrical Code.

(Application for copies should be obtained from National Fire Protection Association, 60 Batterymarch St., Boston, Mass., 02110.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

National Sanitation Foundation (NSF)

Basic Criteria C-2 - Special Equipment and/or Devices.

Listing of Food Service Equipment.

(Application for copies should be addressed to the National Sanitation Foundation, P.O. Box 1468, Ann Arbor, Michigan 48106.)

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N. W., Washington, D. C. 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

* 3.1 First article. When specified (see 6.2), the supplier shall furnish a sample for first article inspection and approval (see 4.2 and 6.3).

3.2 Standard product. The bagging machine shall be new and the regular commercial product of the manufacturer except for any changes necessary to comply with this specification. All parts in any one contract having the same manufacturer's part number shall be functionally and dimensionally interchangeable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

3.3 Code and standards. The bagging machine shall comply with the following:

(1) The electrical control components shall conform to NEMA Standard ICS-1970.

(2) Other electrical materials and components shall conform to UL standards, as applicable.

(3) The installation of the electrical components shall conform to the applicable requirements of NFPA Standard No. 70.

(4) Construction and sanitation details shall conform to NSF Basic Criteria C-2.

* 3.3.1 Certification. Prior to approval of the first article, if one is submitted, or prior to commencement of production, the supplier shall submit satisfactory evidence to the contracting officer or his authorized representative that the bagging machines conform to NSF Basic Criteria C-2 and the electrical components and installation conform to NEMA Standards Publication No. ICS-1970, applicable UL standards, and NFPA Standard No. 70 as specified in 3.3.

3.3.1.1 NFPA and NEMA. Acceptable evidence of meeting the requirements of NFPA Standard No. 70 and NEMA Standards Publication No. ICS-1970, shall be the manufacturer's certified statement that the bagging machine conforms to the applicable requirements.

* 3.3.1.2 UL. Acceptable evidence of meeting the requirements of Underwriters' Laboratories, Inc., shall be the UL label, or Listing Mark or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the electrical materials and components offered have been tested and conform to applicable UL standards.

* 3.3.1.3 NSF. Acceptable evidence of meeting the requirements of NSF shall be:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment", or display of the NSF seal on the fruit and produce bagging machine, or

(2) A certification for the machine issued by NSF under their special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the machines are being procured, indicating that the machine has been tested and conforms to NSF Basic Criteria C-2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

3.4 Materials. The materials shall conform to the referenced specifications and requirements specified herein. Where materials are not definitely specified, they shall be of the quality normally used for the purpose in commercial practice.

3.5 Design and construction. The bagging machine shall be a semi-automatic, self-contained unit capable of filling bags with a predetermined amount of fruit or produce. Bagging of the product by the machine shall be accomplished by the use in combination of a hopper, conveyor, bagging head, weighing scale, clutch, and an electric motor and variable speed drive. The machine shall have a loading cycle as follows:

(a) Weight of bag contents shall be preset on scale.

(b) A button switch shall start the conveyor.

(c) Conveyor shall feed the product from the hopper to the bag held by the bagging head.

(d) When the preset weight is reached, the conveyor shall stop to end the cycle.

The machine shall be mounted on four legs. The two front legs shall have rubber-tired wheels to provide machine mobility.

3.5.1 Voltage. Unless otherwise specified (see 6.2) the machine shall operate on a 120-volt, 60 hertz (Hz), single phase, alternating current system.

3.5.2 Hopper. The hopper shall have all inside surfaces sloping toward the conveyor and a built-in vibrator to prevent damage to, and bridging of, the product at the bottom of the hopper. The minimum hopper capacity shall be 200 pounds.

3.5.3 Conveyor. The conveyor shall carry fruit or produce from the hopper to the bagging head, with no damage to the fruit or produce. The conveyor operation shall be automatically controlled by the clutch.

3.5.4 Bagging head. The bagging head shall be electrically and mechanically connected with the weighing scale and clutch so that as the head is depressed to the preset weight on the scale, the conveyor shall stop to end the loading cycle. The head shall have rubber-tipped prongs for attaching and securely holding a polyethelene or mesh bag.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

* 3.5.5 Weight determination. The predetermining weight selector shall control the weight of the filled bags. The preset weight shall be any amount between one and twenty-five pounds, automatically repeating until re-set to another valve within this range. The readout shall provide instantaneous visual response. Scales, load cells, dials, digital displays, integrated circuits, linkages and other associated components may be used in any combination providing the bagging machine meets all the requirements specified herein.

* 3.5.6 Electric motor. The electric motor shall conform to applicable codes and standards as specified in 3.3.

3.6 Performance. The bagging machine with empty hopper shall operate through a complete loading cycle at each of various preset weights when tested as specified in 4.4.1. The bagging machine shall fill bags at the rate and weight specified in table I when tested as specified in 4.4.2.

TABLE I. Capacity

Commodity	Weight per bag	Rate (Bags per minute)
Potatoes	5 lbs	5 to 7
Potatoes	25 lbs	1 to 2
Apples	3 lbs	9 to 11
Apples	25 lbs	1 to 2

3.7 Finish. The bagging machine shall be finished in accordance with the manufacturer's standard practice. Painted surfaces shall be smooth, adherent, dry, and free from blisters, runs, embedded foreign matter, and unpainted areas.

3.8 Electromagnetic compatability. When specified (see 6.2) the bagging machine shall be equipped for electromagnetic compatability in accordance with class IIB of MIL-STD-461 (see 4.4.3).

3.9 Lubrication. Provisions shall be made on the machine for lubrication of all moving parts requiring lubrication. Seals shall be provided where necessary to prevent leakage of lubricant. The machine shall be constructed so that lubricants will not come in contact with foodstuffs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

3.9.1 Lubrication chart. The supplier shall affix to each machine a corrosion-resistant metal lubrication chart or furnish a brochure or manual attached to the machine indicating:

(a) All points of the machine requiring lubrication.

(b) Grade of lubricant required.

(c) Time interval when lubrication shall be accomplished.

3.10 Maintenance. Parts of the machine requiring operating adjustments shall be readily accessible.

3.11 Special tools. Special tools required for maintenance and adjustment shall be furnished with each bagging machine.

3.12 Marking for identification. The bagging machine shall be marked in accordance with the manufacturer's standard practice.

3.13 Workmanship. The complete bagging machine shall be clean, properly assembled and in alignment. All exposed surfaces shall be free from burrs and sharp edges. Components shall not be loose, bowed, dented, or fractured. Surfaces shall show no evidence of rust or corrosion.

3.13.1 Rivets. Rivets shall be tight and heads shall be completely formed and in full contact with the surface of the riveted member.

3.13.2 Fasteners. Fasteners such as screws, nuts, and bolts shall be drawn tightly, and not cracked or stripped. Fasteners subject to excessive vibration shall be secured with antivibration means such as castellated nuts with cotter pin, lock washer, or self-locking nuts.

3.13.3 Welding. Welding shall be continuous, smooth, adherent, and free from pin holes, fractures, slag inclusion, and flux deposits.

3.13.4 Wiring. Wiring shall be securely joined. Insulation shall not be cut or abraded and when subject to wear and abrasion shall be inclosed in a conduit.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 First article inspection. When a first article is required, it shall be examined for defects in table II, dimensions specified, and tested as specified in 4.4.2 (and 4.4.3 when applicable). The presence of any visual defect, any dimension not within specified requirements or failure to pass any test, shall be cause for rejection of the first article.

4.3 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Inspection of component and material. In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.3.2 End item inspection. The lot shall be all bagging machines offered for inspection at one time. The sample unit shall be one complete bagging machine.

4.3.2.1 Visual examination. The bagging machine shall be examined for defects in table II. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE II. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Not finished as specified.	X	
	Not smooth and adherent, blistered, paint runs, embedded foreign matter, not dry, or unpainted areas.		X
	Areas of rust.		X
Construction and workmanship (general) (applicable to all components and assemblies)	Part missing, not specified type or size.	X	
	Fractured, dented, or bowed.	X	
	Any component loose.		X
	Not in alignment.	X	
	Sharp burrs or slivers.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Rivets	Missing, heads not fully formed, not in full contact with riveted member.		X
Threaded fasteners	Missing, cracked, stripped, or loose.		X
	Lock washers, lock nuts or cotter pins missing where required.		X
Welding and brazing	Missing, not continuous, pin holes, or fractured.	X	
	Slag inclusion or flux deposits not removed.		X
Wiring	Insulation cut or abraded.	X	
	Wiring not securely joined.		X
	Not enclosed in conduit where required.	X	
Lubrication	Not lubricated, where required.		X
Identification marking and lubrication chart	Missing, incomplete, not legible, or not as specified.		X

4.3.2.2 Dimensional examination. Inspection shall be made of the end item for compliance with the dimensions specified. Any dimension not as specified shall be considered a defect. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

4.3.2.3 Testing of the end item. When a preproduction sample is not required, the initial production item shall be tested as specified in 4.4.2 (and 4.4.3 when applicable). Any nonconformance shall be cause for rejection of the lot. All bagging machines shall be tested as specified in 4.4.1. Any nonconformance shall be cause for rejection of the unit.

4.3.3 Code and standards compliance. Proof of compliance with the requirements of 3.3 shall be made available to the Government representative.

4.3.4 Examination of preparation for delivery. An examination shall be made to determine that preservation, packaging, packing, and marking as required by section 5 of this specification are complied with. Defects shall be scored as specified in table III. The lot shall be the number of containers

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

offered for inspection at one time. The sample unit shall be one shipping container fully prepared for delivery. The inspection level shall be S-2 and the AQL shall be 4.0, expressed in terms of defects per hundred units.

TABLE III. Examination of preparation for delivery

Examine	Defect
Markings (exterior and interior)	Missing; incorrect; illegible; of improper size, location, sequence, or method of application.
Preservation	Preservative improperly applied or missing.
Materials	Component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components such as incomplete closure of case liners or container flaps; loose strapping; inadequate stapling; bulging or distortion of containers; blocking, and cushioning inadequate, improper, or missing; bolts improperly affixed.
Contents	Bagging machine equipment parts, manual, or special tools (if applicable) missing.

4.4 Tests.

4.4.1 Operational test. The bagging machine with empty hopper and no bag attached shall be operated at preset weights of 10, 15, and 25 pounds. As the bagging head is manually depressed, the scale readings shall be checked when the conveyor stops to determine compliance with the loading cycle requirements of 3.6.

4.4.2 Performance test. The machine shall be operated continuously for a period of 5 minutes with each product and preset weight as specified in table I to determine compliance with the bag filling rate and weight requirements of 3.6.

* 4.4.3 Electromagnetic compatability. When electromagnetic compatibility is required, the first article or initial unit of production, as applicable, shall be tested by the supplier in accordance with test methods CE03 and RE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the supplier or an independent testing agency. The supplier shall furnish the contracting officer a written certification that the Interference Control Plan, the EMI/EMC Test Plan, the electromagnetic test report and the requirements meet MIL-STD-461.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. The scale, wheels, and chute shall be disassembled from the machine. All hardware removed in disassembly shall be packaged in a cotton cloth drawstring bag and the bag secured to the major item.

5.1.1.2 Preservation. Preservation shall be in accordance with Method I of MIL-P-116 as specified herein. All exposed unpainted or uncoated ferrous metal surfaces of the bagger, disassembled parts, and special tools shall be thoroughly cleaned process C-1, dried and coated with type P-14 preservative conforming to MIL-P-116. Grease fittings and bearings shall be filled to capacity with the manufacturer's recommended lubricant containing a rust inhibitor. All coated surfaces that might contact packaging or packing materials shall be covered or wrapped with greaseproof barrier-material conforming to type I or II, grade A of MIL-B-121. The greaseproof cover or wrap shall be secured with tape conforming to PPP-T-60 or PPP-T-45.

5.1.1.3 Packaging.

5.1.1.3.1 Free moving parts. Free moving parts shall be secured with twine made of jute, sisal, or cotton; or tape conforming to type IV of PPP-T-60 in a manner as to immobilize the parts and prevent damage while in transit.

5.1.1.3.2 Wheels. The wheels when removed, shall be wrapped separately in kraft paper conforming to grade B of UU-P-268 and then nested in a snug-fitting fiberboard box conforming to style RSC, type CF, variety SW or type SF, class domestic of PPP-B-636. Closure of the box shall be in accordance with the appendix of the box specification.

5.1.1.3.3 Scales. Each scale, when removable, shall be packaged in a snug-fitting fiberboard box conforming to style RSC, type CF, variety SW, or type SF, class domestic of PPP-B-636. The scale shall be immobilized and cushioned within the box with scored fiberboard spring pads of die-cut fiberboard sheets made from the same material as the box. Closure of the box shall be in accordance with the appendix of the box specification. When scale is not removable all components subject to damage shall be immobilized and cushioned.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

5.1.2 Level C. Bagging machines shall be packaged to afford adequate protection against corrosion, deterioration, and physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice, when it meets this requirement.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Each bagging machine complete with special tools, preserved and packaged as specified in 5.1, shall be packed in a shipping container conforming to overseas type, type 3 load of PPP-B-601; class 2, style 2 or 4, type 3 load of PPP-B-621; or type I or II, class 1 or 2, style a of MIL-C-104. Blocking, bracing, and anchoring of contents within the shipping container shall be in accordance with the appendix of MIL-C-104. Care shall be exercised to insure that the motor and clutch are supported with wood blocking. Each shipping container shall be provided with skids in accordance with the applicable container specification. The contents of each nailed wood and cleated plywood shipping container shall be covered with a full-height shroud made of waterproof barrier material conforming to class E-2, H-1, H-5, or M of PPP-B-1055. All seams of the shroud shall be sealed with a 3/4-inch minimum width continuous seam of water-resistant adhesive conforming to MMM-A-260. Closure and strapping shall be in accordance with the appendix of the applicable container specification.

5.2.2 Level B. Each bagging machine complete with special tools, preserved and packaged as specified in 5.1, shall be packed in a shipping container conforming to domestic type, style A or B, type 3 load of PPP-B-601; class 1, style 2 or 4, type 3 load of PPP-B-621; or type IV, style A of PPP-C-650. Each shipping container shall be provided with skids in accordance with the applicable container specification.

5.2.3 Level C. Bagging machines complete with special tools preserved and packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification rules or National Motor Freight rules, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The bagging machines covered by this specification are intended for use in commissaries to weigh and bag produce and fruit in amounts normally marketed to consumers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

* 6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) When a first article is required (see 3.1, 4.2 and 6.3).
(c) Electrical requirements, if other than specified (see 3.5.1).
(d) When electromagnetic compatibility is required (see 3.8).
(e) Selection of applicable levels of preservation, and packaging and packing (see 5.1 and 5.2).

* 6.2.1 Contract data requirements. Any requirements for equipment manuals for the items covered by this specification should be included in DD Form 1423 Contract Data Requirements List and cited in the contract.

* 6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Armed Services Procurement Regulations ASPR 7-104.55. The first article should be a preproduction sample, initial production item, or other specific item described under the definition of a first article in the ASPR. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

6.4 The margins of this specification have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - GL

Review activity:

Army - MD

Preparing activity:

Army - GL

Project No. 3540-A086

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

Bagging Machine, Fruit and Produce MIL-B-40611C(GL)

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 84 1426

REPLACES EDITION OF 1 OCT 84 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. Army Natick Laboratories
Natick, Massachusetts 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding General
U. S. Army Natick Laboratories
ATTN: AMXRES-RQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.