MIL-C-40617C
25 March 1980
SUPERSEDING
MIL-C-40617B
20 May 1968

MILITARY SPECIFICATION

CABINETS, DELIVERY AND STORAGE, PASTRY; AND TRUCK, DOLLY, PASTRY CABINETS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers pastry cabinets and a dolly truck (see 6.1).

1.2 Classification.

1.2.1 Cabinets. The cabinets shall be of the following types and grades as specified (see 6.2).

Type I - 11 pan
Type II - 40 pan with casters

Grade A - Stainless steel
Grade B - Aluminum

1.2.2 Dolly truck. The dolly trucks shall be of the following grades as specified (see 6.2).

Dolly truck - Applicable to type I cabinet only
Grade A - Stainless steel
Grade B - Aluminum

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7320

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:25Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

FF-C-77 - Casters, Rigid and Swivel (Institutional Duty)

MILITARY

MIL-B-2316 - Bakery Equipment, Including Unit Assemblies, Repair Parts and Tools, Preparation for Delivery Of

STANDARD

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

(Copies of specifications and standards required by the contractor in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL SANITATION FOUNDATION (NSF) STANDARD

Standard No. 2 - Food Service Equipment and Appurtenances

Seal of Approval Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, PO Box 1468, Ann Arbor, MI 48106.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Standard product. The units furnished under this specification shall be the manufacturer's standard commercial product, except for any changes necessary to comply with specification requirements.

3.2 NSF standard and certification. The units shall comply with the applicable requirements of NSF Standard No. 2. Prior to commencing production the contractor shall submit to the contracting officer or his authorized representative, satisfactory evidence that the units he proposes to furnish under this specification meet the applicable requirements of NSF Standard No. 2. Acceptable evidence of meeting the applicable requirements of this standard shall be:

a. A listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF seal on the finished units, or

b. A certification for the units issued by NSF under their one time contract evaluation certificate service, or

c. A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the units are being procured, indicating that the units have been tested and conform to NSF Standard No. 2.

3.3 Materials and components. The materials and components shall be as specified herein. Materials and components not specifically specified shall be of the quality normally used by the manufacturer provided the completed item complies with all of the provisions of this specification (see 6.3).

3.3.1 Casters. Casters shall be type I (rigid) and type II (swivel), class C, 5 inch (127 mm) diameter wheels, style c, mounting P of FF-C-77.

3.4 Design and construction. The design and construction of the cabinets and dolly trucks shall be as specified herein. The cabinets shall be fabricated of stainless steel (grade A) or aluminum (grade B). The cabinets shall accommodate pastry pans having nominal overall dimensions of 18 x 26 x 1-1/4 inches (457 x 660 x 32 mm) deep. The minimum capacity of the type I and II cabinets shall be 11 and 40 pans, respectively. Pan runners shall be spaced 1-1/2 inch ± 1/8 (38 mm ± 3) on centers. The cabinet pan runners shall support the pans at the rims or bottoms sufficiently to preclude droppage and spillage of the pans. When the cabinet has no frame, the cabinet sides shall be formed to serve as sides. When the cabinet has a frame, the frame and panels shall be riveted or welded to form the sides, ends and back. Single or double doors shall be located at the front of the cabinet. The doors shall be provided with a continuous hinge or with two or more separate hinges. The doors shall be open at least 180 degrees. Provisions shall be made on the walls of the cabinet for holding the doors in the open position. A gravity actuated door latch or a two point vertical rod latch actuated by a handle shall be provided for each door. The door shall close

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:25Z
Check the source to verify that this is the current version before use.

tightly against the cabinet frame. The cabinets shall have either two trunk handles or one full length tubular handle on each side of the cabinet. The handle brackets shall be made so as to limit the swing of the handle to 90 degrees from the normal position of being folded flush against the cabinet wall. The width (inside) of the trunk bail shall not be less than 4 inches (102 mm) and shall be fabricated from a rod not less than 3/8 inch (10 mm) diameter. The tubular handle outside diameter shall not be less than 3/4 inch (19 mm) and the handle shall be equal in length to the width of the cabinet.

3.4.1 Type I. The type I cabinet accommodations shall not be less than 11 pastry pans. The cabinet dimensions shall not be less than 18 inches high x 19 inches wide x 26 inches deep (457 x 483 x 660 mm). The cabinet shall be provided with means to interlock a cabinet with a cabinet on top in accordance with the manufacturer's standard commercial practice. When the cabinets are stacked and interlocked the top cabinet shall not slide off the cabinet underneath. The handles for the cabinet shall be located in line, 5 inches ± 1 (127 mm ± 25) from the top. The cabinet with dolly truck specified in 3.4.3 shall show no evidence of damage or distortion of the cabinet or dolly truck when tested as specified in 4.4.1. When cabinets are procured without dolly trucks, they shall show no evidence of damage or distortion when tested as specified in 4.4.2. The type I, grade A cabinet runners shall show no evidence of bending or or metal flaking when tested as specified in 4.4.4.

3.4.2 Type II. The type II cabinet accommodations shall not be less than 40 pastry pans. The cabinet dimensions shall not be less than 69 inches high x 20-1/2 inches wide x 27-1/2 inches deep (1753 x 521 x 699 mm). The cabinet handles shall be located in line, 24 to 26 inches (610 to 660 mm) above the floor. The cabinet base shall be provided with two eyebolts constructed of steel rod with a diameter of not less than 3/8 inch (10 mm) and with an eye opening diameter of not less than 7/8 inch (22 mm). One eyebolt shall be located at the front center and the other at the rear center of the cabinet. The eyebolts shall not protrude beyond the cabinet base horizontally. The eyebolt opening shall be perpendicular to the base of the cabinet. The cabinet shall not become damaged or distorted when tested as specified in 4.4.3. The type II, grade B cabinet runners shall show no evidence of binding or metal flaking when tested as specified in 4.4.4.

3.4.3 Dolly truck. The truck shall be fabricated from stainless steel (grade A) or aluminum (grade B). The truck shall be provided with sides, corner angle brackets or by other standard commercial means to preclude the type I cabinets from sliding off the sides of the truck. When sides are furnished they shall be bent or formed 90 degrees up from the truck base. The base of the truck shall be provided with two eyebolts constructed of steel rod with a diameter of not less than 3/8 inch (10 mm) and with an eye opening diameter of not less than 7/8 inch (22 mm). One eyebolt shall be located at the front center and the other at the rear center of the base of the truck. The eyebolts shall not protrude

Source: https://assist.dla.mil -- Downloaded: 20261O-21T19:25Z
Check the source to verify that this is the currentversion before use.

beyond the front of the base of the truck. The eyebolt opening shall be perpendicular to the base of the truck. When specified (see 6.2), a dolly truck shall be provided to accommodate the type I, cabinet. When the type I cabinet is resting on the truck platform the clearance shall be not greater than 1/2 inch (13 mm) between the type I cabinet base and the truck sides or corner angle brackets. When the truck is procured separately, information for matching to the existing type I cabinets shall be furnished (see 6.2). When tested as specified in 4.4.5 the dolly truck shall not be damaged or distorted and casters shall be workable.

3.4.4 Casters. Four casters (two rigid and two swivel) as specified in 3.3.1 shall be provided on the dolly truck and type II cabinet, with the two swivel casters on the attendant's side, equipped with foot brakes. Casters and caster mounting areas shall not show any evidence of damage or distortion when tested as specified in 4.4.5.

3.5 Marking. The units shall be marked in accordance with the manufacturer's commercial practice and shall include the manufacturer's name and date of manufacture.

3.6 Workmanship. The units shall be free from defects such as fractures, splits, punctures, tears, dents, creases, deteriorations or malformation. There shall be no sharp edges, burrs or slivers, scratches, die or tool marks.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where indicated hereinafter.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.2 End item inspection. The inspection lot shall consist of all complete units offered for inspection at one time. The sample unit shall be one completed unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

4.4.2.1 Visual examination. Examination of the end items shall be made for the defects in table I. The inspection level shall be level II with and acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Classification Minor
Finish	Not clean	X	
Design, construction, and workmanship (applicable to all components and assemblies)	Fractured, split, punctured, torn, bent, bruised, deteriorated or malformed	X	
	Sharp edges, burrs or slivers, scratches, die or tool marks	X	
Cabinets	Pan runners do not support pans by rims or bottom	X	
	Sides not formed to serve as frame for the frameless construction	X	
	Top and bottom sections not welded or riveted to sides and frames	X	
Doors and latches	Single or double door missing	X	
	Not provided with a continuous hinge or not with a minimum of two separate hinges per door	X	
	No provisions on wall of cabinet for holding door in open position	X	
	Door latch not gravity actuated or not two point vertical rod type latch actuated by a handle	X	
	Door does not close against door cabinet frame	X	
	Door edges not reinforced by structural shape or forming of the panels	X	
Handles	Cabinet not provided with trunk type or full length tubular handles		X
	Truck type handle does not fold flush against wall of cabinet		X
Cabinets (type I)	Interlocking means for stacking missing	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Cabinets (type II) and dolly truck	Missing eyebolts	X	
	Eyebolt opening not perpendicular to cabinet base and dolly truck platform	X	
	Protrusion of the eyebolts horizontally beyond the cabinet base or dolly truck base	X	
Dolly trucks	Does not stack type I cabinets	X	
	Corner angle brackets or sides missing	X	
Casters (type II cabinet and dolly truck)	Not provided with four swivel casters	X	
	Casters not removable	X	
	Foot brakes not on the two casters on the attendant's side	X	
Marking	Not specified data, missing, incomplete, not legible		X

4.2.2.2 Dimensional examination. Examination shall be made of the end item for compliance with dimensions specified. Any dimension that is not within the specified tolerance shall be classified as a defect. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

4.2.2.3 End item testing. The end item shall be tested for the characteristics indicated in table II. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

TABLE II. End item tests

Characteristic	Requirement paragraph	Test method	No. of determinations per sample unit	Results reported as
Drop test:				
Type I cabinet with dolly truck	3.4.1	4.4.1	1	Pass or fail
Type I cabinet without dolly truck	3.4.1	4.4.2	1	Pass or fail
Type II cabinet	3.4.2	4.4.3	1	Pass or fail
Metal flaking test, types I and II, grade B cabinets	3.4.1 and 3.4.2	4.4.4	1	Pass or fail
Drop test, dolly truck	3.4.3	4.4.5	1	Pass or fail
Obstacle caster tests, dolly truck and type II cabinet	3.4.4	4.4.6	1	Pass or fail

4.2.3 Examination of preparation for delivery. Examination shall be made for preservation and packaging, packing, and marking in accordance with MIL-B-2316.

4.3 Certificate examination. Certificates of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with specifications requirements shall be examined and validated (see 3.2).

4.4 Methods of inspection.

4.4.1 Drop test, type I cabinet with dolly truck. Type I cabinets stacked three high on a dolly truck shall be dropped ten times from a 12 inch (305 mm) height so that the casters of the truck strike a flat firm surface. Any evidence of damage or distortion shall constitute failure of this test (see 3.4.1).

Source: https://assist.dla.mil -- Downloaded: 20261O-21T19:25Z
Check the source to verify that this is the currentversion before use.

4.4.2 Drop test, type I cabinet without dolly truck. A type I cabinet shall be placed on a dolly similar to that specified in 3.4.3 and dropped ten times so that the casters of the dolly truck strike a flat firm surface. Any evidence of damage or distortion shall constitute failure of this test (see 3.4.1).

4.4.3 Drop test, type II cabinet. A type II cabinet shall be raised by the handles and dropped 10 times from a 12 inch (305 mm) height so that the casters of the truck strike a flat firm surface. Any evidence of damage or distortion shall constitute failure of this test (see 3.4.2).

4.4.4 Metal flaking test, types I and II, grade B cabinets. An 18 by 26 by 1-1/4 inch (457 x 660 x 32 mm) pastry pan with half round open bead top edges weighted with a uniformly distributed 10 pound (4.5 kg) load shall be inserted and removed ten times from each set of runners in the cabinet. Any evidence of binding or metal flaking from pan runners shall constitute failure of this test (see 3.4.1 and 3.4.2).

4.4.5 Drop test, dolly truck. A dolly truck loaded with a uniformly distributed 250 pound (113 kg) load shall be dropped three times from a 12 inch (305 mm) height so that the casters of the truck strike a flat firm surface. Any evidence of damage or distortion and unworkable casters shall constitute failure of this test (see 3.4.3).

4.4.6 Obstacle caster tests, dolly truck and type II cabinet. A dolly truck loaded with a uniformly distributed 200 pound (90.7 kg) load or where applicable a type II cabinet completely filled with pans each loaded with a uniformly distributed 5 pound (2.2 kg) load shall be passed ten times over a 1/4 inch (6 mm) obstacle at a speed which shall not be less than 2 miles per hour (3 km/h). Any evidence of damage or distortion of caster or caster mounting area shall constitute failure of this test (see 3.4.4).

5. PACKAGING

5.1 Levels A, B, and C. Cabinets shall be preserved and packaged, packed and marked for each level of protection in accordance with the applicable requirements of MIL-B-2316 (see 6.2).

6. NOTES

6.1 Intended use. The cabinets are intended for the delivery and storage of pastry. The dolly truck is intended for the transportation of stacked type I cabinets. One dolly truck is normally used with three type I cabinets.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type and grade of cabinet required (see 1.2.1 and 6.1).

Source: https://assist.dla.mil -- Downloaded: 20261O-21T19:25Z
Check the source to verify that this is the current version before use.

(c) Grade of dolly truck required (see 1.2.2 and 6.1).
(d) If required, number of dolly trucks for type I cabinets (see 1.2.2 and 3.4.3).
(e) Information for matching existing type I cabinets and dolly trucks (see 3.4.3).
(f) Selection of the applicable levels of preservation, packing and marking required (see 5.1).

6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3).

6.4 Metric equivalents. Metric equivalents, indicated in parentheses throughout this document, are based on practices, conversion factors, and symbols specified in ASTM E 380 Standard for Metric Practice, and are for information only. In each instance, the value stated in US customary units shall be controlling.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify the changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SA
Air Force - 99

Preparing activity:

Army - GL

Project No. 7320-0691

Review activities:

Army - MD
Navy - SA
DLA - GS

User activity:

Navy - MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government Fold on lines on reverse side, staple in corner, and send to preparing activity Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE

MIL-C-40617C Cabinets, Delivery and Storage, Pastry; and Truck Dolly, Pastry Cabinets

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

VENDOR ☐ USER ☐ MANUFACTURER

☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT ? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

a. GIVE PARAGRAPH NUMBER AND WORDING

b. RECOMMENDED WORDING CHANGE

c. REASON FOR RECOMMENDED CHANGE(S)

REMARKS

SUBMITTED BY (Printed or typed name and address — Optional)

TELEPHONE NO.

DATE

FORM 1426
1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

DRDNA-ES

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314

Commander
US Army Natick Research and Development Command
ATTN: DRDNA-ES
Natick, MA 01760

NATICK OP 1 AUG 78
FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.