MIL-R-40607D
17 June 1986
*SUPERSEDING
MIL-R-40607C
29 June 1971

MILITARY SPECIFICATION

RACKS, CUTLERY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 Scope. This document covers cutlery racks for attachment to table legs and for mounting on a flat upright surface.

* 1.2 Classification. The cutlery rack shall be of the following styles and sizes, as specified (see 6.2).

Style I - With support brackets (leg mounting)

Size 1 - For attachment to tables with end legs spaced 24-inches on centers
Size 2 - For attachment to tables with end legs spaced 29-inches on centers

Style II - Without support brackets (mounting on flat upright surface)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-L-10547	-	Liner, Case, and Sheet, Overwrap, Water Vaporproof or Waterproof, Flexible

STANDARDS

FEDERAL

FED-STD-601	-	Rubber; Sampling and Testing

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-130	-	Identification Marking of U.S. Military Property

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

2-9-181	-	Racks, Cutlery; Assembly and Details

* (Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

NATIONAL SANITATION FOUNDATION (NSF)

Listing of Food Service Equipment

Standard No. 2 - Food Service Equipment and Appurtenances

(Application for copies should be addressed to the National Sanitation Foundation, 3475 Plymouth Road, P.O. Box 1468, Ann Arbor, MI 48106.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

* A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip
D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

* 3.2 Codes and standards. The cutlery racks shall conform to the applicable requirements of NSF Standard No. 2. Satisfactory evidence that these requirements have been met shall be submitted to the contracting officer or his authorized representative prior to the start of production (see 4.4.3).

3.3 Materials (see 6.4). The materials specified shall conform to the applicable documents specified herein. Materials not definitely specified shall be of the quality currently used by the manufacturer for his cutlery racks provided the completed racks conform to all provisions of this document.

* 3.3.1 Stainless and heat resisting steel. Stainless and heat resisting steel shall conform to type 302 or 304 of ASTM A 167.

3.3.2 Rubber. Rubber shall have a durometer hardness of 50 ± 10 when tested as specified in 4.4.1.1.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:24Z
Check the source to verify that this is the current version before use.

Change from previous issue. The margins of this document are marked with

* 3.4 Design and construction. Style I cutlery racks are designed with bracket supports for attaching to table legs and style II cutlery racks are designed without bracket supports for mounting to an upright flat surface. The racks as specified in 1.2 shall conform to the design and dimensions shown on Drawing 2-9-181. The guard and support brackets shall be fabricated from the stainless and heat resisting steel specified in 3.3.1. The retainer shall be fabricated from the rubber specified in 3.3.2. The style I racks shall be provided with four stainless steel bolts, wing nuts, and lock washers for mounting.

* 3.5 Data-name plates. The racks shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for; (a) Methods of applying, (b) Identification tags, (c) Information not required and (d) Optional marking information shall not apply. The data plates shall be made of minimum 20 gauge corrosion-resisting metal and attached to the racks by rivets, screws or welding in such a manner as to meet the applicable National Sanitation Foundation sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved or applied by photosensitive means:

National Stock Number
Procurement Instrument Identification Number
Specification Data
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (see 6.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the item.

* 3.6 Finish. All fabrication marks shall be removed and all exterior exposed surfaces of stainless steel components shall have a 2 B finish or better.

3.7 Workmanship. The finished racks shall be clean and free of dents, sharp edges, burrs, and slivers. There shall be no cracks, holes, wrinkles, or deformities. The surface opposite the indented markings shall show no visible evidence of unevenness, penetration, or distortion. There shall be no visible evidence of discoloration on the metal parts. Welds shall be ground smooth and shall be free of flashes, scale, rust, pits and foreign matter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

* 4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects in table I and for compliance with dimensions specified. The presence of any of the defects listed in table I, or any dimension not within specified requirements shall be cause for rejection of the first article.

* 4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified or qualified in this document or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

4.4.1.1 Rubber hardness test. Rubber shall be tested in accordance with method 3021 of FED-STD-601 to determine compliance with the durometer hardness specified in 3.3.2. The lot shall be all rubber offered for acceptance at one time. Three samples shall be taken from each lot. Failure of any sample to comply shall be cause for rejection of the lot.

4.4.2 End item inspection. The lot shall consist of all racks of one size offered for inspection at one time. The sample unit shall be one completely fabricated cutlery rack.

4.4.2.1 Visual examination. Examination shall be made of the cutlery racks for the defects listed in table I. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major and 6.5 for total (major and minor combined) defects.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Fabrication marks not removed	X	
	Not a 2 B finish or better	X	
Design	Any design feature not conforming to referenced drawing	X	
Construction	Any component missing	X	
Workmanship	Dirty or dented	X	
	Sharp edges, burrs, or slivers	X	
	Cracks, deformities, wrinkles	X	
	Metal discoloration		X
*Data-name plates	Omitted or not as specified		X
	Information incomplete or not legible		X
	Not located so as to be readily visible to operator		X
Welds	Not ground smooth, flashes, pits, rust, scale, foreign matter imbedded	X	
Marking	Missing, not indented, metal penetration or distortion	X	
	Illegible, incomplete, incorrect, wrong location		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

4.4.2.2 Dimensional examination. Examination shall be made for dimensions specified on Drawing 2-9-181. Any dimension not within tolerance shall be a defect. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

* 4.4.3 Certification compliance examination. Certifications, certified test reports or listing marks for standards, submitted in accordance with 3.2 shall be examined and validated as proof of compliance. Prior to Government approval of first shipment the contractor shall submit to the contracting officer or his authorized representative for approval, certification that the racks he proposes to furnish meet the applicable requirements of NSF as follows:

* 4.4.3.1 NSF. Acceptable evidence of meeting the applicable requirements of NSF Standard No.2 as follows:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished rack or,

(2) A certification for the rack issued by NSF under their special one-time contract evaluation/certification service, or

(3) A certified test report acceptable to the contracting officer with the advice of the Army Surgeon General from an independent testing laboratory, indicating the racks have been tested and conform to the specified NSF Standards.

* 4.4.4 Packaging examination. The fully packaged end item shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container, fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Components missing, damaged, or not as specified.
Contents (exterior and interior)	Contents per container is more or less than specified.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

5.1.1 Level A.

* 5.1.1.1 Disassembly. The support brackets of the style I racks shall be removed, lock washers and wing nuts replaced and secured finger tight.

* 5.1.1.2 Unit packing. Each complete cutlery rack, together with support brackets when applicable, shall be unit packed in the most compact manner, in a snug-fitting, fiberboard box conforming to style RSC (end opening) type CF, (variety SW) or SF, class domestic of PPP-B-636. The contents shall be immobilized in a manner to prevent movement during transit. Each box shall be closed in accordance with PPP-B-636.

* 5.1.2 Commercial. Cutlery racks shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Six cutlery racks of one style and size only, preserved as specified in 5.1, shall be packed in snug-fitting cleated-plywood shipping containers conforming overseas type, type 2 load of PPP-B-601. Each shipping container shall be provided with a type I or II, grade C case liner conforming to MIL-L-10547. Closure and strapping shall be in accordance with PPP-B-601.

5.2.2 Level B packing. Six cutlery racks of one style and size only, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Closure shall be in accordance with method II of PPP-B-636.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

* 5.2.3 Commercial packing. Cutlery racks, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking. In addition to any special marking required by the contract or purchase order, unit packs and shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:24Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The cutlery racks are intended for attachment to tables for holding knives and other cutlery items. The style I, size 1 rack is for use on the end of tables (with legs spaced 24 inches apart on centers) specified in MIL-T-2256. The style I, size 2 rack is for use on the side of the type II, style I, size 3 table (with legs spaced 29 inches apart on centers) specified in MIL-T-2256.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Style and size cutlery rack required (see 1.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Government approved manual number to be included on data name plate (see 3.5).
e. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
f. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

* 6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for inspection and approval of the first article.

* 6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.3).

6.5 Changes from previous issue. The margins of this document are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Preparing activity:

Army - GL

Project No. 7320-0771

Review activities:

Army - MD, TS
Navy - MC, MS
DLA - GS

User activity:

Navy - SA
Air Force - 84

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:24Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-R-40607D	Racks, Cutlery

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OI, 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:24Z
Check the source to verify that this is the current version before use.