MIL-S-40601D
9 July 1985
SUPERSEDING
MIL-S-40601C
24 March 1971

MILITARY SPECIFICATION

SAWS, BAND, MEAT-CUTTING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers meat-cutting band saws powered by electric motors.

1.2 Classification. Meat-cutting band saws shall be of the following sizes as specified (see 6.2).

Size 1 - Minimum cutting clearance of 14-1/2 inches high by 12-1/2 inches wide.

Size 2 - Minimum cutting clearance of 17-1/2 inches high by 15 inches wide.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

CC-M-641 - Motor, Alternating Current (Integral Horse-power, 200 HP and Smaller).
TT-P-664 - Primer Coating, Synthetic, Rust-Inhibiting, Lacquer Resisting.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

GGG-B-421	- Blades, Band Saw - Wood Cutting, Metal Cutting, and Meat Cutting.
PPP-B-636	- Box, Fiberboard.
PPP-T-45	- Tape, Gummed, Paper, Reinforced and Plain, For Sealing and Securing.
PPP-T-60	- Tape, Pressure-Sensitive Adhesive, Waterproof, For Packaging.

MILITARY

MIL-C-104	- Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted.
MIL-P-116	- Preservation, Methods of.
MIL-B-121	- Barrier-Material, Greaseproofed, Waterproofed, Flexible.
MIL-V-173	- Varnish, Moisture-and-Fungus-Resistant (For the Treatment of Communications, Electronic, and Associated Electrical Equipment).
MIL-V-13811	- Varnish, Waterproofing, Electrical, Ignition.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-461	- Electromagnetic Emission and Susceptibility for the Control of Electromagnetic Interference.
MIL-STD-462	- Electromagnetic Interference Characteristics, Measurement Of

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

UNDERWRITERS LABORATORIES, INC.

Standard No. 73 - Motor-Operated Appliances

(Application for copies should be addressed to the Underwriters' Laboratories, Inc. 333 Pfingsten Road, Northbrook, IL 60062.)

NATIONAL SANITATION FOUNDATION (NSF)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

Standard No. 8 - Commercial Powered Food Preparation Equipment Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, MI 48105.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Standard product. Band saws shall be the manufacturers standard product except for any changes necessary to meet document requirements.

* 3.2 Standard compliance. The band saws shall conform to the applicable requirements of NSF Standard No. 8 and UL Standard No. 73. Satisfactory evidence that these requirements have been met shall be submitted to the Contracting Officer or his authorized representative prior to the start of production (see 4.3).

* 3.3 Materials (see 6.3) and components. Materials not definitely specified herein shall be of the quality normally used by the manufacturer for his band saws provided the completed item complies with all provisions of this document. Commercial tolerences are applicable to all metal thickness and diameters.

* 3.3.1 Band saw blades. Band saw blades shall be a minimum 5/8 inch wide conforming to type I, style 2, class B of GGG-B-421, except blade thickness shall be 0.020 inch to 0.025 inch.

3.3.2 Castings. Castings shall be sound and free from patching, misplaced coring, cracks, porosity, or warpage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

3.4 Design and construction. The size 1 band saw shall have a minimum cutting clearance of 14-1/2 inches high by 12-1/2 inches wide. The size 2 band saw shall have a minimum cutting clearance of 17-1/2 inches high by 15 inches wide. Each band saw shall have a manually operated sliding table and a stationary table for holding the product to be cut. The band saw blade shall be driven by an electric motor and shall be capable of attaining a speed of 3,000 feet per minute. The distance from the floor to the band saw table-top shall be not greater than 37 inches and the overall height of the band saw shall not exceed 76-1/2 inches. The saw shall be mounted on four adjustable feet.

* 3.4.1 Motor. Unless otherwise specified (see 6.2), the electric motor and electrical components shall be designed for operation on a nominal 208-volt, 3-phase, 60-hertz, alternating-current system. The motor for the size 1 and the size 2 band saws shall conform to CC-M-641. The size 1 band saw shall be not less than 2 horsepower and the size 2 band saw shall be not less than 3 horsepower. The motor shall be a drip-proof, splash-proof, or totally enclosed type located in the base of the band saw. The band saw shall be furnished with a drip-proof control switch, located so as to be convenient to the operator.

3.4.2 Drive. The lower blade pulley shall be mounted directly on the motor shaft, or shall be driven by V-belt pulleys or silent chains. Pulley shafts shall be supported by ball or roller bearings and shall have provisions for lubrication. Means shall be provided for adjusting and maintaining the tension of the V-belt or silent chain.

* 3.4.3 Blade. Each band saw shall be supplied with two spare blades in addition to the one supplied with the unit. Blades shall conform to 3.3.1. The machine shall be designed for ease of removal and replacement of blades. Adjustable and replaceable devices for continuous cleaning of the blade during operation shall be provided.

3.4.3.1 Blade pulleys. The band saw shall be provided with an upper and lower blade pulley fabricated of aluminum, cast iron, or steel. Pulley diameters for size 1 band saw shall be a minimum 13 inches and for size 2 band saw shall be a minimum of 16 inches. The rim of the pulleys shall be designed to maintain the blade in proper cutting position. The upper pulley shall be mounted in a manner to allow quick removal. Adjustable and replaceable devices, for continuous cleaning of both upper and lower pulleys during operation shall be provided.

3.4.3.2 Blade tension adjustment device. An adjusting device shall be provided to apply the correct operating tension to the band saw blade. The device shall automatically maintain the tension during operation when tested as specified in 4.4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

3.4.3.3 Lower blade guide. A lower blade guide shall be provided in the stationary table to keep the blade running straight and true. A backup block or bearing to receive the thrust of the blade while cutting shall be provided below the working surface of the stationary and movable tables.

3.4.3.4 Upper blade guide and guard assembly. An upper blade guide consisting in part of a backup bearing or backup block shall be provided to keep the blade running straight and true. A blade guard to protect the operator shall be attached to the guide. The guard and guide shall be vertically adjustable as a complete assembly to clear the product being cut. The guide and guard assembly shall be mounted to allow quick removal for cleaning purposes.

3.4.4 Tables.

3.4.4.1 Stationary tables. The stationary table shall be fabricated from corrosion-resisting steel. The top surface area of the stationary table for the size 1 band saw shall be not less than 500 square inches and the table length shall be not less than 30 inches. The top surface area of the stationary table for the size 2 band saw shall be not less than 675 square inches and the table length shall be not less than 35 inches.

3.4.4.2 Movable table. The movable table shall be fabricated from corrosion-resisting steel and shall have a minimum 1-inch high vertical flange across the pushing end. The movable table for the size 1 band saw shall be not less than 15 inches wide by 18 inches long and the movable table for the size 2 band saw shall be not less than 15-1/4 inches wide by 22 inches long. The movable table shall slide in tracks equipped with ball, roller, or open-type bearings and shall be provided with a stop at the end of the cutting stroke. At the end of the cutting stroke the vertical flange of the movable table shall clear the saw blade. The movable table shall be constructed to allow quick removal from the machine.

3.4.5 Gage plate. A gage plate and a scale with visible markings shall be provided to allow cutting of meat into desired thicknesses. The gage plate shall be fabricated from corrosion-resistant metal or anodized aluminum and shall be capable of being quickly removed from the band saw or swung away from the stationary table.

3.4.6 Pusher plate. A removable, corrosion-resistant metal or anodized aluminum pusher plate shall be provided to allow safe cutting of short ends of meat. The pusher plate shall slide on tracks or grooves and shall be provided with a stop to prevent the plate from contacting the blade. Means shall be provided on the machine to store the pusher plate when not in use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

3.4.7 Scrap receptable. A scrap pan or drawer for catching product scraps shall be provided in the base of the band saw. The scrap pan or drawer shall be fabricated from corrosion-resistant metal, plastic material, or metal suitably plated, anodized, or plasticized to resist corrosion. The scrap pan or drawer shall be accessible for easy removal, emptying and cleaning.

3.4.8 Protection from moving parts. All moving parts shall be completely guarded except that portion of the band saw blade used for cutting. The upper blade pulley and support guard shall be provided with a hinged or latched panel. The base shall be fully enclosed and shall have removable panels to provide access to all parts.

* 3.4.9 Lubrication. Means (fittings) shall be provided for lubricating bearings, shafts, and other moving parts requiring lubrication. Seals shall be provided where necessary to prevent leakage of lubricant into the product zone. At the time of delivery, the band saws shall be completely lubricated and ready for operation.

3.5 Repair and maintenance. Provisions shall be made to allow for ready adjustment, service, and replacement of electrical system components. In addition, there shall be free access to inspect, service, and adjust any component or equipment as provided for by this document, or as indicated by the component or equipment manufacturer.

3.6 Operation. Each band saw, complete with band saw blade, shall be operationally tested as specified in 4.4.2 for conformance with the following requirements:

(a) Proper operation of adjusting devices.
(b) Proper operation of starting and stopping devices.
(c) No undue vibration or noise.
(d) No overheating of bearings.
(e) No binding.

3.7 Stability. The band saws shall be so constructed that when a load of 125 pounds (size 1) or 175 pounds (size 2) is suspended from the left side, front, or right side of the movable table the band saw shall not tilt (see 4.4.1).

3.8 Electromagnetic compatibility. When specified (see 6.2), band saws shall be designed and equipped for electromagnetic compatibility in accordance with class IIB of MIL-STD-461 (see 4.4.3).

3.9 Fungus and moisture resistance treatment of electrical components. When specified (see 6.2), electrical components shall be treated for fungus and moisture resistance. The electrical circuit, including all components and connections, shall be protected from the deleterious affects of moisture and fungus growth by an overall treatment with varnish conforming to MIL-V-173 with the following exceptions:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

(a) Components or circuit elements which are inherently fungus and moisture resistant or which are hermetically sealed need not be treated.

(b) Components or circuit elements whose functions will be adversely affected by varnish coatings shall not be treated.

3.10 Marking.

* 3.10.1 Identification. The band saws shall be marked with the manufacturer's name, trade name or trade mark readily identifiable with said manufacturer.

3.10.2 Special marking. Band saws shall be provided with a corrosion-resistant metal warning plate, affixed in a conspicuous location containing the following: Warning: Operate with safety guards and removable panels in place.

3.11 Finish. The band saw shall be smooth on all surfaces and edges; free from discoloration or stains and shall be finished in accordance with the manufacturer's standard practice.

3.12 Workmanship. The finished band saw shall be clean and not contain any burrs, slivers, sharp edges, or rough tool, gouge or grind marks. Bolt holes and rivet holes shall be accurately punched or drilled and any obstruction that prevents proper seating shall be removed. All threaded fasteners shall be drawn tight. Rivets shall be tightly driven, fully peened, and shall completely fill the holes. Painted surfaces shall not be blistered, peeled, dipped, scratched, area of no film, runs, sags, any stains, or foreign matter imbedded in finish. The finished item shall not be fractured, buckled, bent, punctured, malformed, or damaged.

3.12.1 Welding. All surfaces to be welded shall be clean. Welding shall be accomplished using welding rods having a composition compatible with that of the welded material, welding shall be free of pits, burn through, flashes, fractures, undercuts, weld metal or base metal cracks, incomplete fusion or slag inclusion. Welds shall be sound, smooth. After grinding there shall be no evidence of grind marks, discoloration, cracks or crevices. All scale or flux deposits shall be removed from the finished welds.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be in accordance with MIL-STD-105.

* 4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.2.1.1 Casting inspection. Castings shall be inspected to determine conformance with 3.3.2. The inspection lot shall be the amount of castings offered for inspection at one time. Any nonconformance shall be cause for rejection of the lot.

4.2.2 In-process examination. Examination of the fungus and moisture resistance treatment shall be made to establish conformance with 3.9. Whenever nonconformance is noted, correction shall be made to the affected items and operation.

* 4.2.3 End item visual examination. The end item shall be examined for the defects listed in table I. The lot size shall be expressed in units of band saws. The sample unit shall be one band saw. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. - End item visual defects

Examine	Defect	Classification Major	Minor
Finish	Not finished where required	X	
	Blistered, peeled, chipped, scratched, runs, sags, wrinkles, area of no film or finish not smooth, stained, or foreign matter imbedded in finish (painted surfaces)		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

TABLE I. - End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship (general)	Any component not specified type	X	
	Any component fractured, dented, or malformed	X	
	Any component loose or not in proper alignment		X
	Any burrs, slivers, sharp edges, rough tool gouge, or grind marks	X	
	Unit perceptibly out of square	X	
	Functioning component that requires abnormal force to operate		X
	Any adjustable assembly that cannot be adjusted	X	
	Any adjustable assembly not properly adjusted		X
	Movable table vertical flange does not clear saw blade at end of cutting stroke	X	
Welding	Missing; incomplete; or not fused, sound, or smooth	X	
	Any evidence of pits, burn holes, flashes, fractures, undercuts, weld metal or base cracks, incomplete fusion, or slag inclusion		X
	Flux (when used) not removed		X
Bolts, nuts, screws, studs, rivets, and any other type of threaded fasteners (as applicable)	Missing, broken, stripped, or fractured	X	
	Loose		X
	Rivets not fully peened or upset		X
	Rivets heads not in full contact with riveted members		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

TABLE I. - End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction (detailed)			
Blades	One or more missing	X	
	Cleaning devices not as specified	X	
	Upper or lower blade guides missing or not as specified	X	
	Backup bearings or block missing or not as specified	X	
Pulleys and shafts	Not specified type	X	
	Bearings missing	X	
	Cleaning devices not as specified	X	
Tables	Movable table not equipped with specified bearings	X	
	Vertical flange missing or not as specified	X	
	Stop missing (movable table)	X	
	Movable table not removable	X	
Gage plate	Plate not marked		X
Pusher plate	Stop missing or improperly located	X	
Guards	Missing or not specified type	X	
Motor	Not type or horsepower specified	X	
Lubrication	Seals missing where required	X	
	Insufficiently lubricated	X	
	Lubrication means (fittings) not accessible, or not provided for lubricating bearings, shafts, or other moving parts.	X	
Identification marking	Missing, incomplete, or not legible		X
Special marking	Missing, incomplete, or not legible		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

* 4.2.4 End item dimensional examination. The end item shall be examined for compliance with dimensions listed below. Any dimension not meeting requirements shall be classified a defect. The lot size shall be expressed in units of band saws. The sample unit shall be one band saw. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Paragraph	Dimensions
3.4	Minimum cutting clearances; Maximum height to table top; Maximum overall height.
3.4.3.1	Minimum pulley sizes.
3.4.4.1	Maximum square inch of table surfaces and maximum length-stationary tables.
3.4.4.2	Minimum length and width-moveable tables.

* 4.2.5 End item testing.

4.2.5.1 Representative item testing. One representative end item from each lot shall be tested for stability as specified in 4.4.1. Any test failure shall be cause for rejection of the lot.

4.2.5.2 Operational testing. Every end item shall be tested for operation as specified in 4.4.2. Any test failure shall be cause for rejection of the end item exhibiting the test failure.

4.2.5.3 Electromagnetic compatability testing. When electromagnetic compatability is required (see 6.2), the initial production item shall be tested for electromagnetic compatability as specified in 4.4.3. Any test failure shall be cause for rejection of the item, for necessary design and construction changes, and for repetition of the above electromagnetic testing on the next produced item.

* 4.2.6 Packaging inspection. An examination shall be made to determine whether the preservation, packing, and marking comply with section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged. The lot size shall be the number of shipping containers in the inspection lot. The inspection level shall be S-4 and the AQL expressed in terms of defects per hundred units, shall be 6.5.

Source: https://assist.dla.mil -- Downloaded: 202640-21T19:23Z
Check the source to verify that this is the current version before use.

Examination	Defect
Markings	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Preservation	Preservative improperly applied or missing.
Materials	Component missing, or damaged.

* 4.3 Certificate compliance examination. Certifications, certified test reports, or listing marks for standards, as applicable, submitted in accordance with 3.2, shall be examined and validated as proof of compliance (see 4.3.1 and 4.3.2).

4.3.1 NSF. Acceptable evidence of meeting the requirements of NSF Standard No. 8 shall be one of the following:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF Seal on the finished band saw shall be submitted prior to approval of the preproduction sample, if one is required by the acquisition document, or prior to approval of the first shipment, or

(2) A certification for the band saw issued by NSF under their special one-time contract evaluation/certification service shall be submitted prior to approval of the preproduction sample, if one is required by the acquisition document, or prior to approval of the first shipment, or

(3) A certified test report, acceptable to the contracting officer with the advice of the Army Surgeon General from an independent testing laboratory, indicating that the Band Saw has been tested and conforms to the specified NSF Standard.

4.3.2 UL certification. Prior to approval of the preproduction sample, if one is required by the acquisition document, or prior to approval of the first shipment, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the band saws meet the applicable requirements of UL Standard No. 73. Acceptable evidence of meeting applicable requirements of UL Standard No. 73 shall be the UL listing mark or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the band saws have been tested and conform to the applicable requirements of UL Standard No. 73.

4.4 Methods of inspection.

4.4.1 Stability. The band saw shall not be bolted to the floor for this test. The movable table shall be moved to its extreme left-hand position and a weight of 125 pounds (size 1) or 175 pounds (size 2) shall be suspended from the left-hand edge. The test shall be repeated with the movable table in its center position and the weight suspended from the front edge, and again with

Source: https://assist.dla.mil -- Downloaded: 202640-21T19:23Z
Check the source to verify that this is the current version before use.

the movable table in its extreme right-hand position and the weight suspended from the right edge. During the test the band saw shall be checked to determine compliance with 3.7. Any noncompliance with the requirements specified shall constitute failure of this test.

4.4.2 Operational test. The band saw shall be operated without load for a minimum period of 5 minutes to determine compliance with 3.4.3.2 and 3.6. Inability to meet the operational requirements specified shall constitute failure of this test.

4.4.3 Electromagnetic compatibility test. When electromagnetic compatibility test is required (see 3.8), the band saw shall be tested by the contractor in accordance with the test methods CE03 and RE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the contractor or an independent testing agency. The contractor shall furnish the contracting officer written certification that the Interference Control Plan, the EMI /EMC Test Plan, the electromagnetic compatibility test report, and the requirements meet MIL-STD-461.

* 5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2)

5.1.1 Level A.

5.1.1.1 Disassembly. The movable table, gage plate, pusher plate, V-belt, and all detachable protruding parts of each band saw that might be damaged during shipment shall be removed.

5.1.1.2 Cleaning and drying. All exposed uncoated ferrous metal surfaces of each band saw, including corrosion-resisting steel surfaces and the saw blade and pulleys shall be cleaned process C-1 of MIL-P-116 and thoroughly dried.

5.1.1.3 Application of preservative. Surfaces, cleaned and dried as specified, shall be coated with type P-14 preservative of MIL-P-116. The V-belt pulleys shall be coated with primer conforming to TT-P-664.

5.1.1.4 Protection of preservative. Surfaces from which preservative compound might be removed by contact with packaging and packing materials shall be covered or wrapped with greaseproof barrier-material conforming to type I or II, grade A, class 1 or 2 of MIL-B-121. Barrier-material shall be secured with tape conforming to type III, grade B of PPP-T-45, cotton tape or twine, or heat sealed when heat-sealable barrier-material is used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

5.1.1.5 Sealing. Switches, terminal, control, boxes, and all openings into the motor shall be sealed with tape conforming to PPP-T-60 and the tape overcoated with varnish conforming to MIL-V-13811. For motor opening, a caution tag shall be attached to the saw with the following inscription:

Caution: Remove protective tape from the exterior of the motor before operation of the saw.

5.1.1.6 Unit packing. Parts of each band saw that are free to move, including the saw blade, pulleys, and scrap receptacle, shall be secured in place to prevent movement while in transit. Hinged panels shall be secured with a minimum 1-inch width conforming to PPP-T-60. Detached components shall be prepared method III of MIL-P-116 and unit packed in a fiberboard box conforming to style RSC, V3c or V3s or PPP-B-636. Each box shall be closed and waterproofed with tape in accordance with the appendix of PPP-B-636. The equipment and repair parts manual shall be prepared method IC-1 of MIL-P-116 and unit packed in the fiberboard box with the detached components.

5.1.2 Commercial. Each band saw shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A or Commercial as specified (see 6.2).

5.2.1 Level A packing. Each band saw, preserved as specified in 5.1, shall be packed in a shipping container conforming to type I, class 1 or 2, style a of MIL-C-104. Detached components shall be secured in an unused portion of the base of the shipping container. Anchoring of the contents and closure and strapping shall be in accordance with the appendix of MIL-C-104.

* 5.2.3 Commercial packing. Band saws, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

* 5.3 Marking. In addition to any special marking required by the contract or purchase order, unit packs and shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. Meat-cutting band saws are intended for cutting fresh or frozen meat, fish, or poultry (including bones) into desired portions. The size 1 machine is intended for use in kitchens and commissary meat markets. The size 2 machine is intended for use in central meat cutting plants and commissary store meat markets.

* 6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

stretcher so that strap is held firmly by

b. Size of band saw required (see 1.2).
c. Electrical characteristics, if other than specified herein (see 3.4.1).
d. When electromagnetic compatibility is required (see 3.8).
e. When fungus and moisture treatment is required (see 3.9).
f. Selection of the applicable levels of preservation and packing (see 5.1 and 5.2).

* 6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.3).

6.4 Changes from previous issue. The margins of this document are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Air Force - 99

Preparing activity:

Army - GL

Project No. 7320-0480

Review activities:

Army - MD
Air Force - 84
DLA-GS

User activity:

Navy - MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

PROVIDE THE CORRECT ONES/ IMMEDIATELY ADJA

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-40601D	Saws, Band, Meat-Cutting

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:23Z
Check the source to verify that this is the current version before use.