INCH POUND

MIL-S-40601D
INT. AMENDMENT 4(SH)
16 July 1992
USED IN LIEU OF
AMENDMENT 3
30 September 1988

MILITARY SPECIFICATION

SAWS, BAND, MEAT-CUTTING

This interim amendment is approved for use within the Department of the Navy, Naval Sea Systems Command with MIL-S-40601D, dated 9 July 1985.

PAGE 1

1.2: Add the following "Classes" under "Size 2" band saws:

"Class 1 - 3 horsepower motor, minimum
Class 2 - 5 horsepower motor, minimum"

2.1, under "SPECIFICATIONS FEDERAL": Delete "CC-M-641" and its title, and substitute: "CC-M-1807 - Motors, Alternating Current, Fractional and Integral Horsepower (500 HP and smaller)."

PAGE 2

2.1, under "STANDARDS MILITARY': Delete "MIL-STD-461 - Electromagnetic Emission and Susceptibility for the Control of Electromagnetic Interference".
and
"MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of".

2.2, line 5: Delete "Standards No. 73" and its title and substitute:

"Standards No. 763 - Motor Operated Commercial Food Preparing Machines"

PAGE 3

3.2, line 2: Delete "UL Standard No. 73" and substitute "UL Standard No. 763".

3.3: Delete and substitute:

"3.3 Materials (see 6.3) and components. Materials not specifically specified which have painted surfaces shall not corrode, chip, flake or peel when subjected to a cleaning procedure of being completely hosed down with water, or cleaned by high pressure steam or water. Commercial tolerances are applicable to all metal thicknesses and diameters."

AMSC N/A FSC 7320
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

3.4.1: Delete and substitute:

"3.4.1 Motor. Unless otherwise specified (see 6.2), the electric motor and electrical components shall be designed for operation on a nominal 208-volt, 3-phase, 60 Hertz (Hz), alternating - current system. The motor for the size 1 and the size 2 band saws shall conform to CC-M-1807. The size 1 band saw motor shall be not less than 2 horsepower and the size 2 band saw shall be equipped with either a minimum 3 horsepower motor or a minimum 5 horsepower motor, as specified. The motor shall be drip-proof, splash-proof, or totally enclosed type depending on the design of the unit, and shall not be affected by the cleaning procedure specified in 3.3. The motor shall be located in the base of the band saw. The band saw's control switch shall be located in a convenient location for the operator and shall not be affected by the cleaning procedure specified in 3.3."

3.4.2, line 2, after "shaft" add "or gear drive transmission,".

3.8: Delete in its entirety.

3.10.1: Delete and substitute:

"3.10.1 Data-name plates. The band saws shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for: (a) Methods of applying, (b) Identification tags, (c) Information not required and (d) Optional marking information shall not apply. The data plates shall be made of minimum 20 gauge (0.035 inch) corrosion-resisting metal and attached to the band saw by rivets, screws or welding in such a manner as to meet the applicable National Sanitation Foundation sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved or applied by photosensitive means:

National Stock Number
Procurement Instrument Identification Number
Specification Data
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (see 6.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the band saw.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

Add the following new paragraph:

"3.10.3 High voltage labels. When specified for shipboard use, a "Danger High Voltage" label shall be affixed to the equipments outer case assembly, on or adjacent to each service access cover and adjacent to one of the fasteners which secures the cover. A high voltage warning label shall also be placed near the high voltage components inside the equipment. The label shall include but is not limited to the following warnings:

a. A warning of high voltage.
b. Power supply must be disconnected before using.
c. Access covers must be in place during use.
d. Servicing should be done by authorized individuals."

3.11, line 2: After "stains" add "period" and delete the remainder of sentence, and add the following new sentence: "Finish for components not available in stainless steel or aluminum, e.g. painted surfaces, shall not peel, be blistered, dipped, chipped, or scratched; or have area of no film or finish, runs, sags, wrinkles, or foreign matter imbedded in the finish."

3.12, lines 6 to 8: Delete fifth sentence.

PAGE 8

Add the following new paragraph:

"4.1.2 Certification. A certificate of compliance will be acceptable as evidence that the requirements of 3.3 have been met."

Table I, under finish, "Defect" column, line 6: Delete "(painted surfaces)" and substitute "(painted surfaces of components not available in stainless steel or aluminum."

PAGE 10

Table I, delete all information pertaining to "Identification marking" and substitute the following:

"Data-name plate	Omitted or not as specified	Minor
	Information incomplete or not legible	Minor
	Not located so as to be readily visible to the operator	Minor"

PAGE 11

4.2.5.3: Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.

PAGE 12

4.3.1, (1), lines 3 and 4: Delete "prior to approval of the preproduction sample, if one is required by the acquisition document, or".

4.3.2, lines 1 and 2: Delete "Prior to approval of the preproduction sample, if one is required by the acquisition document, or".

4.3.2, lines 5, 6 and 9: Delete "UL Standard No. 73" and substitute "UL Standard No. 763".

PAGE 13

4.4.3: Delete in its entirety.

PAGE 15

6.2, b: Delete and substitute:

"b. Size and class of band saw required (see 1.2)."

6.2, d: Delete in its entirety.

6.2, add the following:

"g. Government approved manual number to be included on data-name plate (see 3.10.1)."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity
Navy - SH
(Project 7320-N895)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:23Z
Check the source to verify that this is the current version before use.