MIL-T-40625A
27 December 1965
SUPERSEDING
MIL-T-40625
20 June 1962

MILITARY SPECIFICATION

TUBING, BIAS SEWN (BURLAP OR OSNABURG), CLOTH

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers tubing, bias sewn, made of burlap or osnaburg having a flat width as specified (see 3.4.2).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

V-T-276 - Thread, Cotton.
CCC-C-429 - Cloth, Osnaburg, Cotton.
CCC-C-467 - Cloth, Burlap, Jute (or Kenaf).

MILITARY

MIL-B-3149 - Baling of Clothing and Equipage.

STANDARDS

FEDERAL

Fed. Std. No. 751 - Stitches, Seams, and Stitchings.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

FSC 8135

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:26Z
Check the source to verify that this is the current version before use.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Preproduction sample approval.- When required (see 6.2), before production is commenced, the supplier shall submit to the contracting officer for approval a one-yard sample of the tubing he proposes to furnish.

3.2 Materials.- Materials used in the construction of bias sewn tubing shall comply with 3.2.1 or 3.2.2 and 3.2.3.

3.2.1 Cloth, burlap, jute (or kenaf).- The burlap cloth shall conform to the requirements of CCC-C-467. Class shall be as specified (see 6.2).

3.2.2 Cloth, osnaburg, cotton.- The osnaburg cloth shall conform to the requirements of class 2 of CCC-C-429.

3.2.3 Thread.- The thread for seaming the tubing shall be cotton thread conforming to type IA1 of V-T-276. Needle thread shall be ticket No. 12, 4 ply, and looper thread ticket No. 16, 4 ply.

3.3 Construction of bias-sewn tubing.- The seams shall be type SSa-1 or LSa-1 with stitch type 401 in accordance with Fed. Std. No. 751. Stitching shall be three to six stitches inclusive per inch. The sewing line shall be not less than 3/8 inch nor more than 3/4 inch from the edge of the cloth. The degree of bias of the bias-sewn tubing shall be not less than 40° or more than 50° and the angle used within the range shall remain constant throughout the sewing operation.

3.4 Length and width of tubing.-

3.4.1 Length.- Tubing shall be furnished in one continuous length, not exceeding 200 pounds gross weight per roll (see 5.1.1). Alternatively, two or more lengths of tubing may be placed on one roll, provided that each piece be not less than 40 yards in length and that the total gross weight of the pieces shall not exceed 200 pounds.

3.4.2 Width.- Tubing shall be furnished in the finished flat width specified in the contract or order (see 6.2) with a tolerance in width variation of plus or minus 1/2 inch.

3.5 Identification.- Prior to wrapping, each roll shall have a ticket (identification tag) attached to the outer end of the rolled tubing with not finer than 5 ply cotton string doubled to not less than 8 inches long. The ticket shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:26Z
Check the source to verify that this is the current version before use.

be made of not less than 15-point paper stock and the finished surface shall not be calendered or pigmented to the degree that printed, stamped or typed markings would be obliterated. The ticket shall have a reinforced eyelet for attaching the tying cord. The ticket shall be legibly printed, stamped or typed, using water insoluble ink or indelible ribbon with the following information:

Nomenclature
Stock Number
Nominal Roll Length
Width of Tubing
Net Weight of Roll
Inspector

Handwritten entries shall be prohibited. In addition, the ticket shall have sufficient blank space for the inspector's stamp.

3.6 Workmanship.- The finished tubing shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Preproduction sample inspection.- When required, the preproduction sample submitted in accordance with 3.1 shall be inspected for the defects in table I.

4.3 Sampling for inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated herein.

4.3.1 Component and material inspection.- In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.4 Inspection of the end item.-

4.4.1 Examination of the end item.- Examination of the end item shall be in accordance with the classification of defects, inspection levels, and acceptable quality levels set forth below.

Source: https://assist.dla.mil -- Downloaded: 202640-21T19:26Z
Check the source to verify that this is the current version before use.

4.4.1.1 Examination of the end item for defects in construction, size and identification.- The sample unit for this examination shall be one roll of tubing.

TABLE I.- Construction, size and identification of tubing

Characteristic	Defects	Category Major	Category Minor
Construction			
Stitches	More than six or less than three per inch.	101	
	Less than 3/8 inch or more than 3/4 inch from edge of cloth.	102	
Bias	Less than 40° or more than 50° on the angle.	103	
Tubing			
Length	One continuous length exceeding 200 pounds.	104	
	Less than 40 yards long per piece when two or more lengths per roll.	105	
	Any roll exceeding 200 pounds.	106	
Width	Width tolerance greater than ± 1/2 inch.	107	
Identification			
Ticket	Not attached as specified.		201
	Material differs from that specified.		202
	Too small to allow for inspection stamp.	108	
	Reinforced eyelet missing.		203
Marking of ticket	Not legible, obliterated.	109	
	Water soluble ink used.	110	
	Information not in sequence specified.		204
	Handwritten.	111	

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:26Z
Check the source to verify that this is the currentversion before use.

4.4.1.2 Examination of preparation for delivery.- An examination shall be made to determine that packaging, packing and marking comply with the requirements of Section 5 of this specification. The sample unit shall be one roll of tubing, fully prepared for shipment.

TABLE II.- Packaging, packing and marking

Characteristic	Defects	Category Major	Category Minor
Packaging	Gross weight of roll exceeds 200 pounds.	101	
	Ends of tube extend more than 1 inch beyond rolled tubing.		201
Packing	Paper wrap missing.	102	
	Less than two layers of paper.		202
	Ends not covered with paper.	103	
	Outer cover differs from that specified.	104	
Marking	Omitted, incomplete, incorrect, illegible, of improper size, location, sequence or method of application.	105	

4.4.1.3 Inspection levels and acceptable quality levels (AQLs) for examination.- The inspection levels for determining the sample size and the acceptable quality levels (AQLs) expressed in defects per 100 units (DHU) shall be as follows:

Examination	Inspection level	AQLs Major	AQLs Total
Table I	S-3	1.5	6.5
Table II	S-4	2.5	6.5

4.5 Testing of components.- Testing of components shall be in accordance with the requirements of CCC-C-467 for Cloth, Burlap, Jute (or Kenaf); CCC-C-429 for Cloth, Osnaburg, Cotton; and V-T-276 for Thread, Cotton.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:26Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging.- Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.- The tubing shall be wound on a paperboard tube with the ends of the tube flush with or extending not more than 1 inch beyond each side of the maximum width of the rolled tubing. Gross weight of each roll shall not exceed 200 pounds.

5.1.2 Level C.- The tubing shall be packaged to afford adequate protection against deterioration and damage during shipment from the supply source to the first receiving activity. Each roll shall not exceed 200 pounds in weight. The supplier may use his standard practice when it meets these requirements.

5.2 Packing.- Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A.- Each roll of tubing, packaged as specified in 5.1, shall be wrapped with waterproof paper of any type specified in MIL-B-3149. Paper wrapping shall encircle the roll twice and fold over and cover the ends. Each roll shall then be covered with the same material as the tubing, using methods and closure to conform to any method described in MIL-B-3149. Compression, baling boards, and strapping shall not be used.

5.2.2 Level B.- Each roll of tubing, packaged as specified in 5.1, shall be covered with the same material as the tubing, using methods and closure to conform to any method described in MIL-B-3149. Compression, baling boards, and strapping shall not be used.

5.2.3 Level C.- The tubing, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Shipments shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking.- Rolls of tubing shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- The bias-sewn tubing is used for baling of clothing and textiles and as a cloth covering for bundles.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) When preproduction sample inspection is required (see 3.1).
(c) Materials to be used in the construction of bias-sewn tubing (see 3.2).
(d) Class required if burlap cloth is specified (see 3.2.1).

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:26Z
Check the source to verify that this is the current version before use.

(e) Finished flat width (see 3.4.2).
(f) Applicable levels of packaging and packing required (see 5.1 and 5.2).

6.3 Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SA
Air Force - 69

Preparing Activity:

Army - GL

Project No. 8135-0170

Review activities:

Army - GL
Navy - SA
Air Force - 69

User activity:

Army - SM

Review and User information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current Federal Supply Classification Listing of DOD Documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:26Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE
MIL-T-40625A - Tubing, Bias Sewn (Burlap or Osnaburg), Cloth

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:26Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRXNM-TD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314

U.S.MAIL

Commander
US Army Natick Research and Development Command
ATTN: DRXNM-TD
Natick, MA 01760

NATICK OP 1 JUL 77
FOLD

☆ U.S.GOVERNMENT PRINTING OFFICE: 1980—603-121/3639 2-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:26Z
Check the source to verify that this is the current version before use.