INCH-POUND

MIL-T-40627B
8 June 1992
SUPERSEDING
MIL-T-40627A
29 November 1983

MILITARY SPECIFICATION

TIEDOWN ASSEMBLY, CHAIN TYPE, FOR DRUM(S), FABRIC, COLLAPSIBLE, LIQUID FUEL, CYLINDRICAL, 500-GALLON CAPACITY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers tiedown assemblies for use with 500 gallon capacity cylindrical liquid fuel collapsible fabric drums.

2 APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

PPP-B-601 - Boxes, Wood, CLeated Plywood.
PPP-B-621 - Box, Wood, Nailed and Lock-Corner.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8110
DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:27Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Government drawing. The following Government drawing forms a part of this document to the extent specified herein. Unless otherwise specified, the issue is that cited in the solicitation.

DRAWINGS

ME

TA13226E2255 - Tiedown Assembly, Chain Type for Drum, Fabric Collapsible, Liquid Fuel, Cylindrical, 500-Gallon Capacity.

(Copies of drawings required by contractors in connection with specific acquisition functions should be obtained from the US Army Belvoir Research, Development, and Engineering Center, ATTN STRBE-FSH, Fort Belvoir, VA 22060-5606.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3953 - Strapping, Flat Steel and Seals.
D 4675 - Selection and Use of Flat Strapping Materials.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia PA 19103.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, (except for related associated detail specifications, specification sheets or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:27Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Description. The tiedown assembly shall be as shown on top assembly TA13226E2255 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviations from the prescribed dimensions or tolerances is permissible without prior written approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operating of the tiedown assembly. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or designated representative.

3.2 Material. Material shall be as specified herein and on the applicable drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.2.1 Material deterioration prevention and control. The tiedown assembly shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operation and storage environments to which the tiedown assembly may be exposed.

3.2.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

3.2.3 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the tiedown assembly may be newly fabricated from recovered materials to the maximum extent practicable, provided the tiedown assembly produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the tiedown assembly.

3.3 Welding. The surface of parts to be welded shall be free from oxide, scale, paint, grease, and other foreign matter. Welds shall be continuous, sound, smooth, and free from porosity, cracks, incomplete fusion, and deformation of material. All scale or flux deposits (when flux is used) shall be removed from the finished welds.

3.4 Workmanship. The finished tiedown assembly shall be clean, well made, and free from all burrs, slivers, sharp injurious projections, and any defects which may affect appearance, serviceability, or safety.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:27Z
Check the source to verify that this is the current version before use.

inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined and tested in accordance with referenced specifications, standards, and drawings, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Quality conformance inspection (see 4.3).
b. Inspection of packaging (see 4 4).

4.3 Quality conformance inspection.

4.3.1 Lot. Each lot shall consist of all units of tiedown assemblies manufactured under the same conditions and at the same time, and offered to the Government at the same time.

4.3.2 Sampling. Sample size shall be determined by using MIL-STD-105, table I and IIa. A lot shall be accepted when zero defects are found and rejected when one or more defects are found.

4.3.3 Examination. Samples selected in accordance with 4.3.2 shall be examined for the following defects:

101. Tiedown assembly not in accordance with drawings (see 3.1).
102. Missing, malformed or otherwise impaired parts, components or assemblies (see 3.1).
103. Materials not as specified (see 3.2).
104. Materials not resistant to corrosion or deterioration (see 3.2.1).
105. Contractor does not have documentation available for identification of materials, material finishes, or treatment (see 3.2.2).
106 Used, rebuilt or remanufactured components, pieces, or parts incorporated in the tiedown assembly (see 3.2.3).
107. Welding not as specified (see 3.3).
108. Workmanship not as specified (see 3.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:27Z
Check the source to verify that this is the current version before use.

4.4 Inspection of packaging.

4.4.1 Quality conformance inspection of packaging.

4.4.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.4.1.2 Sampling. Sample size shall be determined by using MIL-STD-105, table I and IIa. A lot shall be accepted when zero defects are found and rejected when one or more defects are found.

4.4.1.3 Examination. Samples selected in accordance with 4.4.1.2 shall be examined for the following defects.

109.	Boxes not as specified for level A or C (see 5.1).
110.	Strapping not as specified for level A or C (see 5.1).
111.	Packing not as specified for level A or C (see 5.1).
112.	Marking missing, illegible, incorrect, or incomplete for level A or C (see 5.2).

5. PACKAGING

5.1 Packing. Packing shall be level A or C as specified (see 6.2).

5.1.1 Level A. Components comprising one complete tiedown assembly shall be compactly packed in a close-fitting box conforming to PPP-B-601, overseas type, style optional or PPP-B-621, class 2, style optional. Care shall be exercised to insure that, as far as practicable, portions of the tiedown covered by chain covers shall be positioned near the top of the shipping container to minimize the weight bearing on the chain covers. Box closure and strapping shall be in accordance with the appendix to the applicable box specification. Strapping shall conform to ASTM D 3953 type 1 or 2, zinc-coated, as applicable, and ASTM D 4675.

5.1.2 Level C. Packing shall be as specified in 5.1.1 except boxes shall be domestic type or class as applicable and strapping may be zinc coated

5.2 Marking (see 6.3). In addition to any special marking specified in the contract or purchase order (see 6.2), marking shall be in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The tiedown assembly described herein is intended for holding one, two, or three drum(s), fabric, collapsible, liquid fuel, cylindrical, MIL-D-23119 (filled to rated capacity only) in position while being transported The tiedown assemblies are designed for use on M44 series 2-1/2-ton and M939 series 5-ton cargo trucks.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:27Z
Check the source to verify that this is the current version before use.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of the specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. Level of packing required (see 5.1).
d. Any special marking required (see 5.2).

6.3 Level of preservation. The tiedown assembly requires no preservation. For purposes of preservation/packing level marking the preservation shall be considered level A.

6.4 Subject term (key word) listing.

Blivet
Drum
Tiedown

6.5 Changes from previous issue Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - ME
Air Force - 69

Review activities:
Army - MT
DLA - GS

User activity:
Navy - MC

Preparing activity:
Army - ME

Project 8110-0291

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1 The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2 The submitter of this form must complete blocks 4, 5, 6, and 7.
3 The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-T-40627B	2. DOCUMENT DATE (YYMMDD) 920608

3. DOCUMENT TITLE
Tiedown Assembly, Chain Type, for Drum(s), Fabric, Collapsible, Liquid Fuel, Cylindrical, 500-Gallon Capacity

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5 REASON FOR RECOMMENDATION

6. SUBMITTER

a NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (if applicable) (2) AUTOVON	7 DATE SUBMITTED

8 PREPARING ACTIVITY

a NAME Betty Taylor	b. TELEPHONE (Include Area Code) (1) Commercial (703) 704-3466	(2) AUTOVON 654-3466
c ADDRESS (Include Zip Code) US Army Belvoir RDE Center ATTN: STRBE-TSE Fort Belvoir, VA 22060-5606	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-346 Telephone (703) 756-2340	AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:27Z
Check the source to verify that this is the current version before use.