MILITARY SPECIFICATION SHEET

TRUCK, LIFT , FORK, REACHING AND TIERING, CONTINUOUS DUTY, NARROW AISLE 4,000 POUND CAPACITY, 50 INCH LIFT, ELECTRIC SHIPBOARD, TYPE 'EE"

The complete requirements for procuring this truck described herein shall consist of this document and Specification MIL-40629B, Truck, Fork? Reaching and Tierirg, Continuous Duty, Narrow Aisle, Electric, Non Pallet Straddling, Shipboard.

REQUIREMENTS

1.	Capacity	4000 Lbs. at 24 inch load center
2.	Type	EE
3.	Collapsed mast height	68 inches (maximum)
4	Fork lift height	50 inchs (minimum)
5	Overall height at 50 inches lift height	78 inches (maximum)
6.	Free lift height	20 inches (minimum)
7.	Fork mounting	MS 16955
8.	Fork size	2-1/8 inches thick (maximum) 4-1/8 inches wide (Maximum) 40 inches long + 0 inches -1/2 inches
9*	Fork spacing (measured between outer edges of forks)	28 inches spread outside (minimum) 26-1/2 inches together (maximum)
10 l	Type of steering	Power
11.	Tangential steering force at rim of hand wheel	5 pounds (maximum)
12.	Lifting speed empty	35 feet per minute minimum
13.	Lifting speed with rated load	50 feet per minute minimum
14 l	lowering speed unloaded	50 feet per minute minimum
15.	High drive speed (forward and reverse)	4 to 4-1/2 miles per hour
16.	Slope ascension	18 percent slope (10.2 degrees)
17.	Longitudinal stability stacking	4 percent slope (2.3 degrees)
	traveling	18 percent slope (10.2 degrees)
18.	Lateral stability - stacking	6 percent slope (3.4 degrees)
	traveling	27 percent slope (15.1 degrees)
19.	Rearward stability - stacking	18 percent slope (10.2 degrees)
	traveling	30 percent slope (16.7 degrees)
20	Static stability	46.5 percent slope (25 degrees)

FSC 3930

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:27Z
Check the source to verify that this is the current version before use.

21. Service brakes	2 Wheels
22 l Parking brakes	Hand brake required
23. Overall truck width	42-1/2 inches (maximum)
24. Fork tilt: forward	2 degrees
rearward	4 degrees
25. Battery	24 V.D.C., 12 cell, 13 plates, 870 A/H at 6 hour rate, Type WE", shock hardened
26. Truck weight (including battery)	7500 pounds (maximum)

Custodian:

Navy - SA

Review Activities:

Navy - SA,MC

User Activities:

Navy - SA,SH,MC

Preparing Activity:

Navy - SA

Project No. 3930-0538

Source: https://assist.dla.mil -- Downloaded: 2026l0-21T19:27Z
Check the source to verify that this is the current version before use.