MILITARY SPECIFICATION SHEET

# TRUCK , LIFT, FORK, REACHING AND TIERING, CONTINUOUS DUTY, NARROW AISLE 4,000 POOUND CAPACITY, 68 INCH lIFT, ELECTRIC SHIPBOARD, TYPE 'EE"

The complete requirements for procuring this truck described herein shall consist of this document and Specification MIL-T-40629B Truck, Fork, Reaching and Tiering, Continuous Duty, Narrow Aisle, Electric, Non Pallet Straddling, Shipboard.

## REQUIREMENTS

| | | |
|---|---|---|
| 1. | Capacity | 4000 Lbs. at 24 inch load center |
| 2. | Type | EE |
| 3. | Collapsed mast height | 68 inchs (maximum) |
| 4. | Fork lift height | 68 inches (minimum)<br>96 inches (maximum) |
| 5. | Overall height at 68 inches lift height | |
| 6. | Free lift height | 20 inches (minimum) |
| 7. | Fork mounting | MS 16955 |
| 8. | Fork size | 2-1/8 inches thick (maximum)<br>4-1/8 inches wide (Maximum)<br>40 inches long + O inches -1/2 inches |
| 9. | Fork spacing (measured between outer edges of forks) | 28 inches spread outside (minimum}<br>26-1/2 inches together (maximum) |
| 10. | Type of steering | Power |
| 11. | Tangential steering force at rim of hand wheel | 5 pounds (maximum) |
| 12. | Lifting speed empty | 35 feet per minute minimum |
| 13. | Lifting speed with rated load | 50 feet per minute minimum |
| 14 l | Lowering speed unloaded | 50 feet per minute minimum |
| 15. | High drive speed (forward and reverse) | 4 to 4-1/2 miles per hour |
| 16. | Slope ascension | 18 percent slope (10.2 degrees) |
| 17. | Longitudinal stability - stacking | 4 percent slope (2.3 degree) |
| | traveling | 18 Percent slope (10. 2 degrees) |
| 18. | Lateral stability - Stacking | 6 percent slope (3.4 degrees) |
| | traveling | 27 percent slope (15.1 degrees) |
| 19. | Rearward stability - stacking | 18 percent slope (10.2 degrees) . |
| | traveling | 30 percent slope (16.7 degrees) |
| 20 | Static stability | 46.5 percent slope (25 degrees) |

FSC 3930

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:27Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| 21. | Service brakes | 2 wheels |
| 22 l | Parking brakes | Hand brake required |
| 23. | Overall truck width | 42-1/2 inches (maximum) |
| 24. | Fork tilt: forward | 2 degrees |
| | rearward | 4 degrees |
| 25 | Battery | 24 V. D. C., 12 cell, 13 plates, 870 A/H at 6 hour rate type "EE", shock hardened |
| 26 | Truck weight (including battery) | 7500 pounds (maximum) |

Custodian:

Navy - SA

Review Activities:

Navy - SA,MC

User Activities:

Navy - SA,SH,MC

Preparing Activity:

Navy - SA

Project No. 3930-0538



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:27Z
Check the source to verify that this is the current version before use.