MIL-T-0040632A(SA)
INT. AMENDMENT-2(SA)
24 March 1969

SUPERSEDING
INT. AMENDMENT-1(SA)
24 July 1967

MILITARY SPECIFICATION

TRUCK, LIFT, FORK, DIESEL, PNEUMATIC-TIRED, GENERAL PURPOSE, 6,000-POUND CAPACITY AT 24-INCH LOAD CENTER

This Interim Amendment is issued for use by the Defense General Supply Center with Military Specification MIL-T-0040632A(SA) dated 9 June 1967.

Page 3

2.1, delete "MIL-I-16910 .....and Limits" without substitution. add in proper sequence,

"MIL-F-3541 - Fittings, Lubrication"
"MIL-T-43169 - Tool Kit, Master Mechanics"
"MIL-STD-461 - Electromagnetic Interference Characteristics Requirements For Equpment"

Page 4

2.1, delete "MS-15001..... Steel, Type III" without substitution.

Page 6

3.1.1, delete the first sentence, "Components.....mandatory.", without substitution.

3.2, line 10, between "requirements." and "Any", insert "When a contract includes both Government furnished engines and contractor furnished engines, the preproduction model(s) and initial production model(s) shall be tested with contractor furnished engines."

FSC 3930

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:28Z
Check the source to verify that this is the current version before use.

Page 7

3.2, line 6, delete "Subsequent" and substitute "Prior".
line 8, after "Government representative", insert "to preclude unauthorized adjustments"
line 15, at end of paragraph, add the following: "The approved preproduction model may be presented for acceptance as the last unit for delivery under the contract after being rehabilitated to reflect a new appearance. This shall include the furnishing of new tires."

3.4.1.2, delete and substitute:

"3.4.1.2 Structural steel. Structural steel shall as a minimum conform to QQ-7-741 unless otherwise specified on the applicable drawings."

Page 8

3.6.1, line 4, delete "(see 4.6.11 and 4.6.12)." without substitution.

Page 9

3.7.1, line 2, delete "MS 15001, MS 15002, and MS 15003" and substitute "MIL-F-3541".

Page 10

3.9.2, lines 3, 4, and 14, delete "waterproof" and substitute "water resistant" in four places.
line 14, delete "or water leaking into".
line 17, between "truck part" and "when tested", insert "which affect proper operation of the truck and its ability to meet all of the requirements specified herein."

Page 11

3.9.3(c), delete without substitution.

3.9.5, lines 2 and 3, delete "the 100 hour load placement test specified in 4.6.22.1(a) and the 300 hour" and substitute "the 2600 cycle".

3.9.7, line 2, delete "19.0" and substitute "19.5".

Page 15

3.10.5.3, line 14, delete "26" and substitute "22".

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:28Z
Check the source to verify that this is the current version before use.

Page 17

3.10.7.1.2, delete without substitution.

Page 18

3.10.8, line 4, between "above the ground" and "and retract fork carriage", insert "and lift".
line 23, delete "for a period of 5 minutes" without substitution.

Page 20

3.10.9, line 1, delete "4" and substitute "2-1/2".
line 3, delete "6BC" and substitute "8B:C".

Add new paragraph

"3.10.12 An adjustable, weather-resistant safety seat belt with a non-corrosive metal-to-metal, quick-release buckle conforming to SAE J4C, type 1 shall be provided. The belt shall be anchored to the seat in accordance with SAE J787a."

3.11, line 3, delete "the above deck and shore requirements of MIL-I-16910" and substitute "Table I, class III C of MIL-STD-461 except that the 20 decibel relaxation of RE05 is not applicable; however the horn when operated may exceed the above limits."

3.13, line 4, delete "18,500" and substitute "18,600".

Page 22

3.17, 1st sentence, delete "and maintenance tools". Add new 2nd and 3rd sentences as follows: "All special hand tools required for maintenance of the truck shall be provided and shipped with each truck procured. Special hand tools are those not listed in MIL-T-43169."

Page 23

3.20, line 4, between "connections" and "malfunctions" insert a comma.

3.20.2, lines 1 and 2, delete "punched or drilled" and substitute "formed".
line 6, delete "torqued" and substitute "tightened".

Page 24

3.20.5, delete and substitute:

"3.20.5 Machine work. All parts shall be manufactured to insure accuracy of assembly through the correct use of jigs, fixtures or tape controlled machines or any desired combination of these. Like parts shall be interchangeable."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:28Z
Check the source to verify that this is the current version before use.

4.1, 2nd sentence, delete and substitute: "Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government."

Page 29

Table V. Delete the 10th and 11th test on the page, i.e., Low temperature and High temperature tests.

Page 30

Table V. Delete the 6th test on the page, i.e., Endurance test (Load Placement).

Page 35

4.6.5, line 3, delete "a draft rate exceeding 1 inch per hour" without substitution.

4.6.6, line 2, delete "diameter" and substitute "radius".
line 4, delete "3.5" and substitute "5".
lines 4 and 5, delete "During operation and after" and substitute "After".
line 7, after "deformation", add the following: "At this time the Government reserves the right to conduct brief operational tests to assure acceptance."

Pages 36 and 37

4.6.11, delete without substitution.

Page 37

4.6.12, delete without substitution.

Page 38

4.6.14.2, line 2, between "positions," and "measure radius", insert "operate truck in reverse, then in forward, then".

4.6.15.1, delete without substitution.

4.6.15.4, delete without substitution.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:28Z
Check the source to verify that this is the current version before use.

Page 39

4.6.16.3(c), lines 7, 8, and 9, delete "retain load for ..... compliance with 3.10.8" and substitute "examine for appreciable wear. Appreciable wear is defined as inability to retain load for a five minute period without exceeding the downward drift, longitudinal tilt drift and rotational function drift dimensions specified in 3.10.8."

Page 40

4.6.20, delete "MIL-I-16910" and substitute "MIL-STD-461".

4.6.22.1, line 1, delete ", and load placement".
line 4, delete "methods Nos. 8 and 9" and substitute "method No. 8."
line 5, delete "in test methods 8 and 9" and substitute "above".
line 6, between "servicing," and "and", insert "inspection,".

4.6.22.1(a), delete without substitution.

4.6.22.1(b), delete "300 hours" and substitute "2600 cycles".

Page 41

4.6.23, line 25, between "examination" and "shall be made" insert "including magnetic particle inspection of class 2 and class 3 welds as specified in MIL-STD-1261".

Page 43

5.1.1.7.1, delete and substitute:

"5.1.1.7.1 Cooling system. Prior to start of engine preservation, cooline systems shall be filled to capacity with a clean solution consisting of equal parts by volume of antifreeze (ethylene glycol) conforming to type 1 of O-A-548, and water. Engine shall be operated to assure coverage of all interior parts and surfaces. When cooling system is thermostatically controlled, engine shall be operated until a temperature has been reached that causes thermostat to open, assuring complete mixing and even distribution of the antifreeze solution. A warning tag, conforming to UU-T-81, type A, bearing the information:

COOLING SYSTEM FILLED WITH WATER AND ANTIFREEZE (ETHYLENE GLYCOL)

IN EQUAL PARTS BY VOLUME--DO NOT DRAIN

shall be securely attached to radiator filler neck. The tag and the

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:28Z
Check the source to verify that this is the current version before use.

printing thereon shall be waterproofed in accordance with MIL-STD-129.

Page 45

5.1.1.7.6, line 4, after "seat", insert "or in the box specified in 5.1.1.23. The spark arresting device shall also be stored in the box."

5.1.1.7.8, end of paragraph, add the following: "When an oil bath air cleaner is furnished, the tag shall also contain a warning to fill to the proper level with oil."

Page 46

5.1.1.7.9, line 1 on page, after "compartment", insert "or to the box specified in 5.1.1.23 in such a manner that the electrolyte bottle shall be in an upright position and all precautionary markings visible." At end of paragraph, add "The wood box shall be marked as specified in 5.3.1."

Add the following new paragraph in proper sequence:

"5.1.1.12.1 Interior surfaces of the brake drum. Interior surfaces of the brake drum, including brake cams, anchor pins, adjusting screw and braking surfaces, shall be coated with a thin film of primer conforming to TT-P-664. Care shall be exercised to prevent primer from contacting brake lining and rubber impregnated parts. A warning tag, bearing the information: BRAKE DRUMS PRESERVED; DO NOT APPLY BRAKES WHEN VEHICLE IS BEING MOVED UNTIL ISSUED TO USER. MOVE VEHICLE WITH RIGID TOW BAR. ADJUST BRAKES BEFORE PLACING IN OPERATION, shall be securely attached in a conspicuous location within the operator's compartment."

Page 47

5.1.1.23, line 1, after "Intermediate packaging" add "(on vehicle equipment package)".

line 2, delete "shall be intermediate" and substitute "and the muffler and spark arresting device, when applicable, shall be"

at end of paragraph add "All items shall be adequately blocked, braced and cushioned within the package to prevent damage to these items."

Page 48

Add the following new paragraph in proper sequence:

"5.1.2.6 Brakes. Use method as specified in 5.1.1.12.1."

5.2.1, line 3, delete "secured in" and substitute "secured to".

Page 49

5.3.1 Add new paragraph sequence as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:28Z
Check the source to verify that this is the current version before use.

"5.3.1 Special marking. The electrolyte pack shall be marked in accordance with MIL-S-207."

Page 55

Test Method 1, para 2.d., delete without substitution.

Page 58, 59, 60 and 61

Test Methods 4 and 5, delete without substitution.

Page 64

Test Method 8, para 2, delete in its entirety and substitute the following: "Drive the truck with rated payload in carry position, for 2600 cycles over the test course. A cycle is one complete lap around the course depicted in Figure A-1. Speed over the course for each cycle shall average not less than 5 mph. Negotiate the course 50 percent of the time in a clockwise direction and 50 percent of the time in a counterclockwise direction. Negotiate the course at least 25 times per hour. All turns shall be in 4-wheel steer and all travel over crossties and potholes areas shall be in 2-wheel steer. After each 8 hours, operate the side shift at full speed and full load for 10 full-stroke cycles. During the last 600 cycles, travel over potholes and crossties shall be in a 4-wheel drive and travel on flat stabilized surface shall be in 2-wheel drive."

Page 65

Test Method 9, para 1, at the end of the sentence, delete the period and add", course A".

para 3c, 8th line, delete the following: "for a total of 35 hours".

para 3c, 10th line, delete the following: "each hour" and substitute "in the one hour test".

paragraphs 3d and 3e, delete in their entirety without substitution.

Page 68

Figure A-1, note 2, at the end of the note, add: "Percentages are minimum."

Section B-B, add "minimum" after angle measurement of "24.2°".

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:28Z
Check the source to verify that this is the current version before use.

Amendment-2
A 5592

Custodians:

Navy - SA
Air Force - 84

Review Activities:

Navy - MC, OS, YD
Air Force - 85

Preparing Activity:

Navy - SA

Project No. 3930-N280

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:28Z
Check the source to verify that this is the current version before use.