MILITARY SPECIFICATION

WRAPPING MACHINES, MEAT AND PRODUCE, AUTOMATIC, SHRINK FILM

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 Scope. This specification covers electrically operated automatic machines for plastic film wrapping of meat and produce.

* 1.2 Classification. The wrapping machines shall be of the following type (see 6.2 and 6.5).

Type II For wrapping plastic film

* 1.2.1 Class and speeds. Type II wrapping machines shall be of the following class and speeds (see 6.2 and 6.5).

Class A - Automatic.

High speed - With a minimum speed of 30 packages per minute for wrapping meat or produce.

Medium speed - With a minimum speed of 22 packages per minute for wrapping meat or produce.

2. APPLICABLE DOCUMENTS

* 2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

L-P-370 - Plastic Film, Sheet and Strip (Polyvinyl Chloride, Copolymer or Vinylidene Chloride and Vinyl Chloride, or Polyethylene)

FSC 3540

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

L-P-378 - Plastic Sheet and Strip, Thin Gauge, Polyolefin
CC-M-1807 - Motor, Alternating Current, Fractional and Integral Horsepower (500 Horsepower and Smaller)
MMM-A-260 - Adhesive, Water-Resistant (For Sealing Waterproofed Paper)
PPP-B-636 - Boxes, Shipping, Fiberboard
PPP-B-1055 - Barrier Material, Waterproofed, Flexible
PPP-C-650 - Crates, Wood, Open and Covered
PPP-T-45 - Tape Gummed, Paper Reinforced and Plain, for Sealing and Securing

MILITARY

MIL-C-104 - Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted
MIL-P-116 - Preservation-Packaging, Methods of
MIL-B-121 - Barrier Material, Greaseproofed, Waterproofed, Flexible
MIL-S-43147 - Scale Systems, Prepackaged Food

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-461 - Electromagnetic Interference Characteristics Requirement for Equipment
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of
MIL-STD-1474 - Noise Limits for Army Material

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

UNDERWRITERS' LABORATORIES, INC., (UL)

Electrical Construction Materials List

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 207 East Ohio Street, Chicago, IL, 60611; 1285 Walt Whitman Road, Melville, LI, NY 11746 or 1655 Scott Boulevard, Santa Clara, CA 95050.)

NATIONAL ELECTRICAL MANUFACTURER'S ASSOCIATION (NEMA)

Standard ICS - Industrial Controls and Systems

(Application for copies should be addressed to the National Electrical Manufacturer's Association, 155 East 44th Street, New York, NY 10017.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA No. 70 - National Electrical Code

(Application for copies should be addressed to the National Fire Protection Association, 60 Batterymarch Street, Boston, MA 02110.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies shall be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, NW, Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies shall be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

* 3.1 First article. When specified (see 6.2), the contractor shall furnish a sample for first article inspection and approval (see 4.2 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

* 3.2 Standard product. The automatic wrapping machines shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product with any added features to comply with the requirements of this specification. Modification to add features shall not incorporate different parts unless such parts are used on other commercial models. Standard or modified commercial products furnished in accordance with this specification shall be identifiable in all regular manufacturer's or commercial service organizations servicing the brand involved. Service organizations shall be capable of providing complete parts and repair services on models furnished to the Government consistent with their normal commercial practices.

* 3.3 Code and standards.

3.3.1 NFPA. The wrapping machines shall be wired to conform to NFPA No. 70.

3.3.2 UL. The wire, fittings and conduit shall conform to applicable Underwriters' Laboratory (UL), standards.

3.3.3 NEMA. Motor controllers, switches, relays and time delays shall conform to performance requirements of NEMA Standards No. ICS.

* 3.3.4 Certification. Prior to approval of the first article or if none is submitted, prior to approval of the first shipment, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the wrapping machines he proposes to furnish meet the requirements specified in 3.3.1, 3.3.2 and 3.3.3.

* 3.3.4.1 NFPA. Acceptable evidence of meeting requirements of 3.3.1 shall be the manufacturer's certified statement that the wrapping machine is wired in accordance with NFPA No. 70.

* 3.3.4.2 UL. Acceptable evidence of meeting requirements of 3.3.2 shall be the UL label, a listing in the UL "Electrical Construction Material List" or a certification from an independent testing laboratory acceptable to the contracting officer or his authorized representative that the wrapping machines, wiring, fittings and conduit conform to the applicable UL standards.

* 3.3.4.3 NEMA. Acceptable evidence of meeting the requirements of 3.3.3 shall be the manufacturer's certified statement that the motor controllers, switches, relays and time delays, conform to NEMA Standard No. ICS. A tag or label attached to these items stating these components conform to this standard is acceptable evidence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

3.4 Materials. Materials not definitely specified shall be of the quality normally used by the manufacturer for wrapping machines provided that the complete item complies with all provisions of this specification.

* 3.5 Design and construction. The wrapping machines shall be capable of wrapping and heat sealing packages with an overwrap of plastic film as specified herein. The machines shall have a rigid frame, electric motor drives, package conveyor and shall wrap and heat seal packages automatically at speeds as specified (see 1.2.1). The wrapping machines shall be capable of accommodating the attachment of a type I, style A, automatic scale system conforming to MIL-S-43147 and shall be capable of weighing, computing, conveying, printing, identifying, dispensing, and affixing labels to packaged items. The machines shall have either adjustable legs or casters at the option of the manufacturer. When casters are used, means to lock or immobilize the casters shall be provided. All parts of the machines likely to come in contact with meat or produce being wrapped shall be corrosion-resisting steel or aluminum and readily accessible for cleaning. All adjustable and operational controls specified hereinafter shall be conveniently located for the operator.

* 3.5.1 Heat sealing units. The machines shall have heat sealing units with thermostatic control. The thermostats shall be capable of accomplishing temperature adjustment of the heating surfaces. The heat sealing units with the sealing surface at 475 F., plus or minus 5 F., shall have adequate capacity to achieve a 30 F. heat recovery at the sealing surface within 60 seconds in a refrigerated preparation room ambient of 45 F., plus or minus 10 F. when tested as specified in 4.4.1. Heat sealing surfaces shall have polytetrofluorethylene covers.

* 3.5.2 Motors. Motors and gear motors shall conform to CC-M-1807.

* 3.5.3 Electrical characteristics. Unless otherwise specified (see 6.2), wrapping machines shall operate from a 240-volt, 1-phase, 60 Hz power source.

3.5.4 Lubrication. Machines shall have lubrication means for all moving parts. Seals shall be provided to prevent leakage of lubricants. Lubricating fittings shall be readily accessible. At the time of delivery, the machine shall be completely lubricated with the manufacturer's standard lubricant.

3.5.4.1 Lubricating chart. Lubricating chart shall be furnished by the contractor and attached to each machine. The instructions on the chart shall indicate the grade of lubricant to be used and the parts to be serviced periodically.

* 3.5.5 Wrapping. The machine shall wrap and seal packages automatically, as specified herein, with an overwrap of plastic film conforming to class III of L-P-370. Unless otherwise specified (see 6.2), the machine shall have a heat shrink tunnel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

* 3.5.5.1 Heat shrink tunnel. The heat shrink tunnel shall have insulated corrosion-resisting steel or aluminum sheet metal walls with an inlet and outlet door. The doors shall be slitted, heat resistant, pliable material to retain heat and provide means for the passage of wrapped packages through the tunnel. Tunnel heat and temperature shall be controllable between 100 F. and 300 F. The tunnel shall be capable of shrinking the film overwrap of the package.

* 3.5.6 Function, class A. Wrapping machines, in addition to conforming to 3.5, shall automatically feed, measure, wrap, cut, fold, and seal the overwrap film on a package. At the option of the manufacturer, the film shall be fed by power means or drawn by the pack to be wrapped at the wrapping section of the machine. An adjustable tensional means shall be provided to control slack as the film is being fed. The film shall be dispensed from a roll mounted on an arbor or shaft with means for centering the roll. Adjustable frictional means shall be provided to prevent overrunning of the film roll. The machine shall have no less than 3 arbors or shafts to allow the mounting of 3 rolls of film of various widths at one time. The machine shall have infeed and outfeed conveyors with adjustable guides to accommodate packages of various widths. The wrapping speed of the machine may be variable or constant at the option of the manufacturer. When the machine has various speeds, means for changing and locking the setting shall be provided.

* 3.5.6.1 High speed machines. The high speed machines, in addition to conforming to 3.5.6, shall wrap and seal a package with bottom end folds. The machine shall be capable of wrapping packages of the following sizes:

a. Length - 5 inches minimum to 12-1/2 inches maximum.
b. Width - 3-1/2 inches minimum to 9-1/2 inches maximum.
c. Height - 3/8 inch minimum to 4-3/4 inches maximum.

* 3.5.6.2 Medium speed machines. The medium speed machines, in addition to conforming to 3.5.6, shall wrap and seal a package with bottom end folds. The machine shall be capable of wrapping packages of the following sizes:

a. Width - 3 inches, minimum to 9 inches maximum.
b. Length - 5 inches minimum to 12-1/2 inches maximum.
c. Height - 1/2 inch minimum to 5 inches maximum.

* 3.6 Performance. Wrapping machines, when tested as specified in 4.4.2, shall operate and wrap packages in a refrigerated preparation room at ambient temperature of 45° F. plus or minus 10 F. as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

a. Using pulp, styrofoam, and clear plastic trays, approximately 5 inches wide by 8 inches long by 1 inch high filled to approximately 4 inches high the machine shall wrap packages automatically at speeds indicated in table I, with no jamming.

b. The machines shall snuggly wrap the package overwrap with no tearing of the film.

c. The machines shall heat seal end folds on the package to produce a fusion of interfaces of the film.

d. The package overwrap shall be fed or dispensed smoothly with no tearing, wrinkling or snarling of the film.

3.6.1 Shrink tunnel. Wrapping machines with shrink tunnel shall operate and wrap packages as specified in 3.6 and heat shrink the film to produce a taut overwrap of the package when tested as specified in 4.4.3.

TABLE I. Performance speed

Type II machines	Packages per minute, minimum
Class A, high speed	30
Class A, medium speed	22

3.7 Electromagnetic compatibility. When specified (see 6.2), wrapping machines shall be equipped for electromagnetic compatibility in accordance with class IIB of MIL-STD-461 (see 4.4.4).

* 3.8 Marking for identification. Wrapping machines shall be marked for identification in accordance with the manufacturer's standard practice.

* 3.9 Finish. Wrapping machines shall be finished in accordance with the manufacturer's commercial practice. Painted surface coatings shall be smooth, adherent and free of blisters, runs, imbedded foreign matter, and areas of no coating.

* 3.10 Workmanship. Wrapping machines shall be clean, properly assembled, and in alignment. All exposed surfaces shall be free from burrs and sharp edges. Components shall not be loose, bowed, dented, or fractured. Surfaces shall have no evidence of rust or corrosion.

3.10.1 Rivets. Rivets shall be tight and heads completely formed and in full contact with the surface of the riveted member.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

3.10.2 Fasteners. Fasteners such as screws, nuts, and bolts shall be drawn tight. Fasteners subject to vibration shall be secured with antivibration means such as castellated nuts with cotter pin, lock washer or self-locking nuts.

3.10.3 Welding. Welding shall be continuous, smooth, adherent, free from pin holes, fractures, slag inclusion, and flux deposits.

3.10.4 Wiring. Wiring shall be securely ground. Insulation shall not be cut or abraded and, when subject to wear, the wire shall be inclosed in a conduit.

3.11 Warning label. Each machine shall be permanently and legibly marked with the following statement:

"TO BE USED ONLY WITH WRAPPING MATERIALS APPROVED FOR USE WITH FOOD AND FOOD PRODUCTS."

* 3.12 Noise limits. The machine shall meet the noise limits specified in MIL-STD-1474 and where practicable, shall not exceed 85 decibels A-weighted at the normal operator position.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is reponsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. When a first article is required, it shall be examined for defects in table II, dimensions specified, and tested in accordance with 4.4.1, 4.4.2, 4.4.3, 4.4.4, and 4.4.5, as applicable.

4.3 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

4.3.2 End item inspection. A lot shall consist of all wrapping machines of one type, class and speed offered for inspection at one time. The sample unit for this inspection shall be one completely fabricated wrapping machine.

4.3.2.1 Visual examination. Examination shall be made of the end item for the defects in table II. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects expressed in terms of defects per hundred units.

TABLE II. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Not finished in accordance with manufacturer's standard commercial practice		X
	Painted surface coating not smooth or adherent, not free of blisters, runs, imbedded foreign matter or areas of no coating		X
Construction and workmanship (general) (applicable to all components and assemblies)	Unit not clean		X
	Not perceptibly in alignment	X	
	Surface not free of burrs or sharp edges	X	
	Adjustable assembly that cannot be adjusted	X	
	Components loose, bowed, dented, or fractured	X	
Rivets	Fractures	X	
	Loose, head not fully formed or not in full contact with riveted surface		X
Fastener	Loose	X	
	Fractured or stripped	X	
	Cotter pins of castellated nuts, lock washers, or lock nuts missing		X
Welding	Not continuous, smooth, adherent, not free from pinholes, or fractures	X	
	Slag inclusion or flux deposits		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Electrical wiring	Wiring cut, abraded not properly joined, loose at terminals not securely grounded or not inclosed in specified conduit where required	X	
	Adequate slack not provided or required insulation stripped from wiring	X	
Lubrication (where applicable)	Not lubricated where required	X	
	Fitting not accessible for servicing		X
Lubrication chart	Lubrication chart missing, incomplete not legible	X	
Identification marking or warning label	Missing, incomplete, not legible, not as specified		X

* 4.3.2.2 End item testing. Each wrapping machine shall be tested in accordance with 4.4.1, 4.4.2 and 4.4.3 (when applicable) and failure of any test shall be cause for rejection of the item. When a first article is not required, the test specified in 4.4.4 (when applicable) and 4.4.5 shall be performed on one production unit and failure of the test shall be cause for rejection of the lot.

4.3.3 Code and standards compliance. Proof of compliance with the requirements of 3.3.1 shall be made available to the Government representative.

4.3.4 Packaging inspection. An examination shall be made to determine that preservation, packaging, packing and marking as required by section 5 of this specification are complied with. Defects will be as specified in table III. The lot shall be all wrapping machines offered for inspection at one time. The sample unit shall be one wrapping machine fully prepared for delivery. The inspection level shall be S-2 and the AQL shall be 4.0 expressed in terms of defects per hundred units.

TABLE III. Packaging defects.

Examine	Defect
Marking (exterior and interior)	Missing; incorrect; illegible; of improper size, location, sequence or method of application

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

TABLE III. Packaging defects (cont'd)

Examine	Defect
Materials	Components missing, damaged or otherwise defective
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping or tape banding, inadequate stapling, bulging or distortion of containers, blocking, bracing, cushioning, case liners inadequate, improper, or missing
Contents	Wrapping machine equipment parts or special tools (if applicable) missing

4.4 Tests. The tests in 4.4.1, 4.4.2 and 4.4.3 shall be conducted in an ambient of 45 F., plus or minus 10 F., as specified in 3.5.1.

4.4.1 Heat recovery test. The heat sealing units of the wrapping machine shall be energized and adjusted with the thermostat until a temperature of 475 F. is obtained at an approximate central point on the heat sealing surface. When temperature equilibrium within plus or minus 5 F., has been reached, the temperature of the heating surface shall be cooled 30 degrees by lowering the thermostat. The thermostat shall be raised again and the time required to increase the temperature of the heating surface 30 F. shall be checked. Inability of heat sealing units to meet heat recovery requirements of 3.5.1 shall constitute failure to pass this test.

4.4.2 Performance test. The wrapping machine shall be loaded and threaded with applicable film, and operated at applicable speeds specified in table I. Pulp, styrofoam and clear plastic trays, filled with a wooden filler of approximate dimensions, 4 inches wide by 7 inches long and 4 inches high, shall be fed into the machine to wrap. Each type of tray shall be continuously fed for a period of 30 minutes. Inability of the machine to meet the operation and wrapping requirements of 3.6 shall constitute failure to pass this test.

4.4.3 Shrink tunnel test. Wrapping machine with shrink tunnel shall be tested in accordance with 4.4.2. Inability of the machine to meet the operating, wrapping and shrinking requirements of 3.6.1 shall constitute failure to pass this test.

4.4.4 Electromagnetic compatibility test. When electromagnetic compatibility is required, the unit shall be tested by the contractor in accordance with test

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

Methods CE03 and RE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the contractor or an independent testing agency. The contractor shall furnish the contracting officer written certification that the Interference Control Plan, the EMI/MEC Test Plan, the Electromagnetic Compatibility Test Report and the requirements meet MIL-STD-461.

* 4.4.5 Noise test. The wrapping machine shall be tested for conformance with the noise limits of 3.12 in accordance with MIL-STD-1474.

5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. Removable components of each machine, such as air compressor, air hose, discharge table, prefold table, film trays and removable conveyors, legs and casters shall be disassembled in order to reduce cube and prevent damage while in transit. Care shall be exercised to avoid disassembly where the function of the item may be impaired or where special tools, calibration, or technical personnel may be needed for reassembly at the point of use.

5.1.1.2 Preservation. Exposed, uncoated ferrous metal surfaces of each machine and disassembled components shall be cleaned process C-1 of MIL-P-116 and thoroughly dried. Surfaces cleaned as specified shall be coated with type P-14 preservative of MIL-P-116. The air compressor shall be preserved in accordance with the industry's practice.

5.1.1.3 Protection of preservatives. Surfaces from which preservative compound might be removed by contact with packaging and packing materials shall be covered or wrapped with greaseproof barrier-material conforming to type I or II, grade A of MIL-B-121. Barrier-material shall be secured with tape conforming to PPP-T-45, cord or twine, or heat sealed when heat sealable barrier-material is used.

5.1.1.4 Packaging. Parts of each machine that are free to rotate shall be securely fastened in a fixed position to prevent movement or vibration while in transit. Disassembled components shall be packaged in a snug-fitting fiberboard box or boxes conforming to type CF or SF, class weather-resistant or domestic, style optional of PPP-B-636. Fiberboard inserts or other cushioning material shall be used to separate and immobilize the contents of the box. Each box shall be securely closed in accordance with the appendix of the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

5.1.2 Level C. Machines shall be preserved and packaged to afford adequate protection against corrosion deterioration and damage during shipment from supply source to receiving activity.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A packing. Each machine together with detached components preserved and packaged as specified in 5.1, shall be packed in a crate conforming to type I, class 1 or 2, style a of MIL-C-104. Alternatively, type II machines may be packed in a crate conforming to type V, style A, class 1 of PPP-C-650. Fiberboard boxes conforming to class weather-resistant of PPP-B-636 (see 5.1.1.4), shall be wrapped in a barrier-material conforming to class C-1, C-2(a), E-1, or E-2 of PPP-B-1055. All seams and closures of the wrap shall be completely sealed with a three-fourths of an inch minimum width continuous seam of water-resistant adhesive conforming to MMM-A-260. Alternatively, class domestic fiberboard boxes, (see 5.1.1.4), shall be waterproofed in accordance with the appendix of the box specification. Wrapping machines, packed in crates conforming to PPP-C-650, shall be waterproofed in accordance with the appendix thereto.

5.2.2 Level B packing. Machines preserved and packaged as specified in 5.1, shall be packed as specified in 5.2.1, except waterproofing of fiberboard boxes shall not be required and shroud made from 50 pound minimum basis weight (24 by 36-500) kraft paper or 0.004-inch minimum thickness polyethylene film conforming to type I of L-P-378 may be used in lieu of waterproof crate liner or shroud.

5.2.3 Level C packing. Machines, preserved and packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The wrapping machines covered by this specification are intended for use in commissaries for wrapping meat and produce.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Type, class and speed required (see 1.2).
* (c) When a first article is required (see 3.1, 4.2 and 6.3).
(d) When voltage other than specified in required (see 3.5.3).
(e) When a heat shrink tunnel is not required (see 3.5.5).
(f) When electromagnetic compatibility is required (see 3.7).
(g) Selection of the applicable levels of preservation-packaging and packing (see 5.1 and 5.2).
(h) Whether installation and instruction services of the item by the contractor are required and point of contact for such services when required.

6.3 Contract data requirements. Any data items to be delivered under any contract for items covered by this specification should be specifically cited in the contract in accordance with the applicable regulations of the procuring activity.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should be a preproduction sample, initial production item or other specific item described under the definition of a first article in the ASPR. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

6.5 Type I and type II, class B, styles 1 and 2 of MIL-W-40614B, dated 28 March 1969 were deleted for this revision.

6.6 The margins of this specification have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - SA

Review activities:

Army - MD
Navy - MS

Preparing activity:

Army - GL

Project No. 3540-0085

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-W-40614C WRAPPING MACHINES, MEAT AND PRODUCE, AUTOMATIC, SHRINK FILM

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

DRXNM-TD G

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

Commander
US Army Natick Research and Development Command
ATTN: DRXNM-TD G
Natick, MA 01760

NATICK OP 1 Apr 76

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:25Z
Check the source to verify that this is the current version before use.