[METRIC]
A-A-2657A
OCTOBER 6,1997
SUPERSEDING
A-A-2657
November 20, 1990

COMMERCIAL ITEM DESCRIPTION

BINDER, AWARD CERTIFICATE

The General Services Administration has authorized the use of this commercial item description for all Federal agencies.

1. SCOPE. This commercial item description covers a binder which is used to contain and protect 25.7 x 30.8 cm (10-1/8 x 12-1/8 inch) award certificates.

2. SALIENT CHARACTERISTICS.

2.1. Design of binder. The binder opens as a book, and the inside of the back cover shall have ribbon retainers at each corner to securely retain the certificate. The binder is intended for formal presentation.

2.2. Construction. The binder shall consist of a front and back chipboard cover and a joining hinge area. When opened, the binder shall be at least 32.1 cm (12-5/8 inches) high and no more than 55.9 cm (22 inches) wide, including the 1.3 cm (1/2 inch) center hinge score. When closed, the binder shall be not less than 26.4 cm (10-3/8 inches) wide. The outside covering material shall be turned and glued over the edges to cover the margins inside the front and back cover boards and the hinged area.

Beneficial comments, recommendations, additions, deletions, clarification, etc. and any data which may improve this document should be sent to:
General Services Administration, Engineering Division 2FYEE
Rm. 20-128, 26 Federal Plaza, New York, NY 10278

FSC7510

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:24Z
Check the source to verify that this is the current version before use.

There shall be no cover board in the hinge area. The lining material shall extend over the inside of the back and front cover to a point that overlaps the turned edge of the outside covering. An outside hinge reinforcement strip of not less than 6.0 cm (2-3/8 inch) wide and glued under the lining shall be included and shall be the same color as the covering material.

2.3. Materials. The covering material shall be light weight, levant grain, regular finish, imitation leather. The inside lining shall be either Granada tag cloth backed by a sheet of white bleached chemical wood bond paper, or number 2 felt-finished text paper, such as wausau felt. The front and back covers shall be of 0.25 ± 0.005 cm (0.100 inch ± 0.002 inch) chipboard. The panels shall accommodate 30.8 x 25.7 cm (12-1/8 x 10-1/8 inch) award certificates.

2.4. Colors. The covering material shall be a dark blue near match to color chip 15044 of Federal Standard 595 (within a range of color chips 15042 to 15045) and the lining material shall be a white near match to color chip 37875 of Federal Standard 595 (within a range of color chips 37875 to 37886). Colors shall be tested in accordance with para. (3.2).

2.5. Corner ribbon retainers. The inside of the back cover shall have four diagonally mounted, 1.7 ± 0.08 cm (11/16 ± 1/32 inch) wide grosgrain white corner ribbon retainers. The opening side of the ribbon retainers shall be located not further than 1.9 cm (3/4 inch) from each of the four corners of the back lining sheet. The ends of these ribbon retainers shall be folded and glued under the back lining sheet.

2.6. Inside decoration. The inside of the front cover shall have a diagonally mounted, 2.2 ± 0.16 cm (7/8 ± 1/16 inch) wide; red, white and blue grosgrain ribbon. This ribbon shall be located in the upper right hand corner (with the red stripe nearer the right corner). This ribbon shall be mounted such that, it is located 1.9 ± 0.16 cm (3/4 ± 1/16 inch) in the horizontal and vertical direction from the corner of the front lining sheet. The ends of this ribbon shall be folded and glued under the front lining sheet.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:24Z
Check the source to verify that this is the current version before use.

2.7. The ribbons used shall be colorfast (see 3.3).

2.8. Outside decoration. A gold-colored border shall be heat stamped on the outside of the front cover. The border shall consist of 3 lines which follow the outer edges of the binder. The lines shall appear straight (except for the corners) and concentric with the outside of the cover.

Line 1 shall be 0.16 ± 0.08 cm (1/16 +/- 1/32 inch) wide and located 0.32 ± 0.08 (5/8 ±1/32 inch) from the outer edge.

Line 2 shall be 0.16 ± 0.08 cm (1/16 inch +/- 1/32 inch) wide and located)32 ± 0.08 (1/8 ± 1/32 inch) from the inside edge of Line 1.

Line 3 shall be 0.16 ± 0.08 cm (1/16 inch wide +/- 1/32 inch) and located 0.95 ± 0.08 cm (3/8 +43 1/32 inch) from the inside edge of line 2.

2.9. Workmanship. Completed binders shall present a neat, finished appearance both inside and outside. The binders shall be free from defects which may affect their durability, serviceability, or appearance.

3. Quality Assurance Provision

3.1. Product Conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards and quality assurance practices and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

3.2. Color shall be determined visually as a general match to the applicable color as determined in accordance with ASTM D 1729.

3.3. Colorfastness shall be tested for by using the following procedures. There shall be no transfer, bleeding or discoloration of colors, apparent to the naked eye after testing. The ribbon shall be tested as a part of an assembled binder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.

Two pieces of white blotting paper shall be cut to a size such that they could be slipped under the ribbon and contact the full length and width of the visible portion of the ribbon. One piece of the blotting paper shall be uniformly dampened with water and slipped under the ribbon to contact it as described above. The other piece of dry blotting paper shall be placed on top of the ribbon and held in place, until such time as the dry plotting paper becomes uniformly dampened. Then, carefully remove both pieces of blotting paper and examine them and the ribbon, and adjacent binder surfaces, for conformance. Allow the ribbon to fully air dry and, again, examine for conformance (see 2.7).

4. Preparation for Delivery

Packaging, packing and marking shall be as specified in the contract or order. Packaging and packing shall be adequate to protect the binders from damage that will affect their durability, serviceability or appearance.

5. Regulatory Requirements

5.1. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

6. Notes

7. Ordering Data. Purchasers should select the preferred options permitted herein and included the following information in procurement documents:
(A) Packaging, packing, marking

7.1. Sources of Documents.

7.1.2 Application for copies of technical documents referenced herein: The issue date of invitation for bids or request for proposal shall apply.

7.1.3 FED-STD-595 may be obtained from the General Services Administration Specifications Section (3FP-E), Suite 8100, 470 EAST L'ENFANT PLAZA, SW WASHINGTON, DC 20407.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.

7.1.4 Public Law 94-580, Resource Conservation and Recovery Act, is part of U.S. Code, Title 42. Available from the Congressional Printing Office, Washington, D.C. 20402.

7.1.5 ASTM Standard test methods can be obtained from the American Society for Testing and Materials; 100 Barr Harbor Dr., West Conshohocken, PA 19428-2959.

7.1.6 National Stock Numbers (NSNs). The following is a listing of the NSN assigned which correspond to this CID. The list may not be indicative of all possible NSNs associated with the CID.

NSN
7510-00-157-8618

MILITARY INTERESTS:
NONE: DOD has no registered interest in revisions and amendments to this Commercial Item Description until further notice.

Preparing Activity:
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.