[INCH-POUND]
A-A-2977
October 2, 1996

COMMERCIAL ITEM DESCRIPTION

HOE, MORTAR MIXING

The General Services Administration has authorized the use of this Commercial Item Description for procurement of type III, hoe specified in of GGG-H-496C for all federal agencies.

1. SCOPE.

1.1 Scope. This Commercial Item Description covers mortar mixing hoes used for mixing mortar. The hoes are provided with two holes in the blade to aid in the mortar mixing operation.

2. CLASSIFICATION.

2.1 Classification. Not applicable.

3. SALIENT CHARACTERISTICS.

3.1 Design. Mortar mixing hoes shall consist of a blade, gooseneck shank, crosspin, and handle, and either a tapered socket or steel ferrule. The blade and shank shall be either forged from one piece of steel or two pieces of steel welded together so as to provide a hoe of a strength at least equal to the one-piece construction. The blade shall have two round holes approximately 1-3/4 inches in diameter with each hole located approximately in the center of each half of the blade. The hoes shall have a sheared or squared edge. Overall dimensions for the two hoe sizes are identified in Table I.

TABLE I. Mortar mixing hoes dimensions

Size no.	Width of blade		Depth of blade		Length of handle		Diameter of shank
	Minimum (Inches)	Maximum (Inches)	Minimum (Inches)	Maximum (Inches)	Minimum (Inches)	Maximum (Inches)	Minimum (Inch)
1	8-3/4	9-1/4	5-3/4	6-1/4	65	67	5/8
2	9-3/4	10-1/4	5-3/4	6-1/4	65	67	5/8

3.1.1 Construction. The hoe shall have either a tapered socket or inserted shank construction. The tapered socket, having a minimum wall thickness of 0.060 inch, shall be properly welded to the gooseneck shank. With the inserted shank construction, the gooseneck shank shall terminate in a drive tang which shall be forced into the

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: General Services Administration, Federal Supply Service, Tools and Appliances Commodity Center, Kansas City, MO 64131.

Distribution Statement A. Approved for public release; distribution is unlimited. FSC 5120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

end of the handle at least 3 inches. A tapered tubular steel ferrule not less than 6 inches long which can be cupped or have a steel cap where the handle attaches to the shank, is acceptable. Longitudinal seams of all ferrules shall be closed by a continuous weld. The two types of hoe construction shall be similar to Figure 1.




Figure 1. Hoe, mortar mixing.

3.1.2 Handle. The handle shall be either of sound, thoroughly seasoned, straight-grained ash or hickory. The handles shall have one end rounded and the other end tapered to properly fit in the socket or ferrule. The diameter of the handle shall be 1-5/16 inch minimum and shall be properly shaped, smooth, and clear lacquered.

3.1.3 Crosspins. Crosspins consisting of nails or rivets having a minimum body diameter of 0.110 inch shall be used to connect the handle to the socket or ferrule. Nails, if used, shall be well driven and shall pass through one wall of the socket or ferrule and 2/3 the distance through the handle.

3.1.4 Blade. The blade shall be flat or slightly concave and shall have a pitch of 70 to 85 degrees with respect to the handle.

3.1.5 Load. The assembled hoe shall be capable of withstanding a load of between 75 to 80 pounds applied, for a minimum of two minutes, to the blade with the handle held in the vertical position between two parallel jaws at least 10 inches from the blade without evidence of damage or permanent deformation not to exceed 1/8" from permanent set.

3.2 Identification marking. The tool shall be marked with the manufacturer's name or identifying symbol and the state or country of manufacture, unless otherwise specified. All identification markings shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

3.3 Workmanship. Details of workmanship shall be in accordance with the best commercial practice. Paints, coatings, platings, and finishes shall be smooth, adherent, continuous, and not stained or discolored. External surfaces shall be free of tool and gouge marks, nicks, or other surface imperfections. The item shall be free from manufacturing workmanship defects (e.g., sharp or rough external edges, corners, or surfaces) and material workmanship defects (e.g., pits, rips, fins, burrs, tears, nodules, cracks, blisters) which may adversely impact the item's serviceability, durability, safety, or appearance.

4. REGULATORY REQUIREMENTS.

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

5. QUALITY ASSURANCE PROVISIONS.

5.1 Product conformance. The product provided to the Government shall conform to the contractually specified requirements. For product characteristics and requirements which are not contractually specified, the provided product shall conform to the producer's own drawings, standards, specifications, and quality assurance practices for the highest quality product commercially offered by the producer. If the product is not commercially offered by the producer, the best commercial practices shall apply. The Government reserves the right to require proof of such conformances prior to first delivery and thereafter as provided for under the provisions of the contract.

5.2 Responsibility for inspection. Unless otherwise specified, the contractor is responsible for the performance of all inspection requirements and may use any commercial facilities (including the contractor's own facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any inspections deemed necessary to assure the item conforms to the specified requirements.

5.3 Bid sample(s). When a bid sample requirement is specified in the solicitation, the bid sample(s) shall be inspected for all salient characteristics by the Government. A failure of any bid sample to meet the salient characteristics shall be cause for rejection.

5.4 First article sample(s). When a first article requirement is specified in the contract, the first article sample(s) shall be inspected for all salient characteristics. A failure of any first article sample to meet the salient characteristics shall be cause for rejection.

6. PACKAGING.

6.1 Packaging. Requirements of preservation, packing, packaging, and marking of packages shall be as specified in the contract or order.

7. NOTES.

(This section contains information of a general or explanatory nature that is not mandatory.)

7.1 Addresses for obtaining copies of referenced documents:

Federal Specifications and Standards: Federal Supply Service Bureau, Specification Section, Suite 8100, 470 L'Enfant Plaza, SW, Washington, DC 20407.

Federal Acquisition Regulations (FAR): Government Printing Office, Superintendent of Documents, Washington, DC 20402-9371.

ANSI/ASQC Z1.4: American Society for Quality Control, P.O. Box 3005, 611 East Wisconsin Avenue, Milwaukee, WI 43201-4606.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and should include the following information in procurement documents:

(a) Title, number, and date of this Commercial Item Description.
(b) When applicable, the appropriate NSN(s).
(c) If bid samples are required, the number of samples required, and the subjective inspection requirements.
(d) If first article samples are required and the number of samples required.
(e) If lot sampling inspection is required and the applicable lot sampling requirements. For example:

Sampling for inspection. Sampling for inspection (both examinations and testing) shall be in accordance with ANSI/ASQC Z1.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

Inspection. Each sample tool shall be examined and tested for all salient characteristics. The Inspection Level shall be S-2 with an Acceptable Quality Level of 4.0, expressed in terms of defects per hundred units.

(f) What preservation, packing, packaging, and marking of packages are required.

7.3 National Stock Numbers (NSNs). The following list of NSNs corresponds to the hoe specified in this CID. This list may not be indicative of all possible NSNs associated with this CID.

NSN	SIZE
5120-00-224-9466	1
5120-00-243-2788	2

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions or notices to this Commercial Item Description until further notice.

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.