[INCH POUND]
A-A-3135
March 26, 1998
SUPERSEDING
A-A-982
May 20, 1982
A-A-983
May 20, 1982

COMMERCIAL ITEM DESCRIPTION

WHEELBARROWS

The General Services Administration has authorized the use of this commercial item description (CID) by all federal agencies.

1. SCOPE

1.1. Scope. This commercial item description covers general utility and contractors wheelbarrows.

2. CLASSIFICATION

2.1 Classification. The wheelbarrows shall be of the following type, class and size as specified (see 7.2).

Type I - General Utility
Type II - Contractors

Class A - Steel handles
Class B - Wood handles

Size 1 - Heaped capacity 4.0 cubic feet (17 gauge minimum)
Size 2 - Heaped capacity 5.0 cubic feet (16 gauge minimum)
Size 3 - Heaped capacity 6.0 cubic feet (16 gauge minimum)

3. SALIENT CHARACTERISTICS

3.1 Tray. The wheelbarrow trays shall be formed from sheet steel. The gauge shall correspond to the size of the wheelbarrow as specified in 2.1. The tray shall have a reinforced or rolled edge around the open perimeter edge of the tray.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: General Services Administration, Engineering Branch (7FXEE), 819 Taylor Street, Fort Worth, TX 76102.

FSC 3920

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

3.2 Handles. The handles shall be tubular steel or hardwood as specified in the contract or order. Hardwood handles shall have a smooth rounded end at the lifting point. Steel handles shall be round or square with an outside diameter of 1-1/4 inches minimum with a schedule 40 minimum wall thickness.

3.3 Legs. Supporting legs shall be steel channel or steel tubing. A horizontal steel brace shall be provided between the legs.

3.4 Wheel and tire assembly. The wheel shall be one or two piece steel construction. The pneumatic tire shall be tubeless or tube type and shall be assembled to the wheel and ready for installation.

TABLE I
COMPONENT REQUIREMENTS

SIZE	CAPACITY	WHEEL DIAMETER	TIRE SIZE	AXLE BEARINGS
1	4 cu.ft.	6 inch	3.50 X 6	oilube, roller or ball
2	5 cu.ft.	8 inch	4.80 X 8	oilube, roller or ball
3	6 cu.ft.	8 inch	4.80 X 8	Ball or roller w/grease zerk fitting

NOTE: The requirements in this table are considered minimum.

3.5 Axle Assembly. Minimum axle diameter shall be 0.50 inch. The axle shall be supported by the type of bearing listed in Table I. When specified, an axle bearing grease zerk fitting shall be installed in the bearing hub and easily accessible for in-service lubrication.

3.6 Wheel Guard. The front ends of the handles shall be securely fastened together by a steel wheel guard. If the handles are formed from one piece tubular steel, the wheel guard may be an integral part of the handles.

3.7 Tray Braces. The wheelbarrows shall have either steel tray braces and/or risers on each side of the wheel, for tray stability. The tray braces shall run vertically or diagonally and the risers shall run parallel from the handle to the forward underside of the tray.

3.8 Fasteners. All fastener hardware used for assembly (i.e lock washers, washers or self-locking nuts) shall be included for assembly and plated to prevent corrosion.

3.9 Finish. All assembly hardware shall be zinc plated. All other metal assembly components of the wheelbarrow shall be either plated or painted the standard commercial color used by the manufacturer. Wooden handles and risers shall be finished with a protective coating. Poly risers are not painted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

3.10 Workmanship. All components and assemblies of the wheelbarrows including castings, forgings, molded parts, stampings, bearings, seals and machined surfaces shall be free from burrs and sharp edges, sand, dirt, fins, pits, sprues, scale, flux and other extraneous material. All external surfaces shall be plated or painted and free from rust and corrosion as specified. Components made from wood shall be free from decay, splits, checks, holes, knots larger than 1/2 inch diameter or loose knots. All assembly components relative to each individual size wheelbarrow shall be interchangeable throughout the life of the contract to insure ease of assembly by the customer. The wheelbarrow assembly shall not contain any defects in materials or workmanship, which would affect appearance, serviceability or designed functional performance.

4. REGULATORY REQUIREMENTS

4.1 Regulatory Requirements. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Metric Products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

5. QUALITY ASSURANCE PROVISIONS

5.1 Product Conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards and quality assurance practices and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

6. PACKAGING

6.1 Packaging. The preservation, packing and marking shall be as specified in the contract or order. The supplier is required to ship all individual detail components necessary to completely assemble each wheelbarrow.

7. NOTES

7.1 Part Identification Number (PIN). Wheelbarrows conforming with this commercial item description shall be identified by a part number configuration consisting of identification of a portion of the specification number, the type, class and size. An example of the part number configuration is shown below.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

Part Identification Number (PIN) as follows:

AA3135IA2
| |||___ Size 1 or 2
| ||____ Class A or B
| |___ Type (I or II)
|_____ General CID number.

PART NUMBER	NSN
AA3135IB1	3920-00-171-4001
AA3135IA1 or IB1	3920-00-640-9236
AA3135IA2 or IB2	3920-00-244-9284
AA3135IIB3	3920-00-329-4303
AA3135IIA3	3920-00-530-4317
AA3135IIB2	3920-00-827-7471

7.2 Ordering data. Purchaser's should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a. Title, number, and date of this commercial item description.
b. Type, class and size
c. The preservation, packing and marking desired.

MILITARY INTERESTS:

Custodians:
AIR FORCE - 99

Reviewer:
Air Force 84

PREPARING ACTIVITY:
GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.