[Metric]
A-A-3155
December 3, 1997

COMMERCIAL ITEM DESCRIPTION
COAT RACK, WALL MOUNTED , WOOD, EXECUTIVE TYPE

This Commercial Item Description was developed by the National Furniture Center, Federal Supply Service, General Services Administration, Washington, D. C. 20406, based upon currently available technical information.

1. SCOPE

1.1 Scope. This Commercial Item Description covers the general and detailed requirements for one size Executive type, wall mounted wood Coat Rack, available in three finishes.

2. SALIENT CHARACTERISTICS

2.1 Wood Finishes/Woods The coat racks shall be available in three different finishes. Wood species shall be one of those specified after each finish.

Oak - on Red Oak or Ash
Walnut-on Walnut, Cherry, or Mahogany 1/
Mahogany - on Mahogany 1/, Walnut or Cherry
1/ Khaya/African or Swietenia/American

2.2 The finish shall match the standard laminate samples in color, with a satin finish. The finishing process shall include compatible stain , sealers, fillers (if necessary), lacquer, top coats and sanding and rubbing to meet the required finish test (4.2.2). The natural grain of the wood shall not be clouded by the finishing process. It shall be uniform, smooth, with no discoloration, grit, tackiness, peeling, flaking, blistering, cracking, damage or rub through. The finishes shall match the following standard samples as specified in the contract or order.

Federal Walnut Standard Finish (FSS-L-01024) (Executive Office)
Federal Mahogany Standard Finish (FSS-L-01025) (Executive Office)
Federal Oak Finish (FSS-L-01023)

2.3 Wood. Wood used for exposed parts, shall be bright, well sanded, and free from brashness, discoloration, worm holes, splits, shake, or other defects which affect the appearance or which may affect the serviceability of the finished product. All wood, shall be uniformly kiln dried to a 5 to 8 percent moisture content as determined by the oven-drying method. After drying, it shall be held in temperature and humidity controlled storage for a sufficient time to ensure uniform moisture distribution among the individual pieces. The members shall be made of solid wood, a maximum of two full length glued pieces, carefully selected and assembled for similar grain and color.

2.4 Adhesives. The adhesives used shall be any that will develop an average block shear strength of 19 300 kPa minimum. (4.3.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

2.5 Hardware.

2.5.1 Face Hardware. The coat hooks shall be made of polished cast brass (Baldwin No. BH0781-030 or equal). The castings shall be true, without air or sand holes or other defects. All ornamentation on face of the hardware shall have a clean and even surface. All surfaces shall be smoothly and evenly finished. Hardware shall receive minimum one coat of baked synthetic clear finish.

2.5.2 Attaching Hardware. Each coat rack shall be provided with two minimum 38 mm x M5 self tapping mounting screws for mounting to solid substrate. In addition, two minimum M5 (3/16") x 63 mm toggle bolts shall be provided for optional drywall mounting.

2.6 Design. The coat rack shall be a rectangular block of wood 610 mm long x 90 mm wide x 19 mm thick cut off at each corner at about 45 degrees and shaped on the 4 upper edges in a continuous cove shape with its edges well rounded. The grain pattern shall run the length of the unit. About 100 mm from each end, counterbore holes for the installation of mounting screws or bolts. The holes shall be capped with snug fitting 16 mm button plugs. (Tolerances length +/-2 mm, others +/- 1 mm) Four coat hooks shall be mounted to the face of the wood , approximately 165 mm apart with brass face screws.

3.1 Identification marking. Each coat rack shall be permanently and legibly marked in an inconspicuous place with the Federal Stock Number, contract number, date of manufacture and the manufacturer's name or trademark, so that the source of supply may be readily determined.

3.2 Workmanship. The methods of machining, finishing, assembly and the finished appearance of the coat rack shall be in strict accordance with the requirements of this specification. Where specific requirements are not given, good commercial practice of the contract furniture industry shall be used.

4. QUALITY ASSURANCE PROVISIONS

4.1 Inspection Provisions. Details of the first article sample requirements are contained in the solicitation. In addition, approval of the first article sample authorizes the start of production, but does not relieve the contractor of responsibility from conformance with all other applicable provisions of this CID. Inspection requirements are stated in the solicitation.

4.2 Testing.

Component	Characteristic	Reference	Test Method
Adhesive	Block shear test	2.4	ASTM D 905-94
Finish	Toughness and adhesion	2.2	4.2.2 herein

4.2.1 Test for Adhesives. Test in accordance with ASTM D 905. Rerun test if the average shear strength of all samples is below 19 300 kPa; there is a 10 percent or greater difference between high and low specimen values, and at least one test specimen broke at more than 19 300 kPa.
Disregard a test specimen in computing the average if it breaks at less than 19 300 kPa; and it has 50 percent or more wood failure.

4.2.2 Test for Finish. The toughness and adhesion test shall be made by using Organic Coating Adhesion Tester, US Testing Company, Model Number 1001, in accordance with instructions for using, as provided for by the manufacturer of the tester (see 6.3). The panel shall be marred both parallel and perpendicular to the grain. The resulting indentation shall be examined for whitening (film separation) or cracking, which is not acceptable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging, Packing and Marking. Package, pack and mark shipping containers in accordance with the contract or order.

6. NOTES

6.1 Ordering data. Purchasers should include the title, number, and date of this Commercial Item Description, required finish, quality assurance provisions, and packaging, packing and marking requirements in procurement documents.

6.2 Standard sample. Sample panels of the standard colors are obtainable, without charge, from the National Furniture Center, GSA-FSS-3FNE, Washington, DC 20406.

Federal Walnut Standard Finish (FSS-L-01024) (Executive Office)
Federal Mahogany Standard Finish (FSS-L-01025) (Executive Office)
Federal Standard Oak Finish (FSS-L-01023)

6.3 Organic Coating Adhesion Tester. Information about the Organic Coating Adhesion Tester, Model No. 1001, may be obtained from:

(US Testing Company, Inc., 1415 Park Avenue, Hoboken, New Jersey 07030)

6.4 American Society for Testing and Materials (ASTM) Standard:

ASTM D 905-94 - Standard Method of Test for Strength Properties of Adhesives in Shear by Compression Loading.

(Copies may be obtained from American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2925.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.