[INCH-POUND]
A-A-3158
June 9, 1998
SUPERSEDING
ZZ-M-71F
February 26, 1987

COMMERCIAL ITEM DESCRIPTION

MATTING, RUBBER AND VINYL

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This commercial item description (CID) covers, rubber and vinyl matting used in hospitals, ships, laboratories and buildings for general use.

1.2 Classification. The matting covered by this commercial item description shall be of one type, made of rubber composition, rubber composition with one ply cotton sheeting or vinyl composition.

2. SALIENT CHARACTERISTICS

2.1 Material.

2.1.1 Rubber. The rubber matting shall be made from synthetic rubber or a mixture of synthetic and reclaimed rubber, with or without cotton sheeting.

2.1.1 Cotton sheeting. The sheeting, when used in the construction of rubber matting, shall be plain woven cotton.

2.1.2 Vinyl. Vinyl matting shall be compounded polymer or copolymer of chloride resin, plasticized with phosphate or phthalated plasticizers only.

2.2 Design. The rubber and vinyl composition matting shall have either a longitudinal corrugation or a patterned corrugation on the upper surface, at the supplier's option. The pattern shall be uniform and provide a non-slip surface.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Branch (7FXEE), 819 Taylor Street, Fort Worth, TX 76102-6114.

FSC 7220

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

When vinyl composition is used the lower surface of the matting shall be finished with a knurled surface.

2.2.1 Longitudinal corrugations. When longitudinal corrugations are used the upper surface of the matting shall be grooved with 6-1/2 to 8-1/2 grooves per inch (2.54cm). The grooves shall be either rounded or triangular.

2.2.2 Depth of corrugation. The depth of corrugation shall be not greater than 50 percent of the overall thickness of the matting.

2.3 Resistance to fungi. When specified (see 6.1), the matting shall be tested in accordance with ASTM G21 for resistance to fungi. When fungi resistance is specified, the ASTM G21 rating required (see 6.1).

2.4 Dimensions.

2.4.1 Width. The width of the matting shall be as specified (see 6.1):

18 inches ± ½ inch (46cm ± 1.3cm)
24 inches ± ½ inch (61cm ± 1.3cm)
36 inches ± ½ inch (92cm ± 1.3cm)
48 inches ± ¾ inch (122cm ± 1.9cm)

2.4.2 Thickness. The thickness of the matting shall be 1/8 inch (0.32cm), 3/16 inch (0.5cm) or 1/4 inch (0.6cm), as specified (see 6.1). All thickness dimensions are minimum.

2.4.3 Length of roll. Unless otherwise specified (see 6.1), the matting shall be furnished in rolls of 25 linear yards minimum (23 meters). No roll shall contain more than one piece.

2.5 Color. The color of the matting shall be as specified (see 6.1)

2.6 Workmanship. The mats shall be free from embedded foreign material, cracks, tears, objectionable odor or any other defect affecting appearance or serviceability of the item.

2.7 Measurement system. The values stated in inch-pound units are to be regarded as the standard. The metric values stated in parentheses are for information purposes only.

2.8 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerances specified and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

3. REGULATORY REQUIREMENTS

3.1 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. QUALITY ASSURANCE PROVISIONS

4.1 Product Conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5. PACKAGING

5.1 Packaging. Preservation, packing, and marking shall be as specified in the contract or order.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a. Title, number and date of this commercial item description.
b. Width, thickness and length, if other than specified.
c. Color required (see 2.5).
d. When fungi resistance is required.
e. Acceptable fungi resistance.
f. Preservation, packing, and marking desired.

6.2 Source of Documents.

6.2.1 ASTM standard G21 is available from the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, Pa. 19428-2859.

6.3 National Stock Numbers (NSNs): The following is a list of NSNs assigned which correspond to this CID. The list may not be indicative of all possible NSNs associated with the CID.

NSN	Width	Thickness	Length
7220-00-034-7225	48.0 inches (122cm)	0.125 inch (0.318cm)	25 yd (23 meters)
7220-00-254-4240	36.0 inches (91cm)	0.125 inch (0.318cm)	25 yd (23 meters)
7220-00-634-0216	18.0 inches (46cm)	0.250 inch (0.635cm)	36.0 inches (91cm)
7220-00-753-2981	24.0 inches (61cm)	0.125 inch (0.318cm)	10 yd (9.1 meters)
7220-00-753-2982	36.0 inches (91cm)	0.125 inch (0.318cm)	10 yd (9.1 meters)
7220-00-965-4699	36.0 inches (91cm)	0.188 inch (0.477cm)	25 yd (23 meters)
7220-00-965-4769	24.0 inches (61cm)	0.188 inch (0.477cm)	25 yd (23 meters)

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:30Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

NONE: DoD has determined that no military activity has an official interest in this commercial item description.

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:30Z
Check the source to verify that this is the current version before use.