AA-H-570a
Interim Amendment-3
May 13, 1974
SUPERSEDING
Interim Amendment-2
March 16, 1966

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

HOUSEHOLD FURNITURE, LIVING ROOM, WOOD, UPHOLSTERED

This interim amendment was developed by the Federal Supply Service, General Services Administration, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification AA-H-570a, dated October 11, 1962.

PAGE 1

Paragraph 2.1 Federal Specifications: Add the following in proper sequence:

"V-T-295 - Thread, Nylon."

PAGE 2

Paragraph 2.1 (continued). Delete "CCC-F-66 - Fabrics, Upholstery". Add the following in proper sequence:

"TT-S-300 - Shellac, Cut.
CCC-A-680 - Artificial Leather (Cloth Coated), Vinyl Resin, Expanded Layer (Upholstery).
CCC-C-540 - Cloth, Upholstery.
MMM-A-260 - Adhesive, Water-Resistant, (For Sealing Waterproofed Paper).
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-1055 - Barrier Material, Waterproofed, Flexible.
PPP-C-650 - Crates, Wood, Open and Covered."

Under Federal Standards: Add the following in proper sequence:

"Fed. Test Method Std. No. 175 -- Adhesives, Methods of Testing."

Delete the first two paragraphs, right hand column at top of page 2, and substitute the following:

"(Activities outside the Federal Government may obtain copies of Federal Specifications, and Handbooks as outlined under General Information in the Index of Federal Specifications, Standards, and Handbooks and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, MO., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA."

FSC 7105

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

Under Military Specifications: Delete "MIL-W-6110 - Wood; Determination of Moisture Content Of."

Under Military Standards: Add "MIL-STD-1363 - Measurement of Wood Moisture Content."

PAGE 3

Paragraph 2.2 Other publications: Add the following in proper sequence:

"ASTM Designation: D751-60T - Methods of Testing Coated Fabrics (Tentative).
ASTM Designation: D1564-71 - Standard Methods of Test for Slab Flexible Urethane Foam."

"Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)"

"National Motor Freight Traffic Association, Incorporated, Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., 1616 P Street, N.W., Washington, D. C. 20036.)"

Paragraph 3.3.1.1 Burlap. Add the following at the end of the paragraph:

"Alternatively, a spunbonded polyethylene sheet fabric weighing not less than 1.15 ounce per square yard or spunbonded polypropylene sheet fabric weighing not less than 2 ounces per square yard may be used."

PAGE 4

Paragraph 3.3.1.2.1 Sheet webbing. Line 3, delete the "period" and substitute a "comma" and add the following:

"or a plain woven fabric of 100 percent polypropylene weighing not less than 5.0 ounces per square yard, 16 ± 1 by 14.5 ± 1 yarns per square inch, flat or ribbon yarns with a breaking strength of not less than 250 pounds in warp and fill when tested in accordance with Method 5100 of Federal Test Method Standard No. 191, Textile Test Methods."

After paragraph 3.3.1.2.2 Strip webbing, add the following new paragraph:

"3.3.1.2.3 Rubber webbing. The rubber webbing shall be 2-1/4 inches, plus or minus 1/8 inch wide, having a breaking strength of not less than 300 pounds and an elongation of not less than 35 percent when tested as specified in Method B of ASTM Test Method D751-60T, except that specimen and jaw widths shall be the same as the width of the webbing, and specimen shall be placed in machine under 1 pound initial load."

Paragraph 3.3.1.3 Cambric. Delete the entire paragraph and substitute the following:

"3.3.1.3 Cambric. Cambric shall contain not less than 40 threads per inch in the warp and not less than 28 threads per inch in the filling, when tested in accordance with Method 5051 of CCC-T-191. Weight shall be not less than 2 ounces per square yard when tested in accordance with Method 5041 of CCC-T-191. The cambric shall be black or natural, with the face side glazed. Alternatively, a black, or gray spunbonded polyethylene sheet fabric weighing not less than 1.5 ounce per square yard or spunbonded polypropylene sheet fabric weighing not less than 2 ounces per square yard may be used."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

Paragraph 3.3.1.6 Thread. Line 8, delete "laundering" and substitute "dry cleaning".

Paragraph 3.3.1.6.1 For machine seaming and stitching. Delete in its entirety and substitute the following:

"3.3.1.6.1 For machine seaming and stitching. Seaming and stitching thread shall be type IB3, ticket No. 16, 4 ply, cotton thread conforming to V-T-276, or minimum 7-pound breaking strength nylon filament thread conforming to V-T-295."

PAGE 5

Paragraph 3.3.1.7.1 Cotton welt or jacket cord (class 2 furniture). Line 4, delete comma and add "or No. 60 cotton welt consisting of No. 4 yarn and four strands of eight ply."

Paragraph 3.3.1.8.3, first sentence: At end of sentence add: "except that the following additional restrictions on manufacturing defects shall apply:

1. Internal voids shall not be so large as to be perceptible to sight or touch through uncut surfaces.

2. The top and bottom surfaces of the foam shall be free from unrepaired surface voids 1/8 inch or greater in depth and 1/2 inch or larger in width.

3. On cushions where cut edges are to be banded, voids up to 1 inch in width and not exceeding 1/2 inch in depth need not be repaired prior to banding. The finished banded edge shall show no visible depression.

4. On vertical cut surfaces not banded, exposed voids up to 1 inch in width and not more than 1/4 inch in depth need not be repaired.

5. On horizontal cut surfaces, exposed voids up to 3/4 inch in width and not more than 1/8 inch in depth, or up to 1/2 inch in width and not more than 1/4 inch in depth need not be repaired."

Paragraph 3.3.1.8.3.2: Delete and substitute the following:

"3.3.1.8.3.2 Crowned cushions. The crowned pin-core cushions shall have filling of the material specified in 3.3.1.8.3. Each cushion filler shall have a crown, produced by the molding process, from front to back. The crown may be on one or both sides of the filler. The contour of the top ends shall be achieved by a slab stock boxing of the same density as the pin-core. The banding shall be 3 inches wide before applying, and centered to provide an even, uniform contour on both sides. Banding shall be cemented to the pin-core cushion and the seams carefully closed without opening or gap between cushion and banding. Unless otherwise specified (see 6.2), the crowned (center) portion of seat cushions shall be not less than 4-13/16 inches thick and not more than 5-1/4 inches thick. The back cushions need not be crowned and shall be 4 inches thick, having a plus tolerance of 3/16 inch and a minus tolerance of 1/8 inch. Thickness of the pin-core cushions shall be measured as specified in paragraph 14 of ASTM Designation D1055-59T."

After paragraph 3.3.1.8.3.2, add new paragraph 3.3.1.8.3 as follows:

"3.3.1.8.3 Urethane foam. The Prime urethane foam shall be Grade USU 27 for the chair backs and Grade USU 34 for the chair seats as defined in PS 13-69, Uncored Slab Urethane and shall conform to the requirements of Table VI when tested as specified in the applicable sections of ASTM D-1564-71. The urethane foam shall be slab or molded stock and shall not contain any filler material. The urethane foam test specimen shall be not less than 4 inches thick plus or minus 1/8 of an inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

TABLE VI. Physical properties of urethane foam

Property	Requirement	
	Chair Back	Chair Seat
25 percent Indentation load deflection; lbs.	27 ± 3	34 ± 4
Indentation load ratio (65 percent/25 percent): minimum	1.9	1.9
Compression set 22 hours/158 degrees F., 90 percent deflection, percent max.	15%	15%
Steam autoclave test (condition B)		
Percent change in 25 percent comp. load deflect; percent maximum	-20%	-20%
Comp. set 22 hour/158 degrees F., 90 percent deflect; percent max.	20%	20%
Fatigue test (procedure A)		
25 percent indentation load ratio loss; percent max.	25%	25%
Thickness loss percent max.	5%	5%
Rebound Resilience	45%	45%
Prime Urethane Density, pounds/cu. ft.	2.0 to 2.5	3.0 to 3.5

Paragraph 3.3.1.9 Upholstery padding material. Line 14, delete "0.4 to 0.9" and substitute ".001 to .0013". Line 15, add: "Initial thickness shall be measured with 1-pound load instead of 4-pound load." Line 17, after "inches" add "two layers of cotton may be substituted for the hair pad". Line 19, after "inches", add "one layer of cotton may be substituted for bound hair".

PAGE 6

Paragraph 3.3.1.9 (continued). Line 1, after "foam rubber" add "or urethane foam".

Paragraph 3.3.1.10 Base insulator material. Line 8, delete "0.8125 to 3.2" and substitute ".002 to .0035". Line 18, after "bound hair" add "a layer of cotton may be substituted for bound hair". At the end of the paragraph, add the following:

"A wire mat as specified in 3.3.3.1.2.3 shall be applied over the burlap whenever cotton has been used in lieu of bound hair for the seat decking or the back. The wire mat shall be secured in place by hog rings spaced not greater than five inches around the border wire or to the frame on four sides with staples having one-half inch leg not greater than five inches apart."

Paragraph 3.3.1.12, at the end of the paragraph add the following:

"Class 2 furniture when upholstered in artificial leather, shall have upholstery nails for class 1 furniture used for trim as design requires."

PAGE 7

Paragraph 3.3.1.14 Upholstery covers (class 2 furniture). Line 11, add "ribbed or".

PAGE 11

After paragraph 3.3.3.1.2, add new paragraph as follows:

"3.3.3.1.2.3 Wire mat (Class 2 Furniture). The wire mat shall have a series of steel wires uniformly spaced not more than one inch apart, running at right angles to longitudinal fiber cords which are uniformly spaced not more than eight inches apart. The wires shall pierce and pass through the center cords and shall be crimped around the border cords. The wires shall be 19 gage (nominal 0.041 inch diameter) oil-tempering steel wire with a tensile strength range of 226,000 p.s.i. The spirally wound fiber cords shall be constructed of not less than 30-pounds, Kraft paper. The center cords shall be not less than 0.16 inch in diameter, with or without a three-strand sisal or jute core, and shall have a breaking strength of not less than 100 pounds after being pierced. The border cords shall be not less than 0.125 inch in diameter with a breaking strength of not less than 100 pounds. Testing shall be as specified in paragraph 4.4.2."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

Paragraph 3.3.4.1 Lumber. Line 6, delete "MIL-W-6110" and substitute "MIL-STD-1363". Line 24 (right hand column) delete the last part of the paragraph beginning with "Exposed parts" and substitute the following:

"Exposed parts, except back posts on the davenport and easy chair, and the back posts, front legs and stumps of the occasional chair, shall be constructed of one piece of wood. Unexposed parts and the above exposed components shall be constructed of either one piece of wood or from full-length glued stock. The exposed components shall be cut so as to minimize visibility of glue lines and finished component shall contain not more than one glue line."

Paragraph 3.3.4.1.1 delete "Sweetgum, red, or sap."

Page 12

Paragraph 3.3.4.2, line 4: After "grooved", add "or compressed with longitudinal grooves."

Paragraph 3.3.4.4, last sentence: Delete "type I or II, class Z of."

Add the following paragraph in proper sequence:

"3.3.4.4.1 Alternate adhesive. For either assembly gluing, edge gluing, or built-up stock, and aliphatic resin emulsion type of adhesive, not a primarily polyvinyl acetate base adhesive, designed for use in furniture manufacturing, may be used. The adhesive shall meet the following requirements when tested in accordance with 4.4.4,4.4.5, 4.4.6, and 4.4.7:

Properties	Requirements
Block shear strngth at room temperature	2800 p.s.i. minimum average; 50 percent wood failure minimum average.
Heat resistance (Block shear strength at 150 degrees F)	Average block shear strength and wood failure shall be not less than 80 percent of the average values obtained at room temperature.
Viscosity, at 77 degrees F	1000 to 7000 centipoises.
Acidity of dried film	pH 5.0 plus or minus 1.5

Add new paragraphs after 3.3.4.10

"3.3.4.11 Welding and Brazing.

3.3.4.11.1 Fusion welding. Fusion welding consists of any welding process in which the weld is carried out solely by the melting of the metals to be joined, without any mechanical pressure. The joining is usually accomplished through the fusion of metal deposits from an external source.

3.3.4.11.2 Brazing. Brazing is a process wherein coalescence is produced by heating to suitable temperatures above 800 degrees F. and by using a filler metal having a melting point below that of the base metals. The filler metal is distributed between the surfaces of the joint by capillary attraction. The filler metal shall be nickel bronze rod (nickel content 9.5% tensile strength 70,000 - 75,000 p.s.i.) unless otherwise specified herein.

Page 13

Paragraph 3.4.1.3: Add the following at the end of the paragraph:

"Alternatively, imitation, separate welt boxing produced by a cushion boxing machine may be employed for cushions of class 2 items. This boxing shall be made of one piece of fabric folded over welting cords at each edge and doubled back. Cords shall be secured by stitching through the resultant three

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

thicknesses of material. The machine shall be adjusted so that sufficient space is available between stitching rows and welting cords to accommodate stitching rows for sewing top and bottom panels to the boxing. The top and bottom panels shall be sewn to the boxing with type 301 stitching through the resultant four thicknesses of material. The rows of 301 stitching shall be placed close to welt cords, and shall run between the cords and the boxing construction stitch rows. Boxing construction stitch rows and stitch rows for attaching panels shall not be made over one another. The resultant cushion cover shall not be made over one another. The resultant cushion cover shall give the appearance of separate weld construction, showing no stitches on the outside. Number of stitches for Type IV, artificial leather and expandable artificial leather shall be 5 to 7 stitches per inch."

Paragraph 3.4.1.4.1. Line 24, at end of alternate (2) add the following: "When cotton is used as an alternate to hair pad, delete the hog ring fasteners."

Page 16

Paragraph 3.4.2.1 Delete entirely and substitute the following:

"(Class 2, Method A construction). The upholstered items supplied under Method A shall conform to the requirements for Method B, except for spring units. The spring units and upholstery covers shall be formed to fit the specific designs of frames selected."

"All davenports require a minimum of five (5) legs, unless otherwise specified."

Paragraph 3.4.2.2.1 Wood frames (Class 2, Method B.

Line 5 delete "1-1/16" and substitute "1-1/32".

Paragraph 3.4.2.2.1, line 5 (top of page 17, left hand column) delete "2-7/8 inches" and substitute "3 inches". Line 6, delete "2-7/8 inches" and substitute "3 inches".

Line 16 (top of page 17, right hand column) after word "point" add new sentence "when width or wood member does not permit two 1/4 inch bolts or two dowels, one or two number 10 wood screws as required may be used at each securing point."

Delete 29th to 34th lines beginning with the word "When" and eding with the word "13/16 inch." and substitute the following. "The frame members for class 2, Method A furniture only, shall be not less than 13/16 inch in thickness."

Line 35, delete "68" and substitute "63".

Page 18

Paragraph 3.4.2.2.3 Coil spring and insulated seat platform (Class 2., Method B).

Line 15, (left column) after Webbing add "or strip."

Line 17, (right column) after "fastenings." insert "when polyethylene sheet fabric is used it shall be fastened to each spring on the front edge and not less than 5 inches apart on side and across the back. Alternatively, items with "wire-woven in burlap" , spring may be covered with polythylene sheet fabric or 10 ounce burlap and wire mat as specified in 3.3.3.1.2.3 secured to the border by hog rings spaced not greater than 5 inches apart.

Paragraph 3.4.2.2.3, lines 31 and 32 (right hand column) delete "or artificial leather".

Page 19

Paragraph 3.4.2.2.6, line 4, delete "arms" and substitute "top of arm frame."

Page 20

Paragraph 3.4.3.3.7.3, line 3, and line 10 delete "artificial or".

Line 28, delete "M" and substitute "IM".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

Add the following at the end of the paragraph:

"Loose seat and back cushions covered with artificial or genuine leather shall have pocket pleats on each end of the zipper boxing piece. Near the bottom edge of the back cushion and near the back edge of the seat cushion. Not more than three pieces including the zipper pieces of material shall be used in the cushion boxing."

"Alternatively, in lieu of pocket pleats, when covering material is artificial or genuine leather, upholstery fabric of comparable color may be used for the zipper boxing piece of the cushion border. Doubled over fabric material, double stitched through each end of the zipper tape may be used in lieu of a top and bottom as specified in 3.4..2.2. .3"

After paragraph 3.4.2.2.7.3 add the following new paragraph 3.4.2.2.7.4 Application of Welts. "The covered welting cord of same upholstery material, unless otherwise specified, or as shown by illustration, shall be applied around perimeter of bottom base frame, outside backs, arms and wings of sofas and chairs."

Paragraph 3.4.2.3.2.1, Line 9, delete "2 inches" and substitute "1-7/8 inches."

Line 18, after "nails" add "or blue-barbed nails 7/8 inch long."

Line 19, delete "1-1/2 inches long."

Page 21

Paragraph 3.4.2.3.2.1, line 52, delete "and slips". Delete last sentence beginning with "Twine" and ending with "springs."

Page 25

After paragraph 4.3.1 add the following new paragraph:

4.3.1.1 as follows:

"4.3.1.1 Testing of components for Class 2 furniture. At the time of preproduction sample examination, and quarterly thereafter during the life of the contract, unless otherwise specified, the contractor shall make the following available to the Government representative:

(a) Certificates of compliance* and/or laboratory test reports** as indicated in Table V A for the components required for the furniture items on the contract or order. Where laboratory test reports are required, the laboratory must be acceptable to the Government. All certificates and reports shall identify clearly the source and manufacturer's code, model, or other trade designation for the applicable component. If the source, composition, or other changes are made in a component during the life of the contract, new certificates of compliance and/or laboratory test reports shall be made available to the Government representative.

(b) Statements annotated on the foregoing reports as to whether or not the components are regularly purchased in the quality indicated for his commercial production or are specially purchased for Government contracts.

Acceptance of manufactured items with respect to quality of components will be based on review of these reports by the Government representative. However, at any time during the contract period the Government representative may sample and test one or more components being used in the manufacture of items for the Government. If any component fails to meet requirements, no further shipments will be permitted until either the discrepancy has been resolved, or a new component lot has been received, tested and incorporated into furniture units on hand.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

*Certificate of compliance (certificate) shall mean a certification by the contractor or his supplier that the component complies with the characteristic requirements referenced in Table V A. While specific test data need not be presented it is assumed that tests have been run on that or like material to determine compliance.

**Laboratory test report (test report) shall mean a report presenting test data on that specifc lot of material being incorporated in the furniture.

TABLE V. A. Testing of Components of Class 2 Furniture

Component	Characteristic	Requirement Reference	Test Method	Sample Unit	Document Required
Wood	Moisture content	3.3.4.1	MIL-STD-1363	one piece	Test report
Dowels	Moisture content	3.3.4.2	MIL-STD-1363	5 dowels	Test report
Adhesive	Block shear Heat resistance Acidity of dried film	3.3.4.4.1 3.3.4.4.1 3.3.4.4.1	1031 of Fed. Test Method Std. No. 175 and para 4.4.5 1/ -2/ -3/	1/2 pint	Test report
Upholstered padding material	Composition Density, lb/cv. in. Compressibility, lb./sq. in.	3.3.1.9 3.3.1.9 3.3.1.9	Certificate MIL-H-10368	1/2 yard	Test report
Webbing sheet form	Weight/sq. yd., oz.	3.3.1.2.1	5041 of CCC-T-191	1/2 yard	Certificate
strip form	Identification Yarns per inch	3.3.1.2.2	Certificate 5050.1 of) CCC-T-191)		Certificate
	Breaking strength, lb.		5100 of CCC-T-191)	3 yards	Test report
	Wgt. per 144 l in. yds.		5041 of CCC-T-191		
Burlap	Wgt./sq. yd., oz.	3.3.1.1	5041 of CCC-T-191	1/2 yard	Certificate
Muslin	Wgt./sq. yd., oz.	3.3.1.14.1	5041 of CCC-T-191	1/2 yard	Certificate
Cambric	Wgt./ 1 in. yd. oz.	3.3.1.3	5041 of CCC-T-191	1/2 yard	Certificate
Fabric	Wgt./sq yd. (oz.)	CCC-C-oo540	5041 of CCC-T-191	1/2 yard	Certificate
	Identification of material	CCC-C-00540	Applicable of CCC-F-00540	1/2 yard	Certificate
	color fastness	CCC-C-00540	Applicable of CCC-T-191	1/2 yard	Test report

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

Component	Characteristic	Requirement Reference	Test Method	Sample Unit	Document Required
	Coating Compound	CCC-C-00540	Commercial	1/2 yard	Certificate
	Water Resistance	CCC-C-00540	Std Applicable of CCC-C-00540	1/2 yard	Certificate
	Mildew Resistance	CCC-C-00540	Applicable of CCC-C-00540	1/2 yard	Certificate
Leather, artificial	Total weight	3.3.1.14.3	4.4.1 of CCC-A-700	3 yards	Test report
	Coating weight	3.3.1.14.3	4.4.1 of CCC-A-700	3 yards	Test report
	Breaking strength	3.3.1.14.3	5100 of CCC-T-191	3 yards	Test report
	Adhesion of coating	3.3.1.14.3	4.4.3 or 4.4.4 of CCC-A-700	3 yards	Test report
	Blocking	3.3.1.14.3	5872 of CCC-T-191	3 yards	Test report
	Treatment (a) 1	3.3.1.14.3	5903T of CCC-T-191	3 yards	Certificate
Leather, artificial	Treatment (b)	3.3.1.14.3	4.4.8 of CCC-A-700	3 yards	Certificate
Leather, genuine	Resistance to crocking	3.3.1.14.4	3011 of KK-L-311		
	Breaking strength	3.3.1.14.4	2031 of KK-L-311		
	Acidity	3.3.1.14.4	6621 of KK-L-311		
Twine	Identification Breaking strength	3.3.1.5	Certificate 4102 of CCC-T-191	one spool or tube	Certificate
Top deck covering (when rep material used)	Wgt./sq.yd., oz.	3.4.2.2.3	5041 of CCC-T-191	1/2 yard	Certificate
Front Edge cover (when base insulator used)	Identification Density Compressibility	3.4.1.4.1	Certificate MIL-H-10368	1/2 yard	Test Report
Foam latex pad	Apparent density Compression resistance Flexing Air-oven aging	3.3.1.8.1	MIL-R-5001	72 sq. in.	Test report

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

Component	Characteristic	Requirement Reference	Test Method	Sample Unit	Document Required
In-core latex foam	Apparent density Compression resistance Flexing Air oven aging	3.3.1.8.3	MIL-R-5001	72 sq. in.	Test Report
Cotton felt	Composition Wgt./yd. (27 in. width)	3.3.1.4.1	Certificate 5041 of CCC-T-191	1/2 yard	Certificate
Cellulose fiber felt	Density, lb./cu.ft	3.3.1.4.1	5041 of CCC-T-191	1/2 yard	Certificate
Thread	Breaking strength, lbs.	3.3.1.6	4100 of CCC-T-191	one spool, cone or tube	Certificate
	Fastness to laudering		4610 of CCC-T-191		
Slide fastener	Breaking strength Endurance Holding strength Salt spray	3.4.2.2.7.3	V-F-106	3	Certificate
Springs (all units except Method C, Flat-spring base)	Composition Tensile strength	3.3.2	Certificate	4 ft.	Certificate
Springs (for Method C, Flat spring base) Hanger bars and frame irons	Composition	3.4.2.3.2.2.1	Certificate	6 inches	Certificate
C-Sahped leaf spring and arch supports	Composition Rockwell hardness	3.4.2.3.2.2.2	Certificate	6 inches	Certificate
Crossbars, extension leaf, connecting band, stabilizers	Composition Rockwell hardness	3.4.2.3.2.2.3	Certificate	6 inches each	Certificate
Border wire	Tensile strength	3.4.2.3.2.2.7	Certificate	2 ft.	Certificate
Finish system Stain Wood filler Sealer Washcoat Lacquer	Resistance to alcohol boiling water ultra-violent print Toughness & adhesion	3.3.4.6 3.3.4.7 3.3.4.8 3.3.4.9 3.3.4.5 (as above)	Panel test of finish TT-L-57 4.3.3.3 4.3.3.6 4.3.3.7 4.3.3.4 AA-C-300	1/2 pint each	Test report

1/ The following modifications apply when testing casein-type adhesive. The test blocks shall be placed under pressure between 10 and 20 minutes after spreading the adhesive, the adhering pressure shall be 175 ± 25 pounds per square inch, and the test blocks shall be held under pressure for at least four hours.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

2/ The following modifications apply when testing animal adhesive. The moisture content of the wood shall be from 6 to 9 percent. The joints shall be conditioned at a relative humidity of 40 ± 4 percnet.

3/ Whenever a specimen fails at a load of less than 2,800 pounds per square inch and the failure occurs 50 percent or more in the wood, the specimen shall be disregarded in computing the average. In case the shearing strength of one or more specimens is 2,800 pounds per square inch or higher, the variation among individual specimens is 10 percent or more (based on the strongest joint) the test shall be run again, provided the average is less than the required 2,800 pounds per square inch.

Page 26

Paragraph 4.3.2.1, table of defects: Under Construction and Workmanship, third defect (Joint open--), change defect classification to "minor".

Classification column (top of page, right hand column): Reverse classification headings as follows: "Major" "Minor".

Page 30

Add the following new paragraphs:

"4.4.4. Shear strength test. Block shear strength shall be determined in accordance with Method 1031 of Fed. Test Method Std. No. 175.

4.4.5 Heat resistance test. Heat resistance shall be determined in accordance with Method 1031 of Fed. Test Method Std. No. 175, except conditioned specimens to be heated at 150 degrees F. plus or minus 2 degrees F. for 16 hours plus or minus 1 hour in a forced air circulation oven. Each specimen shall be tested while still hot and immediately upon removal from the oven.

4.4.6 Viscosity test. Viscosity at 77 degrees F. shall be determined per Brookfield viscosity test procedure described in MMM-A-193, except that alternatively an LVF Brookfield Viscometer at 12 r.p.m. may be used.

4.4.7 Acidity of dried film test. The acidity of dried film shall be determined in accordance with Method 4011 of Fed. Test Method Std. No. 175.

Page 32

Paragraph 5.2.1.1.2, Delete and substitute the following:

5.2.1.1.2 Nailed wood containers. Each nailed container conforming to PPP-B-621 shall be provided with skids in accordance with the container specification.

Page 33

Delete paragraphs 5.2.2.1 and 5.2.2.2 entirely and substitute the following:

5.2.2.1 Davenport (classes 1 and 2-type I) and love seat (class 2-type VI). Each class 1 or class 2 davenport or love seat, packaged as specified in 5.1, shall be packed in an unsheathed crate conforming to PPP-C-650, style B except that the dimension limitations shall be waived and the distance between intermediate members shall not exceed eight inches. Blocking and bracing shall be applied to immobilize the item of furniture while in transit and maintain 1 inch clearance between the legs and base of the crate. Blocking and bracing shall be provided with cushioning material wherever it comes in contact with the furniture item.

5.2.2.2 Easy chair (classes 1 and 2-type II), occasional chair (classes 1 and 2-type III and class 2-type IV), and sectional cavenport (class 2-type V). Each class 1 or class 2 and each chair section of the sectional davenport, packaged as specified in 5.1, shall be packed in a close fitting shipping container conforming to PPP-B-591, class 1, style A except that the minimum grade of fiberboard shall be 275; PPP-B-601, domestic type, style A, except that the minimum thickness of the plywood shall be 3/16 inch; PPP-B-621, class 1, style 2, 2 1/2, 3, 4, or 4 1/2; PPP-B-636, type CF, class domestic, grade 275, style FOL; or PPP-B-640, class 1, style G. When boxes conforming to PPP-B-636 are used, the manufacturer's joint shall be lapped and secured with metal fastening spaced not more than 2 inches apart.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

The box shall be closed in accordance with the appendix to the box specification."

Page 34

After paragraph 5.3.2.1 and the following new paragraph.

"5.3.3 Special marking. The top panel of each shipping box, with the item of furniture in it's proper upright position, shall be marked in characters not less than 2 inches high as follows:

FURNITURE
HANDLE WITH CARE
TOP
THIS SIDE UP

Arrows shall be placed on all four sides of each shipping box not more than 4 inches down from the top edge to indicate the position in which the container shall be stored and loaded during shipment. The word "UP" shall be marked at the base of the arrows in letters not less than 2 inches high.

The front and back panels of each shipping box shall be marked in characters not less than 2 inches high as follows:

Page 34

Paragraph 6.2, sub-paragraph (e): Delete in its entirety and substitute: "(e) Thickness if other than specified (see 3.3.1.8.3.2)".

GSA DC 74-12373

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.