AA-P-560a
April 27, 1966

SUPERSEDING
Int. Fed. Spec. AA-P-00560 (GSA-FSS)
May 14, 1964

FEDERAL SPECIFICATION

POINTER, LECTURE

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 The lecture pointers covered by this specifiation are of hardwood, with rubber tips, and of one type and one grade.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specification:

PPP-B-636—Box, Fiberboard.

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-W-6110—Wood; Determination of Moisture Content of.

Military Standards:

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.

3.1.1 *Wood.* Pointers shall be of hardwood meeting the requirements of this specification. Wood shall be uniformly dried to a moisture content of not more than 12 percent (see 4.4.1) and shall be free from imperfections such as loose knots, chips, dents, pitch pockets, chipouts, splinters, and splits. Mineral specks, burls, tight knots not exceeding 1/16-inch in diameter, and birds' eyes will be permitted.

3.1.2 *Rubber.* Rubber used for the tip shall be natural rubber, synthetic rubber, or a mixture of natural and synthetic rubber.

3.1.3 *Screw eye.* The screw eye shall be of steel and shall have a bright plated finish.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:40Z
Check the source to verify that this is the currentversion before use.

3.2 **Construction.** The pointer shall be made from a wooden rod turned, polished, tapered, and corners rounded in accordance with good commercial practice. A screw eye shall be centered in the butt end of the rod. The opposite end of the rod shall be undercut and tapered for a distance of not less than 1/2 inch. A tapered rubber tip shall be securely fastened with good quality adhesive to the undercut portion of the rod. The permissible departure from a flat, smooth surface shall be not more than 3/16 inch (see note and 4.4.2).

Note. Permissible departure from the flat, smooth surface refers to the distance between two lines parallel to the length of the pointer, one line touching points on the edge of the pointer of maximum bulge, the other line touching points on the edge where there is a maximum depression.

3.3 **Dimensions and tolerances.** The overall length of the pointer exclusive of screw eye shall be 36 ± 1 inch.

3.3.1 *Rod.* The diameter of the rod measured at 1-1/2 inches from the rubber tip and at 1-1/2 inches from the screw eye shall be 9/16 ± 1/16 inch. The diameter of the pointer measured at 12 inches from the rubber tip shall be 3/32 ± 1/32 inch less than the diameter measured at 1-1/2 inches from the rubber tip.

3.3.2. *Tip.* The tip shall be not less than 1-1/4 inches in length. The untapered end of the tip shall have the same outside diameter as the rod at the rubber-tip end.

3.3.3 *Screw eye.* The inside diameter of the screw eye shall be not less than 1/4 inch.

3.4 **Finish.** The wooden rod shall have a clear coating of shellac, varnish, or lacquer. All surfaces of the pointer shall have a smooth uniform finish.

3.5 **Workmanship.** Pointers shall be free from defects and imperfections which affect appearance or which impair serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 **Responsibility for inspection.** Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 **Sampling.**

4.2.1 *Lot.* For purposes of sampling, a lot shall consist of all lecture pointers offered for inspection at one time.

4.2.2 *Sampling for visual and dimensional inspection.* A random sample of pointers shall be taken from each lot in accordance with MIL-STD-105, inspection level S-3, acceptable quality level (AQL) 4.0 percent defective. The sample unit shall be one pointer.

4.2.3 *Sampling for test.* A random sample of pointers shall be taken from each lot in accordance with MIL-STD-105, inspection level S-1, AQL 4.0 percent defective. The sample unit shall be one pointer.

4.2.4 *Sampling for preparation for delivery.* Sampling shall be in accordance with MIL-STD-105. For examination of interior packages, the sample unit shall be one shipping container fully prepared for delivery and selected just prior to the closing operations. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be II and the AQL shall be 4.0 defects per hundred units.

4.3 **Visual and dimensional examination.** Samples taken in accordance with 4.2.2 shall be examined for defects listed in table I. Any lecture pointer in the sample contain-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

ing one or more defects shall be rejected. If the number of defective pointers in the sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

TABLE I. *Classification of lecture pointer defects*

Examine	Defects
Material:	
Wood	Not of hardwood (3.1.1).
	Not free from imperfections listed in 3.1.1.
Rubber	Not as required in 3.1.2.
Screw eye	Not as required in 3.1.3.
Construction:	Not in conformance with 3.2.
Dimensions and tolerances:	
Overall length	Not as required in 3.3.
Rod	Not as required in 3.3.1.
Tip	Not as required in 3.3.2.
Screw eye	Not as required in 3.3.3.
Finish:	Not in conformance with 3.4.
Workmanship:	Not in conformance with 3.5.

4.4 **Tests.** Samples taken in accordance with 4.2.3 shall be tested as described in 4.4.1 and 4.4.2. Any lecture pointers in the sample containing one or more defects shall be rejected. If the number of defective pointers in the sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

4.4.1 *Moisture content.* Moisture content shall be determined by the oven drying or electrical moisture meter method described in MIL-W-6110.

4.4.2 *Straightness tolerance.* Position the pointer on a flat, smooth surface in a horizontal plane. Roll the pointer 360° by gently touching the pointer at 1-1/2 inches from the rubber-tip end. Continue the rolling and determine the maximum departure of the pointer from the flat surface. Measure the distance of departure. (See 3.2 and note.)

4.5 **Inspection of preparation for delivery requirements.** An inspection shall be made to determine that packaging, packing, and marking requirements of section 5 are complied with. Defects shall be scored in accordance with table II.

TABLE II. *Classification of preparation for delivery defects*

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate sealing.
	Bulging or distortion of container.

5. PREPARATION FOR DELIVERY

(For civil agency procurement the definitions and application of levels of packaging and packing shall be in accordance with Fed. Std. No. 102.)

5.1 **Packaging.** Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 *Level A.* Twelve pointers shall be packaged together in a close-fitting box conforming to PPP-B-636, class weather-resistant, FPF. The box shall be closed and waterproof sealed in accordance with the appendix to the box specification.

5.1.2 *Level B.* Twelve pointers shall be packaged together in a close-fitting paperboard sleeve or tied together with not less than 2 ties of cotton tape.

5.1.3 *Level C.* The pointers shall be packaged in accordance with supplier's commercial practice.

5.2 **Packing.** Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 *Level A.* Eight unit packages of pointers shall be packed in a close-fitting box conforming to PPP-B-636, V3c. The box shall be closed, waterproof sealed with tape and strapped in accordance with the appendix to the box specification.

5.2.2 *Level B.* Eight unit packages of pointers shall be packed in a close-fitting box conforming to PPP-B-636, class domes-

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:40Z
Check the source to verify that this is the currentversion before use.

tic. The box shall be closed in accordance with the appendix to the box specification.

5.2.3 *Level C.* The pointers shall be packed to insure carrier acceptance and safe delivery to destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 **Standard pack (civil agency procurements).** The standard pack for civil agency procurements shall be as specified in 5.1.2 and 5.2.2 (see 6.3).

5.4 **Marking.**

5.4.1 *Civil agencies.* In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.4.2 *Military activities.* In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 **Intended use.** Lecture pointers are intended for use in directing attention to material presented on chalkboards and flipcharts.

6.2 **Ordering data.** Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(*a*) Title, number, and date of this specification.

(*b*) Selection of applicable levels of packaging and packing required (see 5.1 and 5.2).

6.3 **Standard pack for civil agencies.** The standard pack requirements in 5.3 are intended for use in procurements of stores stock replenishments. Procuring officers should use the standard pack requirements when it is known that the material will be shipped from a supplier to a domestic warehouse, supply depot, or intermediate storage point for temporary storage, subsequent issue, or shipment to eventual user.

6.4 **Transportation data.** Transportation descriptions and minimum weights applicable to this commodity are:

Rail:

Blackboard pointers.
Carload minimum weight 24,000 pounds, subject to Rule 34, Uniform Freight Classification.

Motor:

Blackboard pointers.
Truckload minimum weight 24,000 pounds, subject to Rule 115, National Motor Freight Classification.

DOD coordination has been waived.

☆ U.S. GOVERNMENT PRINTING OFFICE: 1966—203355/414

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.