[METRIC]
A-A-59748/1
October 25, 2002

COMMERCIAL ITEM DESCRIPTION

# FUSEHOLDER BLOCK, DEAD-FRONT, 60 AMPERES, 1 POLE, ACCOMODATES UNDERWRITER LABORATORY (UL) CLASS J FUSE CARTRIDGES

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies.

The complete requirements for procuring the fuseholders described herein shall consist of this document and the issue in effect of CID A-A-59748.

CLASSIFICATION. This CID uses a classification system that is included in the Part Identification Number (PIN) as shown in the following example (see notes).




SALIENT CHARACTERISTICS.

Interface and physical dimensions. Fuseholders supplied to this CID shall be as specified herein (see figure 1).

Ampere rating. The ampere rating shall be 60 amperes maximum.

Voltage rating. The voltage rating shall be 600 V ac maximum.

Fuseholder accommodation. This fuseholder accepts class J fuses.

Blown fuse indicator. Applicable fuseholders shall be supplied with a blown fuse indicator light in handle (see table I.)

TABLE I. Electrical characteristics.

| AA59748/01- | Blown fuse indication |
|---|---|
| 001 | Nonindicating |
| 002 | Indicating |

NOTES.

PIN. The PIN should be used for Government purposes to buy commercial products to this CID. See section 2 for PIN format example.

AMSC N/A FSC 5920
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:25Z
Check the source to verify that this is the current version before use.




| mm | Inches |
|---|---|
| 3.0 | 0.118 |
| 6.5 | 0.256 |
| 40.0 | 1.575 |
| 62.0 | 2.441 |
| 89.0 | 3.504 |
| 115.0 | 4.528 |
| 122.0 | 4.803 |

NOTES:

1. Dimensions are in inches.
2. Tolerance is ±0.13 mm (± .005 inch), unless otherwise specified.

FIGURE 1. Configuration and dimensions.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:25Z
Check the source to verify that this is the current version before use.

Commercial products. As part of the market analysis and research effort, this CID was coordinated with the following manufacturers of commercial products. At the time of CID preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

| Manufacturer's CAGE | Manufacturer's name and address |
|---|---|
| 75915 | Littelfuse Incorporated<br>800 E. Northwest Highway<br>Des Plaines, IL 60016-3096<br>Phone number (847) 824-1188<br>Facsimile number (847) 391-0894<br>E-mail: electronics@littelfuse.com<br>URL: www.littelfuse.com |

Part number (P/N) supersession data. This CID supersedes the following MFR's P/N's as shown. This information is being provided to assist in reducing proliferation in the Government inventory system.

TABLE II. P/N supersession data.

| CID dash number (see table I) | MFR's CAGE 75915 |
|---|---|
| AA59748/01- | MFR's P/N 1/ |
| 001 | LPSJ60-1 |
| 002 | LPSJ60-1ID |

1/ The manufacturer's P/N shall not be used for procurement to the requirements of this CID. At the time of preparation of this CID, the aforementioned commercial products were reviewed and could be replaced by the CID P/N shown.

MILITARY INTERESTS:

Custodians:
Navy - EC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - 7FXE

Preparing activity:

DLA-CC

Project 5920-0764-01



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:25Z
Check the source to verify that this is the current version before use.