NOT MEASUREMENT SENSITIVE

MIL-L-11484/228
5 June 1995

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, ACHIEVEMENT AWARD, OFFICE OF PROTECTION SERVICES, SMITHSONIAN INSTITUTE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

DIMENSIONS:
DIAMETER: 5/8 inch (1.59 cm) (REF)
THICKNESS (At Edge): 0.085 inch ± 0.010 inch (0.216 cm ± 0.025 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-17T17:30Z
Check the source to verify that this is the current version before use.

2. Attaching device shall be prong with pick and flat ball clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

Custodians:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0812)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:30Z
Check the source to verify that this is the current version before use.