NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/231E(IH)
12 November 2024
SUPERSEDING
MIL-DTL-11484/231D(IH)
6 January 2020

DETAIL SPECIFICATION SHEET

# LAPEL BUTTON, LIFESAVING MEDAL, OFFICE OF PROTECTION SERVICES, SMITHSONIAN INSTITUTE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.




MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Brass, Oxidized, Buffed Relieved and shall match The Institute of Heraldry Metal Finish Chip Number 4.

DIMENSIONS:
DIAMETER: 5/8 inch (REF)
THICKNESS (At edge): 0.085 inch ± 0.005 inch

ATTACHING DEVICE:
1. Attaching device shall be prong with pick and flat ball clutch.

2. The prong shall be centered on the reverse side and fused or soldered to the lapel button.



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:31Z
Check the source to verify that this is the current version before use.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. This item is not authorized for commercial sale and may be produced only under Government contract. A copy of the original purchase order from the Government Agency concerned must accompany all written requests prior to the loan of a government hub or die.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2025-012)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:31Z
Check the source to verify that this is the current version before use.