MILITARY SPECIFICATION SHEET

CONVERTERS, SYNCHRO SIGNAL (PANEL MOUNTED) TYPE EON

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-24105.

TABLE I. Requirements.

Requirement	Value	Unit	Tolerance
Input reference voltage	115	AC volts	±1%
Input frequency	400	Hertz	±1%
Output reference voltage	26	AC volts	±1%
Output frequency	400	Hertz	±1%
Channel(s) input and output	1 In, 1 Out		
Gear ratio	2 : 1		
Sync time	7.0	Seconds	Max.
Accuracy:			
Static accuracy	1.0	Degrees	Max.
Constant velocity	1.0	Degrees	Max.
Harmonic motion	1.0	Degrees	Max.

AMSC N/A FSC 6125

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:13Z
Check the source to verify that this is the current version before use.

NOTES:

1. The synchro signal converter identified and specified by this specification shall conform to all requirements and be subjected to all tests delineated in MIL-C-24105 unless otherwise specified.

TABLE II. Military part number variant characteristics.

Military part no.	Number of channels	Output device		Classification (see MIL-C-24105, 1.2)
		Size	Type	
M24105/44-01	Two	23	CX	E 0 N A
M24105/44-02	Two	23	CDX	E 0 N D
M24105/44-03	Two	23	TRX	E 0 N F
M24105/44-04	Two	23	TDX	E 0 N J

Custodians:
Navy - SH

Review activities:
Navy - OS
DLA - GS

Preparing activity:
Navy - SH
(Project 6125-0239-43)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:13Z
Check the source to verify that this is the current version before use.