# MILITARY SPECIFICATION SHEET

## CONVERTERS, SYNCHRO SIGNAL (PANEL MOUNTED) TYPES J1F AND J2F

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-24105.

TABLE I. Requirements.

| Requirement | Value | Unit | Tolerance |
|---|---|---|---|
| Input reference voltage | 26 | AC volts | ±1% |
| Input frequency | 400 | Hertz | ±1% |
| Output reference voltage | 115 | AC volts | ±1% |
| Output frequency | 400 | Hertz | ±1% |
| Channel(s) input and output | 1 In, 3 Out | | |
| Gear ratio | 36: 1/18,1,36 | | |
| Sync time | N/A | Seconds | Max. |
| Accuracy: 1/18 speed; | (1) (2) | | |
| Static accuracy | 0.2 0.5 | Degrees | Max. |
| Constant velocity | 0.2 0.5 | Degrees | Max. |
| Harmonic motion | 0.2 0.5 | Degrees | Max. |
| 1 speed; | | | |
| Static accuracy | 0.5 | Degrees | Max. |
| Constant velocity | 0.5 | Degrees | Max. |
| Harmonic motion | 0.5 | Degrees | Max. |
| 36 speed; | | | |
| Static accuracy | 1.0 | Degrees | Max. |
| Constant velocity | 1.0 | Degrees | Max. |
| Harmonic motion | 1.0 | Degrees | Max. |

FSC 6125

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:17Z
Check the source to verify that this is the current version before use.

NOTES:

1. The synchro signal converter identified and specified by this specification shall conform to all requirements and be subjected to all tests delineated in MIL-C-24105 unless otherwise specified.
2. The converter's 1/18-speed accuracy is based on gear type 1 or 2 as specified in 1.2.2 of MIL-C-24105.

TABLE II. Military part number variant characteristics.

| Military part no. | Number of channels | Output device | | Classification (see MIL-C-24105, 1.2) |
|---|---|---|---|---|
| | | Size | Type | |
| M24105/76-01 | One | 23 | CX | J 1 F A |
| M24105/76-02 | One | 23 | CX | J 2 F A |
| M24105/76-03 | One | 23 | TRX | J 1 F F |
| M24105/76-04 | One | 23 | TRX | J 2 F F |

Custodians:
Navy - SH

Review activities:
Navy - OS
DLA - GS

Preparing activity:
Navy - SH
(Project 6125-0239-75)



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:17Z
Check the source to verify that this is the current version before use.