MIL-B-1658D
30 July 1982
SUPERSEDING
MIL-B-1658C
4 May 1977

MILITARY SPECIFICATION

BAG, FIELD COOKING OUTFIT, CUTLERY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers an olive drab, cotton duck cutlery bag in one type and size, with a drawstring closure.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

V-T-285	-	Thread, Polyester
T-T-881	-	Twine, Cotton, Seine
UU-P-268	-	Paper, Kraft, Wrapping
CCC-C-419	-	Cloth, Duck, Cotton, Unbleached, Plied-Yarns Army and Numbered
CCC-D-950	-	Dyeing and Aftertreating Processes for Cotton Cloths
DDD-L-20	-	Label for Clothing, Equipage and Tentage, (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7360

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:35Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-T-43566 - Tape, Textile, Cotton, General Purpose, Natural or in Colors

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment

DRAWING

US ARMY NATICK RESEARCH AND DEVELOPMENT LABORATORIES

5-3-54 - Bag, Field Cooking Outfit, Cutlery: Assembly Details and Sections

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Guide sample. Guide samples of the end item, when furnished, are solely for guidance and information to the contractor (see 6.3). Variations from this document may appear in the sample, in which case this document shall govern.

3.2 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 6.2 and 6.4).

3.3 Materials. Materials specified shall conform to the applicable documents and requirements specified herein (see 6.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:35Z
Check the source to verify that this is the current version before use.

3.3.1 Cloth, cotton, duck. The cloth shall conform to type I, No. 10 hard texture of CCC-C-419.

3.3.1.1 Color and treatment. The cloth shall be dyed to match shade olive drab No. 7 and shall conform to type I, class B of CCC-D-950.

3.3.2 Tape, textile, cotton. The tape shall be dyed to match shade olive drab No. 7 and shall conform to type I, class 4, 3/4 inch (19 mm) width of MIL-T-43566.

3.3.3 Thread, polyester. The thread for all stitching shall conform to type I, class 1, sub-class E, size FE for binding of V-T-285. The thread shall be dyed olive drab 7 to match shade S-1 (CA 66022).

3.3.4 Twine, cotton, seine. The cotton seine twine shall conform to type II, No. 120 of T-T-881.

3.4 Construction. The construction shall conform in all respects to the drawings listed in section 2 and as specified herein.

3.4.1 Stitches, seams and stitching. Stitching shall conform to stitch type 301 of FED-STD-751, 8 to 10 stitches per inch.

3.4.1.1 Type 301 stitching. Ends of stitching shall be backstitched or overstitched not less than 1 inch except where ends are turned under or caught in other seams and stitching. Thread tension shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be imbedded in the materials sewed.

3.4.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during stitching, the stitching shall be repaired by restarting the stitching a minimum of one inch back of the end of the stitching. 1/

b. Thread breaks, or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of one inch in back of the defective area, continue over the defective area and continue a minimum of one inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials and restitching in the required mannner. 1/

1/ When making the above repairs, the ends of the sitching are not required to be backstitched.

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:35Z
Check the source to verify that this is the currentversion before use.

3.4.2 Thread ends. All thread ends shall be trimmed to 1/4 inch maximum length.

3.4.3 Lubrication of thread. There shall be no lubrication of the thread by any means, prior to or during sewing (see 4.4.1.1).

3.5 Marking. The identification marking shall be applied in the location shown on the applicable drawing and shall conform to type IV, class 5 of DDD-L-20. The letters "US" shall be applied in the size characters and in the location indicated on the applicable drawing and shall conform to type IV, class 9 of DDD-L-20. Fastness of class 9 marking shall be as specified for class 5 marking.

3.6 Repairs. Repairs such as mends, darns, patches or splices are not permitted on the bag.

3.7 Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in 4.4.3.1, shall be removed from production and replaced with nondefective and properly matched components.

3.8 Workmanship. The finished and assembled bag shall conform to the quality of product established by this document. The occurence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.3), it shall be examined for the defects specified in 4.4.3.1 and 4.4.3.2. The presence of any defect shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:35Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.1.1 Certification. The contractor shall furnish a certificate of compliance for the requirement specified in 3.4.3.

4.4.2 In-process inspection. Inspection shall be made at any point or during any phase of the manufacturing process to determine whether cut lengths, cut parts, markings for location of components, and location of assembled component parts are in accordance with specified requirements. Whenever nonconformance is noted, corrections shall be made to the parts affected and lot in process. Parts which cannot be corrected shall be removed from production.

4.4.3 End item examination. The end item shall be examined in accordance with 4.4.3.1 and 4.4.3.2. The lot size shall be expressed in units of one bag. The sample unit shall be one bag.

4.4.3.1 Visual examination. The end item shall be examined for the defects listed below. The inspection lot shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

Examine	Defect	Classification Major	Minor
Fabric	Hole, cut, tear, smash, broken or missing yarn, or open place clearly visible at normal inspection distance (approximately 3 feet)	X	
Tape	Not firmly and tightly woven; edges frayed or scalloped.	X	
	Multiple floats		X
	Any cut, hole, tear or smash	X	
	Abrasion mark, slub, broken end or pick		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:35Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Classification Minor
Open seam	1/2 inch or less		X
	More than 1/2 inch	X	
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken, or when two or more consecutive skipped or runoff stitches occur.		
Raw edge (on edge required to be finished)	More than 1/2 inch in length when securely caught in stitching	X	
	NOTE: Raw edge not securely caught in stitching shall be classified as an open seam.		
Runoff (see open seam)			
Seam and stitch type	Wrong seam or stitch type	X	
Stitch tension	Loose, resulting in a loose bobbin or top thread		X
	Excessively tight, resulting in puckering of material		X
Stitches per inch	One stitch less than minimum specified		X
	Two or more stitches less than minimum specified	X	
	One or more stitches in excess of maximum specified		X
	NOTE: Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the materials in order to sew over heavy places or heavy seams, or in turning corners shall be classified as follows:		
	(a) Within the minor defect classification - no defect		
	(b) Within the major defect classification - minor defect		

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:35Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Classification Minor
Thread breaks, skipped stitches, or runoffs	Not overstitched as specified		X
NOTE:	Thread breaks or two or more consecutive skipped or runoff stitches not overstitched shall be classified as open seams.		
Ends of stitching	Not secured as specified		X
Rows of stitching	Any row missing	X	
Components and assembly	Any component part omitted or not as specified or any required operation omitted (unless otherwise classified herein)	X	
	Needle chews	X	
	Any mend, darn, patch or splice	X	
Binding	Loosely applied but not exposing raw edge of material		X
	Loosely applied exposing raw edge of material	X	
	Not turned under or finished in seam		X
Marking	Omitted, illegible, incorrect, or misplaced		X
Location markings	Drilled	X	
	Printed marking more than 1/32 inch in width		X
Cleanness	Any spot or stain clearly noticable		X
Drawstrings	Not tied as specified		X
Thread ends	Not trimmed to 1/4 inch maximum length		X

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:35Z
Check the source to verify that this is the current version before use.

4.4.3.2 Dimensional examination. Examination shall be made for compliance with all dimensions shown on the drawings which can be examined on the end item, including stitch margins and gauge, excluding reference dimensions. Any dimension exceeding the applicable tolerance shall constitute a defect. The inspection level shall be S-3 and the AQL shall be 10.0 defects per hundred units.

4.4.4 Packaging inspection. An examination shall be made to determine that preservation, packing and marking requirements comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged with the exception that it need not be closed. Examination of closure defects listed below shall be made on shipping containers fully packaged. The lot size shall be the number of containers in the inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged or not as specified
Workmanship	Inadequate application of components, such as incomplete closure of container flap, improper taping, loose strapping, inadequate stapling Bulged or distorted container
Content	Number of bundles per container is more or less than specified 1/

1/ For this defect, one bundle shall be examined from each shipping container in the sample.

4.4.5 Palletization examination. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the end item inspection lot. The inspection level shall be S-1 and the AQL shall be 6.5 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:35Z
Check the source to verify that this is the current version before use.

Examine	Defect
Finished dimensions	Length, width or height exceeds specified maximum requirements
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Loan not bonded with required straps as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Ten bags shall be evenly stacked, alternately reversed top to bottom, to form a compact bundle and securely tied at each end with cotton tape or twine.

5.1.2 Commercial. Bags shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. One hundred twenty bags, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to grade V2s, style RSC-L of PPP-B-636. The inside of each fiberboard shipping container shall be fitted with a liner, conforming to type CF, class weather resistant, variety DW, grade V15c of PPP-B-636. Level A bundles shall be packed flat, three in length, one in width, and four in depth within a shipping container. Each container ~~shall have the contents covered on the top and bottom with a sheet of 30-pound~~ minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636 except that inspection shall be in accordance with 4.4.4.

5.2.2 Level B packing. One hundred twenty bags, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to type CF (variety SW), or SF, class domestic, grade 275, style RSC-L of PPP-B-636. The inside of each fiberboard shipping container shall be fitted with a liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A bundles

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:35Z
Check the source to verify that this is the current version before use.

shall be packed flat, three in length, one in width, and four in depth within the shipping container. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to type I, grade B of VV-P-268. Each container shall be closed in accordance with Method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4.

5.2.3 Commercial packing. Bags, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

5.3 Palletization. When specified (see 6.2), bags, packed as specified in 5.2, shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or document, unit packs, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or MIL-STD-1188, as applicable.

6. NOTES

6.1 Intended use. The bag covered by this document is a component of various cooking outfits, including "Cooking Outfit, Field, Small Detachment". The bag, in the above outfit, serves to carry and stow various kitchen implements which, with the bag, compose a utensil kit.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this document.
(b) When a first article is required (see 3.2, 4.3 and 6.3).
(c) Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
(d) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(e) When palletization is required (see 5.3).

6.3 Samples. For access to samples (see 3.1), address the contracting activity issuing the invitation for bids.

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:35Z
Check the source to verify that this is the current version before use.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of DAR 7-104.55. The first article should be a preproduction sample consisting of one completed bag. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for inspection and approval of the first article.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.3).

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - MD
DLA - GS

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 7360-0142

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:35Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-B-1658D Bag, Field Cooking Outfit, Cutlery

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:35Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and
Development Command
ATTN: DRDNA -ES
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:35Z
Check the source to verify that this is the current version before use.