INCH-POUND

MIL-B-1658E
28 September 1990
SUPERSEDING
MIL-B-1658D
30 July 1982

MILITARY SPECIFICATION

BAG, FIELD COOKING OUTFIT, CUTLERY

This specification is approved for use by all Departments and Agencies of the Department of Defence.

1. SCOPE

1.1 Scope. This specification covers olive drab, cotton duck cutlery bag in one type and size, with a drawstring closure.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7360

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:35Z
Check the source to verify that this is the currentversion before use.

SPECIFICATIONS

FEDERAL

A-A-203	-	Paper, Kraft, Untreated
V-T-285	-	Thread, Polyester
T-T-881	-	Twine, Cotton, Seine
CCC-C-419	-	Cloth, Duck, Cotton, Unbleached, Plied-Yarns Army and Numbered
CCC-D-950	-	Dyeing and Aftertreating Processes for Cotton Cloths
DDD-L-20	-	Label for Clothing, Equipage and Tentage, (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-L-35078	-	Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-T-43566	-	Tape, Textile, Cotton or Polyester, General Purpose, Natural or in Colors

STANDARDS

FEDERAL

FED-STD-751	-	Stitches, Seams and Stitchings

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-147	-	Palletized Unit Loads
MIL-STD-731	-	Quality of Wood Members for Containers and Pallets

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWING

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-3-54	-	Bag, Field Cooking Outfit, Cutlery: Assembly Details and Sections

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:35Z
Check the source to verify that this is the current version before use.

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-EMSS, Natick, MA 01760-5014).

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Copies may be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3), in accordance with 4.3.

3.2 Guide sample. Guide samples of the end item, when furnished, are solely for guidance and information to the contractor (see 6.4). Variations from this document may appear in the sample, in which case this document shall govern.

3.3 Material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3.1 Cloth, cotton, duck. The cloth shall conform to type I, No. 10 hard texture of CCC-C-419.

3.3.1.1 Color and treatment. The cloth shall be dyed to match shade olive drab No. 7 and shall conform to type I, class B of CCC-D-950.

3.3.2 Tape, textile, cotton. The tape shall be dyed to match shade olive drab No. 7 and shall conform to type I, class 4, 3/4 inch (19 mm) width of MIL-T-43566.

3.3.3 Thread, polyester. The thread for all stitching shall conform to type I, class 1, sub-class E, size FE for binding of V-T-285. The thread shall be dyed olive drab 7 to match shade S-1.

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:35Z
Check the source to verify that this is the currentversion before use.

3.3.4 Twine, cotton, seine. The cotton seine twine shall conform to type II, No. 120 of T-T-881.

3.4 Construction. The construction shall conform in all respects to drawing No. 5-3-54 listed in section 2 and as specified herein.

3.4.1 Stitches, seams and stitching. Stitching shall conform to stitch type 301 of FED-STD-751, 8 to 10 stitches per inch.

3.4.1.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched 1/2 inch minimum except when caught in other stitching or turned under in the hem. Thread tension shall be maintained so that there will be no loose stitching resulting in puckering of material sewn. The lock shall be embedded in the material sewn.

3.4.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of one inch behind the end of the stitching. 1/

b. Thread breaks, two or more consecutive skipped stitches or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of one inch before the defective area (1/2 inch on Box, Box and Cross and W-W stitching) and continue a minimum of one inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.4.2 Thread ends. All thread ends shall be trimmed to 1/4 inch maximum length.

3.4.3 Lubrication of thread. There shall be no lubrication of the thread by any means, prior to or during sewing (see 4.4.1.1).

3.5 Marking. The identification marking shall be applied in the location shown on the applicable drawing and shall conform to type IV, class 5 of DDD-L-20. The letters "US" shall be applied in the size characters and in the location indicated on drawing No. 5-3-54 and shall conform to type IV, class 9 of DDD-L-20. Fastness of class 9 marking shall be as specified for class 5 marking.

3.6 Repairs. Repairs such as mends, darns, patches or splices are not permitted on the bag.

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:35Z
Check the source to verify that this is the currentversion before use.

3.7 Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects, or damages that are classified as defects in 4.4.3, shall be removed from production and replaced with nondefective and properly matched components.

3.8 Workmanship. The finished and assembled bag shall conform to the quality of product established by this specification and the occurence of defects shall not exceed the applicable acceptable quality level.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1.3 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:35Z
Check the source to verify that this is the currentversion before use.

4.3 First article inspection. When a first article is required (see 3.1 and 6.3), it shall be examined for the defects specified in 4.4.3 and 4.4.4. Any nonconformance shall be cause for the rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Component and material certification. A certificate of compliance may be acceptable as evidence that the bag conforms to the requirement specified in 3.4.3.

4.4.2 In-process inspection. Inspection of subassemblies shall be made to ascertain that construction details which cannot be examined in the finished product are in accordance with specified requirements. The Government reserves the right to exclude from consideration for acceptance, any material or service for which in-process inspection has indicated nonconformance.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of bags. The sample unit shall be one bag. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Fabric	Hole, cut, tear, smash, broken or missing yarn, or open place clearly visible at normal inspection distance (approximately 3 feet)	101	
Tape	Not firmly and tightly woven; edges frayed or scalloped	102	
	Multiple floats		201
	Any cut, hole, tear or smash	103	
	Abrasion mark, slub, broken end or pick		202
Open seam	1/2 inch or less		203
	More than 1/2 inch	104	

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:35Z
Check the source to verify that this is the currentversion before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken, or when two or more consecutive skipped or runoff stitches occur.		
Raw edge (on edge required to be finished)	More than 1/2 inch in length when securely caught in stitching	105	
	NOTE: Raw edge not securely caught in stitching shall be classified as an open seam.		
Runoff (see open seam)			
Seam and stitch type	Wrong seam or stitch type	106	
Stitch tension	Loose, resulting in a loose bobbin or top thread		204
	Excessively tight, resulting in puckering of material		205
Stitches per inch	One stitch less than minimum specified		206
	Two or more stitches less than minimum specified	107	
	One or more stitches in excess of maximum specified		207
	NOTE: Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the materials in order to sew over heavy places or heavy seams, or in turning corners shall be classified as follows: (a) Within the minor defect classification - no defect (b) Within the major defect classification - minor defect		

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:35Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Thread breaks, skipped stitches, or runoffs	Not overstitched as specified		208
	NOTE: Thread breaks or two or more consecutive skipped or runoff stitches not overstitched shall be classified as open seams.		
Ends of stitching	Not secured as specified		209
Rows of stitching	Any row missing	108	
Components and assembly	Any component part omitted or not as specified or any required operation omitted (unless otherwise classified herein)	109	
	Needle chews	110	
	Any mend, darn, patch or splice	111	
Binding	Loosely applied but not exposed raw edge of material		210
	Loosely applied exposing raw edge of material	112	
	Not turned under or finished in seam		211
Marking	Omitted, illegible, incorrect, or misplaced		212
Location markings	Drilled	113	
	Printed marking more than 1/32 inch in width		213
Cleanness	Any spot or stain clearly noticeable		214
Drawstrings	Not tied as specified		215
Thread ends	Not trimmed to 1/4 inch maximum length		216

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:35Z
Check the source to verify that this is the current version before use.

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on drawing No. 5-3-54. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of bags. The sample unit shall be one bag. The inspection level shall be S-3 and the AQL shall be 10 defects per hundred units.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL shall be 6.5 defects per hundred units.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:35Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A preservation. Ten bags shall be evenly stacked, alternately reversed top to bottom, to form a compact bundle and securely tied at each end with cotton tape or twine.

5.1.2 Commercial preservation. Bags shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. One hundred twenty bags, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to grade V2s, style RSC-L of PPP-B-636. The inside of each fiberboard shipping container shall be fitted with a liner, conforming to type CF, class weather resistant, variety DW, grade V15c of PPP-B-636. Level A bundles shall be packed flat, three in length, one in width, and four in depth within a shipping container. Inside dimensions of each shipping container shall be approximately 24 inches in length, 19-1/2 inches in width and 12 inches in depth. Each container shall have the contents covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each shipping container shall be closed, waterproofed, and reinforced with strapping or tape banding as specified in the appendix of PPP-B-636, except that inspection shall be in accordance with 4.4.5. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to non-metallic strapping, except for type II, class F loads.

5.2.2 Level B packing. One hundred twenty bags, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to type CF (variety SW), or SF, class domestic, grade 275, style RSC-L of PPP-B-636. The inside of each fiberboard shipping container shall be fitted with a liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A bundles shall be packed flat, three in length, one in width, and four in depth within the shipping container. Inside dimensions of each shipping container shall be approximately 24 inches in length, 19-1/2 inches in width and 12 inches in depth. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each container shall be closed in accordance with Method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:35Z
Check the source to verify that this is the current version before use.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.3 Commercial packing. Bags, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), bags packed as specified in 5.2.2 and 5.2.3 shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be in accordance with appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The bag is a component of various cooking outfits, including "Cooking Outfit, Field, Small Detachment". The bag, in the above outfit, is intended to carry and stow various kitchen implements which, with the bag, compose a utensil kit.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Levels of preservation and packing (see 5.1 and 5.2).
e. Type and class of unit load required (see 5.2.1).
f. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
g. When palletization is required (see 5.3).

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:35Z
Check the source to verify that this is the current version before use.

4.1 Responsibility for inspection. Unless otherwise specified in the

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Sample. For access to samples, address the contracting activity issuing the invitation for bids or request for proposal.

6.5 Subject term (key word) listing.

Individual equipment
Protective covers
Utensil kit

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify change with respect to the previous issue due to the extensiveness of the changes.

MILITARY INTERESTS:

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - MD
Air Force - 84
DLA - GS

User activity:

Navy - MC

PREPARING ACTIVITY:

Army - GL

(Project 7360-0167)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-B-1658E	1990 September 28

3. DOCUMENT TITLE

BAG, FIELD COOKING OUTFIT, CUTLERY

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
U.S. Army Natick RD&E Center	508-651-5221	256-5221
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: STRNC-ES Natick, MA 01760-5014	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-01-16T13:35Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:35Z
Check the source to verify that this is the current version before use.