MIL-C-1588G
30 September 1985
SUPERSEDING
MIL-C-1588F
20 May 1975

MILITARY SPECIFICATION

# COOKING OUTFIT, FIELD, SMALL DETACHMENT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This document covers one type of a small detachment, field cooking outfit. The outfit includes a stove, windshield and cover, pots, pans, utensils, cutlery, and tools.

## 2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

| | | |
|---|---|---|
| H-B-1490/5 | - | Brush, Scrub, Floor |
| FF-O-601 | - | Openers, Can; Hand and Mounted |
| FF-R-556 | - | Rivet, Solid, Small; Rivet Split, Small; Rivet, Tubular, Small; Burr; and Cap, Rivet; General Purpose |
| QQ-A-250/2 | - | Aluminum Alloy 3003, Plate and Sheet |

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7360

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:32Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| QQ-S-698 | - | Steel Sheet and Strip, Low Carbon |
| QQ-S-775 | - | Steel Sheets, Carbon, Zinc-Coated (Galvanized) by the Hot Dip Process |
| QQ-W-423 | - | Wire, Steel, Corrosion-Resisting |
| QQ-W-461 | - | Wire Steel, Carbon, (Round, Bare and Coated) |
| RR-D-400 | - | Dippers, Kitchen, (Corrosion-Resisting Steel) |
| RR-K-260 | - | Kitchen and Food Serving Utensils (Aluminum) |
| RR-L-30 | - | Ladles, Kitchen, Stainless Steel |
| RR-S-617 | - | Spoons, Food Service, (Basting, Straining, and Mixing) |
| SS-S-736 | - | Stones, Sharpening |
| TT-E-529 | - | Enamel, Alkyd, Semigloss |
| GGG-C-746 | - | Cutlery, Galley and Kitchen (Cleaver, Forks, Knives, Spatulas, Steel and Server) |
| PPP-B-601 | - | Boxes, Wood, Cleated-Plywood |
| PPP-B-636 | - | Boxes, Shipping, Fiberboard |
| PPP-T-45 | - | Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing |
| PPP-T-60 | - | Tape, Packaging, Waterproof |

MILITARY

| | | |
|---|---|---|
| MIL-P-116 | - | Preservation, Methods Of |
| MIL-B-121 | - | Barrier Material, Greaseproofed, Waterproofed, Flexible |
| MIL-B-1291 | - | Bag, Cotton, Duck, Tools, and Maintenance Parts, Stove, Cooking, Outfit |
| MIL-B-1658 | - | Bag, Field Cooking Outfit, Cutlery |
| MIL-R-1982 | - | Rolls, Cutlery, Canvas |
| MIL-S-7947 | - | Steel, Sheet and Strip (1095) Aircraft Quality |
| MIL-L-10547 | - | Liners, Case, and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible |
| MIL-C-10578 | - | Corrosion Removing and Metal Conditioning Compound (Phosphoric Acid Base) |
| MIL-W-10698 | - | Wrenches, Open End and Wrenches, Assemble Stamped Steel |
| MIL-U-10815 | - | Utensils, Cooking, Corrosion-Resisting Steel |
| MIL-H-10868 | - | Hose Assembly, Rubber, Utility Gasoline (1/4-Inch Inside Diameter) |
| MIL-V-10908 | - | Valve, Drip, Adjustable Feed |
| MIL-A-10957 | - | Adapter Kit, Gravity Feed, for 5 Gallon Military Gasoline Can, and 55 Gallon Drum |
| MIL-P-15328 | - | Primer (Wash), Pretreatment (Formula No. 117 for Metals) (Metric) |



Source: https://assist.dla.mil -- Downloaded: 20261O-16T13:32Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-595 - Colors

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

DRAWINGS

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

5-13-53 - Cooking Outfit, Field, Small Detachment; Illustration and Assembly
5-13-54 - Cooking Outfit, Field, Small Detachment; Sections
5-13-55 - Cooking Outfit, Field, Small Detachment; Details "A"
5-13-56 - Cooking Outfit, Field, Small Detachment; Details "B"
5-13-57 - Cooking Outfit, Field, Small Detachment; Details "C"
5-13-58 - Cooking Outfit, Field, Small Detachment; Details "D"
5-13-59 - Cooking Outfit, Field, Small Detachment; Details "E"
5-13-60 - Cooking Outfit, Field, Small Detachment; Details "F"
5-13-61 - Cooking Outfit, Field, Small Detachment; Details "G"

(Copies of documents, required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip
A 263 - Corrosion-Resisting Chromium Steel Clad Plate, Sheet and Strip
A 319 - Gray Iron Castings for Elevated Temperatures for Non-Pressure Containing Parts
D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:32Z
Check the source to verify that this is the current version before use.

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.5, 6.2, and 6.3).

3.2 Materials (see 6.6). Materials not definitely specified shall be of the quality normally used by the manufacturer for cooking outfits provided the completed item complies with all provisions of this document.

3.2.1 Tinners' rivets. Tinners' rivets shall conform to type IV, grade C of FF-R-556.

3.2.2 Aluminum alloy plate and sheet 3003. Aluminum alloy plate and sheet, 3003, shall conform to QQ-A-250/2. Temper shall be as specified herein.

3.2.3 Stainless clad steel plate, sheet and strip. Stainless clad steel plate, sheet and strip shall conform to ASTM A 263.

3.2.4 Low carbon steel sheet and strip. Low carbon steel sheet and strip shall conform to QQ-S-698.

3.2.5 Stainless steel sheet and strip. Stainless sheet and strip shall conform to ASTM A 167.

3.2.6 Carbon steel sheet zinc coated. Carbon steel zinc coated sheet shall conform to type I, class e of QQ-S-775.

3.2.7 Stainless steel wire. Stainless steel wire shall conform to QQ-W-423.

3.2.8 Carbon steel wire. Carbon steel wire shall conform to QQ-W-461.

3.2.9 Carbon steel sheet and strip (1095 aircraft quality).. Carbon steel sheet and strip (1095 aircraft quality) shall conform to MIL-S-7947.

3.2.10 Cast iron. Cast iron parts for the burner shall conform to the chemical composition of class II, type A of ASTM A 319.

3.2.11 Insulation. Insulation for the stove body shall be composed of mineral wool fibers, block form.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:32Z
Check the source to verify that this is the current version before use.

3.3 Components. One field coking outfit shall consist of the following components as specified:

| Components | Quantity |
|---|---|
| **Stove and Windshield:** | |
| Stove and Body as shown on Drawing 5-13-53 and 5-13-54 | 1 |
| Burner assembly as specified in 3.4.8 | 1 |
| Adapter, Gravity Feed conforming to MIL-A-10957 | 1 |
| Drip Valve conforming to MIL-V-10908 | 1 |
| Hose Rubber conforming to length 2 of MIL-H-10868 | 1 |
| Plates, Perforated as shown on Drawing 5-13-60 | 4 |
| Pipe, Stove as specified in 3.4.1 and Drawing 5-13-59 | 1 set |
| Windshield as shown on Drawing 5-13-58 | 1 |
| Cover, Windshield as shown on Drawing 5-13-58 | 1 |
| **Pans, and Cooking Pots:** | |
| Pans, Frying as specified in 3.4.3 | 2 |
| Pan, Sanitizing as specified in 3.4.4 | 1 |
| Pots, Cooking, With Cover, Size No. 3 (6-quart capacity) as specified in 3.4.5 | 2 |
| Pot, Cooking, With Cover, Size No. 2 (11-quart capacity) as specified in 3.4.5 | 1 |
| Pot, Cooking, With Cover, Size No. 1 (13-1/2-quart capacity) as specified in 3.4.5 | 1 |
| **Utensil Kit:** | |
| Bag, Cutlery conforming to MIL-B-1658. | 1 |
| Brush, Scrub conforming to H-B-1490/5. | 1 |
| Dipper, Kitchen conforming to size 1 of RR-D-400. | 1 |
| Ladle, Kitchen conforming to size d of RR-L-30. | 1 |
| Shaker, Salt conforming to type VIII, style A of RR-K-260. | 1 |
| Shaker, Pepper conforming to type VIII, style B of RR-K-260. | 1 |
| Turner, Food conforming to type IV of MIL-U-10815. | 1 |
| **Cutlery Kit:** | |
| Roll, Cutlery conforming to type I of MIL-R-1982. | 1 |
| Fork, Food Preparation conforming to MIL-U-10815. | 1 |
| Knife, Cook's conforming to type IV, Size, Grade of GGG-C-746. | 1 |
| Knives, Paring conforming to type V Grade of GGG-C-746. | 2 |
| Openers, Can conforming to type I any class of FF-O-601. | 2 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:32Z
Check the source to verify that this is the current version before use.

Cutlery Kit (cont'd):

| | |
|---|---|
| Spoon, Basting conforming to type I, 15 inch long of RR-S-617. | 1 |
| Stone, Sharpening conforming to type II, class B, style 14 of SS-S-736. | 1 |

Tool Kit:

| | |
|---|---|
| Bag, Canvas, Tools and Maintenance Parts conforming to MIL-B-1291. | 1 |
| Wrench, Straight, Open End, 3/8 inch by 9/16 inch conforming to type I of MIL-W-10698. | 1 |
| Wrench, Straight, Open End, 1/4 inch by 7/16 inch conforming to type I of MIL-W-10698. | 1 |
| Wrench, Alligator Jaw and Screw Driver 7/8 inch jaw opening conforming to type II of MIL-W-10698. | 1 |

Technical Manual:

| | |
|---|---|
| TM 10-7300-200-12 as specified in 3.7. | 1 |

3.4 Design and construction. The design and construction of components shall be as specified herein and as shown on Drawing Nos. 5-13-53 and 5-13-61.

3.4.1 Pipe, stove. The stove pipe shall be fabricated of the zinc-coated steel specified in 3.2.6 and as shown on Drawing 5-13-59.

3.4.2 Windshield handle. The windshield handles shall be fabricated of carbon steel wire as specified in 3.2.8 and as shown on Drawing 5-13-58 and shall be zinc plated prior to attachment.

3.4.3 Pans, frying. The frying pan bodies shall be fabricated of steel specified in 3.2.3 and as shown on Drawing 5-13-59. The frying pan bodies shall have a 2B finish or better. The handles for the frying pans shall have a number 2D finish or better.

3.4.4 Pan, sanitizing. The sanitizing pan body shall be fabricated of the steel specified in 3.2.3 and as shown on Drawing 5-13-61. The rivets shall be as specified in 3.2.1. The handles shall be snap-back type fabricated of steel wire as specified in 3.2.7. The sterilizing pans shall not leak water when tested as specified in 4.5.1. The sterilizing pans shall be coated with tin and retinned by the hot dip method.

3.4.5 Pots, cooking. The cooking pot bodies shall conform to 3003-0 aluminum specified in 3.2.2 and be fabricated as shown on Drawing 5-13-61. The cooking pot covers shall conform to 3003-H14 aluminum specified in 3.2.2 and be fabricated as shown on Drawing 5-13-61. After forming, the cooking pots and covers shall be given a frosted finish in accordance with the manufacturer's standard practice.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:32Z
Check the source to verify that this is the current version before use.

The stainless steel handles for the pot bodies shall have a number 2D finish or better. The cooking pots shall not leak water when tested as specified in 4.5.1.

3.4.6 Draw clamp. Draw clamps shall be fabricated from steel specified in 3.2.9.

3.4.7 Riveting. The driven rivets shall completely fill the holes. Heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the riveted members.

3.4.8 Burner assembly. The burner shall be fabricated from the material specified in 3.2.10. The burner shall successfully burn gasoline over a range of flame heights (high-low-medium) when tested as specified in 4.5.2.

3.5 Finish. After fabrication and completion of all riveting and welding, the exterior surfaces of the windshield cover, windshield body with door and stove body shall be thoroughly cleaned and conditioned with a metal conditioner conforming to MIL-C-10578, then coated with wash-primer conforming to MIL-P-15328. Alkyd, semi-gloss enamel, conforming to class A of TT-E-529 shall be applied to the primed surfaces. The windshield handles shall be zinc plated prior to being attached to the windshield. The sterilizing pan shall be coated with tin and retinned by the hot dip method. Unless otherwise specified (see 6.2), the color shall be olive drab, conforming to color No. 24087 of FED-STD-595.

3.6 Marking for identification. The letters "US"; the manufacturer's name, trade name, or trademark of such known character easily identifiable with said manufacturer; and year of contract shall be embossed or stamped as indicated on the drawings.

3.6.1 Instruction plate. An instruction plate for the stove shall be as shown on Drawing 5-13-56. The ground coat of vitreous enamel shall be blue or black and shall not exceed 0.005 inch in thickness. The finished surface shall be free from blisters, and uncoated spots. The instruction plate shall be located where it will be easily visible to the user of the stove. The following instructions, in white letters, shall be fired into the ground coat of enamel:

INSTRUCTIONS

1. Handle fuel with caution.
2. Have fuel can 18 to 25 inches above burner level and as far away from stove as possible.
3. Tighten all hose connections and adapter before operating.
4. Use full length of smoke stack to assure proper functioning of burner.
5. When starting, shut off drip valve before elevating the fuel can.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:32Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS (cont'd)

6. Lift draft gage prior to igniting burner and remove burner from well.

7. Cover all openings with perforated plates.

8. After burner is lit and fully warmed, close draft gate.

9. Smoke after 3 minutes of operation indicates excessive flow of fuel.

10. Set windshield cover loosely in place on the stove to speed cooking.

11. Reduce fuel flow to the slowest possible drip and open draft gate before shifting or removing pots and pans while burner is in operation.

12. Use caution in relighting hot burner. (Remove burner from well, light, and replace in well).

13. Keep burner clean. Soot contains lead.

14. Operate only in fully ventilated area.

15. Fuel may be siphoned if necessary.

WARNING

Throughly wash any utensil in which burner parts have been stored before using for cooking purposes.

3.7 Government furnished property. The Government will furnish one copy of the following Technical Manual with each cooking outfit (see 6.2):

TM 10-7300-200-12 - Operational, Organization Manual. Including Repair Parts and Special Tools Lists: Stove, Gasoline, 2-Burner, 5000 Btu/hr with Hinged Windshield and Carrying Case; Stove, Gasoline, 1-Burner, Field Cooking Outfit, Small Detachment.

3.8 Workmanship. There shall be no sharp edges, splinters, burrs, slivers, splits, cracks, cuts, dents, warp, or creases, or other imperfections which may cause personal injury. The cooking outfit shall be free of corrosion, and welds shall be smooth and complete. Finished coatings shall be smooth and uniform.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:32Z
Check the source to verify that this is the current version before use.

herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to the prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.1.1, 4.4.2, and 4.4.3 and tested as specified in 4.5.1 and 4.5.2. The presence of any defect or failure of any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.1.1 Component visual examination. In addition to the inspection indicated in 4.4.1, each lot of components listed below shall be separately examined for the defects listed in table I. The lot size shall be expressed in units of like components. The sample unit shall be one component. The inspection level shall be II, and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 6.5.

(a) Burner assembly.
(b) Pipe, stove.
(c) Cooking outfit body (inside and outside box).
(d) Pan, frying.
(e) Pan, sanitizing.
(f) Pots, cooking (each size).

TABLE I. Component visual defects

| Examine | Defect |
|---|---|
| Finish | Rough or sharp edges, burrs, or slivers. |
| Burner assembly | Any fracture, split, crack, cut, dent, warp, or crease. Rust or corrosion. |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:32Z
Check the source to verify that this is the current version before use.

TABLE I. Component visual defects (cont'd)

| Examine | Defect |
|---|---|
| Burner assembly (cont'd) | Weld at top of flame shield not complete.<br>Weld not smooth and uniform. |
| Pipe, stove | Zinc coating omitted, not smooth, or not uniform.<br>Lock band missing (No. 1 joint).<br>Slot missing.<br>Spot welds fractured, burned through, or pitted on lock band or joints. |
| Pan, frying | Not a number 2D or better finish on frying pan handles.<br>Not a number 2B or better finish on frying pan body.<br>Spot welds missing, burned through, or fractured.<br>Handle not welded to body as specified. |
| Pan, sanitizing, with cover | Rivet in handle retainer missing, loose, or not smoothly peened.<br>Spot welds missing, burned through, or fractured. |
| Pots, cooking | Not a number 2D finish or better (handles and retainers).<br>Not a frosted finish (bodies and covers). |
| Cooking outfit (inside and outside box and windshield) | Enamel finish wrong color or missing.<br>Sags or runs.<br>Handles and draw bolts spring not plated.<br>Rivet missing, not clinched, or head on wrong side.<br>Spot welds missing or not sound.<br>Latch on windshield does not turn freely after riveting.<br>Drawbolts or cover keepers missing. |
| Bolts, nuts, screws, studs, and other types of threaded fasteners | Missing, not type specified, broken, stripped, or fractured.<br>Loose. |
| Soldering (when applicable) | Missing, not adherent, or incomplete. |
| TM-10-7330-200-12 | Missing or not correct Technical Manual. |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:32Z
Check the source to verify that this is the current version before use.

TABLE I. Component visual defects (cont'd)

| Examine | Defect |
|---|---|
| Identification marking | Missing, incomplete, or not legible. |
| Instruction markings | Not specified type or size, not in proper location, or not affixed as prescribed |

4.4.1.2 In-process component examination. Examination shall be made of the following fabrication processes to establish conformance with specified requirements. Whenever nonconformance is noted, correction shall be made to the process and all items processed.

(a) 3.4.2 - Windshield handles shall be zinc plated prior to being attached to the windshield.

(b) 3.4.4 - The sanitizing pan shall be coated with tin and retinned by the hot dip method.

(c) 3.4.7 - The driven rivets shall be full, neatly made, concentric with rivet holes and in full contact with the riveted members.

4.4.1.3 Leakage testing. The sanitizing pan and each size of cooking pot shall be tested for leaks as specified in 4.5.1. The lot size shall be expressed in units of sanitizing pans and cooking pots. The sample unit shall be one sanitizing pan and one cooking pot of each size. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.2 End item visual examination. The end item shall be examined for the defects listed in table II. The lot size shall be expressed in units of cooking outfits. The sample unit shall be one cooking outfit. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 1.5.

TABLE II. End item visual defects

| Examine | Defect |
|---|---|
| Assembly | Component missing.<br>Arrangement of components not in accordance with approved sample. |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:32Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

| Examine | Defect |
|---|---|
| Workmanship | Any component cracked, cut, dented, warped, or creased.<br>Sharp edges, splinter, burrs, slivers, splits which might cause injury.<br>Weld missing.<br>Weld not ground smooth or is pitted.<br>Weld fractured or burned through.<br>Weld separated (no fusion to metal parts)<br>Uneven finish coating. |

4.4.3 End item dimensional examination. The end item shall be examined for conformance to the dimensions specified on Drawings 5-13-53 through 5-13-61. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of cooking outfits. The sample unit shall be one cooking outfit. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.4 End item testing. One representative production unit (see 6.4) shall be tested as specified in 4.5.2. Any nonconformance shall be cause for rejection of the inspection lot.

4.4.5 Packaging inspection. An examination shall be made to determine that the preservation, packing, and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged. The lot size shall be the number of shipping containers in the inspection lot. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

| Examine | Defect |
|---|---|
| Marking (exterior and interior) | Omitted; incorrect; illegible; of improper size, location, sequence, or method of application. |
| Preservative application | Preservative improperly applied or missing. |
| Materials | Any component missing, damaged, or not as specified. |

4.4.6 Palletization examination. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and AQL, expressed in terms of defects per hundred units, shall be 6.5.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:32Z
Check the source to verify that this is the current version before use.

| Examine | Defects |
|---|---|
| Finished dimensions | Length, width, or height exceeding specified maximum requirements. |
| Palletization | Pallet pattern not as specified.<br>Interlocking of loads not as specified.<br>Load not bonded with required straps as specified. |
| Weight | Exceeds maximum load limits. |
| Marking | Omitted; incorrect; illegible; of improper size,location, sequence, or method of application. |

4.5 Methods of inspection.

4.5.1 Leakage test. The sterilizing pan and cooking pots shall be filled to capacity with water and allowed to stand for 15 minutes. At the end of this time, the outside of the sterilizing pan and cooking pots shall be checked to determine compliance with 3.4.4 and 3.4.5.

4.5.2 Operation test. The assembled burner including hose shall be connected to a supply of gasoline and then the burner shall be lighted and the flame observed over a range of flame heights (high-low-medium) to determine compliance with 3.4.8. Any nonconformance shall constitute failure of this test.

5. PACKAGING

5.1 Preservation. Preservation shall be level A.

5.1.1 Level A.

5.1.1.1 Cleaning. All metal surfaces of the components of the cooking outfit shall be cleaned in accordance with process C-1 of MIL-P-116 and thoroughly dried.

5.1.1.2 Preservative application. The metal surfaces of the burner complete with fittings, the cook's knife, the paring knives, the can openers, tools, and the sterilizing pan, cleaned as specified in 5.1.1.1, shall be coated with type P-14 preservative of MIL-P-116. Each section of the disassembled stovepipe sections, cleaned as specified, shall be coated inside and outside with type P-7 preservative of MIL-P-116.

5.1.1.3 Unit packing.

5.1.1.3.1 Adapter, gravity feed. The gravity feed adapter shall be unit packed level A in accordance with MIL-A-10957.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:32Z
Check the source to verify that this is the current version before use.

5.1.1.3.2 Burner. The burner complete with fittings, shall be individually unit packed in accordance with method IC-1 of MIL-P-116 or wrapped with greaseproof barrier-material conforming to type III or IV, class 1 of PPP-T-60.

5.1.1.3.3 Hose. The hose shall be preserved in accordance with the applicable requirements of MIL-H-10868.

5.1.1.3.4 Pipe, stove. The stovepipe, shall be nested and wrapped in greaseproof barrier-material conforming to type I, grade A, class 1 or 2 of MIL-B-121. The ends of the greaseproof barrier-material shall be crimped and stuffed into the end of the smallest diameter pipe to form a compact pack. The wrapped stovepipe shall then be completely wrapped in a single-faced corrugated fiberboard. The closure shall be effected by means of minimum 2-inch width tape conforming to type III, grade B of PPP-T-45.

5.1.1.3.5 Technical manual. The technical manual shall be unit packed in accordance with method IC-1 of MIL-P-116.

5.1.1.3.6 Knives, tools, and can openers. The cook's knife, paring knives, tools, and can openers, shall be unit packed by items in a bag or wrap as specified in 5.1.1.3.2.

5.1.1.3.7 Stone, sharpening. Each stone shall be enclosed in an open end snug-fitting glued tube made of not less than 0.020 inch, No. 1 finish bending chipboard.

5.1.1.3.8 Component placement.

5.1.1.3.8.1 Bag, cutlery. The scrubbing brush, dipper, ladle, salt and pepper shakers, and the cake turner shall be placed into the cutlery bag and the bag closed.

5.1.1.3.8.2 Roll, cutlery. The fork, spoon, and stone shall be placed inside their respective pocket of the cutlery roll. The knives shall be placed on top of their respective pocket and openers shall be placed adjacent to the knives. The roll shall then be closed, rolled, and tied with the tapes.

5.1.1.3.8.3 Kit, tool. The two open end wrenches, alligator jaw wrench, and screwdriver shall be placed in the canvas drawstring bag and the bag closed.

5.1.1.3.8.4 Windshield section. The sterilizing pan shall be placed inside the windshield. The two frying pans shall be placed side by side in the bottom of the sterilizing pan. The two small pots (6 qt.) shall be placed side by side in one frying pan. The 13-1/2-quart pot shall be placed in the other frying pan. The 11-quart pot shall be placed in the 13-1/2 quart pot. The cutlery bag shall be placed in the 11-quart pot. Care shall be taken to be sure dipping portion of ladle and dipper are at opposite ends of the bag. The technical



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:32Z
Check the source to verify that this is the current version before use.

manual and tool kit, shall be placed on top of the cutlery bag. The pots shall be covered with their respective covers. The windshield cover shall then be secured to the windshield by locking the three windshield draw clamps on the three windshield cover keepers.

5.1.1.3.8.5 Stove section. The stovepipe shall be placed on one side of the baffle plate within the stove section, the cutlery roll shall be placed on the other side of the baffle plate. The burner, complete with fittings shall be placed alongside of the cutlery roll, and the adapter, shall be placed on the cutlery roll. The contents of the stove section shall be immobilized and the four perforated plates shall be replaced and secured with tape as specified in 5.1.1.3.2.

5.1.1.3.9 Securing of windshield and stove section. The windshield section , as specified in 5.1.1.3.8.4, shall be placed on top of the stove section as specified in 5.1.1.3.8.5, and the two components secured together with draw clamps provided for that purpose. The stovepipe hole, burner hole, and all other openings and crevices into the outfit shall be sealed with tape conforming to type III or IV of PPP-T-60 or a combination of tape specified herein and barrier-material as specified in 5.1.1.3.2. The draft gate shall be secured with tape as specified herein.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Each complete cooking outfit, preserved as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to overseas type, style A or B, grade A or B, type 2, load of PPP-B-601. Wood or built-up fiberboard pads shall be used to provide clearance for protruding handles, draw clamps, or other projections and to immobilize the unit within the shipping container. The inside dimensions of the shipping container shall approximate 26-3/4 inches in length, 18-3/4 inches in width, and 12 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be provided with a type I or II, grade C case liner conforming to MIL-L-10547. Closure and strapping shall be in accordance with the appendix of the container specification.

5.2.2 Level B packing. Each complete cooking outfit, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC, type CF, (variety optional) or type SF, class domestic of PPP-B-636. Wood or built-up fiberboard pads shall be used to provide clearance for protruding handles, draw clamps or other projections and to immobilize the unit within the shipping container. The inside dimensions of the shipping container shall approximate 26-3/4 inches in length, 18-3/4 inches in width, and 12 inches in depth. Approximate dimensions are furnished as guide only. Closure shall be in accordance with method II as specified in the appendix of PPP-B-636.



Source: https://assist.dla.mil -- Downloaded: 20261O-16T13:32Z
Check the source to verify that this is the current version before use.

5.2.2.1 Weather-resistant shipping containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with method III as specified in the appendix of PPP-B-636.

5.2 3 Commercial packing. Cooking outfits preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), cooking outfits packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type I or Ia, as applicable, of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bond O or P. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers and palletized unit loads in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The cooking outfit is used for preparing rations in the field for 6 to 25 men.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this document.
(b) When a first article is required (see 3.1, 4.3, and 6.3).
(c) Whether color of windshield cover, windshield, stove body, and burner shield is to be other than specified (see 3.5).
(d) Source and delivery of Government furnished manual (see 3.7).
(e) Selection of applicable levels of packing (see 5.1)
(f) Whether weather-resistant grade fiberboard shipping containers are required for level B shipment (see 5.2.2.1).
(g) When palletization is required (see 5.3)

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample consisting of one complete cooking outfit. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for inspection and approval of the first article.

6.4 End item test. Performance of test as specified in 4.5.2 should be limited to one successful demonstration of compliance to the requirement of this document for each contract.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:32Z
Check the source to verify that this is the current version before use.

6.5 Contract data requirements. Any data items to be delivered under any contract for items covered by this document should be specifically called for in the contract in accordance with the applicable regulations of the procuring activity.

6.6 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.2).

6.7 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:

Army - GL
Air Force - 99

Review activities:

Air Force - 84
DLA - GS

Preparing activity:

Army - GL

Project No. 7360-0152



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:32Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| MIL-C-1588G | Cooking Outfit, Field, Small Detachment |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR |
| b. ADDRESS *(Street, City, State, ZIP Code)* | ☐ USER |
| | ☐ MANUFACTURER |
| | ☐ OTHER *(Specify)*: _____ |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:32Z
Check the source to verify that this is the current version before use.