INCH-POUND

MIL-H-1608H
25 November 1991
SUPERSEDING
MIL-H-1608G
30 June 1986

MILITARY SPECIFICATION

HOOKS, TENT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers steel wire tent hooks.

* 1.2 Classification. Tent hooks shall be of the following types and sizes as specified (see 6.2).

Type I - Triangle eye (hook in line with center of eye)

Size 1 - 1 inch
Size 2 - 1-1/2 inch

Type III - Square eye - size 1-1/2 inch
Type IV - Trapezoid eye - size 1-1/2 inch
Type V - Diamond eye - size 1-1/2 inch
Type VI - Diamond eye, shackle type - size 1-1/2 inch

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:33Z
Check the source to verify that this is the currentversion before use.

documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

TT-E-485	-	Enamel, Semigloss, Rust-Inhibiting
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-B-640	-	Boxes, Fiberboard, Corrugated, Triple-Wall

MILITARY

MIL-L-10547	-	Liners, Case, and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible

STANDARDS

FEDERAL

FED-STD-595	-	Colors Used In Government Procurement

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-970	-	Standards and Specifications, Order of Preference for the Selection of

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-4-166	-	Hook, Tent; Assembly and Details
5-4-355	-	Hooks, Tent

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:33Z
Check the source to verify that this is the current version before use.

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-UX, Natick, MA 01760-5017.)

* 2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 153 - Zinc coating (Hot Dip) on Iron and Steel Hardware
A 575 - Merchant Quality Hot Rolled Carbon Steel Bars
A 853 - Steel Wire, Carbon, for General Use
B 633 - Electrodeposited Coatings of Zinc on Iron and Steel
D 1005 - Measurement of Dry Film Thickness of Organic Coatings
D 2092 - Preparation of Zinc-Coated Steel Surfaces for Painting
D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

* 3.2 Materials and components. The materials and components shall be as specified herein and on the applicable drawings. Materials and components not specified shall be selected by the contractor in accordance with MIL-STD-970. Materials and components specified in accordance with MIL-STD-970 shall not degrade the operational suitability or effectiveness of the burner. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

* 3.2.1 Wire, steel, carbon. Carbon steel wire shall conform to steel number 1010-1020, bare finish, annealed in process of ASTM A 853.

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:33Z
Check the source to verify that this is the current version before use.

3.2.2 Steel bar, carbon. Carbon steel bar shall conform to grade M 1010-M 1020 of ASTM A 575.

3.2.3 Enamel. Enamel shall conform to type I or II, composition G or L, as applicable, olive drab color No. 24087 of TT-E-485.

3.3 Construction. The construction of the tent hooks shall conform to the requirements specified herein, and as shown on Drawings 5-4-166 and 5-4-355.

3.3.1 Fabrication.

* 3.3.1.1 Type I, III, IV and V tent hooks. The body for the type I, III, IV and V tent hooks shall be fabricated from steel wire specified in 3.2.1. The ends of the formed wire body shall be securely welded as shown on Drawing 5-4-355, and all welds shall be complete, sound and uniform. The type I, size 1 tent hook shall be capable of withstanding a load of 125 pounds minimum in tension without any evidence of cracked or fractured weld or permanent distortion of the wire body when tested as specified in 4.4.5. The type I, size 2, and types III, IV, and V tent hooks shall be capable of withstanding a load of 500 pounds minimum in tension without any evidence of cracked or fractured weld or permanent distortion of the wire body when tested as specified in 4.4.5.

3.3.1.2 Type VI tent hook. The hook portion shall be fabricated of steel wire specified in 3.2.1. The upper and lower shackles shall be fabricated of steel bar specified in 3.2.2. The welding of the hook to the upper shackle shall be complete, sound and uniform. After enameling, the tent hook shall be assembled with bolt and the self-locking nut shall be drawn up finger-tight.

3.3.2 Deburring. All burrs, sharp edges, and rough spots shall be removed prior to application of the finish.

3.4 Finish.

* 3.4.1 Zinc coating. After complete fabrication of the tent hooks and prior to assembly of the type VI tent hook, all tent hooks and components (except bolt and nut) shall be zinc coated. The zinc coating shall conform to either ASTM A 153 with preparation for painting in accordance with method A, crystalline zinc phosphate conversion treatment of ASTM D 2092 or to type IV, thickness classification Fe/Zn12 of ASTM B 633. As an alternate, use chromate conversion type II of ASTM B 633.

3.4.2 Enameling. All zinc coated surfaces of tent hooks and components (except bolt and nut) shall be completely coated with enamel specified in 3.2.3. The coating shall be a smooth, uniform, dry film without runs, wrinkles, blisters, area of thin or no film, scratch, foreign matter embedded in the finish, and wet or tacky paint.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:33Z
Check the source to verify that this is the current version before use.

* 3.4.3 Epoxy powder coating. As an alternate to the zinc coating and enameling specified in 3.4.1 and 3.4.2, the surfaces may be prepared and coated as follows:

a. The tent hooks shall be prepared for coating by mechanical means. The surfaces shall be thoroughly and uniformly textured by sand blasting with 80-grit aluminum oxide. Prepared surfaces shall be kept clean during subsequent handling. Handling to be by clean-gloved hands or by clean implements. The surface shall be epoxy coated not more than 8 hours after sand blasting.

b. The finish coating shall be olive drab conforming to color No. 24087 of FED-STD-595, electrodeposited epoxy powder coating conforming to H.B. Fuller Co., Kativo Powder No. REP-43286-20 or equal.

c. The electrodeposited epoxy powder coating shall be baked in accordance with commercial practice.

d. The thickness of the baked coating shall be .003 ± .001 inch when tested as specified in 4.4.4.1.

e. The final coating shall be smooth and uniform in appearance, free from wrinkles and streaks.

3.5 Marking for identification. Hooks shall be marked with the manufacturer's identification in accordance with industry's practice.

3.6 Workmanship. All welding shall be free from pits, slag inclusion, porosity, crack, fracture, flash and excess flux deposits. The finished tent hooks shall be clean and free of dirt and grease. Threads and finish of bolt and nut shall be free from damage, i.e., nut shall not bind on bolt. The tent hook shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 20261O-16T13:33Z
Check the source to verify that this is the current version before use.

5/ For classes 3 and 4, these requirements are not applicable.

* 4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

* 4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

* 4.3 First article inspection. When a first article is required (see 3.1 and 6.2), the tent hook shall be examined for the defects specified in 4.4.3 and 4.4.4 and shall be tested for the strength characteristic specified in 4.4.5. Any nonconformance shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

* 4.4.2 In-process inspection. Examination shall be made of the following fabrication processes to establish conformance with specified requirements. Whenever nonconformance is noted, correction shall be made to the process and all items affected. Items which cannot be corrected shall be removed from production. The Government reserves the right to exclude from consideration for acceptance any material for which in-process inspection has indicated nonconformance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:33Z
Check the source to verify that this is the current version before use.

Requirement or operation	Requirement reference
(a) Removal of burrs, sharp edges, and rough spots prior to finishing	3.3.2
(b) Zinc coating of tent hooks and components (except bolt and nut) prior to enameling	3.4.1

* 4.4.3 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of tent hooks. The sample unit shall be one tent hook. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Finish	Not finished	101	
	Type or color of finish not as specified		201
	Coating is not smooth or uniform		202
	Finish is not dry, i.e., wet or tacky to touch	102	
	Run, wrinkle, or blister		203
	Area of no film exposing bare metal	103	
	Area of thin film exposing zinc coating		204
	Any scratch or foreign matter embedded in finish		205
Construction and workmanship	Any component not as specified or missing, e.g. shackle, bolt or nut	104	
	Type VI tent hook not assembled or the self-locking nut has not been drawn up finger-tight		206
	Threads or finish of bolt or nut is damaged, i.e., nut binds on bolt		207
	Not clean, i.e., has dirt or grease		208
	Burr, sharp edge, or rough spot		209
Welding	Missing where required	105	
	Not type specified	106	
	Incomplete or not sound	107	
	Not uniform		210
	Pits, slag inclusion or porous		211

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:33Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Welding (cont'd)	Crack or fracture	108	
	Flash or excess flux deposit has not been removed		212
Identification marking	Missing, illegible, or incomplete		213

* 4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of tent hooks. The sample unit shall be one tent hook. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

* 4.4.4.1 Epoxy coating thickness examination (when applicable). The end item shall be examined for thickness of the expoxy coating in accordance with ASTM D 1005. Three observations shall be made per sample unit. Any epoxy coating with a minimum thickness not as specified in 3.4.3 shall be classified as a defect. The lot size shall be expressed in units of tent hooks of one type offered for inspection at one time. The sample unit shall be one tent hook. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.5 End item testing. Types I, III, IV, and V tent hooks shall be tested for strength as specified in 4.5.1. The inspection level shall be S-2 with an AQL of 2.5, expressed in terms of defects per hundred units. The requirement shall be applicable to the individual unit. There shall be one determination per sample unit for types I, III, and IV hooks, and two determinations per sample unit for type V hooks.

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size location, sequence, or method of application

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:33Z
Check the source to verify that this is the current version before use.

Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

4.5 Methods of inspection.

4.5.1 Strength test. The tent hooks shall be tested as shown on Drawing 5-4-355. The load rate shall not exceed 1000 pounds per minute. The type I, size 1 tent hook shall be subjected to a pull of 125 pounds minimum. The type I, size 2, III, IV, and V tent hooks shall be subjected to a pull of 500 pounds minimum. After the test load has been released, the tent hooks shall be examined. Any tent hook having evidence of cracked or fractured weld or permanent distortion of the wire body shall be classified as a defect.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

* 5.1.1 Level A preservation. Three hundred and twenty type I, size 1 hooks; 100 type I, size 2 hooks; 75 type III, type IV or type V hooks; or 35 type VI hooks shall be packed in a snug-fitting fiberboard box conforming to style RSC, type CF, variety optional, or type SF, class domestic, grade 200 of PPP-B-636. Each box shall be agitated during filling to assure compact and well filled box. Closure shall be in accordance with PPP-B-636.

5.1.2 Commercial preservation. Hooks shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Nineteen hundred and twenty type I, size 1 hooks; 600 type I, size 2 hooks; 450 type III, type IV, or type V hooks; or 210 type VI hooks, packaged as specified in 5.1, shall be packed in a shipping container conforming to overseas type, style A of PPP-B-601; or class 2, style 2 or 4 of PPP-B-621. Each shipping container shall be provided with a type I or II, grade C sealed case liner conforming to MIL-L-10547. Closure and strapping shall be in accordance with the appendix of the applicable container specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:33Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing. Nineteen hundred and twenty type I, size 1 hooks; 600 type I, size 2 hooks; 450 type III, type IV, or type V hooks; or 210 type VI hooks, packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to class 1, style E of PPP-B-640; class I, style 2 or 4 of PPP-B-621; or domestic type, style A or B of PPP-B-601.

* 5.2.2.1 Weather-resistant shipping containers. When specified (see 6.2), the shipping container shall be V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of PPP-B-636.

5.2.3 Commercial packing. Hooks, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking. In addition to any special marking required by the contract or purchase order, unit packs and shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The tent hooks are intended for use on various types of tents and shelters.

* 6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Type and size of tent hook required (see 1.2).
c. Issue of DODISS to be cited in solicitation, and if required the specific issue of individual documents referenced (see 2.1.1 and 2.2).
d. When a first article is required (see 3.1, 4.3, and 6.3).
e. Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209-4. The first article shall be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in acquisition documents regarding arrangements for selection, inspection and approval of the first article.

6.4 International standardization agreement. Certain provisions of this document are the subject of international standardization agreement as cited in NATO, STANAG NO. 2882. When amendment, revision, or cancellation of this

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:33Z
Check the source to verify that this is the current version before use.

document is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

* 6.5 Subject term (keyword) listing.

Attachment fixtures
Fasteners

6.6 Changes from previous issue. The margins in this specification are marked with asterisks (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Preparing activity:

Army - GL

(Project 8340-0548)

Review activities:

Air Force - 45, 82
DLA - CT

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:33Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-H-1608H	1991 November 25

3. DOCUMENT TITLE

HOOKS, TENT

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)
	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)
U.S. Army Natick RD&E Center	(1) Commercial: 508-651-4531 (2) AUTOVON/DSN: 256-4531
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: STRNC-UXT Natick, MA 01760-5017	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026/10-16T13:33Z
Check the source to verify that this is the current version before use.