MIL-S-1698G
28 August 1984
SUPERSEDING
MIL-S-1698F
15 June 1972

MILITARY SPECIFICATION

SLINGS, BAG AND CASE CARRYING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers three types of adjustable carrying slings made of webbing with hardware attached.

1.2 Classification.

1.2.1 Types. Slings shall be of the following types as specified (see 6.2).

Type I - General Purpose
Type II - ST-19-A
Type III - 19-3/4 Inches Long

2. APPLICABLE DOCUMENTS

* 2.1 Government documents. Unless otherwise specified, the following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8465

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:38Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

V-T-285	-	Thread, Polyester.
TT-E-529	-	Enamel, Alkyd, Semigloss
UU-P-268	-	Paper, Kraft, Wrapping.
DDD-L-20	-	Label; For Clothing, Equipage, and Tentage, (General Use).
PPP-B-636	-	Boxes, Shipping, Fiberboard.

MILITARY

MIL-F-495	-	Finish, Chemical, Black, For Copper Alloys.
MIL-C-496	-	Clips, End, Strap.
MIL-W-530	-	Webbing, Textile, Cotton, General Purpose, Natural or in Colors.
MIL-B-543	-	Buckles, Tongueless and Web Strap.
MIL-L-3851	-	Loops, Slide (For Equipage).
MIL-L-11075	-	Loops, Strap Fastener.
MIL-S-43770/1-		Snap Hooks, Wire Body, Fixed Loop Eye, Flat Spring Closure, with Retainer.
MIL-W-44049	-	Webbing, Textile and Tape, Textile, Polypropylene, General Purpose, Natural or in Colors.

FEDERAL

FED-STD-751	-	Stitches, Seams, and Stitchings.

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-147	-	Palletized Unit Loads

DRAWINGS

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

2-1-80	-	Sling, Bag and Case Carrying, Type I, General Purpose.
2-2-256	-	Sling, Bag and Case Carrying, Type III, 19-3/4 Inches Long; Assembly and Details.
2-4-68	-	Sling, Bag and Case Carrying, Type II, ST-19-A Assembly Complete.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

(Copies of documents required by manufacturers connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

* 2.2 Other publications. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

B 633 - Electrodeposited Coatings of Zinc on Iron and Steel
D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Guide samples. Samples of the end item, when furnished, are solely for guidance and information to the manufacturer (see 6.3). Variation from this document may appear in the sample, in which case this document shall govern.

3.2 First article. When specified a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.4).

3.3 Materials. (See 6.6).

3.3.1 Webbing.

* 3.3.1.1 Webbing for type I sling. The 2-inch webbing shall be cotton conforming to type IIa, class 4 of MIL-W-530, or as an alternate, the webbing shall be polypropylene conforming to type IIa, class 4, of MIL-W-44049. The webbing shall be dyed color Olive Drab 7.

3.3.1.2 Webbing for type II sling. The webbing shall be dyed O.D. 7 and shall conform to type III, class 4, 2-inch width of MIL-W-530.

3.3.1.3 Webbing for type III sling. The webbing shall be dyed O.D. 7 and shall conform to type III, class 4, 1-inch width of MIL-W-530.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

3.3.2 Thread, polyester. The polyester thread for the slings shall be dyed O.D. S-1 C.A. 66022 and shall conform to type I, class 1, sub-class A, size FF of V-T-285. The dyed thread shall show fastness to weathering equal to or better than the standard sample. When no standard sample is available, the thread shall show "good" fastness to weathering.

3.3.3 Metal components for type I sling.

3.3.3.1 Loop, slide. The slide loop for the type I sling shall be brass or steel and shall conform to class 1 or class 3, style 2, size 2 inch, construction A, of MIL-L-3851.

3.3.3.2 Loop, strap. The strap loop for the type I sling shall be brass or steel wire and shall conform to type I or III, style E, 2-1/16 by 1/4 inch, of MIL-L-11075.

3.3.3.3 Snaphook. The snaphooks for type I sling shall be brass or steel wire and shall conform to dash No. CWBC3 or SWZE3 of MIL-S-43770/1.

3.3.4 Metal components for type II sling.

3.3.4.1 Loop, slide, brass. The slide loop for the type II sling shall be brass, 2-1/4 inch, conforming to North and Judd Manufacturing Company No. 4883 or equal (see 4.3.1.1). Prior to the use of the "or equal" item, the contractor shall submit the item to the contracting officer with supporting data for approval. The slide loop shall have a black chemical finish conforming to MIL-F-495.

3.3.4.2 Snap, swivel, loop eye. The loop eye swivel snaps for the type II sling shall be cast malleable iron, 2 inch, conforming to North and Judd Manufacturing Company No. 017 or Covert Manufacturing Company No. 017 or equal (see 4.3.1.1). Prior to the use of the "or equal" item, the contractor shall submit the item to the contracting officer with supporting data for approval. The finish shall consist of electroplated zinc followed by a phosphate treatment and bake enameling. The phosphate zinc plate shall be 13 um thick conforming to ASTM B 633. After phosphating and drying, surfaces shall be given a finish of black enamel conforming to type II of TT-E-529. The coating shall level out to a continuous uniform film without objectionable orange peel, wrinkles, drops, streaks or area of no film.

3.3.5 Metal components for type III sling.

3.3.5.1 Buckle. The 2-bar tongueless buckle shall conform to type II, style 1, class 1 or class 3, size 1 inch of MIL-B-543.

3.3.5.2 Clip. The end clip shall conform to type I, class 1 or class 2, size 1 inch of MIL-C-496.

3.4 Construction. The construction shall conform in all respects to the drawings listed in section 2 and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

3.4.1 Stitching, machine. All stitching shall conform to type 301 of FED-STD-751, with 6 to 8 stitches per inch.

3.4.1.1 Automatic stitching. Any of the stitching operations cited in this document may be performed with an automatic machine provided the requirements for stitch pattern, stitches per inch, size and types of thread are met; and at least three tying, overlapping or backstitches are used to secure the ends of stitching.

3.4.1.2 Type 301 stitching. Ends of all stitching shall be backstitched or backtacked not less than 1/2 inch except where ends are caught in other seams and stitching. Thread tensions shall be maintained so that there will be no loose or tight stitching and the lock will be imbedded in the materials sewed.

3.4.1.2.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 3/4 inch back of the end of stitching. 1/

b. Thread breaks or two or more consecutive skipped or runoff stitches noted during inspection of the item (in-process or end item), shall be repaired by overstitching. The stitching shall start a minimum of 3/4 inch in back of the defective area, continue over the defective area, and continue a minimum of 3/4 inch beyond the defective area onto the existing stitching.

c. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of stitching are not required to be backstitched.

3.4.1.3 Thread ends. All thread ends shall be trimmed to 1/4 inch maximum length.

3.4.2 Setting of end clip (type III sling). The webbing shall be inserted the full depth of the clip. The clip shall be securely attached without cutting the webbing and the webbing shall be flat at the point of entry.

3.4.3 Wax dipping of webbing end (type III sling). The cut end of the cotton webbing not enclosed in end clip shall be dipped 1/4 inch full width minimum into a melted mixture of approximately 50 percent beeswax and 50 percent paraffin. Temperature of the melted mixture shall be 180 ± 20 F.

* 3.4.4 Fusing of ends of polypropylene webbing (type I sling). All ends of polypropylene webbing shall be fused. The apparatus used to fuse the webbing ends shall be capable of providing sufficient heat to provide a smooth edge

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

with the cut end of the webbing yarns all fused together. Fusing of the webbing ends shall be accomplished prior to being assembled for stitching.

3.5 Marking.

3.5.1 Marking on webbing. The identification marking shall be applied in the location shown on the applicable drawing and shall conform to type IV, class 5 of DDD-L-20. The marking "US" for type I or "ST-19-A" for type II, as required, shall be applied in the size characters and the location indicated on the applicable drawing, and shall conform to type IV, class 9 of DDD-L-20. Fastness of class 9 marking shall be as specified for class 5 marking.

3.5.2 Alternate marking on polypropylene webbing (type I sling). A type VI label of DDD-L-20 may be used in lieu of direct item marking. The label color shall be medium green and the marking shall conform to the type I sling marking requirements specified in 3.5.1. The label shall not be wider than, or any portion of it allowed to extend beyond the edge of the webbing which it is to be attached to.

3.6 Workmanship. The finished and assembled sling shall conform to the quality of product established by this document. Occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.2, components and materials shall be inspected in accordance with all requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.1.1 Certification. The contractor shall furnish a certificate of compliance for the requirements specified in 3.3.4.1 and 3.3.4.2.

4.4.2 In-process inspection (types I and II). Inspection shall be performed prior to fabrication of the type I or II sling to determine compliance with cut length requirement. Any cut length of webbing not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of unassembled slings. The sample unit shall be one unassembled sling. The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5.

4.4.3 End item visual examination. The end item shall be examined for the defects listed below. The lot size shall be expressed in units of slings. The sample unit shall be one sling. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

Examine	Defect
Webbing	Any hole, cut, or tear Frayed or scalloped edges; not firmly or tightly woven Abrasion mark, multiple floats
Hardware	Broken or malformed, failing to serve intended purpose, finish omitted, corroded area, burr, or sharp edge Not as specified
Finish	Not as specified
Assembly	Any hardware component not assembled as specified
End clip (type III)	Not properly or securely set
Snap hook (types I and II)	Defective, fails to function properly
Open seam	Any

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:38Z
Check the source to verify that this is the current version before use.

Examine	Defect
NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more continuous skipped or runoff stitches occur.
Runoffs	(See open seam)
Seam and stitch type	Wrong seam or stitch type
Stitch tension	Loose, resulting in a loosely exposed top or bobbin thread; tight, resulting in tightness of seams
Stitches per inch	One or more stitches less than minimum specified One or more stitches in excess of maximum specified
Stitching margin	Not within specified tolerance
Thread breaks	Overstitched less than 3/4 inch (all types)
"W" stitching	One or more rows of stitching omitted (all types)
Box stitching	One or more rows of stitching omitted (type I)
Stitching ends	Backstitched less than 1/2 inch
Components and assembly	Any component part or required operation omitted (unless otherwise classified herein) Mend or darn Any component reversed, i.e. not assembled as indicated on drawing Needle chews
Webbing end (exposed)	End of cotton webbing (type III) not wax dipped as specified End of polypropylene webbing not fused as specified.
Thread ends	Not trimmed to 1/4 inch maximum length
Marking	Omitted, illegible, incorrect, not specified type or size, misplaced Label wider than webbing or extends beyond edge of webbing

4.4.4 End item dimensional examination. The end item shall be examined for defects in dimensions. Any dimension not within the established tolerance shall be classified as a defect. The lot size shall be expressed in units of slings. The sample unit shall be one sling. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:38Z
Check the source to verify that this is the current version before use.

4.4.5 Packaging inspection. An examination shall be made to determine that the preservation, packing, and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged. The lot size shall be the number of shipping containers in the inspection lot. The inspection level shall be level S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible, of improper size, location, sequence, or method of application.
Materials	Any component missing. Any component damaged.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, improper taping, loose strapping or inadequate stapling. Bulged or distorted container.
Content	Number of bundles per container is more or less than required. Number of slings per bundle is more or less than required. 1/

1/ For this defect, one bundle shall be examined from every ten bundles in each shipping container in the sample.

4.4.6 Palletization examination. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

Examine	Defect
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A packing. Each type I and type II sling shall be adjusted to its shortest length and folded in half to an approximate length of 14-1/2 and 17 inches, respectively. Each type III sling shall be folded in half to approximately 10 inches in length. Five folded slings for one type only shall be neatly stacked in a bundle, reversing each sling end for end. Each bundle shall be securely tied with cotton tape or twine approximately two inches in from each end.

5.1.2 Commercial. The slings shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A. Two hundred and fifty type I slings, eighty type II slings, or five hundred type III slings, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A unit pack arrangement of each type of sling within a shipping container and approximate inside dimensions of shipping containers shall be as specified in table I. Each container shall have the contents completely covered on the top and bottom with a sheet of 30 pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced in accordance with the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

TABLE I. Level A unit pack arrangement and approximate inside dimensions of shipping containers 1/

Type of sling	Level A unit pack arrangement packed flat	Approximate inside dimensions 1/ of shipping containers (inches)
Type I	Ten in length by one in width by five in depth	23-1/2 by 15 by 15
Type II	Eight in length by one in width by two in depth	22-1/2 by 17-1/2 by 10
Type III	Two in length by five in width by ten in depth	20 by 12-1/2 by 11-1/4

1/ Approximate dimensions are furnished as a guide only.

5.2.2 Level B packing. Two hundred and fifty type I slings, eighty type II slings, or five hundred type III slings, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A unit pack arrangement of each type of sling within a shipping container and approximate inside dimensions of shipping containers shall be specified in table I. Each container shall have the contents completely covered on the top and bottom with a sheet of 30 pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.2.1 Water-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.3 Commercial packing. Slings, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), slings of one description only, packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet patterns shall be in accordance

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:38Z
Check the source to verify that this is the current version before use.

with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951 as applicable.

6. NOTES

6.1 Intended use. The slings are used by Military personnel within the Department of Defense. Type I, type II and type III slings are components used with various bag or case assemblies to carry miscellaneous equipment as follows:

Type I sling is used with the following items:

Bag, BG - 44.
Case. Tentage Repair Kit.
Field Pack, Canvas Combat.
Field Pack, Combat (Nylon).
Public Address Sets.
Shutter Telescope: AN/GVA-1.
Telephone Sets.

Type II sling is used to carry the following:

Reeling Machine, TM-E11-362 to DL31W1-3R6-311, RL31, (with one or two reels of wire).

Type III sling is used to carry a converter for telephone and telegraph set.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this document.
b. Type required (see 1.2.1).
c. When first article is required (see 3.2, 4.3 and 6.4).
d. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

6.3 Samples. For access to samples, address the contracting office issuing the invitation for bids.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209-4. The first

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

article should be a preproduction sample consisting of at least one completely finished sling assembly. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for inspection and approval of the first article.

6.5 Marginal identification. The margins of this document are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in those notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

6.6 Recycled materials. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.3).

Custodians:

Army - GL
Navy - NU
Air Force - 99

Review activities:

Army - MD, ER
Air Force - 82

User activities:

Army - AR
Navy - MC
Air Force - 45

Preparing activity:

Army - GL

Project No. 8465-0651

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:38Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation as too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760-5014

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-1698G	Slings, Bag and Case Carrying

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* — Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* — Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* — Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 2026-01-16T13:38Z
Check the source to verify that this is the current version before use.