INCH-POUND
MIL-DTL-1698H
31 August 2023
SUPERSEDING
MIL-S-1698G
28 August 1984

DETAIL SPECIFICATION

SLINGS, BAG AND CASE CARRYING

This document is approved for use by all Departments and Agencies of the Department of Defense (DoD).

1. SCOPE

1.1 Scope. This specification covers three (3) types of bags and case carrying adjustable slings made of webbing with hardware attached.

1.2 Classification. The slings will be available in the following types as specified.

1.2.1 Types.

Type I - General Purpose
Type II - ST-19-A
Type III - 19-3/4 inches long

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

Comments, suggestions, or questions on this document should be addressed: Attn: DLA Troop Support, 700 Robbins Street, Philadelphia, PA 19111-5096. Since contact information can change, verify the currency of the address information using Acquisition Streamlining and Standardization Information System (ASSIST) online database https://assist.dla.mil .

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

COMMERCIAL ITEM DESCRIPTIONS

A-A-203 - Paper, Kraft, Untreated
A-A-55620 - Loops, Slide for Equipage
A-A-59963 - Thread, Polyester

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-F-495 - Finish, Chemical, Black, for Copper Alloys
MIL-C-496 - Clip, End, Strap
MIL-DTL-530 - Webbing, Textile, Cotton, General Purpose, Natural or in Colors
MIL-B-543 - Buckles, Tongueless and Web Strap
MIL-L-3851 - Loops, Slide (For Equipage)
MIL-DTL-4088 - Webbing, Textile, Woven, Nylon
MIL-L-11075 - Loops, Strap Fastner
MIL-DTL-32075 - Label: For Clothing, Equipage, and Tentage, (General Use)
MIL-W-44049 - Webbing, Textile And Tape, Textile, Polyropylene, General Purpose, Natural Or In Colors

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-129 - Military Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

(Copies of these documents are available online at https://quicksearch.dla.mil)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation or contract.

U.S. ARMY, DEVCOM – SOLDIER CENTER

2-1-80 - Sling, Bang and Case Carrying, Type I, General Purpose
2-4-68 - Sling, Bag and Case Carrying, Type II, ST-19-A Assembly Complete
2-2-256 - Sling, Bag and Case Carrying, Type III, 19-3/4 inches Long, Assembly and Details

(Copies of drawings are available from the U.S. Army, DEVCOM Soldier Center, ATTN: FCDD-SCP-PEI, 15 General Greene Avenue, Natick, MA 01760-5019.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

(Comments, suggestions, or questions on this document should be addressed to: U.S. Army, DEVCOM – Soldier Center, ATTN: FCDD-SCD-PEI, 15 General Greene Avenue, Natick, MA 01760-5019.)

OTHER GOVERNMENT DOCUMENTS AND PUBLICATIONS

CODE OF FEDERAL REGULATIONS

Title 16 CFR Part 303 – Rules and Regulations Under the Textile Fiber Products Identification Act

(Copies of this documents are available online at https://www.ecfr.gov)

(Copies of specifications, standards, drawings and publications required by contractors in connection with specification procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AEROSPACE INDUSTRY ASSOCIATION OF AMERICA INC.

NASM 43770-1 - Snap Hooks, Wire Body, Fixed Loop Eye, Flat Spring Closure with Retainer

(Copies of these documents are available from https://www.aia-aerospace.org)

AMERICAN SOCIETY FOR QUALITY (ASQ)

ASQ/ANSI Z1.4 - Sampling Procedures and Tables for Inspection by Attributes

(Copies of this document are available online at https://asq.org)

ASTM INTERNATIONAL

ASTM B633	- Zinc on Iron and Steel, Electrodeposited Coatings of
ASTM D1974/D1974M	- Fiberboard Boxes, Methods of Closing, Sealing, and Reinforcing, Standard Practice for
ASTM D3990	- Standard Terminology Relating to Fabric Defects
ASTM D5118/D5118M	- Boxes, Fiberboard Shipping, Fabrication of
ASTM D6193	- Standard Practice for Stitches and Seams

(Copies of these documents are available online at https://www.astm.org)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Unless a specific exemption has been obtained, nothing in this document, supersedes applicable laws and regulations.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2 and 6.3), a sample shall be subjected to first article inspection in accordance with 4.3.1.

3.2 Conformance inspection. When specified, a sample shall be subjected to inspection in accordance with 4.3.2.

3.3 Standard sample. Unless otherwise indicated, the finished sling bag and case carrying, shall match the standard sample for shade and appearance, and shall, be equal to or better than the standard sample with respect to all characteristics for which the standard sample is referenced (see 6.3).

3.4 Recycled, recovered, environmentally preferable, or biobased materials. Recycled, recovered, environmentally preferable, or biobased materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

3.5 Material(s).

3.5.1 Webbing.

3.5.1.1 Webbing for Type I sling. The 2-inch webbing shall be nylon conforming to MIL-DTL-4088 Type VIIIb, or as an alternative the webbing shall be polypropylene conforming to Type IIa, Class 4 of MIL-W-44049. The webbing shall be dyed color Camouflage Green 483 and shall have a finished length of 48-inches.

3.5.1.2 Webbing for Type II sling. The 2-inch webbing shall be nylon conforming to MIL-DTL-4088 Type VIIIb. The webbing shall be dyed Camouflage Green 483 and shall have a finished length of 54-inches.

3.5.1.3 Webbing for Type III sling. The 1-inch webbing shall be nylon conforming to MIL-DTL-4088 Type II. The webbing shall be dyed Camouflage Green 483 and shall have a finished length of 19.75-inches.

3.5.2 Thread, polyester. The polyester thread for the slings shall conform to Type I, Class 1, Subclass A, size FF of A-A-59963 and shall be dyed Camouflage Green 483. The dyed thread shall show fastness to weathering equal to or greater than the standard sample. When no standard sample is available, the thread shall show a minimum of 3.5 Grade for fastness to weathering.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

3.5.3 Metal components.

3.5.3.1 Metal components for Type I sling.

3.5.3.1.1 Loop, slide. The slide loop for the Type I sling shall be brass or steel and shall conform to Class 1 or Class 3, Style 2, Size 2-inch, construction A, of MIL-L-3851.

3.5.3.1.2 Loop, strap. The strap loop for the Type I sling shall be brass or steel wire and shall conform to Type I or III, Style E, 2-1/16 by 1/4-inch, of MIL-L-11075.

3.5.3.1.3 Snaphook. The snaphooks for the Type I sling shall be brass or steel wire and shall conform to dash No. CWBC3 or SWZE3 of NASM 43770-1.

3.5.3.2 Metal components for Type II sling.

3.5.3.2.1 Loop, slide, brass. The slide loop for the Type II sling shall be brass, 2-1/4 inch, conforming to MIL-L-3851for 2-inch strap (A-A-55620), 7S, construction B, Class 1 Style 2, except that opening length shall be 1/4-inch and the overall length shall be 1-1/16-inches. The slide loop shall have a black chemical finish conforming to MIL-F-495.

3.5.3.2.2 Snap swivel, loop eye. The loop eye swivel snaps for the Type II sling shall be cast malleable iron, 2-inch. Prior to the use of the "or equal" item, the contractor shall submit the item to the contracting office with supporting data for approval. The finish shall consist of electroplated zinc followed by a phosphate treatment and bake enameling. The phosphate zinc plate shall be 13 um thick conforming to ASTM B633. After phosphating and drying, surfaces shall be given a finish of black enamel conforming to Type II semi-gloss. The coating shall level out to a continuous uniform film without objectionable orange peel, wrinkles, drops streaks or area of no film.

3.5.3.3 Metal components for the Type III sling.

3.5.3.3.1 Buckle. The 2-bar tongueless buckle shall conform to Type II, Style 1, Class 1 or Class 3, size 1-inch of MIL-B-543.

3.5.3.3.2 Clip. The end clip shall conform to Type I, Class 1 or Class 2, size 1-inch of MIL-C-496.

3.6 Construction. The construction shall conform in all respects to drawing 2-1-80 for Type I, drawing 2-4-68 for Type II, and drawing 2-2-256 Type III and as specified herein.

3.6.1 Stitching, machine. All stitching shall conform to Type 301 of ASTM D6193, with 6 to 8 stitches per inch.

3.6.1.1 Automatic stitching. Any of the stitching operations cited in this document may be performed with an automatic machine provided the requirements for stitch pattern, stitches per

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

inch, size and types of thread are met; and at least three (3) tying, overlapping or backstitches are used to secure the ends of stitching.

3.6.1.2 Type 301 stitching. Ends of all stitching shall be backstitched or bartacked not less than 1/2-inch except where ends are caught in other seams and stitching. Thread tensions shall be maintained so that there will be no loose or tight stitching and the lock will be imbedded in materials sewed.

3.6.1.2.1 Repairs to type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When the thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 3/4-inch back of the end of stitching. 1/
b. Thread breaks or two (2) or more consecutive skipped or runoff stitches noted during inspection of the item (in-process or end item), shall be repaired by overstitching. The stitching shall start a minimum of 3/4-inch in back of the defective area, continue over the defective area, and continue a minimum of 3/4-inch beyond the defective area onto existing stitching. 1/
c. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials, and restitching in the required manner.

1/ When making the above repairs, the ends of stitching are not required to be backstitched.

3.6.1.3 Thread ends. All thread ends shall be trimmed to 1/4-inch maximum length.

3.6.2 Setting of the end clip (Type III sling). The webbing shall be inserted the full depth of the clip. The clip shall be securely attached without cutting the webbing and the webbing shall be flat at the point of entry.

3.6.3 Wax dipping of webbing end (Type III sling). The cut end of the cotton webbing not enclosed in the end clip shall be dipped 1/4-inch full width minimum into a melted mixture of approximately 50 percent beeswax and 50 percent parrifin. The temperature of the melted mixture shall be 180 (±20) °F.

3.6.4 Fusing the ends of polypropylene webbing (Type I sling). All ends of polypropylene webbing shall be fused. The apparatus used to fuse the webbing ends shall be capable of providing sufficient heat to provide a smooth edge with the cut end of the webbing yarns all fused together. Fusing of the webbing ends shall be accomplished prior to being assembled for stitching.

3.7 Marking.

3.7.1 Marking on webbing. The identification marking shall be applied in the location shown on the applicable drawing and shall conform to Type IV, Class 5 of MIL-DTL-32075. The marking “US” for Type I or “ST-19-A” for Type II, as required, shall be applied in the size characters and the location indicated on the applicable drawing, and shall conform to Type IV,

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

Class 9 of MIL-DTL-32075. Fastness of Class 9 marking shall be as specified for Class 5 marking.

3.7.2 Alternate marking on polypropylene webbing (Type I sling). A Type VI label of MIL-DTL-32075 may be used in lieu of direct item marking. The label color shall be medium green and the marking shall conform to the Type I sling marking requirements specified in 3.5.1. The label shall not be wider than, or any portion of it allowed to extend beyond the edge of the webbing which it is to be attached.

3.7.3 Bar code hang tag. Each sling bag and case carrying shall have a barcode label/hangtag conforming to Type VIII, Class 17 of MIL-DTL-32075. The bar coding element shall be a 13 digit National Stock Number (NSN). There shall be a 12 digit Universal Product Code (UPC) number assigned for all NSNs by the contracting activity. The initials "UPC" must appear beneath the code. The barcode for NSN and UPC type shall be a medium to high density and shall be located so that it is completely visible on the slings bag and case carrying when it is folded and/or packaged as specified and so it causes no damage.

3.8 Toxicity. Unless otherwise specified in the contract or procurement documents, the finished slings, bag and case carrying, shall not present a health hazard and shall show compatibility with prolonged, direct skin contact when tested as specified in 4.7.

3.9 Workmanship. The finished slings bag and case carrying shall be uniform in quality and shall conform to the quality of product established by this specification. The occurrence of defects, as specified in 4.4, shall not exceed the criteria specified in the contract or purchase order.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2)
b. Conformance inspection (see 4.3)

4.2 Inspection conditions. Unless otherwise specified, excluded, amended, modified or qualified in this specification or applicable procurement documents (see 6.2), all inspections shall be performed in accordance with all the requirements of referenced documents.

4.3 Types of inspections.

4.3.1 First article inspection. The first article, submitted in accordance with 3.1 shall be inspected for appearance, color, finished measurements listed in Table II, examination for defects in 4.4 and tested for the characteristics as specified in Table II.

4.3.2 Conformance inspection. Conformance inspection shall include the examination of defects in 4.4 and the tests of 4.6 through 4.7 as applicable. Sampling for inspection shall be performed in accordance with ASQ/ANSI Z1.4 and with acceptance quality limits as specified in the contract and/or procurement documents, except where otherwise indicated. (See 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

4.3.3 Component and material inspection. In accordance with 4.2, components and materials shall be inspected in accordance with all requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.3.3.1 Certification. The contractor shall furnish a certification of compliance (CoC) for the requirements specified in 3.3.4.1 and 3.3.4.2.

4.3.4 In-process inspection (Types I and II). Inspection shall be performed prior to fabrication of Type I or Type II sling to determine compliance with cut length requirement. Any cut length of webbing not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of unassembled slings. The sample unit shall be one (1) unassembled sling. The inspection level and the acceptable quality limit (AQL), expressed in terms of defects per hundred units, shall be as specified in the contract or solicitation.

4.4 Visual examination. The slings bag and case carrying shall be examined for the defects listed in Table I.

TABLE I. Defects.

Defect		Classification	
		Major	Minor
Webbing	Outside – Any hole, cut, tear, or weakening defect such as smash, multiple float, needle chew, loose slub, fabric cut on wrong side, stamping marks.	101	
	Color not as specified.		201
	Visible mend, broken or missing yarn, misweave, thin place, shade part/bar greater than 1/4-inch.	102	
Hardware	Finish not as specified	103	
	Any hardware component not assembled as specified	104	
	End Clip (Type III) Not properly or securely set	105	
	Snap Hook (Type I and Type II) Defective fails to function properly	106	
Finish	Not as specified	107	
Assembly and construction	Not as specified	108	
	Open seams	109	
	Runoffs (see open seams)	110	
Seam and Stich type	Wrong seam or stitch type	111	
Stitch Tension	Loose, resulting in a loosely exposed top bobbin thread; tight resulting in tightness of seams	112	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

TABLE I. Defects - Continued

Defect		Classification	
		Major	Minor
Stitches per inch	One (1) or more stitches less than the minimum specified. One (1)or more stitches in excess of the maximum specified.	113	
Stitching margin	Not within specified tolerance	114	
Thread breaks	Overstitched less than 3/4 inch (all types)	115	
"W" stitching	One (1) or more rows of stitching omitted (all types)	116	
Box stitching	One (1) or more rows of stitching omitted (Type I)	117	
Stitching ends	Backstitched less than 1/2 inch		202
Components and assembly	Any component part or required operation omitted (unless otherwise classified herein) Mend or darn Any component reversed, i.e. not assembled as indicated on the drawing. Needle chews.	118	
Webbing end (exposed)	End of cotton webbing (Type III) not wax dipped as specified. End of polyproplene webbing not fused as specified.	119	
Thread ends	Not trimmed to 1/4 inch maximum length		203
Marking	Omitted, illegible, incorrect, not specified type or size misplaced. Label wider than webbing or extends beyond edge of webbing	120	

4.5 Methods of inspection.

4.5.1 End item dimensionsal examination. The end item shall be examined for defects in dimensions. Any dimension not within the established tolerance shall be classified as a defect. The lot size shall be expressed in units of slings. The sample unit shall be one (1) sling. The inspection level and the AQL shall be as specified in the contract or solicitation.

4.6 Component and end item testing. The slings, bag and carrying case shall be tested for the characteristics listed in Table II. The methods of testing as specified wherever applicable and as listed in Table II shall be followed. All test reports shall contain the individual values utilized in expressing the final results. The sample unit shall be as specified in the contract or solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

TABLE II. Component and end item testing.

Characteristic	Requirement Reference	Test method
Webbing	3.5.1	
Type I Finished dimensions Color	3.5.1.1	MIL-DTL-4088 or alternate MIL-W-44049 Calibrated ruler 4.6.1
Type II Finished dimensions Color	3.5.1.2	MIL-DTL-4088 Calibrated ruler 4.6.1
Type III Finished dimensions Color	3.5.1.3	MIL-DTL-4088 Calibrated ruler 4.6.1.
Thread Color	3.5.2	A-A-59963 4.6.1
Metal Components	3.5.3	
Type I Loop, slide Finished dimensions Loop, strap Finished dimensions Snaphook Finished dimensions	 3.5.3.1 3.5.3.1.1 3.5.3.1.2 3.5.3.1.3	 MIL-L-3851 Calibrated Ruler MIL-L-11075 Calibrated ruler NASM 43770/1 Calibrated ruler
Type II Loop, slide, brass Finished dimensions Finish	 3.5.3.2 3.5.3.2.1	Calibrated ruler MIL-F-495
Snap swivel loop eye Finished dimensions Thickness Finish	 3.5.3.2.2	 Calibrated ruler ASTM B633 A-A-2962. Type II was semigloss. Gloss level is ASTM D523
Type III Buckle Clip Dimensions	 3.5.3.3 3.5.3.3.1 3.5.3.3.2	 MIL-B-543 MIL-C-496 Calibrated ruler
Toxicity	See 3.8	See 4.7 and 6.6

4.6.1 Visual shade matching (all Classes). The color and appearance of the Slings, Bag and Case Carrying shall match the standard sample when viewed using the AATCC EP 9, Option C, (see 6.5) with a primary light source simulating the spectral quality of average daylight, CIE Illuminant D65, with a color temperature of 6500 (± 200) Kelvin (K) illumination of 100 (± 20) foot candles. Alternatively, the color and appearance of the Slings, Bag and Case Carrying shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

match the standard sample with a primary light source simulating artificial daylight, CIE Illuminant D75, with a color temperature of 7500K (± 200) illumination of 100 (± 20) foot candles in lieu of D65. (See 6.5.1). The Slings, Bag and Case Carrying shall also be a good match to the standard sample with a secondary source simulating the spectral quality of incandescent lamplight, CIE Illuminant A, with a color temperature of 2856K (± 200).

4.7 Toxicity test. When the toxcity requirement (see 3.8) can be demonstrated with historical use data on the finishing treatments used, toxicity testing may not be required (see 6.2 and 6.6).

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The slings are used by Military personnel within the Department of Defense. Type I, Type II and Type III slings are components used with the various bags, or case assemblies to carry miscellaneous equipment as follows:

Type I - Sling is used with the following items:
Bag, BG-44
Case. Tentage Repair Kit.
Field Pack, Canvas Combat.
Field Pack, Combat (Nylon).
Public Address Sets.
Shutter Telescope: AN/GVA-1
Telephone Sets.

Type II - Sling is used to carry the following:
Reeling Machine, TM-E11-362 to DL31W1-3R6-311, RL31, (with one (1) or two (2) reels of wire).

Type III - Sling is used to carry a converter for the telephone and telegraph set.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

6.2 Acquisition requirements. Acquisition documents should specify the following.

a. Title, number, and date of this specification.
b. Type required (see 1.X).
c. The specific issue of individual documents referenced (see 2.).
d. When first article is required (see 3.1 and 4.3.1).
e. When toxicity is required (see 3.8, 4.7).
f. Inspection conditions (see 4.2).
g. Performance inspection with acceptance quality limits (AQL) (see 4.3.2 and 4.3.4).
h. Packaging (see 5.1).

6.3 Standard sample. For access to samples and pattern drawings, address the contracting activity issuing the invitation for bids or request for proposal.

6.4 Certificate of compliance. The contracting activity may select to accept a certificate of compliance for that specified requirement.

6.5 Visual shade matching. In 2017, Option A of AATCC Evaluation Procedure 9, Visual Assessment of Color Difference of Textiles was changed to Option C. NOTE: In case of confusion, the viewing geometry should be "The specimen plane and illumination source will be parallel to each other and aligned so that the light flux is incident at the center of the specimen plane, which is set at a 35 (± 5°) angle relative to the horizontal. The observer will view the specimens at a 90° angle, relative to the plane of the specimens".

6.5.1 In 2022, the U.S. Military (All Services) accepted D65 as the new preferred light source for visual shade matching due to the supply chain issues with D75.

6.6 Toxicity testing. If dermal toxicity testing is required, it will be conducted using Title 40, Protection of Environment, Code of Federal Regulations current edition and applicable sections, which are also consistent with the following OECD tests:

Skin Sensitization 406 and Dermal Irritation 404 (https://www.oecd-ilibrary.org/environment/oecd-guidelines-for-the-testing-of-chemicals-section-4-health-effects_20745788?page=1

Dermal Sensitization (https://www.law.cornell.edu/cfr/text/40/798.4100)
Dermal Toxicity (https://www.law.cornell.edu/cfr/text/40/798.2250)

6.7 National Stock Numbers (NSN).

Type I - 8465002690682
Type II – 8465004981713
Type III - 8465002755755

6.8 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.

6.9 Subject term (key word) listing.

Cover, Water Canteen
Field Pack, Canvas Combat.
Field Pack, Combat (Nylon).
Public Address Sets.
Reeling Machine,
Shutter Telescope: AN/GVA-1
Telephone Sets
Telegraph Sets
Tentage Repair Kit.

Custodians:
Army – GL
Navy - NU
Air Force - 11

Preparing activity:
DLA-CT

(Project 8465-2023-007)

Review activities:
Army – AR, ER, MD
Navy - MC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:38Z
Check the source to verify that this is the current version before use.