MIL-S-1734H
6 December 1984
SUPERSEDING
MIL-S-1734G
30 July 1974

MILITARY SPECIFICATION

SLIPS, TENT LINE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This documents covers two types of tent line slips.

1.2 Classification. The tent line slips furnished under this document shall be of the following types as specified (see 6.2):

Type I - Flat, quick release
Type II - Casting

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-A-200/8 - Aluminum Alloy 6061, Bar, Rod, Shapes, Tube and Wire, Extruded

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8340

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:42Z
Check the source to verify that this is the currentversion before use.

QQ-A-250/8 - Aluminum Alloy 5052, Plate and Sheet
QQ-A-250/11 - Aluminum Alloy 6061, Plate and Sheet
QQ-M-31 - Magnesium Alloy, Bars,, Rods, and Special Shaped Sections, Extruded
QQ-M--38 - Magnesium Alloy Die Castings (AZ91A)
QQ-M-44 - Magnesium Alloy Plate and Sheet (AZ31B)
QQ-M-55 - Magnesium, Alloy, Permanent and Semi-Permanent Mold Castings
QQ-M-56 - Magnesium Alloy, Sand Castings
TT-E-529 - Enamel, Alkyd, Semi-Gloss

TT-P-1757 - Primer Coating, Zinc Chromate, Low-Moisture-Sensitivity
PPP-B-601 - Boxes, Wood, Cleated-Plywood
PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-M-3171 - Magnesium Alloy, Processes for Pretreatment and Prevention of Corrosion On
MIL-L-10547 - Lines, Case, and Sheet, Overwraps, Water Vapor or Waterproof Flexible

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

DRAWING

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

5-4-26 - Slips, Tent Line

(Copies of documents required by the manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:42Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

B 94 - Magnesium - Alloy Die Castings
B 449 - Chromate Treatment on Aluminum
B 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 5.2 and 6.3).

3.2 Materials (see 6.4). Materials when specified shall conform to the applicable documents and requirements specified herein.

3.2.1 Magnesium alloy.

3.2.1.1 Bar. Magnesium alloy bar shall conform to composition AZ80A-F of QQ-M-31.

3.2.1.2 Plate. Magnesium alloy plate shall conform to condition H24 or H26 of QQ-M-44.

3.2.1.3 Castings. Magnesium alloy castings shall be fabricated by any one of the following methods:

a. Die casting - Die casting shall conform to QQ-M-38 or magnesium alloy AZ91B of ASTM B 94.

b. Permanent mold casting - Permanent mold casting shall conform to composition AZ91C, temper T6 of QQ-M-55.

c. Sand casting - Sand casting shall conform to alloy AZ91C, temper T6 of QQ-M-56.

3.2.2 Aluminum.

3.2.2.1 Alloy 5052. Aluminum alloy 5052 plate and sheet shall conform to either temper H24, H26, H34, or H36 of QQ-A-250/8.

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:42Z
Check the source to verify that this is the currentversion before use.

3.2.2 Alloy 6061. Aluminum alloy 6061 shall conform to temper T6 of QQ-A-250/11, or QQ-A-200/8.

3.2.3 Primer. Primer shall conform to composition G or L, as applicable, color Y of TT-P-1757.

3.2.4 Enamel. Enamel shall conform to composition G of L, as applicable, olive drab color No. 24087 of TT-E-529.

3.3 Construction. Construction of the tent line slips shall conform to Drawing 5-4-26 and as specified herein.

3.3.1 Type I. Type I tent slip shall be fabricated of either magnesium alloy specified in 3.2.1.1 or 3.2.1.2 or aluminum alloy specified in 3.2.2.1 or 3.2.2.2. The tent line slip shall be sound and free from seams, slivers, laminations, grooves or cracks.

3.3.2 Type II. Type II tent line slips shall be fabricated of any one of the three materials specified in 3.2.1.3. The casting shall be sound and free from repair such as impregnation, peening and weld.

3.4 Finish. Any burr, sharp edge and rough spot shall be removed prior to application of finish.

3.4.1 Chemical treatment. All surfaces of the magnesium tent line slips shall be given a chemical treatment conforming to type I, III, or IV of MIL-M-3171. All surfaces of the aluminum tent line slips shall be prepared for painting in accordance with class 1 or 2 of ASTM B 449.

3.4.2 Priming. After the chemical treatment, all surfaces shall be coated with primer specified in 3.2.3.

3.4.3 Enameling. After dying, all primed surfaces shall then be coated with enamel specified in 3.2.4. The coating shall level out to produce a smooth, uniform, dry film without runs, wrinkles, streaks, grit, coarse particles, and areas of thin or no film.

3.5 Workmanship. The finished tent line slips shall be clean, smooth, and free from fracture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required, it shall be examined for defects specified in 4.4.3 and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.2 In-process inspection. Examination shall be made of the following operations to establish conformance to specified requirements. Whenever non-conformance is noted, correction shall be made to the items affected, the lot in process, and to the operation. Parts which cannot be corrected shall be removed from production.

Requirement or operation	Requirement reference
Removal of burr, sharp edge, and any rough spot	3.4
Chemical treatment of all surfaces prior to application of primer	3.4.1
Drying of prime coat to application of enamel	3.4.3

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:42Z
Check the source to verify that this is the current version before use.

4.4.3 End item visual examination. The end item shall be examined for the defects listed in table I. The lot size shall be expressed in units of slips. The sample unit shall be one slip. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 10.0 for total (major and minor combined) defects.

Examine	Defect	Classification Major	Classification Minor
Finish	Not finished.	X	
	Color of finish is not as specified.		X
	Coating not smooth or not uniform		X
	Finish is not dry, i.e., wet or tacky to touch.		X
	Run, wrinkle, streak, grit or coarse particles.		X
	Area of no film exposing bare metal.	X	
	Area of thin film exposing primer coating.		X
Construction and workmanship (applicable to all types of slips)	Any slip not fabricated of the applicable referenced material.	X	
	Not fabricated as specified, such as wrong type, any hole not drilled through or hole not countersunk as required.	X	
	Not clean or not smooth.		X
	Fractured.	X	
	Not sound.	X	
	Evidence of burr, sharp edge, or any rough spot.		X
Type I slip	Seam, sliver, lamination, groove, or crack.		X
Type II slip	Repairs such as impregnation peening, or weld.		X

4.4.4 End item dimensional examination. The end item shall be examined for conformance to the specified dimensions shown on the drawing. Any dimensions not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of slips. The sample unit shall be one slip. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

4.4.5 Packaging inspection. An examination shall be made to determine that preservation, packing, and marking comply with section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged with the exception that it need not be closed. Examination of closure defects listed below shall be made on shipping containers fully packaged. The lot size shall be the number of containers in the inspection lot. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, not as specified.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, improper taping, loose strapping, or inadequate stapling. More than one type of slip packed in any container. Bulged or distorted container.
Content	Number of unit packs per shipping container is more or less than required. Number of required components per unit pack is more or less than required.

4.4.6 Palletization examination. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Not as specified. Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limit.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Four hundred tent line slips of one type only shall be unit packed in a snug-fitting fiberboard box conforming to style RSC, type CF, variety SQW, or type SF, class domestic, grade 200 of PPP-B-636. Each box shall be agitated during filling to assure a compact package having a minimum of void space. Each container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except the inspection shall be in accordance with 4.4.5.

5.1.2 Commercial. The tent slips shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Twenty-four hundred tent line slips of one type only, preserved as specified in 5.1, shall be packed in the most compact manner in a snug-fitting shipping container conforming to overseas type, style A or J, type 2 load of PPP-B-601. Each container shall be waterproofed with a sealed case liner conforming to type I, or II, grade C of MIL-L-10547; and closed and reinforced with steel strapping in accordance with the appendix of PPP-B-601.

5.2.2 Level B packing. Twenty-four hundred tent line slips of one type only, preserved as specified in 5.1, shall be packed in the most compact manner in a snug-fitting shipping container conforming to style FTC, type CF, class domestic, variety DW, grade 350 of PPP-B-636. Closure and reinforcing with strapping or tape banding shall be in accordance with class weather-resistant requirements in the appendix of PPP-B-636, except the inspection shall be in accordance with 4.4.5.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.3 Commercial. Slips preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

5.3 Palletization. When specified (see 6.2), slips packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The tent line slips are intended to be used for adjusting and holding tension on guy lines and ropes of various tents.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type of tent line slip required (see 1.2).
c. When a first article is required (see 3.1, 4.3 and 6.3).
d. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
e. When weather-resistant fiberboard shipping containers shall be required for level B pack (see 5.2.2.1).
f. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for inspection and approval of the first article.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.2).

6.5 International standardization agreements. Certain provisions of this specification are the subject of international standardization agreement as cited in NATO, STANAG No. 2882, relative to camouflage requirements for tents, shelters and subsidiary components. When amendment, revision, or cancellation of this specification is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:42Z
Check the source to verify that this is the current version before use.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Review activities:

Army - MD
Air Force - 82
DLA - CT

User activities:

Navy - MC, YD
Air Force - 45

Preparing activity:

Army - GL

Project No. 8340-0458

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:42Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-1734H	Slips, Tent, Line

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:42Z
Check the source to verify that this is the current version before use.