INCH-POUND

MIL-DTL-1734J
30 January, 2002
SUPERSEDING
MIL-S-1734H
6 December, 1984

DETAILED SPECIFICATION

SLIPS, TENT LINE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers two types of tent line slips.

1.2 Classification. (see 6.2).

Type I - Flat, quick release
Type II - Casting

2. APPLICABLE DOCUMENTS

*2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise

Beneficial comments (recommendations, additions, deletions, clarifications) and any pertinent data which may be of use in improving this document should be addressed to: Defense Supply Center Philadelphia, Clothing and Textiles Directorate, Attn: DSCP-CNR, 700 Robbins Ave., Philadelphia, PA 19111-5096 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8340

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:41Z
Check the source to verify that this is the current version before use.

specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

TT-E-529	- Enamel, Alkyd, Semi-Gloss
TT-P-1757	- Primer Coating, Zinc Chromate, Low-Moisture-Sensitivity

MILITARY

MIL-L-10547	- Liner, Case and Sheet, Overwraps, Water Vapor or Waterproof, Flexible

*2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY BIOLOGICAL & CHEMICAL COMMAND

5-4-26	- Slips, Tent Line

(Copies of drawings are available from the U. S. Army Biological and Chemical Command, ATTN: SSCNC-EMSS, NATICK, MA 01760-5017.)

*2.3 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-B-80	- Magnesium-Alloy Sand Castings
ASTM-B-94	- Magnesium – Alloy Die Castings
ASTM-B-107	- Magnesium-Alloy Extruded Bars, Rods, Shapes, Tubes and Wire
ASTM-B-199	- Magnesium-Alloy Permanent Mold Castings
ASTM-B-209	- Aluminum and Aluminum-Alloy Sheet and Plate
ASTM-B-449	- Chromate Treatment on Aluminum

(Applications for copies of referenced documents should be addressed to the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19426-2959.)

SOCIETY OF AUTOMOTIVE ENGINEERS

AMS 3171	- Magnesium Alloy, Processes for Pretreatment and Prevention of Corrosion on

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:41Z
Check the source to verify that this is the current version before use.

AMS 4375 - Sheet and Plate, Magnesium Alloy, 3.0AL – 1.0ZN – 0.20MN (AZ31B-0) Annealed and Recrystallized
AMS 4376 - Sheet and Plate, Magnesium Alloy, 3.0AL – 1.0ZN – 0.20MN (AZ31B-H26) Cold Rolled and Partially Annealed
AMS 4377 - Sheet and Plate, Magnesium Alloy, 3.0AL – 1.0ZN – 0.20MN (AZ31B-H24) Cold Rolled, Partially Annealed

(Applications for copies of referenced documents should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096-0001)

*2.4 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification takes precedence. Nothing in this specification, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

*3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 4.2 and 6.2).

*3.2 Materials and components. Materials and components shall be as specified herein and on the applicable drawings. Materials and components not definitely specified shall be of the quality normally used by the manufacturer provided the completed item complies with all the provisions of this document.

3.2.1 Magnesium alloy.

*3.2.1.1 Bar. Magnesium alloy bar shall conform to ASTM-B-107.

*3.2.1.2 Plate. Magnesium alloy plate shall conform to condition H24 or H26 of AMS 4375, AMS 4376 or AMS 4377.

*3.2.1.3 Castings. Magnesium alloy castings shall be fabricated by any one of the following methods:

a. Die casting - Die casting shall conform to magnesium alloy AZ91B of ASTM B 94.

b. Permanent mold casting – Permanent mold casting shall conform to composition AZ91C, temper T6 of ASTM B 199.

c. Sand casting – Sand casting shall conform to ASTM-B-80.

3.2.2 Aluminum.

*3.2.2.1 Alloy 5052. Aluminum alloy 5052 plate and sheet shall conform to ASTM-B-209.

*3.2.2.2 Alloy 6061. Aluminum alloy 6061 shall conform to temper T-6 of ASTM-B-209, ASTM B 241 or ASTM B 221.

3.2.3 Primer. Primer shall conform to composition G or L, as applicable, color Y of TT-P-1757.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:41Z
Check the source to verify that this is the current version before use.

3.2.4 Enamel. Enamel shall conform to composition G or L, as applicable, olive drab color No. 20487 of TT-E-529.

3.3 Construction. Construction of the tent line slips shall conform to Drawing 5-4-26 and as specified herein.

3.3.1 Type I. Type I tent line slips shall be fabricated of either magnesium alloy specified in 3.2.1.1 or 3.2.1.2 or aluminum alloy specified in 3.2.2.1 or 3.2.2.2. The tent line slip shall be sound and free from seams, slivers, laminations, grooves or cracks.

3.3.2 Type II. Type II tent line slips shall be fabricated of any one of the three materials specified in 3.2.1.3. The casting shall be sound and free from repair such as impregnation, peening and weld.

3.4 Finish. Any burr, sharp edge and rough spot shall be removed prior to application of finish.

*3.4.1 Chemical treatment. All surfaces of the magnesium tent line slips shall be given a chemical treatment conforming to type I, II, III or IV of AMS-M-3171. All surfaces of the aluminum tent line slips shall be prepared for painting in accordance with class 1 or 2 of ASTM B 449.

3.4.2 Priming. After the chemical treatment, all surfaces shall be coated with primer specified in 3.2.3.

*3.4.3 Enameling. After dyeing, all primed surfaces shall then be completely coated with enamel specified in 3.2.4. The coating shall be a smooth, uniform, dry film without runs, blisters, wrinkles, streaks, grit, coarse particles, area of thin or no film, scratch or scuff, foreign matter imbedded in finish, and wet or tacky paint.

3.5 Workmanship. The finished tent line slips shall be clean, smooth and free from fracture.

*3.6 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).
b. Conformance inspection (see 4.3).

4.2 First article inspection. When a first article is required (see 6.2) the tent hooks it shall be examined for the defects listed in 4.3.4 and 4.3.5 and tested for the strength characteristic specified in 4.6.1.

4.3 Inspection.

4.3.1 Conformance inspection. Sampling for inspection shall be as specified in the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:41Z
Check the source to verify that this is the current version before use.

4.3.2 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.3.3 In-process inspection. Inspection shall be made of the operations and requirements listed in Table I to establish conformance with the specified requirements. Whenever nonconformance is noted, correction shall be made to the items affected and the operations. Items which cannot be corrected shall be removed from production. The government reserves the right to exclude from consideration for acceptance any material for which in-process inspection has indicated nonconformance.

Table I. In-process inspection.

Requirement or operation	Requirement paragraph
Removal of burrs, sharp edges and rough spots prior to finishing	3.4
Chemical treatment of all surfaces prior to application of primer	3.4.1
Drying of prime coat to application of enamel	3.4.3

*4.3.4 End item visual examination. The end item shall be examined for the defects listed in Table II. The lot size shall be expressed in units of slips. The sample unit shall be one slip. The inspection level shall be II.

TABLE II. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Color of finish is not as specified		201
	Not finished	101	
	Coating not smooth or uniform		202
	Finish is not dry, i.e., wet or tacky to touch		203
	Run, wrinkle, streak, grit or coarse particles		204
	Area of no film exposing bare metal	102	
	Area of thin film exposing primer coating		205
Construction & workmanship (applicable to all types of slips)	Any slip not fabricated of the applicable referenced material	103	
	Not fabricated as specified, such as wrong type, any hole not drilled through or hole not countersunk as required	104	
	Not clean or smooth		206
	Fractured	105	
	Not sound	106	
	Evidence of burr, sharp edge or any rough spot		207
Type I slip	Seam, sliver, lamination, groove or crack		208
Type II slip	Repairs such as inpregnation, peening or weld		209

*4.3.5 End item dimensional examination. Examination shall be made of the end item for compliance with the dimensions on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:41Z
Check the source to verify that this is the current version before use.

tolerance shall be classified as a defect. The lot size shall be expressed in units of slips. The sample unit shall be one slip. The inspection level shall be S-2.

5. PACKAGING

*5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The tent line slips are intended to be used for adjusting and holding tension on guy lines and ropes of various tents.

*6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. Type and size of tent hook required (see 1.2).
d. When first article is required (see 3.1, 4.2 and 6.4).
e. Levels of preservation and packing (see 5.1).

6.3 Sample. For access to standard sample, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article is required, it will be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.5 International standardization agreements. Certain provisions of this document are the subject of international standardization agreements as cited in NATO, STANAG NO. 2882, relative to camouflage requirements for tents, shelters and subsidiary components. When amendment, revision or cancellation of this document is proposed that will modify the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardization offices to change the agreement or make other appropriate accommodations.

*6.6 Subject term (key word) listing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:41Z
Check the source to verify that this is the current version before use.

Attachment fixtures
Fasteners

*6.7 Equal item. Prior to the use of an "or equal" item, the supplier must submit the item, with supporting data to the contracting officer for subsequent approval or disapproval by the responsible military agency.

6.8 Changes from previous issue. The margins of this document have been marked with an asterisk(*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, as written, irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - GL
Navy – NU
Air Force – 11.6

Preparing activity:
DLA-CT

Project No: 8340-0599

Review activities:
Army – MD
Navy – MC, YD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7 and send to preparing activity.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** MIL-DTL-1734J	**2. DOCUMENT DATE** ***(YYYYMMDD)*** 2002/01/30

3. DOCUMENT TITLE
Slips, Tent Line

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN *(If applicable)*	7. DATE SUBMITTED *(YYYYMMDD)*

8. PREPARING ACTIVITY

a. NAME DEFENSE SUPPLY CENTER PHILADELPHIA DSCP-CNRP	b. TELEPHONE *(Include Area Code)* (1) Commercial (215) 737-3290 (2) DSN 444-3290
c. ADDRESS *(Include Zip Code)* 700 Robbins Ave (Bldg 6, C&T) PHILADELPHIA, PA 19111-5092	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman Road, Suite 2533 Fort Belvoir, Virginia 22060-6221 Telephone (703) 767-6888 DSN 427-6888

DD Form 1426, FEB 1999 (EG) PREVIOUS EDITION IS OBSOLETE
WHS/DIOR, Feb 99

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:41Z
Check the source to verify that this is the current version before use.