MIL-P-1601E

20 May 1977
SUPERSEDING
MIL-P-1601D
1 September 1970

MILITARY SPECIFICATION

PROTECTORS, ARM, GASOLINE FIELD RANGE OUTFIT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers arm protectors used to prevent burns to personnel during field cooking operations (see 6.1).

1.2 Classification. The arm protectors shall be of the following types and sizes as specified (see 6.2 and 6.4):

Type I - Protector, arm, long

Size 2 - 15 inches (0.381 meters) overall length

Type II - Protector, arm, short

Size 2 - 11-1/4 (0.286 meters) inches overall length

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7360

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:33Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized and Containerized Unit Loads, 40" x 48" Pallets, Skids, Runners, or Pallet-Type Base

DRAWINGS

US ARMY NATICK RESEARCH AND DEVELOPMENT COMMAND

5-11-964 - Protectors, Arm, Gasoline Field Range Outfit, Long and Short Arm Protector Size 2

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip
A 176 - Stainless and Heat-Resisting Chromium Steel Plate, Sheet and Strip

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:33Z
Check the source to verify that this is the current version before use.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

* 3.1 First article. When specified (see 6.2), the contractor shall furnish a sample for first article inspection and approval (see 4.3 and 6.3).

* 3.2 Materials. Materials shall be as specified herein.

3.2.1 Stainless steel. Stainless steel shall conform to type 301, 302, and 304 of ASTM A 167 or type 430 of ASTM A 176.

3.3 Design and construction. The arm protectors shall be of two types. Each type shall have one size. The arm protectors shall conform to the design, details, material classification, and dimensions shown on Drawing 5-11-964.

3.3.1 Finish. The arm protectors shall have a number 2D or 2B finish and all burrs and slivers shall be removed.

3.4 Marking for identification. Each protector shall be permanently and legibly marked with the manufacturers name, trade name or trademark easily identified with said manufacturer.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for

Source: https://assist.dla.mil -- Downloaded: 20260-16T13:33Z
Check the source to verify that this is the current version before use.

the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3)
2. Quality conformance inspection (see 4.4)

4.3 First article inspection. When a first article is required, it shall be examined for defects in table I and for compliance with dimensions specified. The presence of any defects listed in table I or any dimensions not within specified requirements shall be cause for rejection of the first article.

4.4 Quality conforming inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 End item inspection. The inspection lot for visual and dimensional examination shall consist of all protectors of the same type and size offered for inspection at one time. The sample unit shall be one protector.

4.4.2.1 Visual examination. An examination shall be made of the protectors for the defects listed in table I. The inspection level shall be II with an acceptable quality level (AQL) of 2.5, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect
Finish	Burrs or slivers
Marking	Missing, incomplete, illegible, does not conform to manufacturer's name, trade name or trademark

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:33Z
Check the source to verify that this is the current version before use.

4.4.2.2 Dimensional examination. An examination shall be made of the protectors to determine compliance with dimensions specified. Any dimensions not meeting specified requirements shall be a defect. The inspection level shall be S-2 with an AQL of 2.5, expressed in terms of defects per hundred units.

4.4.3 Inspection of packaging. An examination shall be made to determine that preservation-packaging, packing, and marking as required by section 5 are complied with. Defects shall be as indicated in table II. The lot shall be the number of containers offered for inspection at one time. The sample unit shall be one shipping container fully prepared for delivery except it need not be closed. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

TABLE II. Examination of packaging

Examine	Defect
Markings	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Component missing or damaged
Contents	Number per container is more or less than required
Workmanship	Bulged or distorted containers

4.4.3.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing, and reinforcing shall be in accordance with the appendix of PPP-B-636.

4.4.4 Examination of palletization. An examination shall be made to determine that palletization is in compliance with section 5 of this specification. Defects shall be as specified in table III. The sample unit for this examination shall be one palletized unit load ready for shipment. The lot shall be the number of palletized unit loads submitted for inspection at one time. The inspection level shall be S-1 with an AQL of 6.5 expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:33Z
Check the source to verify that this is the current version before use.

TABLE III. Examination of palletization

Examination	Defect
Finished dimension	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with straps specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

* 5. PACKAGING

* 5.1 Preservation-packaging. Preservation-packaging shall be level A or Commercial as specified (see 6.3).

* 5.1.1 Level A. Twenty-five protectors of one type and size only shall be packaged in the most compact manner in a snug-fitting fiberboard box conforming to style RSC, type CF, variety optional, or type SF, class domestic of PPP-B-636. Closure shall be in accordance with the appendix of PPP-B-636.

* 5.1.2 Commercial. The protectors shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The package and the quantity per package shall be the same as that normally used by the supplier for retail distribution.

* 5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

* 5.2.1 Level A packing. Seventy-five type I, size 2 protectors, or one hundred type II, size 2 protectors, packaged as specified in 5.1 shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced with flat strapping or tape banding in accordance with the appendix of PPP-B-636.

* 5.2.2 Level B packing. Seventy-five type I, size 2 protectors, or one hundred type II, size 2 protectors, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety optional or type SF, class domestic, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II of the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:33Z
Check the source to verify that this is the current version before use.

* 5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2) the fiberboard shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix thereto.

* 5.2.3 Commercial packing. Protectors, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

* 5.3 Palletization. Unless otherwise specified (see 6.2), protectors packed as specified shall be palletized in accordance with Load Type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

* 5.4 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

* 6.1 Intended use. The arm protectors covered by this specification are intended for use as follows:

The type I, size 2, and type II, size 2 are included in the Range and Accessory Outfit, Field, Gasoline; MIL-R-14601.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type and size required (see 1.2).
(c) When a first article is required for inspection and approval (see 3.1, 4.3, and 6.3).
(d) Selection of applicable levels of preservation-packaging and packing (see 5.1 and 5.2).
(e) When weather-resistant class fiberboard shipping containers are required for level B shipment (see 5.2.2.1).
(f) When palletization is required (see 5.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:33Z
Check the source to verify that this is the current version before use.

* 6.3 First article. When a first article is required, it shall be examined, and approved under the appropriate provisions of 7-104.55 of the Armed Services Procurement Regulation. The first article should be a preproduction sample. The first article should consist of one unit. The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for examination and approval of the first article.

* 6.4 Supersession data. Type I, size 1 and type II, size 1, arm protectors, covered by MIL-P-1601D, dated 1 September 1970, have been deleted from this specification since these items are no longer required.

6.5 Changes from previous issue. The margins of this specification are marked with an asterisk (*) to indicate where changes (additions, deletions, modifications, corrections) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Review activities:

Army - MD
Navy - MC
DLA - GS

Preparing activity:

Army - GL

Project No. 7360-0101

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:33Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-P-1601E

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-01-16 13:33Z
Check the source to verify that this is the current version before use.

S/N 0102-014-1802