MIL-P-1735G
7 September 1983
SUPERSEDING
MIL-P-1735F
11 March 1971

MILITARY SPECIFICATION

POTS, COOKING: WITH COVERS AND SPLASH PLATE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers two sizes of aluminum cooking pots with covers and a splash plate.

1.2 Classification. The items shall be as follows (see 6.2).

Pots

Size 1 - 10 gallon
Size 2 - 15 gallon

Covers - one size to fit both size of pots

Splash plate - one size to fit both size of pots

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

A-A-203	-	Paper, Kraft, Untreated
QQ-A-225/7	-	Aluminum Alloy Bar, Rod, and Wire; Rolled, Drawn, or Cold Finished, 5052
QQ-A-200/8	-	Aluminum Alloy 6061, Bar, Rod, Shapes, Tube and Wire Extruded
QQ-A-250/8	-	Aluminum Alloy, 5052, Plate and Sheet
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing

STANDARDS

FEDERAL

FED-STD-66	-	Steel, Chemical Composition and Hardenability

MILITARY

MIL-STD-105	-	Sampling Procures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-130	-	Identification Marking of U.S. Military Property
MIL-STD-147	-	Palletized Unit Loads

DRAWINGS

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT LABORATORIES

2-9-35	-	Pot, Cooking; for Field Range Outfit, 10 Gallons
2-9-120	-	Pot, Cooking; for Field Range Outfit, 15 Gallons

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A167 - Corrosion-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip
D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.4).

* 3.2 Materials (see 6.3) and components. Materials and components shall conform to the requirements specified herein and on Drawing 2-9-35 and 2-9-120. Commercial tolerances shall apply to metal thickness and diameters.

3.2.1 Aluminum.

3.2.1.1 Sheet. Aluminum sheet shall conform to QQ-A-250/8.

3.2.1.2 Bar stock and wire. Aluminum bar stock and wire shall conform to QQ-A-225/7 or QQ-A-200/8.

3.2.2 Corrosion-resisting steel. Corrosion-resisting steel shall conform to type 302 or 304 of ASTM A167.

3.2.3 Carbon steel. Steel sheet, strip, or bar stock shall conform to the chemical composition of any AISI Number from C1008 to C1025 of FED-STD-66.

3.3 Construction. The pots, covers, and splash plates shall be constructed as specified herein and conform to details and dimensions shown on Drawings 2-9-35 and 2-9-120.

3.3.1 Bodies, covers and splash plate. Each pot body, cover, and splash plate excluding handles shall be fabricated of a single piece of aluminum specified in 3.2.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

shall be of the following types and sizes. [illegible] sheets, sheets

3.3.2 Handles.

3.3.2.1 Pot handles. Pot handles shall be fabricated of material specified in 3.2.2 or 3.2.3, as applicable, and shall be riveted to the body.

3.3.2.2 Cover handle. Cover handle shall be fabricated of the corrosion-resisting steel specified in 3.2.2 or of the carbon steel specified in 3.2.3, and shall be riveted to the cover.

3.3.3 Splash plate stud. Splash plate stud shall be fabricated of aluminum specified in 3.2.1.2.

3.3.4 Rivets. The rivets shall be fabricated from aluminum specified in 3.2.1.2 or corrosion-resisting steel specified in 3.2.2. All rivet holes shall be accurately punched or drilled and all metal splinters, excessive roughness, and any burrs preventing proper setting of rivets shall be removed. The rivets shall be neatly and securely peened with heads in full contact with adjacent metal surfaces.

3.4 Finish.

3.4.1 Aluminum. The pot body, splash plate, and covers, including rivets, shall have a smooth, natural finish inside and out. The natural finish may be modified by the forming operations. All scratches deep enough to impede the progress of a fingernail, when drawn across the scratch, shall be removed.

3.4.2 Handles. All dirt, oil, grease, and any other foreign substance shall be removed prior to finishing the handles. Carbon steel handles shall be coated with tin, applied by the hot-dip method, before assembly to the pot body. The coating shall be uniform, smooth, adherent, and all drippings shall be removed. Corrosion-resisting steel handles shall have the manufacturer's standard finish.

3.5 Marking for indentification. The letters "U.S.", manufacturer's name, trade name, or trademark of such known character as to be easily identifiable with said manufacturer, capacity, and date of manufacture shall be indented on the components as shown on the drawings and in accordance with MIL-STD-130. The opposite surface shall show no signs of uneveness or distortion caused by these indented marks.

3.6 Workmanship. The finished pots, covers, and splash plates shall not contain any dents, slivers, sharp edges, or burrs.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

* 4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

* 4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in table I and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

* 4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.2 In-process inspection.

4.4.2.1 Rivet holes. An examination shall be made to determine that rivet hole preparations conform to the requirements of 3.3.4. Whenever nonconformance is noted correction shall be made to the affected items and the lot in process.

4.4.2.2 Handle cleaning and finishing. An examination shall be made of the handles to determine compliance with the cleaning requirements and tin coat requirements, when applicable, of 3.4.2. Whenever noncompliance is noted, correction shall be made to the affected items and the lot in process.

* 4.4.3 End item visual examination. The end item shall be examined for the defects listed in table I. The lot size shall be expressed in units of pots, covers, or splash plate. The sample unit shall be one pot, one cover, or one splash plate, as applicable. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. End item defects

Examine	Defect	Classification Major	Minor
Finish (general)	Deep scratches on surfaces of pot, splash plate, or cover, impeding the progress of a fingernail when drawn across the scratches	X	
	Dirt, grease, or other foreign matter imbedded in finish	X	
	Rough or sharp edges, or burrs	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

TABLE I. End item defects (cont'd)

Examine	Defect	Classification Major	Minor
Finish (pot body and rivets)	Not smooth natural metal finish inside and outside		X
Finish (carbon steel handles)	Not coated	X	
	Coating peeling or flaking	X	
	Area of thin coating		X
	Area of no coating	X	
	Indication of rust or scale	X	
	Not smooth, or having drips on edges		X
Construction and workmanship	Any component missing, bent, fractured, cracked, broken, malformed, or otherwise damaged	X	
	Handle loose	X	
	Handle not located on cover as specified		X
Rivets	Not properly peened	X	
	Head of rivet not in full contact with both surfaces		X
	Rough metal splinters not removed	X	
Marking for identification	Missing, illegible, incorrect, incomplete, wrong size, in wrong location, or not indented		X
	Surface opposite marking shows evidence of penetration through metal	X	
	Surface opposite marking distorted from indenting		X

4.4.4 End item dimensional examination. The end item shall be examined for conformance to dimensions specified on the drawings. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of pots, covers, or splash plates. The sample unit shall be one pot, one cover, or one splash plate, as applicable. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

* 4.4.5 Packaging inspection. An examination shall be made to determine that preservation, packing and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged with the exception that it need not be closed. Examination of closure defects listed below shall be made on shipping containers fully packaged. The lot size shall be the number of containers in the inspection lot. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

Examine	Defect
Markings (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged or not as specified
Workmanship	Inadequate application of components such as; incomplete closure of container flap, loose strapping, improper taping, or inadequate stapling Bulged or distorted container
Content	Number of cooking pots, covers or splash plates per container is more or less than specified

* 4.4.6 Palletization examination. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the end item inspection lot. The inspection level shall be S-1 and the AQL shall be 6.5 defects per hundred units.

Examine	Defect
Finished dimension	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with required straps specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Size 1 cooking pot only. Three size 1 cooking pots shall be nested one within the other, with handles in vertical alignment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

5.1.1.2 Covers and splash plate. Each cover or splash plate shall be wrapped in minimum 30-pound basis weight kraft paper conforming to A-A-203 and sealed with minimum 2-inch width tape conforming to type III, grade B of PPP-T-45.

* 5.1.2 Commercial. Each cooking pot, cover, or splash plate shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing.

5.2.1.1 Size 1 and size 2 cooking pots. Six size 1 cooking pots, preserved as specified in 5.1, or two size 2 cooking pots shall be packed in a snug-fitting wood-cleated plywood box conforming to overseas type, style A or J, grade B, type 2 load of PPP-B-601 or nailed wood box conforming to class 2, style 2 or 4, type 2 load of PPP-B-621. The contents of each shipping container shall be cushioned, blocked and braced, and waterproofed in accordance with the appendix of the applicable container specification.

5.2.1.2 Covers and splash plates. Sixteen covers or thirty-two splash plates, preserved as specified in 5.1, shall be packed as specified in 5.2.1.1.

5.2.2 Level B packing.

5.2.2.1 Size 1 and size 2 cooking pots. Six size 1 cooking pots, preserved as specified in 5.1 or two size 2 cooking pots shall be packed in a snug-fitting shipping container conforming to style RSC-L, type CF (variety SW) or type SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner and a full depth center partition conforming to class domestic, variety DW, grade 275 of PPP-B-636. The cooking pots shall be placed in an upright position with the handle positioned in the corners of the container and the center partition separating two two stacks of cooking pots. Fiberboard filler pads, 17-3/4 inches by 17-3/4 inches, made of the same material as the partition shall be used between the top of the pots and the inside top of the container. The inside dimensions of each shipping container shall approximate 35-3/4 inches in length, 18-1/2 inches in width, and 16-1/4 inches in depth. The approximate dimensions are furnished as a guide only. The length and width dimensions specified are within the corrugated liner. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except the inspection shall be in accordance with 4.4.5.

5.2.2.2 Covers and splash plates. Sixteen covers, or thirty-two splash plates, preserved as specified in 5.1, shall be packed flat in a shipping container as specified in 5.2.2.1. The covers or splash plates shall be arranged in two stacks of 8 covers or 16 splash plates each, with a fiberboard pad, as specified in 5.2.2.1, placed between each cover. Each stack shall be separated by a partition as specified in 5.2.2.1. The dimensions of each shipping container shall be as

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

retaining particles 10 microns (0.01 mm) and larger.

determined for size 1 and 2 cooking pots (see 5.2.2.1). Fiberboard pads, as specified in 5.2.2.1, shall be used as required to fill the voids between the splash plates and the top of the shipping container. Closure of the fiberboard shipping container shall be as specified in 5.2.2.1.

* 5.2.2.3 Weather-resistant fiberboard containers. When specified (see 6.2) the shipping containers shall be V3c, V3s, or V4s, fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification, except the inspection shall be in accordance with 4.4.5.

* 5.2.3 Commercial packing. Cooking pots, covers, or splash plates, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2) cooking, pots, covers, or splash plates packed as specified in 5.2, shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each coarse. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

* 5.4 Marking. In addition to any special marking required by the contract or purchase order, unit pack, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The cooking pots with covers and splash plates are for use as components of the Range and Accessory Outfit, Field covered by MIL-R-14601 consisting of one 10-gallon pot with cover and one 15-gallon pot with cover and splash plate.

* 6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Size and quantity of pots required and quantity of covers and splash plates required (see 1.2).
c. When first article is required (see 3.1, 4.3, and 6.4).
d. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.3).
f. When palletization is required (see 5.3).

* 6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

6.4 First article. When a first article is required it shall be inspected and approved under the appropriate provisions of DAR 7-104.55. The first article should be a preproduction sample. The first article should consist of one unit. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for inspection and approval of the first article.

6.5 Changes from previous issue. The margins of this document are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review activities:

Army - MD
Navy - MC, YD
Air Force - 84

Preparing activity:

Army - GL

Project No. 7330-0556

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

This specification covers fillers for filtering cooking 1. 1. Scope

F-c

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Laboratories
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRDNA-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Laboratories
ATTN: DRDNA-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-1735G	Pots, Cooking: With Covers And Splash Plate

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 82 MAR

PREVIOUS EDITIONS ARE OBSOLETE.

Source: https://assist.dla.mil — Downloaded: 2025-10-18T13:42Z
Check the source to verify that the content is current before use.