MILITARY SPECIFICATION

ACCELEROMETER, MECHANICAL, PILOT'S WARNING, TYPE MA-2

This amendment forms a part of Military Specification MIL-A-25915A(USAF) dated 30 April 1980 and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1: Under "SPECIFICATIONS, Military", delete "MIL-E-5272" and title thereto.

Boxed paragraph, line 3: Delete "HQ AFLC CASO/LODS, Federal Center, Battle Creek MI 49016" and substitute "Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145".

PAGE 2

Under "STANDARDS, Military", add the following:

"MIL-STD-810 - Environmental Test Methods"

PAGE 16

4.5.7, line 2: Delete "procedure I of MIL-E-5272 for a period of 4 hours." and substitute "method 502.1, procedure I of MIL-STD-810 for a period of 4 hours, except that the storage temperature of step 2 shall be -54°C (-65°F) and also, delete steps 4 through 7".

PAGE 18

4.5.8, line 2: Delete "procedure II of MIL-E-5272 for a period of 4 hours." and substitute "method 501.1, procedure I of MIL-STD-810 for 4 hours except delete steps 4 through 7".

4.5.11: Delete entire paragraph and substitute new paragraph as follows:

"4.5.11 Vibration endurance. The accelerometer shall be mounted on a suitable vibration stand with the dial in a vertical plane and with the graduation +1 at 270°. The instrument shall be vibrated with circular motion of 0.018 to 0.020 inch diameter in a plane inclined 45 degrees to the horizontal plane and the frequency of vibration shall be varied uniformly from 5 to 50 cycles per second and return once each hour for a period of 50 hours. Upon completion of the test period, the accelerometer shall be subjected to the test specified in 4.5.3. The dynamic scale error shall not exceed 0.2g. The accelerometer shall not be damaged as a result of this test.

PAGE 19

4.5.12, line 3: Delete "4.5.11.1" and substitute "4.5.12.1".

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:30Z
Check the source to verify that this is the current version before use.

4.5.14, lines 2 and 3: Delete "low temperature test, procedure VI of MIL-E-5272 and an altitude of 70,000 feet (1.31 inches Hg)" and substitute "low temperature test, method 502.1, procedure I of MIL-STD-810, and an altitude of 70,000 feet (1.31 inches Hg) except that the storage temperature for step 2 shall be -62°C (80°F) and the stabilization period shall be 72 hours. The operating temperature of step 4 shall be 24 hours."

4.5.15, lines 2 and 3: Delete "procedure II of MIL-E-5272" and substitute "method 501.1, procedure I, of MIL-STD-810."

PAGE 20

4.5.17, line 2: Delete "humidity test in accordance with procedure I of MIL-E-5272" and substitute "humidity test in accordance with method 507.1, procedure I of MIL-STD-810, except for the following changes: Step 2, delete 65°C (149°F) and substitute 71°C (160°F); Step 4, delete 85 percent and substitute 95 percent, and delete 30°C (86°F) and substutute 20 to 38°C (68 to 100°F); Step 5, delete the last sentence; Step 6, delete and substitute "At the end of the tenth cycle, the equipment shall be returned to standard conditions."

4.5.18, lines 2 and 3: Delete "procedure I of MIL-E-5272." and substitute "method 508.2 of MIL-STD-810 for a period of 28 days. Evidence of fungus growth which would significantly deteriorate accelerometer performance shall be cause for rejection."

4.5.19, line 2: Delete "procedure I of MIL-E-5272" and substitute "method 509.1, procedure I of MIL-STD-810".

4.7 through 4.7.2: Delete entirely and substitute new paragraph as follows:

"4.7 Inspection and test. Tests of methods of preservation and packaging shall be accomplished in accordane with Section 4 of MIL-P-116 to insure compliance with Section 5 of this specification."

PAGE 21

5.1.1.4 through 5.2.2: Delete and substitute new paragraphs as follows:

"5.1.1.4 Unit packaging. Unless otherwise specified by the procuring activity, each unit shall be packaged in quantity unit packs of one each in accordance with method IC-1 of MIL-P-116. Each unit shall be overboxed in a PPP-B-636 carton. Carton shall be large enough to allow for application of sufficient cushioning material between container and bag of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the unit when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Units shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:30Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or C as specified.

5.2.1 Level A. Units packaged as specified in 5.1.1 shall be packed in shipping container conforming to PPP-B-601, style A or B, class overseas, unless otherwise specified by the procuring activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, and of minimum tare and cube, consistent with the protection required.

5.2.2 Level B. Units packaged as specified in 5.1.1 shall be packed in weather-resistant class exterior shipping containers conforming to PPP-B-636. Other requirements as specified in 5.2.1 above are applicable."

PAGE 23

6.4, line 4: Delete period after "10/4" and add "and STANAG 3330."

Custodian:
Air Force - 99

Preparing activity:
Air Force - 71

Project number:
6610-F043

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:30Z
Check the source to verify that this is the current version before use.