MILITARY SPECIFICATION

INDICATOR, PRESSURE, OIL, 0-100 PSI

This amendment forms a part of MIL-I-25950B (USAF), dated 29 Nov 1967, and is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Delete "2.1" And Add:
"2.1 Government documents".

* Add:
"2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation".

Add boxed paragraph at bottom center of page.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

* Under STANDARDS, Military, delete "MIL-STD-100", "MIL-STD-831", "MIL-STD-1186" and "MS33586". Add the following:

"DOD-STD-100 Engineering Drawing Practices
MIL-STD-889 Dissimilar Metals"

* Add:

"2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ASTM D3951 Packaging, Commercial

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia PA 19103.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:35Z
Check the source to verify that this is the current version before use.

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services."

3.3.4: Delete "MS33586" and substitute "MIL-STD-889".

* Add:
"3.3.2.1 Recovered materials. Recovered materials shall be used to the maximum extent possible without jeopardizing the end use of the item".

PAGE 6

3.5. Step b: Delete and add:

"b. Vibration - random vibration of $0.04G^2/Hz$ from 15 to 2,000 Hz".

PAGE 9

3.5.7: Delete "both" and add "bath".

3.6: Delete "MIL-STD-100" and add "DOD-STD-100".

PAGE 10

* Add:

"4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

PAGE 11

Delete "4.4.2."

PAGE 13

4.6.4. Line 4: Delete "table I" and add "table II".

PAGE 14

4.6.6: Add the following sentence to paragraph:

"When no trace of helium is detected, the indicator shall be subjected to and shall pass the test specified in 4.6.10".

4.6.7: Delete existing paragraph and add the following new paragraph:

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:35Z
Check the source to verify that this is the current version before use.

"4.6.7 Vibration. The indicator shall be subjected to a vibration test in accordance with MIL-STD-810, method 514.2, equipment category b.2, table 514.2-IIA, procedure IA, figure 514.2-2A, curve A. The maximum acceleration power spectral density Wo for the functional test shall be $0.04G^2/Hz$. Wo for the endurance test shall be $0.08G^2/Hz$. The low frequency acceleration power spectral density shall be 50 percent of the Wo value. The endurance test time shall be 3 hours per axis. A synchro signal shall be maintained on the stator of the indicator synchro during the functional test to provide an indication of 45 psi. Pointer oscillation and pointer variation shall not exceed the tolerances listed in table III. Upon completion of this test, the indicator shall be subjected to the scale error test at room temperature. The scale errors shall not exceed the tolerances listed in table II."

PAGE 15

4.6.14, Line 2: Delete "method 504" and add "method 504.1".

PAGE 16

4.6.18, Line 2: Delete "method 509" and add "509.1".

4.6.22, Line 3: Delete "Plan I" and add "Plan IC".

4.6.22.1, Lines 7-9: Delete sentence 5 and add:

"For at least 10 minutes out of every hour of ON time, the indicator shall be vibrated in accordance with the random vibration test envelop of Figure B-4, MIL-STD-781. Wo shall be $0.01G^2/Hz$ and W1 shall be $0.005G^2/Hz$.

PAGE 17

* Delete Section 5 in its entirety and add:

"5. PACKAGING.

5.1. Preservation-packaging. Preservation-packaging shall be level A, C, or Industrial, as specified (see 6.2).

5.1.1. Level A.

5.1.1.1. Cleaning. Indicators shall be cleaned in accordance with process C-1 or MIL-P-116.

5.1.1.2. Drying. Indicators shall be dried in accordance with process D-4 or MIL-P-116.

5.1.1.3. Preservation application. Not applicable.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each indicator shall be packaged in quantity unit packs of one each in accordance with Method ICI of MIL-P-116. Overbox completed pack in PPP-B-636 container. Apply sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the indicator when completed packs are subjected to the rough handling drop tests of MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:35Z
Check the source to verify that this is the current version before use.

5.1.2 Level C. Each indicator shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.1.3. Industrial. The Industrial preservation of indicator shall be in accordance with ASTM D3951.

5.2. Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).

5.2.1. Level A. Indicators packaged as specified in 5.1.1. shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, minimum tare and cube consistant with the protection required.

5.2.2. Level B. Indicators packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1 apply.

5.2.3. Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

5.2.4. Industrial. The packaged indicators shall be packed in accordance with ASTM D3951.

5.3. Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance with MIL-STD-129."

PAGE 18

* 6.3 Line 8 and 9 delete "Systems Engineering Group, attn: SEFIP, Wright-Patterson Air Force Base, OH 45433" and add: "OC-ALC/MMEDO, Tinker AFB, OK 73145-5990"

PAGE 19

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment."

Custodian:
Air Force - 99

Preparing Activity:
Air Force - 71

Review Activity:
Air Force 11

Project Number:
6620-F413

☆U.S. GOVERNMENT PRINTING OFFICE: 1988 — 605-036/44908

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:35Z
Check the source to verify that this is the current version before use.