INCH-POUND

MIL-PRF-25962D
AMENDMENT 1
14 August 1998

PERFORMANCE SPECIFICATION

VALVE, LIQUID OXYGEN DRAIN

This amendment forms a part of MIL-PRF-25962D, dated 19 April 1996 and is approved for use by the Department of Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

3.1: Delete and substitute:

"3.1 Qualification. The valves furnished under this specification shall be products that are authorized by the qualifying activity for listing on the applicable qualified products list (QPL) before contract award (see 4.2 and 6.5)."

PAGE 3

3.6.5: Delete and substitute:

"3.6.5 Cleanliness. All surfaces shall be free of visible particulates (50 microns and larger), free of visible fluorinated lubricants, and free of hydrocarbon contamination to a level not greater than 3 milligrams per square foot (mg/ft^2)(see 6.4).

PAGE 3

4.1: Delete and substitute:

"4.1 Classification of inspections. The inspection requirements specified herein are classified as follows (see 6.2):

a. Qualification inspection (see 4.2)

b. Conformance inspection (see 4.3)"

PAGE 3

4.2: Delete and substitute:

"4.2 Qualification inspection. If required (see 3.1 and 6.5), qualification shall be performed on four valves. The four valves shall be subjected to all the tests in 4.6."

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:37Z
Check the source to verify that this is the current version before use.

4.6.2: Delete and substitute:

"4.6.2 Cleanliness. All surfaces shall be free of visible particulates (50 microns and larger), free of visible fluorinated lubricants, and free of hydrocarbon contamination to a level not greater than 3 mg/ft^2 (see 6.4). Cleanliness of the surfaces shall be demonstrated by industrially accepted methods and these cleaning and verification methods shall be identified (see 6.2 and 6.4)."

6.2d: Delete and substitute:

"6.2d "The requirement for the vendor to identify proposed cleaning and verification methods (see 4.6.2)."

6.2f: Delete and substitute:

"6.2f If qualification data is required (see 4.2)"

6.4: Delete and substitute:

"6.4 Cleaning. See MIL-STD-1330 and MIL-STD-1359 for guidance on proven cleaning methods and verifications. Visible inspections are typically conducted using white light to detect particulates and some types of hydrocarbons. The non-volatile residue test in MIL-STD-1359 may be used to baseline the hydrocarbon verification at an acceptable contamination level, however, other cleaning and verification methods that do not contain class I and II ODC solvents should be used in production.

6.5: Add as new paragraph:

"6.5 Qualification. The attention of the contractors is called to the requirements with respect to products requiring qualification. Awards will be made only for products which are, at the time of award of contract, qualified for inclusion in the Qualified Products List (QPL No. 25962) whether or not such products have actually been listed by that date. In order that the manufacturers may be eligible to be awarded contracts or purchase orders for the products covered by this specification, they are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification. Information pertaining to qualification of products may be obtained from Oklahoma City Air Logistics Center/TICLA, 3001 Staff Drive, Suite 1AE1-101A, Tinker AFB, Oklahoma 73145-3036.

Renumber paragraphs 6.5 and 6.6 to paragraphs 6.6 and 6.7, respectively.

Move Custodian, Reviewer, and Preparing activity data from page 5 to new page 7.

Custodian:
Air Force - 99

Preparing activity:
Air Force - 71

(Project 4820-0797)

Reviewer:
DLA - CC

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:37Z
Check the source to verify that this is the current version before use.