MIL-S-25948J
AMENDMENT-1
28 August 1986

MILITARY SPECIFICATION

SUNGLASSES, HGU - 4P (WITH CASE)

This amendment forms a part of Military Specification MIL-S-25948J, dated 17 January 1984 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

After 1.1: Add the following:

"1.2 Classification. Sunglasses shall be of the following types as specified (see 6.2).

Type I - Matte Chrome Frame, Army, Air Force, Marine Corps
Type II - Gold Colored Frame, Navy"

PAGE 2

2.1, Under "SPECIFICATIONS MILITARY": Add the following:

"MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-G-45204 - Gold Plating, Electrodeposited"

PAGE 3

3.2, after "Materials": Add "(See 6.5)".

3.2.1, Paragraph identifier, after "temples": Add "type I (Matte chrome frame)"

Add the following paragraph:

"3.2.1.1 Front and temples type II (gold colored frame). All metal parts of the front and temples, except the pad parts and temple screws, shall be made of nickel silver base metal containing not less than 14 percent nickel. The base metal shall

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-20T07:33Z
Check the source to verify that this is the current version before use.

PAGE 3 (cont'd)

be plated with bright nickel electroplate of not less than 100 millionths of inch thickness, overplated with a bright gold deposit. The gold shall be a minimum of 60 millionths of an inch of 23 carat gold electrodeposit, overplated with a pink color flash of 18 carat bright gold electrodeposit."

PAGE 4

3.3.2, at the end of the paragraph: Add "Type II pad arm shall be nickel - silver overplated with a bright nickel electroplate of not less than 50 millionths of an inch thickness, overplated with a minimum of 60 millionths of an inch of 23 carat bright gold electrodeposit, overplated with a pink color flash of 18 carat bright gold electrodeposit."

PAGE 5

3.4.2, line 1, after "chrome": Add "or gold".

PAGE 7

TABLE III: Delete all data for wave lengths 630 to 730 and substitute:

"Wave length millimicrons	xP	yP	zP	T	xPT	yPT	zPT
630	5,309	2,190	0	0.161	855	353	0
640	3,693	1,443	0	0.160	591	233	0
650	2,349	886	0	0.159	373	141	0
660	1,361	504	0	0.159	216	80	0
670	708	259	0	0.158	112	41	0
680	369	134	0	0.157	58	21	0
690	171	62	0	0.156	27	10	0
700	82	29	0	0.153	13	4	0
710	39	14	0	0.151	6	2	0
720	19	6	0	0.149	3	1	0
730	8	3	0	0.148	1	0	0
				Total	15,085 (X)	15,512 (Y)	16,023 (Z)"

PAGE 10

3.7, lines 15 and 17 after "chrome": Add "or gold".

Source: https://assist.dla.mil -- Downloaded: 202610-20T07:33Z
Check the source to verify that this is the current version before use.

PAGE 11

After 4.1.1: Add the following:

"4.1.2 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

PAGE 15

4.4.2, lines 10 and 11, after "chrome": Add "or gold".
Footnote 2/, lines 1 and 7, after "chrome": Add "or gold".

Table VII, under characteristics, after "Gloss": Add "(type 1 only)".

4.4.3.1.1, under Frame defects, line 2, after "chrome": Add "or gold".

PAGE 21

4.4.3.1.3, third sentence: Delete "prepared for delivery except that it need not be closed." and substitute "packaged".

Fourth sentence: Delete.

PAGE 25

5.1.1, line 2: Delete "packaged" and substitute "unit packed".

PAGE 26

5.2.1, after the last sentence: Add the following:

"Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads."

5.3, Delete and substitute

"5.3 Palletization. "When specified (see 6.2), sunglasses, packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-

Source: https://assist.dla.mil -- Downloaded: 20260-20T07:33Z
Check the source to verify that this is the current version before use.

way entry) type IV or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with the bonding means K and L or film bonding O or P. Pallet pattern shall be number 3 in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contrcting officer."

PAGE 27

Line 1: Delete "Marking" and substitute "5.4 Marking".

6.2, after item (d): Add the following:

"(e) Type of sunglasses required (see 1.2).
(f) Type and class of unit load required (see 5.2.1)".

After 6.4: Add the following:

"6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.2)."

Custodians:

Army - GL
Navy - AS
Air Force - 99

Review activities:

Army - MD
Navy - MS
Air Force - 82
DLA - CT

User activity:

Air Force - 45

Preparing activity:

Army - GL

Project No 8465-0929

☆U.S. GOVERNMENT PRINTING OFFICE: 1988 — 606-036/44806

Source: https://assist.dla.mil -- Downloaded: 20261O-20T07:33Z
Check the source to verify that this is the current version before use.