MILITARY SPECIFICATION

CONTROL, RADIO SET C-2459A(*)/ARC-27A AND
CONTROL, RADIO SET C-3657(*)/ARC-27A

This amendment forms a part of Military Specification MIL-C-22856(WEP) dated 15 March 1961 and has been approved by the Bureau of Naval Weapons, Department of the Navy.

Page 1, paragraph 1.1: Delete "ID-660/ARC" and substitute:

"ID-997/ARC"

Page 1, paragraph 2.1, under SPECIFICATIONS Military: Add:

"MIL-R-23094 Reliability Assurance for Production Acceptance of Avionic Equipment, General Specification for"

Page 3, paragraph 3.2.3.2: Delete and substitute:

"3.2.3.2 Reliability in Mean Time Between Failures - The equipment shall have a minimum of 200 hours of mean (operating) time between failure when tested and accepted as outlined under the requirements of 4.4.2 during which 20,000 switching cycles shall occur."

Page 5, paragraph 3.4.1.4 and 3.4.1.5(1): Add:

"and ID-997/ARC"

Page 5, paragraph 3.4.1.6, after ID-572/ARC: Add:

"or ID-997/ARC"

Page 5, paragraph 3.4.2: Delete "ID-660/ARC" and substitute:

"ID-997/ARC"

Page 7, paragraph 4.4(2): Delete and substitute:

"(2) Reliability Quality Assurance Tests"

Page 8, paragraphs 4.4.2 and 4.4.2.1: Delete and substitute:

"4.4.2 Reliability Quality Assurance Tests - Equipments which have successfully passed the individual tests shall be tested for reliability quality assurance in accordance with Specification MIL-R-23094.

4.4.2.1 Test Level - The Test Level shall be Level III from Table I of Specification MIL-R-23094.

4.4.2.2 ACCEPT-Reject Criteria - Figure 12 of Specification MIL-R-23094 shall be used to determine the accept-reject criteria.

FSC 5821

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:08Z
Check the source to verify that this is the current version before use.

4.4.2.3 Detail Reliability Quality Assurance Test Procedures - The contractor shall prepare the detail reliability quality assurance test procedures and submit for approval of the Bureau of Naval Weapons prior to beginning of test. The procedures shall include, but not be limited to, the following:

(1) Mean Operating Time Between Failures

(2) Length of Heat portion of cycle.

(3) Performance Characteristics to be measured, applicable Specification requirement, Acceptance requirement (if lower), time in cycle that measurement is to be made.

(4) Failure Criteria - In addition to the requirements of Specification MIL-R-23094, the following requirements shall be used to determine when a failure has occurred during the test:

(a) Whenever performance characteristics fall below the Acceptance requirement (4.4.2.3(3)) at least one failure has occurred. If subsequent analysis reveals that several parts have deteriorated, each shall be counted a failure, unless one caused the other parts to fail.

(5) Preventive maintenance; Include preventive maintenance measures and the time at which such maintenance will be required."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:08Z
Check the source to verify that this is the current version before use.