INCH-POUND

MIL-L-22851D
AMENDMENT 1
15 November 1993

MILITARY SPECIFICATION

LUBRICATING OIL, AIRCRAFT PISTON ENGINE (ASHLESS DISPERSANT)

This amendment forms a part of MIL-L-22851D, dated 1 December 1990 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 5

3.7 Workmanship. Delete the first sentence and replace with the following:

"The lubricating oil shall be an uncloudy, homogeneous blend when examined visually at room temperature (25 °C ±3) in a well lighted room or daylight."

PAGE 8

Table II: Insert the following Note 4 immediately after "FTM 791 Method 3403" under the column titled "Test Methods":

"Note 4/ Petroleum ether with a boiling range of 30 to 60°C shall be used in place of trichloroethane."

CONCLUDING MATERIAL

Custodians:
Army - MR
Air Force - 11

Review Activities:
Army - AV
DLA - PS

User activities:
Navy - MC

Preparing activity:
Navy - AS
(Project No. 9150-1122)

International interest:
(See 6.2.3)

AMSC N/A

FSC 9150

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:08:37
Check the source to verify that this is the current version before use.