MIL-F-45556A

30 July 1974
SUPERSEDING
MIL-F-45556
17 November 1964
(See Section 6)

MILITARY SPECIFICATION

FEEDER, AUTOMATIC GUN: M2A1

Tis specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of gun-driven feed mechanism for ammunition belted with M14 links for use on the 20MM, M61 and M16A1 guns. The feeder pulls in the link-belted ammunition, strips the ammunition from the links, ejects the empty links, and feeds the delinked ammunition into the gun. The feeder includes an electrically operated declutching feature for clearing the gun of ammunition, and an ammunition booster take-off assembly.

2. APPLICABLE DOCUMENTS

2.1 The following docments, of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

MIL-W-13855	- Weapons, Small Arms and Aircraft Armament Subsystems General Specification for
MIL-P-14232	- Parts, Equipment and Tools for Army Material, Packaging and Packing of
MIL-I-45607	Inspection Equipment, Acquisition, Maintenance and Despostion of

FSC 1005

Source: https://assist.dla.mil -- Downloaded: 20261O-22T03:24Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-109 - Quality Assurance Terms and Definitions.

DRAWINGS

U.S. Army Weapons Command

F7791084 - Feeder, Automatic Gun; M2A1.

IEL7274645 - Index of Inspection Equipment Lists.

PUBLICATIONS

U.S. Army Weapons Command

LPDS-7751084 - List of Packaging Data Sheets.

P5910556 - Packaging Data Sheet for Feeder, Automatic Gun: M2A1, w/Attaching Parts.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 First article. Requirments for submission of first article shall be3 as specified in the contract (see 6.1). Unless otherwise specified (see 6.1), the first article shall include the pilot pack (see 5.1).

3.2 Materials, contruction and design. Feeders and parts shall conform to the materials construction and design requirement specified herein, on Drawing F7791084 and MIL-W-13855.

3.2.1 Actuating shaft. The actuating shaft shall move through its full range of travel in the feeder shaft without binding to actuate the collar assembly.

3.2.2 Anti-backlash pins. The anti-backlash pins shall be retained on the feeder housing by the spring pins and shall be held normally and returned to the extended position by thesprings. They shall function through their full range of travel under spring action without binding.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

3.2.3 Booster take-off assembly. The booster take-off assembly shall be fastened securely to the housing assembly by the screws so that there shall be no relative movement and the gears shall rotate without binding.

3.2.4 Booster drive gear. The booster drive gear shall be retained securly on the feeder shaft by the lock nut.

3.2.5 Clevis. The clevis shall be retained on the support by the safety wired spring pin and shall move through its full range of tavel without binding to actuate the actuating shaft.

3.2.6 Clevis shield. The clevis shield shall be fastened securely to the support by the screws without binding on the clevis so that there shall be no relative movement.

3.2.7 Clevis and solenoid support. The clevis and solenoid supprt shall be fastended securely to the feeder housing by the bolts so that there shall be no relative movement.

3.2.8 Collar assembly. The collar assembly shall move through its full range of travel on the feeder shaft without binding to engage or disengage the feeder gear or the stop plate as evidenced by feeder operation.

3.2.9 Feeder gear assembly The feeder gear assembly shall be retained securely on the feeder shaft by the lock nut. The anti-backlash arms shall be retained on the feeder gear and stops by the spring pins. The anti-backlash arms and stops shall function through their full range of travel under spring action without binding and shall be held normally and returned to the extended position by spring action. The feeder gear assembly shall rotate without binding with the feeder in the declutched position.

3.2.10 Feeder shaft spring. The feeder shaft spring shall be fastened securely to the feeder spring plate by the screw and self locking nut. The feeder shaft spring shall hold the round against the feeder stripper and guide when the feeder is operated.

3.2.11 Guides, strippers, and retainers. Guides, strippers, and retainers shall be fastened securely to the housing. There shall be no relative movement of these parts and they shall perform their respective guiding, stripping and retaining functions when the feeder is operated.

3.2.12 Lever shaft. The lever shaft shall be retained on the clevis by the spring pin and shall move through its full range of travel under spring action without binding.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

3.2.13 Traveling ring. The traveling ring shall rotate on the traveling ring cam without binding.

3.2.14 Traveling ring cam. The traveling ring cam shall rotate on the feeder shaft without binding.

3.2.15 Timing pin. The timing pin shall engage the timing hole in the drive gear to correctly position the feeder gears tor mounting the feeder on a properly timed gun. The timing pin shall move through its full range of travel without binding and shall be returned and held in the retracted position by action of the spring.

3.2.16 Solenoid assembly. The solenoid assembly shall be fastened securely to the support by the self locking nuts. The armature plate shall rotate through theits full range of travel without binding.

3.2.16.1 Solenoid operation. The solenoid shall actuate the feeder actuating shaft to declutch the feeder when 22 to 32 volts direct current applied to the solenoid. When the solenoid is de-energized it shall allow the feeder actuating shaft to return to its normal extended postion under spring action of the lever shaft.

3.2.16.2 Solenoid dielectric withstanding voltage. Solenoid assemblies shall withstand 1,200 volts root mean square at a frequency of 60 hertz for 5 seconds without disruptive discharge or deterioration.

3.2.16.3 Electrical circuit. The electrical circuit wiring of the solenoid to the connector shall be in accordance with the applicable drawing.

3.2.16.2 Insulation sleeve. The insulation sleeve shall be securely retained in the connector and shall terminate at the solenoid as specified on the applicable drawing.

3.2.17 Timing. The relationship of the sprockets to the feeder gear shall be within the limits specified on the applicable drawing and shall provide for smooth transfer of rounds from the ammunition belt to the gun hand-off position.

3.2.18 Torque. The torque required to rotate the feeder shaft in the feeder assembly without ammunition shall not be more than 20 ounce-inches.

3.3 Performance Characteristics.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T03:24Z
Check the source to verify that this is the currentversion before use.

3.3.1 Functioning. The feeder shall operate without stoppage or breakage parts attributable to the feeder using Government standard 20mm, M51A1 dummy cartridges. The feeder shall completely strip all rounds from the links, shall feed the stripped rounds into the gun, shall eject the empty links completely from the feeder, and perform its clutching and declutching function when opera at a steady state feeding rate of 4000 to 4400 rounds per minute. A steady state torque load of 80 ± 10 pound-inches shall be applied and measured at the booster take-off assembly drive point. Testing shall be as specified in 4.5.3.2.

3.3.2 Endurance. Feeders shall be capable of withstanding the feeding of 12,000 rounds of Government standard 20mm, M51A1 dummy cartridges with a least 120 clutching and declutching operations without functioning failures attributable to the feeder when operated at a steady state rate of 4000 to 4400 rounds per minute. A steady state torque load of 55 ± 30 pound-inches shall be applied and measured at the booster take-off assembly drive point. Testing shall be as specified in 4.5.3.3.

3.4 Interchangeability. Unless otherwise specified on the drawings, all parts shall be interchangeable. Feeders and repair parts shall be capable of meeting the interchangeability test specified in 4.5.3.4.

3.5 Marking. The feeder shall be clearly marked in accordance with the applicable drawings and MIL-W-13855. The identification plate shall be fastened securely to the feeder by the screw without relative movement. Unless otherwise specified (see 6.2), each feeder shall be identified by a serial number assigned by the procuring activity.

3.6 Workmanship. Workmanship shall be in accordance with MIL-W-13855.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

4.2 Quality assurance terms and definitions. Quality assurance terms and definitions used herein are in accordance with MIL-STD-109.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. The first article (initial production unit(s) shall be submitted for inspection in accordance with the contract (see 6.1). The first article shall be representative of the production processes to be used during quantity production. The first article shall be subjected to the quality conformance inspection specified herein and such other inspection as necessary to determine that all rements of the contract have been met.

4.5 Quality conformance inspection.

4.5.1 Inspection lot. The formation, site and presentation of inspection lots of drives, parts and packaging shall be in accordance with MIL-STD-105. Inspection lots shall be as large as practicable, in consideration of quality history, manufacturing conditions, contractor's delivery schedule and within the limitations of MIL-W-13855. Endurance test lot size shall be as specified in 4.5.3.3.1.

4.5.2 Examination.

4.5.2.1 Component parts and concurrent repair parts. Examination of component parts and concurrent repair parts shall be performed in accordance with the criteria specified in the contract (see 6.1). The contractor's examination of these parts shall be accomplished prior to their assembly into the end item or submission for acceppt-ance as repair parts.

4.5.2.2 Feeders. Visually and manually examine each of the feeder parts and assemblies to determine conformance with the applicable requirements. Each step in the examination shall include a visual examination for proper cleaning and presence of the specified protective coating and to determine the general quality, completeness of manufacture, assembly, clarity and legibility of markings, and workmanship. The examination provisions shall be applied at the earliest practical point in manufacture at which it is feasible to inspect for acceptance without risk of change in the characterisitic by subsequent operations. Reinspections of these characterisics on the completed product is not required provided assurance exists that the characteristic has not been changed, degraded or damaged by subsequent manufacturing, assembly, or handling and that adequate inspection record are maintained. Feeders failing to meet the requirements shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

4.5.2.2.1 Parts and assemblies. Parts and assemblies shall be visually and manually examined to determine compliance with the materials, construction and design requirements of 3.2 and the applicable requirements of 3.2.1 through 3.2.15. Parts and assemblies failing to meet the requirements shall be rejected.

4.5.2.2.2 Solenoid operation. Feeders shall be examined for solenoid operation requirements (See 3.2.16.1) after the solenoid dielectric withstanding voltage test by applying 22 and 32 volts direct current to the solenoid to assure that the actuating shaft is operated to declutch the feeder and that when the solenoid is deenergizd it allow the actuating shaft to return to its normal extend extended position under spring action. (Do not energize the solenoid for more than 15 seconds.)

4.5.2.2.3 Solenoid dielectric withstanding voltage. Feeders shall be examined for solenoid diecltric withstanding voltage requirement (see 3.2.16.2) using a current limited high potential tester in accordance with Drawing A7273225 and an electronic timer in accordance with Drawing A7273227. The high potential voltage shall be appplied for five seconds between the coil terminals and grounded metal parts.

4.5.2.2.4 Electrical circuit. Examine feeders for continuity (see 3.2.16.3) using a volt-ohm-millammeter tester in accordance with Drawing A7273226. Continuity of the solenoid circuit shall be examined by applying the low voltage across connector contact pins "A" and “B“. During the check, the lead wires shall be manipulated and any variation in the ohmeter scale shall be considered as attributable to a faulty connection.

4.5.2.2.5 Timing. Feeders shall be examined for timing requirement (see 3.2.17) using the inspection equipment in accordance with Drawing F7273739. The gage shall be attached to the feeder and with the feeder gear engaged to the shaft, the feeder gear shall be rotated to engage the index pin into the feeder index hole. The gage timing plunger shall then be depressed between the nearest gear teeth as the index pin is released. With the feeder gear in this position the gage shall indicate whether the timing requirement has been met.

4.5.2.2.6 Torque. Feeders shall be examind for torque requirement (see 3.2.18) using the inspection equipment in accordance with Drawing D7273309. The feeder shall be held in a horizontal position, the feeder gear fully engaged with the feeder shaft, and the feeder shaft spring loosened when the inspection equipment is attached and the feeder gear and shaft-rotated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

4.5.2.2.7 Visually examine all markings required by the final assembly drawing to assure they are clear and legible.

4.5.2.2.8 Visually examine the identification plate for compliance with the applicable drawing, for secure assembly (see 3.6), serialization and to assure that all pertinent data has been applied.

4.5.3 Testing.

4.5.3.1 Failure data. Unless otherwise specified herein, all tests shall be conducted on a complete feeder. If test requirements cited herein are not met, acceptance of shall be deferred and the contractor shall accomplish as applicable, the following actions:

a. Conduct a failure analysis study performing a dimensional physical and visual examination of the components which are suspected to be the cause of failure or malfunciton.
b. Evaluate and correct the applicable production processes and procedures to prevent recurrence of the same defect(s) in future production.
c. Examine feeders, partially assembled feeders, and components (including components and subassemblies at in-process or final assembly) to insure that material containing the same defect is purged from the inventory and not presented to the Government for acceptance.
d. Submit the results of the failure analysis and the corrective actions taken to the Government for review and approval prior to submitting a reconditioned lot or reconditioned feeder for retest.

4.5.3.2 Function testing. Each feeder shall be tested for functioning (see 3.3.1) usinng the test method specified in 4.6.1. Feeders failing to meet the requirements shall be cause for rejection.

4.5.3.3 Endurance testing.

4.5.3.3.1 Lot size. The initial endurance test lot size shall consist of the initial month's production; subsequent endurance test lot sizes shall consist of f100 feeders.

4.5.3.3.2 Procedure. One feeder shall be selected from each endurance lot and shall be tested for endurance (see 3.3.2) using the test methods specified in 4.6.2. Failure of the feeder to meet the requirements shall be cause for rejection of the represented lot.

Source: https://assist.dla.mil -- Downloaded: 2026t0-22T03:24Z
Check the source to verify that this is the currentversion before use.

4.5.3.4 Interchangeability testing.

4.5.3.4.1 In plant.

4.5.3.4.1.1 Feeders. A sample of three feeders selected from each month's production for interchangeability (see 3.4) using the test mehtod specified in 4.6.3.1.1. Feeders taken for interchangeability testing shall have been found satisfactory in all examinations and tests. The three feeders shall be inspected for and shall comply with the requirements for timing and torque after interchange of parts (see 4.5.2.2.5 and 4.5.2.2.6). In addition the feeders shall be tested for functioning requirements after interchange of parts using the test method specified in 4.6.1. Failure of feeders to meet the requirements of the interchangeability test shall be cause for rejection of the represented lot.

4.5.3.4.1.2 Concurrent repair parts. At least two parts from each inspection lot of concurrent repair parts shall be subjected to the interchangeability test specified in 4.6.3.1.2. Failure of any part to meet the requirements shall be cause for rejection of the represented lot.

4.5.3.4.2 Interplant. When feeders are manufactured concurrently by more than one contractor, each contractor shall forward monthly three feeders for the interplant interchangeability test specified in 4.6.3.2 (see 6.1). The contractor will be informed of any failure of the feeders to meet prescribed requirements. Upon completion of testing agency inspection, samples may be commercially packaged and will be returned to the contractor for repackaging in accordance wiht procurement documents at the contractor's expense.

4.5.3.5 Component parts and concurrent repair parts testing. Raw material testing, part testing, and certification sahll be performed in accordance with the criteria specified in the contract (see 6.1). This will include chemical analyses and physical tests of materials, and tests of protective finish, best treatment, bonding and function of parts as applicable. The contractor shall accomplish these tests prior to assembly of parts into the end item.

4.5.4 Packaging examination and testing. Unless otherwise specified (see 6.1). The packaging examination and testing shall be in accordance with MIL-F-14232.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

4.5.5 Certification. Unless otherwise specified, the contractor shall be responsible for testing necessary to accomplish certification. For each inspection lot of feeders, the contractor shall provide the Government representative with certified statements of compliance with applicable drawings an sspecifications of the following materials and proce3sses specified on Drawing F7791084.

4.5.5 Inspection equipments.

4.5.6.1 Unless otherwise specified in the procurement documents (see 6.1), responsibitlities for acquisition, maintenance, and dispositionof measuring and testing equiment prescribed on lists cntained on the Index of Inspection Equipment Lists, Drawing IEL7274645, and for all other inspection equipment required to perform inspection required by applicable specifications, shall be in accordance wiht MIL-I-45607.

4.5.6.2 When specified in procurement documents, copies of drawings of contractor designed inspection equipment shall be forwarded to Procuring activity (see 4.6.1 4.6.2 and 6.1)

4.6 Test methods.

4.6.1 Functioning test. Feeders shall be tested for functioning requirement using slave M61 or M61A1 guns or Government approved test equipment of the contractor's design (see 4.5.6.2) which simulates the function of the gun. Two belts of 100 rounds each of linked ammunition shall be used for testing each feeder and a steady state torque load of 80 ± 10 pound-inches shall be applied to the booster take-off assembly drive point during functioning. The feeders shall be accelerated up to a feeding steady state rate of 4,000 to 4,4000 rounds per minute before the feeder is declutched at fire-out (without ammunition in feeder). The feeder solenoid shall be energized to declutch the feeder at the instant power to the drive is removed, and shall not be energized for more than 15 seconds at any one time. After feeding each belt of ammunition the recorded data shall be checked to assure proper operation of the declutching mechanism. Instrumentation shall be of the contractor's design and shall be such that gun speed curve, timing marks, primer impulse, feeder declutching actuation and booster take-off torque load is taken and recorded concurrently for use in computing required data for each feeder.

4.6.2 Endurance test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

4.6.2.1 Feeders shall be tested for endurance requirement using slave M61 or M61A1 guns or Government approved test equipment of the contractor's design (see 4.5.6.2) which simulates the function of the gun.

4.6.2.2 Linked ammunition in belts of 100 rounds shall be used and a steady state torque load of 55 ± 30 pound-inches shall be applied to the booster take-off assembly drive point during functioning. The feeders shall be accelerated up to a feeding steady state rate of 4,000 to 4,400 rounds per minute before the feeder is declutched approximately in the middle of each belt. The feeder shall not be declutched at fire-out (without ammunition in feeder). The feeder solenoid shall be energized to declutch the feeder at the instant power to drve is removed, and shall be de-energized after the gun comes to a complete stop. The feeder solenoid shall be checked after each 1,500 rounds for correct timiming and loosening of parts. All loosened parts shall be retightened and recorded. In addition, the feeders shall be cleaned and lubricated after each 1,500 rounds and at the end of each day's testing. The bearings and electrical parts shall be protected from contamination. Instrumentation shall be in accordance with 4.6.1. Data shall be taken and recorded from one belt in each 1,500 round series for use in computing required data.

4.6.2.3 Endurance tested feeders shall be disposed of as specified in procurement documents (see 6.1).

4.6.3 Interchange of parts.

4.6.3.1 In plant.

4.6.3.1.1 Feeders. Feeders shall be tested for interchange of parts by disassembling and then reassembling parts using the parts and prearranged system specified below. Interchange of parts shall be accomplished by dividing the parts of each feeder into three groups of nonmating parts as shown below and distriubting the groups into three different trays until each tray contains parts for a complete feeder. Groups of parts from the first feeder shall be taken in order and placed in trays one thorugh three; groups of parts from the second feeder shall be taken in order and placed in trays two, three and one; groups of parts from the third feeder shall be taken in order and placed in trays three, one, and two. Commercial parts such as screws, spring pins, etc., shall be placed in the same tray as their mating or associate part. Any commercial part rendered unservicable by disassembly shall be replaced without penalty to the interchangeability test. The feeders shall be reassembled using only those parts which are in the same tray.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

Groups of non-mating parts

Group I

Adapter, booster (7268562)
Bearing, ball (2 from feeder shaft) (7794616)
Clevis (7794555)
Collar assembly (7794556)
Gear, bevel (7794578)
Housing and guides (w/remaining parts attached) (7791086)
Ring, traveling (7794562)
Spacer, gear (7790850)
Spacer, sprocket and bearing (7791088)
Spring, helical, compression (lever shaft) (7794569)
Sprocket, rear (7791095)

Group II

Bearing, ball (hub gear) (7794617)
Bearing, ball (feeder shaft-booster end) (7794618)
Cam, traveling ring (7794554)
Gear, drive, booster (7794557)
Gear, feeder (7794558)
Key (7794582)
Plate, cover (7794583)
Shaft, actuating (7794563)
Sprocket, front (77921094)
Stripper, feeder (7268576)
Support, clevis and solenoid (7794575)

Group III

Arm, anti-backlash (7794550) (w/stop, arm 7794574 attached) (5 required)
Gear, hub (7790851)
Guide, front, assembly (7268641)
(Shaft, feeder (7791565)
Shaft, lever (7794565)
Shield, clevis (7790682)
Spring, feeder shaft (7268573)
Spring, helical, compression (stop, arms) (7794570) (5 Required)

4.6.3.1.2 Concurrent repair parts. Concurrent repair parts shall be tested for interchangeability requirement by dissassembling two feeders, previously tested in 4.6.3.1.1, as necessary and then reassembling them using the concurrent repair parts. No hand refinement of parts will be allowed, and the feeders shall operate and function properly. This test may be performed independently of the feeder interchangeability test specified in 4.6.3.1.1, and at more frequent intervals using accepted feeders taken from current production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

4.6.3.2 Interplant. Feeders to subjected to the interplant interchangeability test shall be inspected for timing, (see 4.5.2.2.5) torque, (see 4.5.2.2.6) and functioning requirements using the inspection methods specified in 4.6.1 to assure proper operations before parts are interchanged. Fenders shall be interchanged in a manner similar to the detailed plan specified in 4.6.3.1.1 except that when disassembling, every other feeder shall be one produced by a different manufacturer. After assembly, the feeders shall be inspected for timing, torque, and functioning requirements using the inspection as specified herein. Before feeders are returned to the contractors, the original parts shall be reassembled to their respective feeders.

5. PREPARATION FOR DELIVERY.

5.1 Pilot pack. The pilot pack shall consist of a complete feeder packaged in accordance with Packaging Data Sheet P5910556 for the level of protection specified in the contract (see 6.1), packed level C and forwarded in accordance with 3.1.

5.2 Preservation, packaging, packing and marking. Feeders shall be preserved, packaged, packed and marked in accordance with Packaging Data Sheet P5910556 for the level of protection specified in the contract (see 6.1).

5.3 Repair parts. Repair parts shall be preserved, packaged, packed and marked in accordance with the Packaging Data Sheet or other requirements and for the level of protection specified in the contract (see 6.1).

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of the specification.
(b) Lists of drawings and specifications pertinent to the feeder, showing applicable revision dates.
(c) Inspection criteria for components (see 4.5.2.1 and 4.5.3.5).
(d) Index of inspection equipment lists pertinent to the feeder, showing applicable revision dates.
(e) Shipping instructions for first article and pilot pack (see 3.1 and 5.1).
(f) Requirements for copies of drawings of contractor-designed inspection equipment (see 4.5.6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

(g) List of acceptance inspection equipment to be furnished the contractor (see 4.5.6.1) and responsibilities for other Government property to be furnished the contractor.
(h) Packaging examination and testing, if different (see 4.5.4).
(i) Shipping instructions for feeders and parts when an interplant interchangeability test is required (see 4.5.3.4.2).
(j) Disposition of endurance tested feeders (see 4.6.2.3).
(k) Selection of applicable levels of preservation, packaging, packing and marking (see 5.1 and 5.2).
(l) Packaging of repair parts (see 5.3).
(m) Disposition of Government Furnished property.
(n) Responsibility for assigning serial numbers (see 3.5).
(o) Procedures and methods for demilitarizing and disposing of rejected material.
(p) Disposition of Government Furnished property.

6.3 Contract data requirements. Requirements for monthly reports of the results of the examination, functioning, endurance and interchangeability tests shall be specified on a DD Form 1423 included in the contract.

6.4 Unless otherwise specified (see 6.1 g) the contract should specify the application of MIL-I-45607 and MIL-C-45662 on the management Control Summary List DD Form 1660.

6.5 When warranted, the contract should specify the application of MIL-Q-9858 or MIL-I-45208 as appropriate, on the Management Control Systems Summary List in DD Form 1660.

6.6 Supersession data. This specification included the requirements of Springfield Armory Purchase Description SAPD-197 dated 3 January 1961.

Cusodians:
Army - WC
Navy - OS
Air Force - 84

Review activities:
Navy - OS
Air Force - 84

User activities:
Navy - MC

Preparing Activity
Army - WC

Project Number:
1005-0517

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander US Army Armament Materiel Readiness Command
ATTN: DRSAR-LEE-S
Rock Island, IL 61299

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark o*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil – Downloaded: 2026-02-22T03:24Z
Check the source to verify that this is the current version before use.